

Ships and marine technology — Pressure/ vacuum valves for cargo tanks

ICS 47.020.30,

National foreword

This British Standard is the UK implementation of ISO 15364:2007. It supersedes BS EN ISO 15364:2002 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee SME/32/-/3, Ships and marine technology - Piping and machinery.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 28 February 2009
© BSI 2009

ISBN 978 0 580 54936 6

Amendments/corrigenda issued since publication

Date	Comments

INTERNATIONAL STANDARD

BS ISO 15364:2007

ISO
15364

Second edition
2007-12-15

Ships and marine technology — Pressure/vacuum valves for cargo tanks

*Navires et technologie maritime — Robinets à pression/à vide pour
citernes de chargement*



Reference number
ISO 15364:2007(E)
Documents
Document Sharing Hub
© ISO 2007

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	3
5 Materials	3
6 Other requirements	4
7 Approval tests	5
8 Inspections	6
9 Flow and velocity tests	6
9.1 Determination of capacity	6
9.2 Capacity data	6
9.3 Test apparatus	7
9.4 Flow measurements	7
10 Undamped oscillation tests	8
11 Documentation	9
11.1 General	9
11.2 Installation instructions	10
12 Marking	10
13 Quality assurance	11
Annex A (normative) Installation requirements for ships subject to the International Convention for the Safety of Life at Sea, 2002 (SOLAS)	12
Annex B (normative) Flow test measurements	13
Annex C (informative) Materials selection guidelines	15
Annex D (informative) Corrosion protection guidelines	16
Annex E (informative) Specification information	20
Annex F (informative) Flow graph examples	21
Bibliography	23

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 15364 was prepared by Technical Committee ISO/TC 8, *Ships and marine technology*, Subcommittee SC 3, *Piping and machinery*.

This second edition cancels and replaces the first edition (ISO 15364:2000) which has been technically revised.

Ships and marine technology — Pressure/vacuum valves for cargo tanks

1 Scope

This international standard applies to pressure-vacuum relief valves protecting marine vessel systems, including cargo tanks, which may be subject to gas/vapour pressure or vacuum beyond the design parameters of the system/tank. This International Standard specifies the minimum requirements for performance and testing of pressure-vacuum relief valves, with emphasis on selection of materials, internal finish and surface requirements for pressure-vacuum valves installed on cargo tanks in tankers (see Annex A). This International Standard specifies design and in-service performance criteria, operational testing and maintenance requirements. Certification to this International Standard does not imply suitability for any given installation; it indicates that certain minimum requirements have been considered and that information necessary for determination of suitability is provided to the buyer of the equipment.

This International Standard does not cover all test procedures for devices that prevent the passage of flame, such as flame arresters. Such devices may be used in conjunction with pressure/vacuum valves.

NOTE Additional information for devices to prevent the passage of flame is found in the International Maritime Organization (IMO) “International Convention for the Safety of Life at Sea, 2002” (SOLAS), Chapter II-2, Regulation 4, and IMO Maritime Safety Committee (MSC) Circular No. 677 (MSC/Circ. 677), “Revised Standards for the Design, Testing and Locating of Devices to Prevent the Passage of Flame into Cargo Tanks in Tankers”, as amended by IMO MSC/Circ. 1009.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

International Maritime Organization, Assembly Resolution A.746(18), *Survey Guidelines under the Harmonized System of Survey and Certification*

International Maritime Organization, *International Convention for the Safety of Life at Sea, 2002* (SOLAS), Chapter II-2, Regulation 4

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

administration

government of the state whose flag the ship is entitled to fly

3.2

flame arrester

device to prevent the passage of flame, designed and tested in accordance with a specified performance standard

NOTE Its flame-arresting unit is based on the principle of quenching.

3.3

full opening valve

design that opens fully at the set pressure

3.4

high velocity vent

device to prevent the passage of flame, consisting of a mechanical valve which adjusts the opening available for flow in accordance with the pressure at the inlet of the valve in such a way that the efflux velocity cannot be less than 30 m/s (98 ft/sec)

3.5

maximum experimental safe gap

MESG

property of the respective gas mixture being the maximum clearance of the joint between two parts of the interior chamber of a test apparatus which, when the internal gas mixture is ignited and under specified conditions, prevents ignition of the external gas mixture through a 25 mm (10 in) long joint, for all concentrations of the tested gas or vapour in air

NOTE IEC 60079-1 ^[1] standardizes the test apparatus and the test method.

3.6

maximum intended pressure drop

largest pressure drop generated over a valve for which the test laboratory verifies the corresponding flow capacity

3.7

modulating valve

design that opens proportionally with rise in pressure

3.8

pressure/vacuum valve

device designed to maintain pressure and vacuum in a closed container within preset limits

3.9

standard air

dry air at 21 °C (70 °F) and 1 013,25 hPa (29,92 in Hg) pressure

NOTE This is substantially equivalent to a density of 1,2 kg/m³ (0,075 lb/ft³). Specific heat of dry air = 1 004,8 J/(kg·K) [0,24 Btu/(lb·°R)].

3.10

third party inspection body

organization designated by the administration which is independent from the manufacturer or user and which performs or witnesses the tests and inspections provided for by this International Standard

3.11

transition point valve

design where the valve characteristics change from modulating to full opening at a particular pressure

3.12

verified drawings and diagrams

drawings and diagrams certified to be authentic and complete by the test laboratory issuing the test report in accordance with this International Standard

3.13

verified flow chart

pressure versus flow volume presented in a chart certified by the test laboratory issuing the test report in accordance with this International Standard

4 Symbols and abbreviated terms

D	nominal pipe diameter at device connection
$D_{\min}$	minimum diameter of the piping between the device and the tank allowed for non-oscillating performance
$L_{\max}$	maximum length of the piping between the device and the tank allowed for non-oscillating performance
L_1	pipe length between test tank and the device for flow testing
L_2	pipe length between test tank and the device during non-oscillation testing
P_{closing}	pressure drop over the valve corresponding to the minimum flow required to keep the valve partially open with no contact between the disc and the seat
$P_{\max}$	maximum pressure drop corresponding to the maximum flow volume (Q_3)
P_{set}	set pressure, expressed as the calculated force applied to the disc versus the area on which tank pressure is applied
$P_{1\text{-tpv}}$	pressure at which a transition point valve changes from modulating to full opening
$Q_{1\text{-fov}}$	flow volume needed to open the valve
Q_2	flow volume needed for the valve to remain fully open
$Q_{2\text{-fov}}$	flow volume needed to maintain the valve fully open at P_{set}
$Q_{1\text{-mv}}$	flow volume needed to open the valve
$Q_{2\text{-mv}}$	flow volume needed to maintain the valve fully open
$Q_{1\text{-tpv}}$	flow volume at which a transition point valve changes from modulating to full opening
$Q_{2\text{-tpv}}$	flow volume needed to maintain a transition point valve fully open at $P_{1\text{-tpv}}$
Q_3	flow volume corresponding to the maximum intended pressure drop over the valve
Q_{close}	minimum flow required to keep the valve partially open with no contact between the disc and the seat
$V_{\min}$	minimum volume of the tank allowed for non-oscillating performance

5 Materials

5.1 The device housing, and other parts or bolting used for pressure retention, shall be constructed of materials suitable for the intended service and listed in a recognised national/international standard.

Housings, discs, spindles, seats, springs, gaskets, seals, flame arresters (when included in the design) and all other integral parts, including parts with coatings to prevent corrosion, shall be made of materials resistant to attack by sea water and the liquids and vapours contained in the tank being protected (see Annex C).

Springs plated with corrosion resistant material are not acceptable.

5.2 Non-metallic materials, other than gaskets, seals and diaphragms as allowed by 6.11, shall not be used in the construction of pressure retaining components of the device.

Resilient seals may be installed only if the device is still capable of effectively performing its flame arresting function when the seals are partially or completely damaged or burned.

Non-metallic gaskets shall be made of non-combustible material and suitable for the service intended.

5.3 Materials for connecting pressure-vacuum valves to their respective piping systems should meet standards for physical characteristics similar to those of the piping systems to which they are connected.

5.4 The possibility of galvanic corrosion shall be considered in the selection of materials (see Annex C for additional considerations).

5.5 The verified drawings shall include a complete bill of materials showing conformity with this clause and any other material requirements listed in Clause 6.

6 Other requirements

6.1 The maximum gas leakage rate shall be provided and expressed as the volume in standard air that may leak from the valve at 80 % of the nominal setting.

6.2 Housings, elements, and seal gasket materials shall be capable of withstanding the maximum and minimum pressures and temperatures to which the device may be exposed under normal operating conditions.

6.3 Where welded construction is used for pressure retaining components, welded joint design details, welding and non-destructive testing shall be in accordance with national or international standards. Welders and weld procedures shall be qualified by a recognised organization to ensure consistent quality production of weld joints that are sound and of proper strength, in accordance with recognised national/international standards.

6.4 End-of-line pressure-vacuum valves shall be designed such that condensed vapour and water in the pressure-retaining zone drain from the device into the tank and do not impair the efficiency of the device. The design shall also prevent the accumulation of water inside the device and subsequent blockage due to freezing. Internal components, channels and inner walls to be drained shall be sloped.

6.5 All fasteners essential to the operation of the device shall be protected against loosening.

6.6 Devices shall be designed and constructed to minimize the effect of fouling under normal operating conditions. The design shall be such that the device can be examined for any build-up of residue due to vapour condensation. For certain cargoes that crystallize, heating arrangements may be necessary.

6.7 Devices shall be capable of operating over the full range of ambient air temperatures anticipated. Devices shall be capable of operating in freezing conditions (such as may cause blockage by freezing cargo vapours or by icing in bad weather) and when covered by a layer of ice, the allowed thickness of which shall be stated by the manufacturer in the instruction manual. Devices shall also be capable of operating at whatever surface temperature is developed by heating arrangements.

6.8 End-of-line devices are required to direct the efflux vertically upward (see SOLAS 2002, Ch. II-2 Regulation 4, 5.3.4.1.1.2) and the minimum average velocity of air through a cross section of the valve's outlet to atmosphere shall not be less than 30 m/s for all flow rates.

6.9 A manual means shall be provided to verify that any valve disc and other moving elements lift freely and fully and cannot remain in the open position. The design shall be such that the device is verified not to be inoperable due to corrosion, residue build-up or icing, when the aforementioned manual means is used in combination with the manufacturer's requirements for visual inspection.

6.10 Valve discs and other moving parts shall be guided by a suitable means to prevent binding and ensure proper self-closing (seating), taking into account the possible build-up of condensed vapours passing through the valve during loading, when maintenance is carried out in accordance with the manufacturer's requirements. Valve discs shall normally close against the valve seat by metal to metal contact. Resilient seating seals may be provided if the design is such that the disc closes tight against the seat in case the seals are destroyed, damaged or are otherwise carried away.