

Hydraulic fluid power — Flush-face type, quick-action couplings for use at pressures of 20 MPa (200 bar) to 31,5 MPa (315 bar) — Specifications

ICS 23.100.40

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

National foreword

This British Standard was published by BSI. It is the UK implementation of ISO 16028:1999, including Amendment 1:2006, and implements it as the UK national standard.

The UK participation in its preparation was entrusted by Technical Committee MCE/18, Fluid power systems and components, to Subcommittee MCE/18/-/4, Connectors and associated components.

A list of organizations represented on MCE/18/-/4 can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard, having been prepared under the direction of the Engineering Sector Committee, was published under the authority of the Standards Committee and comes into effect on 15 April 2000

© BSI 2006

ISBN 0 580 34652 8

Amendments issued since publication

Amd. No.	Date	Comments
16680	31 October 2006	Changes to Clause 1 and Subclause 5.2

**Hydraulic fluid power — Flush-face type,
quick-action couplings for use at pressures
of 20 MPa (200 bar) to 31,5 MPa (315 bar) —
Specifications**

*Transmissions hydrauliques — Raccords rapides de type à face plane pour
usage à des pressions de 20 MPa (200 bar) à 31,5 MPa (315 bar) —
Spécifications*



Reference number
ISO 16028:1999(E)

