

Hydraulic fluid power — Single rod, short-stroke cylinders with bores from 32 mm to 100 mm for use at 10 MPa (100 bar) — Mounting dimensions

ICS 23.100.20

National foreword

This British Standard reproduces verbatim ISO 16656:2004 and implements it as the UK national standard.

The UK participation in its preparation was entrusted to Technical Committee MCE/18, Fluid power systems, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international/European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this committee can be obtained on request to its secretary.

Cross-references

The British Standards which implement international publications referred to in this document may be found in the *BSI Catalogue* under the section entitled “International Standards Correspondence Index”, or by using the “Search” facility of the *BSI Electronic Catalogue* or of British Standards Online.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, the ISO title page, pages ii to iv, pages 1 to 4, an inside back cover and a back cover.

The BSI copyright notice displayed in this document indicates when the document was last issued.

Amendments issued since publication

Amd. No.	Date	Comments

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 22 November 2004

© BSI 22 November 2004

ISBN 0 580 44823 1

INTERNATIONAL STANDARD

**ISO
16656**

First edition
2004-06-15

Hydraulic fluid power — Single rod, short-stroke cylinders with bores from 32 mm to 100 mm for use at 10 MPa (100 bar) — Mounting dimensions

*Transmissions hydrauliques — Vérins course courte à simple tige,
d'alésages 32 mm à 100 mm, pour utilisation à 10 MPa (100 bar) —
Dimensions d'interchangeabilité*



