

Space data and information transfer systems — CCSDS file delivery protocol

ICS 49.140

National foreword

This British Standard reproduces verbatim ISO 17355:2003 and implements it as the UK national standard.

The UK participation in its preparation was entrusted by Technical Committee ACE/68, Space systems and operations, to Subcommittee ACE/68/-/7, Space data and information transfer systems, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international/European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this subcommittee can be obtained on request to its secretary.

Cross-references

The British Standards which implement international publications referred to in this document may be found in the *BSI Catalogue* under the section entitled “International Standards Correspondence Index”, or by using the “Search” facility of the *BSI Electronic Catalogue* or of British Standards Online.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, the ISO title page, pages ii and iii, a blank page, pages 1 to 152, an inside back cover and a back cover.

The BSI copyright date displayed in this document indicates when the document was last issued.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 12 June 2003

© BSI 12 June 2003

ISBN 0 580 42046 9

Amendments issued since publication

Amd. No.	Date	Comments

INTERNATIONAL STANDARD

**ISO
17355**

First edition
2003-02-15

Space data and information transfer systems — CCSDS file delivery protocol

*Systèmes de transfert des informations et données spatiales —
Protocole CCSDS de livraison des fichiers*



Reference number
ISO 17355:2003(E)

AVA Documents
Document Sharing Hub

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

International Standard ISO 17355 was prepared by the Consultative Committee for Space Data Systems (CCSDS) (as CCSDS 727.0-B-1, January 2002) and was adopted (without modifications except those stated in Clause 2 of this International Standard) by Technical Committee ISO/TC 20, *Aircraft and space vehicles*, Subcommittee SC 13, *Space data and information transfer systems*.

Space data and information transfer systems — CCSDS file delivery protocol

1 Scope

This International Standard specifies the requirements for a file delivery protocol and associated service for application in the space environment. It is intended for use over the current and envisaged packet delivery services used in the space environment.

The scope and field of application are furthermore detailed in subclauses 1.1 and 1.2 of the enclosed CCSDS publication.

2 Requirements

Requirements are the technical recommendations made in the following publication (reproduced on the following pages), which is adopted as an International Standard:

CCSDS 727.0-B-1, January 2002, *Recommendation for space data system standards — CCSDS file delivery protocol (CFDP)*.

For the purposes of international standardization, the modifications outlined below shall apply to the specific clauses and paragraphs of publication CCSDS 727.0-B-1.

Pages i to v

This part is information which is relevant to the CCSDS publication only.

Page 1-5

Add the following information to the references indicated:

- [1] Document CCSDS 701.0-B-3, June 2001, is equivalent to ISO 13420:—¹⁾.
- [2] Document CCSDS 102.0-B-5, November 2000, is equivalent to ISO 13419:2003.
- [3] Document CCSDS 103.0-B-2, June 2001, is equivalent to ISO 17433:2003.
- [4] Document CCSDS 202.0-B-3, June 2001, is equivalent to ISO 12172:2003.

1) To be published. (Revision of ISO 13420:1997)

3 Revision of publication CCSDS 727.0-B-1

It has been agreed with the Consultative Committee for Space Data Systems that Subcommittee ISO/TC 20/SC 13 will be consulted in the event of any revision or amendment of publication CCSDS 727.0-B-1. To this end, NASA will act as a liaison body between CCSDS and ISO.

***Consultative
Committee for
Space Data Systems***

RECOMMENDATION FOR SPACE
DATA SYSTEM STANDARDS

**CCSDS FILE DELIVERY
PROTOCOL (CFDP)**

CCSDS 727.0-B-1

BLUE BOOK

January 2002



(Blank page)

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

AUTHORITY

Issue:	Blue Book, Issue 1
Date:	January 2002
Location:	Not Applicable

This document has been approved for publication by the Management Council of the Consultative Committee for Space Data Systems (CCSDS) and represents the consensus technical agreement of the participating CCSDS Member Agencies. The procedure for review and authorization of CCSDS Recommendations is detailed in the reference [A1], and the record of Agency participation in the authorization of this document can be obtained from the CCSDS Secretariat at the address below.

This Recommendation is published and maintained by:

CCSDS Secretariat
Program Integration Division (Code M-3)
National Aeronautics and Space Administration
Washington, DC 20546, USA

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

STATEMENT OF INTENT

The Consultative Committee for Space Data Systems (CCSDS) is an organization officially established by the management of member space Agencies. The Committee meets periodically to address data systems problems that are common to all participants, and to formulate sound technical solutions to these problems. Inasmuch as participation in the CCSDS is completely voluntary, the results of Committee actions are termed **Recommendations** and are not considered binding on any Agency.

This **Recommendation** is issued by, and represents the consensus of, the CCSDS Plenary body. Agency endorsement of this **Recommendation** is entirely voluntary. Endorsement, however, indicates the following understandings:

- o Whenever an Agency establishes a CCSDS-related **standard**, this **standard** will be in accord with the relevant **Recommendation**. Establishing such a **standard** does not preclude other provisions which an Agency may develop.
- o Whenever an Agency establishes a CCSDS-related standard, the Agency will provide other CCSDS member Agencies with the following information:
 - The **standard** itself.
 - The anticipated date of initial operational capability.
 - The anticipated duration of operational service.
- o Specific service arrangements shall be made via memoranda of agreement. Neither this **Recommendation** nor any ensuing **standard** is a substitute for a memorandum of agreement.

No later than five years from its date of issuance, this **Recommendation** will be reviewed by the CCSDS to determine whether it should: (1) remain in effect without change; (2) be changed to reflect the impact of new technologies, new requirements, or new directions; or, (3) be retired or canceled.

In those instances when a new version of a **Recommendation** is issued, existing CCSDS-related Agency standards and implementations are not negated or deemed to be non-CCSDS compatible. It is the responsibility of each Agency to determine when such standards or implementations are to be modified. Each Agency is, however, strongly encouraged to direct planning for its new standards and implementations towards the later version of the Recommendation.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

FOREWORD

Until relatively recently the typical storage medium for spacecraft has been the tape recorder, a complex device offering limited data storage and data access. The use of this type of storage has typically been limited to the recording and subsequent dump to the ground of telemetry data. Manipulation from the ground has required significant human intervention and used ad hoc, privately developed protocols.

The introduction of solid state mass memory providing gigabytes of storage with random access opens up a whole new ethos of spacecraft operation where much of the routine traffic to and from the spacecraft will be in the form of files. Furthermore, because of the random access nature of the onboard storage medium, it becomes possible to repeat transmission of data lost on the link and thus guarantee delivery of critical information.

To exploit the potential advantages of onboard mass memory, protocol support is required to provide a standard means to move data to and from the onboard storage medium in the form of files.

While the onboard storage medium has rapidly evolved, the essential constraints of space missions remain:

- limited systems resources in terms of computational power and memory capacities;
- environmental restrictions including noisy, bandwidth limited, asymmetrical, and interrupted communications links, some with very long propagation delay;
- varying user needs including a requirement for early access to transferred data regardless of its quality.

In view of these constraints, it is clear that there is a need for a file delivery service capable of transferring files to and from mass memory located in the space segment. Such a capability must not only operate under the constraints associated with space data communication, but it must also be applicable to the diverse range of mission configurations ranging from single low earth orbiting spacecraft to complex networks of relays, orbiters, and landers.

Through the process of normal evolution, it is expected that expansion, deletion, or modification of this document may occur. This Recommendation is therefore subject to CCSDS document management and change control procedures which are defined in reference [A1]. Current versions of CCSDS documents are maintained at the CCSDS Web site:

<http://www.ccsds.org/>

Questions relating to the contents or status of this document should be addressed to the CCSDS Secretariat at the address indicated on page i.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

At time of publication, the active Member and Observer Agencies of the CCSDS were:

Member Agencies

- Agenzia Spaziale Italiana (ASI)/Italy.
- British National Space Centre (BNSC)/United Kingdom.
- Canadian Space Agency (CSA)/Canada.
- Centre National d'Etudes Spatiales (CNES)/France.
- Deutsches Zentrum für Luft- und Raumfahrt e.V. (DLR)/Germany.
- European Space Agency (ESA)/Europe.
- Instituto Nacional de Pesquisas Espaciais (INPE)/Brazil.
- National Aeronautics and Space Administration (NASA)/USA.
- National Space Development Agency of Japan (NASDA)/Japan.
- Russian Space Agency (RSA)/Russian Federation.

Observer Agencies

- Austrian Space Agency (ASA)/Austria.
- Central Research Institute of Machine Building (TsNIIMash)/Russian Federation.
- Centro Tecnico Aeroespacial (CTA)/Brazil.
- Chinese Academy of Space Technology (CAST)/China.
- Commonwealth Scientific and Industrial Research Organization (CSIRO)/Australia.
- Communications Research Centre (CRC)/Canada.
- Communications Research Laboratory (CRL)/Japan.
- Danish Space Research Institute (DSRI)/Denmark.
- European Organization for the Exploitation of Meteorological Satellites (EUMETSAT)/Europe.
- European Telecommunications Satellite Organization (EUTELSAT)/Europe.
- Federal Service of Scientific, Technical & Cultural Affairs (FSST&CA)/Belgium.
- Hellenic National Space Committee (HNSC)/Greece.
- Indian Space Research Organization (ISRO)/India.
- Institute of Space and Astronautical Science (ISAS)/Japan.
- Institute of Space Research (IKI)/Russian Federation.
- KFKI Research Institute for Particle & Nuclear Physics (KFKI)/Hungary.
- MIKOMTEK: CSIR (CSIR)/Republic of South Africa.
- Korea Aerospace Research Institute (KARI)/Korea.
- Ministry of Communications (MOC)/Israel.
- National Oceanic & Atmospheric Administration (NOAA)/USA.
- National Space Program Office (NSPO)/Taipei.
- Swedish Space Corporation (SSC)/Sweden.
- United States Geological Survey (USGS)/USA.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

DOCUMENT CONTROL

Document	Title	Date	Status
CCSDS 727.0-B-1	CCSDS File Delivery Protocol, Issue 1	January 2002	Original Issue

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

CONTENTS

<u>Section</u>	<u>Page</u>
1 INTRODUCTION	1-1
1.1 PURPOSE AND SCOPE	1-1
1.2 APPLICABILITY	1-1
1.3 CONVENTIONS AND DEFINITIONS	1-1
1.4 REFERENCES	1-5
2 OVERVIEW	2-1
2.1 GENERAL	2-1
2.2 ARCHITECTURE ELEMENTS	2-2
2.3 GENERAL CHARACTERISTICS	2-4
2.4 OVERVIEW OF INTERACTIONS	2-7
3 SERVICE DESCRIPTION	3-1
3.1 SERVICES AT THE USER INTERFACE	3-1
3.2 SUMMARY OF PRIMITIVES	3-1
3.3 SUMMARY OF PARAMETERS	3-2
3.4 SERVICES REQUIRED OF THE UNDERLYING COMMUNICATION SYSTEM	3-6
3.5 CFDP SERVICE PRIMITIVES	3-8
4 PROTOCOL SPECIFICATION	4-1
4.1 PROCEDURES	4-1
5 PDU FORMATS	5-1
5.1 GENERAL	5-1
5.2 FILE DIRECTIVE PDUs	5-4
5.3 FILE DATA PDU	5-11
5.4 TLV PARAMETERS	5-11
6 USER OPERATIONS	6-1
6.1 RESERVED CFDP MESSAGE FORMAT	6-1
6.2 PROXY OPERATION	6-3
6.3 DIRECTORY OPERATIONS	6-9
6.4 REMOTE STATUS REPORT OPERATIONS	6-11
6.5 REMOTE SUSPEND OPERATIONS	6-14
6.6 REMOTE RESUME OPERATIONS	6-17

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

CONTENTS (continued)

<u>Section</u>	<u>Page</u>
7 CFDP SERVICE CLASSES	7-1
7.1 DEFINED CLASSES.....	7-1
7.2 FUNCTIONS OF CLASS 1—UNRELIABLE TRANSFER.....	7-2
7.3 FUNCTIONS OF CLASS 2—RELIABLE TRANSFER	7-5
7.4 FUNCTIONS OF CLASS 3—RELIABLE TRANSFER BY PROXY	7-8
8 MANAGEMENT INFORMATION BASE	8-1
8.1 GENERAL	8-1
8.2 LOCAL ENTITY CONFIGURATION INFORMATION.....	8-1
8.3 REMOTE ENTITY CONFIGURATION INFORMATION.....	8-2
ANNEX A INFORMATIVE REFERENCES	A-1
ANNEX B ACRONYMS	B-1
ANNEX C EXAMPLE OF CHECKSUM CALCULATION	C-1
ANNEX D EXTENDED PROCEDURES	D-1

Figure

1-1 Bit Numbering Convention	1-2
1-2 Octet Convention	1-2
2-1 Architectural Elements of the File Delivery Protocol.....	2-2
2-2 CFDP Procedures	2-4
2-3 Copy Operations, Sequence of Events	2-7
2-4 Put Operations, Sequence of Events	2-8
2-5 Proxy Put Operations, Sequence of Events.....	2-8

Table

5-1 Fixed PDU Header Fields	5-1
5-2 LV Object Format	5-2
5-3 TLV Object Format.....	5-3
5-4 File Directive Codes.....	5-4
5-5 Condition Codes.....	5-5
5-6 End-of-File PDU Contents	5-5
5-7 Finished PDU Contents.....	5-6
5-8 ACK PDU Contents	5-8
5-9 Metadata PDU Contents.....	5-9
5-10 NAK PDU Contents.....	5-10
5-11 Segment Request Form	5-10
5-12 Prompt PDU Contents.....	5-10

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

CONTENTS (continued)

<u>Table</u>	<u>Page</u>
5-13 Keep Alive PDU Contents	5-11
5-14 File Data PDU Contents	5-11
5-15 Filestore Request TLV Contents	5-11
5-16 Filestore Request TLV Action Codes	5-12
5-17 Filestore Response TLV Contents	5-12
5-18 Filestore Response Status Codes	5-13
5-19 Fault Handler Override Field Encoding	5-14
6-1 Reserved CFDP Message Header	6-1
6-2 Originating Transaction ID Message	6-2
6-3 Proxy Operations Message Types	6-3
6-4 Remote Put Order Message	6-4
6-5 Remote Message to User Message	6-4
6-6 Remote Filestore Request Message	6-5
6-7 Remote Fault Handler Override Message	6-5
6-8 Remote Transmission Mode Message	6-5
6-9 Remote Flow Label Message	6-6
6-10 Remote Segmentation Control Message	6-6
6-11 Remote Put Finished Message	6-7
6-12 Remote Filestore Response Message	6-8
6-13 Directory Operations Message Types	6-9
6-14 Directory Listing Request Message	6-9
6-15 Directory Listing Response Message	6-10
6-16 Remote Status Report Operations Message Types	6-11
6-17 Remote Status Report Request Message	6-12
6-18 Remote Status Report Response Message	6-13
6-19 Remote Suspend Operations Message Types	6-14
6-20 Remote Suspend Request Message	6-15
6-21 Remote Suspend Response Message	6-16
6-22 Remote Resume Operations Message Types	6-17
6-23 Remote Resume Request Message	6-18
6-24 Remote Resume Response Message	6-19
7-1 Class 1 Source Procedures	7-2
7-2 Class 1 Destination Procedures	7-3
7-3 Class 2 Source Procedures	7-5
7-4 Class 2 Destination Procedures	7-6
7-5 Class 3 Beneficiary Procedures	7-8
7-6 Class 3 Respondent Procedures	7-8
7-7 Class 3 Originator Procedures	7-9
8-1 Local Entity Configuration Information	8-1
8-2 Remote Entity Configuration Information	8-2

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

1 INTRODUCTION

1.1 PURPOSE AND SCOPE

This document defines a CCSDS File Delivery Protocol (CFDP) and associated service for application in the space environment. It is intended for use over the current and envisaged packet delivery services used in the space environment including:

- CCSDS conventional packet telecommand;
- CCSDS conventional packet telemetry;
- CCSDS Advanced Orbiting Systems (AOS) Path service.

It may also operate over a wide variety of ground network services including those specified by the CCSDS for cross-support purposes.

The protocol operates in the space-to-ground, ground-to-space, and space-to-space directions of transfer. It may be initiated by the file sending or receiving entity.

In the interests of interoperability, protocol elements are included for generalized forms of standard file manipulation operations based on assumptions of a common model for a 'filestore', or medium used to store files. It is recognized, however, that the precise nature and capabilities of filestore management systems are operating-system dependent and, for that reason, the protocol assumes a virtual filestore and associated services that an implementation must map to the capabilities of the actual filestore used.

1.2 APPLICABILITY


This Recommendation specifies a protocol and associated services that are applicable to space missions with continuous duplex contact, intermittent duplex contact, asymmetrical time-disjunct contact, and simplex contact.

1.3 CONVENTIONS AND DEFINITIONS


1.3.1 BIT NUMBERING CONVENTION AND NOMENCLATURE

In this document, the following convention is used to identify each bit in an N -bit field. The first bit in the field to be transmitted (i.e., the most left justified when drawing a figure) is defined to be 'Bit 0'; the following bit is defined to be 'Bit 1' and so on up to 'Bit $N-1$ '. When the field is used to express a binary value (such as a counter), the Most Significant Bit (MSB) shall be the first transmitted bit of the field, i.e., 'Bit 0'.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

**Figure 1-1: Bit Numbering Convention**

In accordance with modern data communications practice, spacecraft data fields are often grouped into 8-bit ‘words’ which conform to the above convention. Throughout this Recommendation, the following nomenclature is used to describe this grouping:

**Figure 1-2: Octet Convention**

By CCSDS convention, all ‘spare’ bits shall be permanently set to value ‘zero’.

1.3.2 ORGANIZATION OF THE RECOMMENDATION

This Recommendation is organized as follows:

- Section 2 provides an overview of the protocol, its intended use, and a description of the main interactions involved in a file transfer.
- Section 3 defines the services provided by the protocol along with the associated primitives and parameters.
- Section 4 is the main body of the protocol specification.
- Section 5 defines the formats for the PDUs.
- Section 6 defines proxy and directory operations.
- Section 7 defines a number of classes of operation designed to meet the most typical operating scenarios.
- Section 8 describes the Management Information Base (MIB).
- Annex A provides a list of informative references.
- Annex B provides a list of acronyms and definitions.
- Annex C provides an example of file checksum calculation.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

- Annex D documents proposed ‘extended’ procedures for conducting successive CFDP file copy operations among three or more entities in a store-and-forward manner.

1.3.3 DEFINITIONS

1.3.3.1 Definitions from OSI Basic Reference Model

This Recommendation makes use of a number of terms defined in reference [5]. The use of those terms in this Recommendation shall be understood in a generic sense, i.e., in the sense that those terms are generally applicable to any of a variety of technologies that provide for the exchange of information between real systems. Those terms are:

- entity;
- Protocol Data Unit (PDU);
- service;
- Service Access Point (SAP);
- Service Data Unit (SDU).

1.3.3.2 Definitions from Open Systems Interconnection (OSI) Service Definition Conventions

This Recommendation makes use of a number of terms defined in reference [6]. The use of those terms in this Recommendation shall be understood in a generic sense, i.e., in the sense that those terms are generally applicable to any of a variety of technologies that provide for the exchange of information between real systems. Those terms are:

- Indication;
- Primitive;
- Request;
- Response.

1.3.3.3 Terms Defined in This Recommendation

Within the context of this document the following definitions apply:

A *CFDP protocol entity* (or *CFDP entity*) is a functioning instance of an implementation of the CFDP protocol, roughly analogous to an Internet protocol ‘host’.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

The functional concatenation of a file and related *metadata* transmitted between two CFDP entities is termed a *File Delivery Unit* (FDU); in this context the term ‘metadata’ is used to refer to any data exchanged between CFDP protocol entities in addition to file content, typically either additional application data (such as a ‘message to user’) or data that aid the recipient entity in effectively utilizing the file (such as file name). Note that an FDU may consist of metadata only. Note also that the term ‘file’ is frequently used in this specification as an abbreviation for ‘file delivery unit’; only when the context clearly indicates that only actual files are being discussed, for example, in the explanation of the segmentation control parameter or the source and destination file name parameters of the CFDP Service Definition, should the term ‘file’ not be read as ‘file delivery unit’.

The individual, bounded, self-identifying items of CFDP data transmitted between CFDP entities are termed *CFDP Protocol Data Units* or *CFDP PDUs*. Unless otherwise noted, in this document the term ‘PDU’ always means ‘CFDP PDU’. CFDP PDUs are of two general types: *File Data PDUs* convey the contents of the files being delivered, while *File Directive PDUs* convey only metadata and other non-file information that advances the operation of the protocol.

A *transaction* is the end-to-end transmission of a single FDU between two CFDP entities. A single transaction normally entails the transmission and reception of multiple PDUs. Each transaction is identified by a unique transaction ID; all elements of any single FDU, both file content and metadata, are tagged with the same CFDP transaction ID.

Any single end-to-end file transmission task has two associated entities: the entity that has the file at the beginning of the task (the *source*) and the entity that has a copy of the file when the task is completed (the *destination*).

Each end-to-end file transmission task comprises a single point-to-point file copy operation. A file copy operation has two associated entities: the entity that has a copy of the file at the beginning of the operation (the *sender* or *sending entity*) and the entity that has a copy of the file when the operation is completed (the *receiver* or *receiving entity*). (Note that file copy operations are functionally equivalent to file transmission tasks. The distinction between the two is preserved in this document solely as a terminological aid for possible future extension of the protocol to multi-point cases, in which a single file transmission task might comprise multiple successive file copy operations.)

Filestore is a generic term referring to the medium used to store files.

The term *offset* is used in a familiar way: the offset of a given octet of file data is the number of data octets that precede this octet in the file.

The file delivery *progress* represented by a given file data PDU is the sum of the offset of the PDU’s file data content (the offset of the content’s first octet) and the length of that file data content.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

The *transmission progress* for a given transaction, delivering some file, is the maximum progress value over all file data PDUs sent so far in the course of this transaction.

Similarly the *reception progress* for a given transaction is the maximum progress value over all file data PDUs received so far in the course of this transaction. If and only if no data are lost in transmission, reception progress is equal to the number of file data octets received.

The term *CFDP user* is used to refer to the software task that causes the local entity to initiate a transaction or the software task that is notified by the local entity of the progress or completion of a transaction. The CFDP user local to the source entity is referred to as the *source CFDP user*. The CFDP user local to the destination entity is referred to as the *destination CFDP user*. The CFDP user may be operated by a human or by another software process. Unless otherwise noted the term *user* always refers to the CFDP user.

1.4 REFERENCES

The following documents contain provisions which, through reference in this text, constitute provisions of this Recommendation. At the time of publication, the editions indicated were valid. All documents are subject to revision, and users of this Recommendation are encouraged to investigate the possibility of applying the most recent editions of the documents indicated below. The CCSDS Secretariat maintains a register of currently valid CCSDS Recommendations.

- [1] *Advanced Orbiting Systems, Networks and Data Links: Architectural Specification.* Recommendation for Space Data System Standards, CCSDS 701.0-B-3. Blue Book. Issue 3. Washington, D.C.: CCSDS, June 2001.
- [2] *Packet Telemetry.* Recommendation for Space Data System Standards, CCSDS 102.0-B-5. Blue Book. Issue 5. Washington, D.C.: CCSDS, November 2000.
- [3] *Packet Telemetry Service Specification.* Recommendation for Space Data System Standards, CCSDS 103.0-B-2. Blue Book. Issue 2. Washington, D.C.: CCSDS, June 2001.
- [4] *Telecommand Part 2—Data Routing Service.* Recommendation for Space Data System Standards, CCSDS 202.0-B-3. Blue Book. Issue 3. Washington, D.C.: CCSDS, June 2001.
- [5] *Information Technology—Open Systems Interconnection—Basic Reference Model: The Basic Model.* International Standard, ISO/IEC 7498-1:1994. Geneva: ISO, 1994.
- [6] *Information Technology—Open Systems Interconnection—Basic Reference Model—Conventions for the Definition of OSI Services.* International Standard, ISO/IEC 10731:1994. Geneva: ISO, 1994.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

The latest issues of CCSDS documents may be obtained from the CCSDS Secretariat at the address indicated on page i.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

2 OVERVIEW

2.1 GENERAL

This Recommendation defines a protocol suitable for the transmission of files to and from spacecraft data storage. In addition to the purely file delivery related functions, the protocol also includes file management services to allow control over the storage medium.

The protocol is capable of operating in a wide variety of mission configurations, from relatively simple low earth orbit spacecraft to complex arrangements of orbiters and landers supported by multiple ground facilities and transmission links.

The protocol is independent of the technology used to implement data storage and requires only a few fundamental filestore capabilities in order to operate. It assumes two filestores, one within the spacecraft and one on the ground, and operates by copying data between the two filestore locations.

The protocol makes no assumptions about the information being transferred and can be utilized for a wide range of applications involving the loading, dumping, and control of spacecraft storage.

The protocol has been specifically designed to minimize the resources required for operation. It is also scaleable, so that only those elements required to fulfill the selected options are required to be implemented.

Although the protocol can operate over a wide range of underlying communication services, this Recommendation assumes the use of CCSDS packet services as defined in references [1] through [4].

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

2.2 ARCHITECTURE ELEMENTS

2.2.1 GENERAL

The architectural elements involved in the file delivery protocol are depicted in figure 2-1 and described below.




Figure 2-1: Architectural Elements of the File Delivery Protocol

2.2.2 USER

The protocol operates at the request of the CFDP user. The user interacts with the protocol using the service primitives defined in section 3.

A CFDP user is always a software task, which may or may not be operated by a human.

Each CFDP protocol entity has one user.

2.2.3 PROTOCOL ENTITY

The protocol entity consists of implementations of the *delivery procedures*, which allow immediate file delivery and manipulation over a single network hop. A single service interface is presented to the user.

2.2.4 FILESTORE

The protocol operates by copying files from storage medium to storage medium, and it is therefore assumed that all CFDP entities have access to a local storage capability. As the ways in which the storage capability is provided will vary, the protocol is built on the premise that any file or organized set of files (i.e., a filestore) can be described in terms of a single standard representation. This representation, called a '**virtual filestore**' is assigned a

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

standard set of attributes which are then used by the protocol to manage the file delivery process. In an implementation, the virtual filestore must be mapped to and from actual hardware and software which constitute the real filestore. This approach allows complete independence from the technology used to implement the filestore.

2.2.5 UNDERLYING COMMUNICATION SYSTEM

The protocol assumes the availability of a single conceptual underlying communication system, referred to as the '**Unitdata Transfer (UT) layer**', to which all CFDP entities in a given CFDP addressing domain have access. In order that the protocol may operate over a wide range of implementations, the services required of the UT layer have intentionally been kept as simple as possible; those services are assumed to be made available to any single CFDP entity at only a single conceptual service access point.

Because of the potential diversity of physical underlying services in use, no reuse of underlying protocol features is utilized beyond the addressing required to identify localities within the domain of the underlying communication system ('**UT addresses**', to which CFDP entities' names may be mapped using information contained in the management information base) and the delimitation of the CFDP Protocol Data Unit (CFDP PDU).

The relative independence of the CFDP protocol specifically implies that all multiplexing to support multiple file delivery transactions occurs internally in the CFDP protocol entity and that sequence auditing and error detection is provided by CFDP. PDU length information is incorporated in the CFDP PDU header to give independence from the underlying protocol and to simplify protocol processing.

It should be noted that although the CFDP protocol can operate over a service where data errors, data loss, and out-of-sequence delivery occur, it is not intended to compensate for networks where these effects are prevalent. Severe performance reductions will result if such an approach is taken. A simplified analysis of CFDP performance is detailed in the CFDP Green Book (CCSDS 720.1-G-1). This analysis will allow implementers to gauge likely performance based on file size, file segment size and bit error probability.

2.2.6 MANAGEMENT INFORMATION BASE

To perform a file delivery, a significant amount of information must be passed by the local user to its local CFDP entity and by the local CFDP entity to the remote CFDP entity. Typically, this data is static and may be stored within the CFDP entities as system tables, referred to as the *Management Information Base (MIB)*. The MIB contains such information as default values for user communications requirements, e.g., for address mapping, and for communication timer settings. The MIB is formally defined as part of the protocol specification in section 8.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

2.3 GENERAL CHARACTERISTICS

2.3.1 GENERAL

The CFDP enables the moving of a file from one filestore to another, where the two filestores are in general resident in separate data systems and often with an intervening space link. Functionally attached to each such file may be metadata of variable size, format, and semantics. The metadata consists of information associated with the file or the file transfer such as file names, filestore requests, or messages to the CFDP user. The functional concatenation of a file and all relevant metadata is termed an FDU, but it is also permissible for an FDU to consist of metadata only.

FDU transmission is accomplished by CFDP entities, each of which has access to exactly one filestore. A transaction is the end-to-end transmission of a single FDU between two CFDP entities. The initiation of the transaction causes a file copy operation to occur between two entities, the sender and the receiver.

As depicted in figure 2-2, the protocol procedures constitute the interaction between two protocol entities. The sending entity is the entity from which the file is copied in a file copy operation. The receiving entity is the entity to which the file is copied in a file copy operation.




Figure 2-2: CFDP Procedures

The reliability of a transaction is determined by whether the transaction is chosen to operate in unacknowledged mode or one of the acknowledged modes. In unacknowledged mode, data delivery failures are not reported to the sender and therefore cannot be repaired. Reception of the complete file is therefore not guaranteed. In acknowledged mode, the receiver informs the sender of any undelivered file segments or ancillary data. These are then retransmitted, guaranteeing complete file delivery.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

Each transaction results in the copying of a single FDU from source to destination. Within any single transaction, the subsidiary actions cancel, suspend, resume, and report may be performed.

The transaction is terminated when one of the following conditions applies:

- the file has been successfully transferred;
- a sending or receiving entity has disallowed the transaction;
- the transaction has been canceled because a fault was detected;
- the source or destination CFDP user has canceled the transaction.

2.3.2 USER OPERATIONS

The term ‘user operations’ refers to the use of the CFDP services offered by the local CFDP entity to cause the CFDP user of a remote CFDP entity to initiate additional CFDP transactions. User operations are implemented using the ‘Message to User’ capability of the protocol to forward an ‘order’ to the remote CFDP user which will in turn initiate a transaction with its local CFDP entity.

Five standard user operations are defined: proxy operations, remote status report operations, remote suspend and resume operations, and directory operations. Directory operations are used to request a listing of the contents of a specified directory in the remote user’s local filestore. Remote status report operations are used to request a report of the status of a specified CFDP transaction at the remote entity. Remote suspend and resume operations are used to request the suspension and resumption of a specified CFDP transaction at the remote entity. Proxy operations are used to initiate the delivery of a file from a remote CFDP entity to some other user, either to the local user itself (in which case the proxy operation functions as a ‘Get’) or to the user of some third CFDP entity. The FDU transmitted in a proxy operation normally contains a file but may contain only metadata, such as filestore directives or a Message to User containing an order to another remote CFDP user.

User operations are described in section 6.

2.3.3 ADDRESSING

Within any single CFDP network (i.e., any set of CFDP entities that is closed under communication), each CFDP entity is assigned a unique name. As each CFDP entity has access to exactly one filestore, identification of a CFDP entity implicitly identifies the associated filestore. At each CFDP entity location, address look-up capabilities are provided using information contained in the associated MIB. This look-up capability provides translation between the network-unique name of a CFDP entity and the corresponding UT address, which may in reality be an Internet address, radio device buffer, APID, virtual channel number, or other implementation-specific mechanism.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)**2.3.4 RETRANSMISSION STRATEGIES**

The quality of service offered by the protocol is selectable, according to mission requirements and transmission capability, and ranges from an unacknowledged option, whereby a file is transmitted with no attempt at completeness should errors occur (errors will be detected and data discarded), to a fully acknowledged option providing error recovery through retransmission. For the acknowledged modes of operation, several sub-options may be selected by the receiver. These sub-options relate to release time of any Negative Acknowledgments (NAKs) and range from immediate release to deferred release (whereby any NAKs are stored until the assumed end of the transmission). The extent of available retransmission strategies is more completely described in section 4.

2.3.5 VIRTUAL FILESTORE

The virtual filestore concept provides for a mapping of protocol filestore directives to actual filestore manipulation. The way in which this mapping is performed in an implementation is a local matter. Allowances are made in the protocol for inclusion of additional filestore directives using the Type-Length-Value (TLV) capability of the Metadata PDU.

To enable interoperability, this Recommendation assumes a minimum set of capabilities from the virtual filestore as follows:

- create file;
- delete file;
- rename file;
- append file;
- replace file;
- create directory;
- remove directory;
- list directory.

In some circumstances, it is advantageous for the CFDP protocol to be able to recognize record boundaries within the file. If this option is to be used, the filestore must have the capability to make the distinction between such files and those which are to be treated as a stream of octets.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

2.4 OVERVIEW OF INTERACTIONS

Figure 2-3 shows the details of a Copy operation. (In all following figures in this section, dashed lines denote optional actions.)




Figure 2-3: Copy Operations, Sequence of Events

All copy operations start with transmission of the Metadata, followed by transmission of the file segments and a PDU to indicate the End of File (EOF). Optional service primitives may be issued at the receiving entity to announce receipt of individual file segments; notification of receipt of Metadata is mandatory.

For reliable transactions, a number of features are added. NAKs are used to request retransmission of lost data. Receipt of the EOF PDU is ensured via an EOF acknowledgement. Since lost data may still be outstanding after the EOF sequence, a Finished PDU is sent when all file data has been successfully assembled. Delivery of this PDU is ensured through use of the Finished acknowledgement.

When the file transmission task is completed the sending and receiving entities issue Notices of Completion. These Notices of Completion are abstract internal events which are not exposed to the CFDP user. They are used to inform the Put procedures (described later in this section) of completion of the file transmission task.

The Put transaction is initiated by a Put.request from a CFDP user to the source entity. The Put.request results in initiation of the FDU transmission procedure and also of the first (possibly only) copy operation. The Put.request also results in the notification of a

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

Transaction identifier to the application so that the transaction may subsequently be unambiguously identified. A Notice of Completion at the source entity causes it to issue a Transaction-Finished.indication. This process is optional at the destination entity. The Put transaction is illustrated in figure 2-4.




Figure 2-4: Put Operations, Sequence of Events

When the source of the file to be transferred is other than the local filestore, the requesting user must initiate a Put transaction containing a message to the user of the remote CFDP entity, the 'proxy user'. This message requests that the proxy user in turn submit a Put.request to that entity. The destination of the requested Put transaction may be the original requesting user (in which case the proxy operation functions as a 'Get') or some third CFDP user. On completion of the second transaction, the proxy user initiates a third transaction to notify the original requesting user of the completion of the proxy operation. A proxy put operation is illustrated in figure 2-5.




Figure 2-5: Proxy Put Operations, Sequence of Events

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

3 SERVICE DESCRIPTION

3.1 SERVICES AT THE USER INTERFACE

3.1.1 The services provided by the protocol shall be made available to the CFDP user and shall include the following:

- a) initiating the transmission of files between filestores;
- b) initiating filestore operations on remote filestores;
- c) receiving events related to the operation of current transactions;
- d) requesting status information related to the current transactions;
- e) sending or receiving messages associated with the current transactions;
- f) suspending, resuming, or canceling the transmission of a current transaction.

3.1.2 The CFDP entity shall be implemented such that virtually any number of transactions may be concurrently in various stages of transmission or reception at a single CFDP entity.

NOTE – To clarify: the implementation must be able to accept a Put.request primitive, and thereupon initiate a new transaction, prior to the completion of previously initiated transactions. The completion of a transaction encompasses the initial transmission of file data by the source entity, the reception of some or all of that data by the destination entity, and any consequent acknowledgment and retransmission data exchange that may be necessary between the two entities. The requirement for concurrent transaction support therefore does not necessarily imply that the implementation must be able to begin initial transmission of file data for one transaction while initial transmission of file data for one or more other transactions is still in progress. (But neither is support for this functional model precluded.)

3.2 SUMMARY OF PRIMITIVES

3.2.1 The CFDP service shall consume the following request primitives:

- a) Put.request;
- b) Report.request;
- c) Cancel.request;
- d) Suspend.request;
- e) Resume.request.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

3.2.2 The CFDP service shall deliver the following indication primitives:

- a) Transaction.indication;
- b) EOF-Sent.indication;
- c) Transaction-Finished.indication;
- d) Metadata-Recv.indication;
- e) File-Segment-Recv.indication;
- f) Report.indication;
- g) Suspended.indication;
- h) Resumed.indication;
- i) Fault.indication;
- j) Abandoned.indication.

3.3 SUMMARY OF PARAMETERS

NOTE – The availability and use of parameters for each primitive are indicated in 3.5, where parameters that are optional are identified with square brackets [thus]. The following definitions apply.

3.3.1 The *destination CFDP entity ID* parameter shall uniquely identify the CFDP entity **to** which the FDU is to be sent.

3.3.2 The *source CFDP entity ID* parameter shall uniquely identify the CFDP entity **from** which the FDU is to be sent.

3.3.3 The *source file name* parameter

- a) shall contain the full path name at which the file to be copied is located at the filestore associated with the source entity;
- b) shall be omitted when the FDU to be Put contains only metadata, such as a message to a user or a standalone filestore request.

3.3.4 The *destination file name* parameter

- a) shall contain the full path name to which the file to be copied will be placed at the filestore associated with the destination entity;
- b) shall be omitted when the FDU to be Put contains only metadata, such as a message to a user or a standalone filestore request.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

3.3.5 The *segmentation control* parameter

- a) shall indicate whether the file being delivered is to be segmented as an array of octets or as an array of variable-length records;
- b) shall be omitted when local and remote file names are omitted.

3.3.6 The *Transaction ID* parameter shall uniquely identify a single instance of FDU delivery and shall contain the ID of the source CFDP entity together with a sequence number that is specific to that entity.

NOTES

- 1 At any moment, any given transaction ID is unique within the CFDP addressing domain that encompasses the source CFDP entity.
- 2 The entity ID and transaction sequence number are variable in length to accommodate differing mission requirements. A common parsing scheme is defined to allow full interoperability despite differing parameter lengths.

3.3.7 The *Condition code* parameter shall provide additional information on some change in transaction status.

3.3.8 The *Status report* parameter shall indicate the status of the indicated file delivery transaction. The format and scope of the *status report* parameter are specific to the implementation. It could contain information such as:

- a) whether the transaction is finished, canceled, suspended, or active;
- b) what extents of the FDU are known to have been successfully received by the receiving CFDP entity;
- c) what extents of the FDU are known to have been transmitted by the sending CFDP entity.

3.3.9 *Fault handler overrides*:

- a) If included, the optional *fault handler overrides* shall indicate the actions to be taken upon detection of one or more types of fault condition. Each fault handler override shall identify both a type of fault condition to be handled and the action to be taken in the event that a fault of this type is detected; each such action shall be one of the following:
 - cancel the file delivery transaction,
 - suspend the transaction,
 - ignore the fault but issue a `Fault.indication` primitive to the local CFDP user, or
 - abandon the transaction and issue an `Abandoned.indication` primitive to the local CFDP user.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

- b) The fault conditions for which handler overrides may be specified are a subset of the conditions listed in table 5-5, later in this specification. The listed conditions that are *not* fault conditions are 'No error', 'Suspend request received', and 'Cancel request received'.
- c) For each type of fault condition for which no *fault handler override* is included among the service request parameters, a default handler shall be selected according to the contents of the MIB.

3.3.10 If included, the optional *transmission mode* parameter shall override the default transmission mode. The values of the transmission mode parameter are 'acknowledged' or 'unacknowledged'.

3.3.11 If included, the optional *Messages to User* parameter shall be transmitted at the beginning of the transaction and delivered to the destination CFDP user upon receipt. Certain messages are defined in the Proxy, Remote Status Report, and Directory Operations section to allow remote initiation of CFDP transactions.

3.3.12 *Filestore Requests:*

- a) if included, the optional *filestore requests* shall be transmitted at the beginning of the transaction and shall be acted upon by the destination entity when all data transfer activities of the transaction are completed;
- b) to indicate the action to be taken, each *filestore request* shall include sub-parameters as follows:
 - *action*,
 - *file name 1*,
 - *file name 2* (present for certain values of the *action* parameter);
- c) the *action* sub-parameter may take the values of:
 - *create file*,
 - *delete file*,
 - *rename file* (*file name 2* present),
 - *append file* (*file name 2* present),
 - *replace file* (*file name 2* present),
 - *create directory*,
 - *remove directory*,
 - '*deny*' *file* (like *delete*, but does not fail if file does not exist),
 - '*deny*' *directory* (like *remove*, but does not fail if directory does not exist);

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

- d) when the value of the *file name 1* or *file name 2* sub-parameter is equal to the value of the *destination file name* parameter, the file to which the filestore request pertains shall be the newly delivered file;
- e) in the case of multiple *filestore requests* in the same transaction, the source entity shall preserve the order in which the requests were submitted and the destination entity shall execute them in this same order.

3.3.13 The *Filestore Responses* parameter shall indicate whether the indicated *filestore requests* in the indicated transaction succeeded or failed and shall include the following additional information for each filestore request:

- if it failed, an explanation;
- if it succeeded, a report in action-specific format (if relevant).

3.3.14 The *Filestore Responses* parameter shall not be used to convey directory listing information; the transfer of directory listing information is achieved via Directory Operations transactions.

3.3.15 The *flow label* parameter may optionally be used to support prioritization and preemption schemes.

NOTE – The *flow label* parameter should be taken as a hint to the order in which PDUs should be transmitted when the opportunity arises, but the manner in which flow labels are used is strictly an implementation matter.

3.3.16 The *offset* parameter shall indicate a displacement from the beginning of the file.

3.3.17 The *length* parameter shall indicate the number of octets of file data received.

3.3.18 The *progress* parameter shall report on current file transmission or reception progress, as defined earlier.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

3.4 SERVICES REQUIRED OF THE UNDERLYING COMMUNICATION SYSTEM

The service primitives and parameters required to access the services of the Unitdata Transfer (UT) layer are:

UNITDATA.request	(UT_SDU, UT Address)
UNITDATA.indication	(UT_SDU, UT Address)

NOTES

- 1 The service assumed of the underlying layer is as simple as possible to allow CFDP to be as generally applicable as possible. For the purposes of this specification the service is referred to as the UT service and the delimited data unit it transfers is the UT Service Data Unit (UT_SDU). Although the UT layer is conceptually a single service, in practice CFDP might use several different physical underlying communication systems at different times, or even concurrently, depending on the remote entities with which it is in communication. In a purely CCSDS network the sole service could be the CCSDS Path or Packet service, and the UT_SDU would be the data field of a CCSDS packet.
- 2 The format and contents of the UT Address parameter depend on the addressing capabilities and conventions of the underlying service. Information in the MIB must enable translation between CFDP entity names and the corresponding UT addresses.
- 3 The CFDP protocol operates over a single conceptual UT service access point. In practice, the implementation of the UT layer is not constrained to provide all services through a single physical service access point. Different physical service access points would necessarily be provided if different physical underlying communication systems were in use concurrently. A given implementation might even maintain a different physical service access point for each remote entity with which CFDP is currently (at any moment) in direct communication.
- 4 The above list of mandatory UT layer service primitives does not imply that the UT layer is prohibited from supporting additional services for the convenience of the CFDP implementation. Possible additional primitives that might prove valuable include:
 - An indication whenever the UT layer is prepared to accept another PDU for transmission to the UT layer instance at an identified UT address. (This indication could be used to implement data flow control. Destination UT address might be needed in the indication because the UT layer might be transmitting concurrently to multiple UT addresses.)
 - An indication whenever the UT layer completes transmission of a UT_SDU whose content is a CFDP PDU to which Positive Acknowledgment procedures apply. (This indication could be used to start positive acknowledgment timers.)

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

- 5 The assumed minimum underlying quality of service is:
- with possible errors in the delivered UT_SDUs;
 - incomplete, with some UT_SDUs missing;
 - in sequence; i.e., the delivered UT_SDUs are delivered in the order in which they were transmitted. (In-sequence arrival is specifically assumed in the design of the immediate, asynchronous, and prompted lost segment detection modes and the Keep Alive mechanism.)

The CFDP protocol can operate over a service where data errors and data loss occur; and when no incremental lost segment detection procedures are in effect, even out-of-sequence data arrival can be tolerated. However, the protocol is not intended to compensate for networks where these effects are prevalent. Severe performance reductions will result if such an approach is taken.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

3.5 CFDP SERVICE PRIMITIVES

3.5.1 Put.request

3.5.1.1 Function

The Put.request primitive shall be used by the application to request delivery of a file from the source filestore to a destination filestore.

3.5.1.2 Semantics

Put.request shall provide parameters as follows:

Put.request	(destination CFDP entity ID, [source file name], [destination file name], [segmentation control], [fault handler overrides], [flow label], [transmission mode], [messages to user], [filestore requests])
-------------	---

3.5.1.3 When Generated

Put.request is generated by the source CFDP user at any time.

3.5.1.4 Effect on Receipt

Receipt of Put.request shall cause the CFDP entity to initiate source entity put procedures.

3.5.1.5 Additional Comments

None.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

3.5.2 Cancel.request**3.5.2.1 Function**

The Cancel.request primitive shall be used to request that a transaction be canceled.

3.5.2.2 Semantics

Cancel.request shall provide parameters as follows:

Cancel.request (transaction ID)

3.5.2.3 When Generated

Cancel.request is generated by any CFDP user at any time during the lifetime of any transaction.

3.5.2.4 Effect on Receipt

Receipt of Cancel.request shall cause a Notice of Cancellation at the local entity.

3.5.2.5 Additional Comments

None.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

3.5.3 Suspend.request

3.5.3.1 Function

The Suspend.request primitive shall be used to request that a transaction be suspended.

3.5.3.2 Semantics

Suspend.request shall provide parameters as follows:

Suspend.request (transaction ID)

3.5.3.3 When Generated

Suspend.request is generated by any CFDP user at any time during the lifetime of any transaction, except that for a transaction sent in unacknowledged mode it can only be generated by the transaction's source user.

3.5.3.4 Effect on Receipt

Receipt of Suspend.request shall cause a Notice of Suspension at the local entity.

3.5.3.5 Additional Comments

None.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

3.5.4 Resume.request

3.5.4.1 Function

The Resume.request primitive shall be used to request that a suspended transaction be resumed.

3.5.4.2 Semantics

Resume.request shall provide parameters as follows:

Resume.request (transaction ID)

3.5.4.3 When Generated

Resume.request is generated by any CFDP user at any time during the lifetime of any transaction, except that for a transaction sent in unacknowledged mode it can only be generated by the transaction's source user.

3.5.4.4 Effect on Receipt

Receipt of Resume.request shall have no effect on any transaction that is not currently suspended. For a transaction that is currently suspended, it shall cause the local CFDP entity to initiate Resume procedures.

3.5.4.5 Additional Comments

User application developers may find it advisable to provide automated support for one special case of transaction resumption, which applies to any transaction which the user application can determine is currently suspended solely due to transaction inactivity (i.e., as a result of an Inactivity fault). On receipt of any service indication produced because of arrival of a PDU for such a transaction, the user application might infer that the transaction's inactivity is ended and thereupon automatically resume the transaction.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

3.5.5 Report.request

3.5.5.1 Function

The Report.request primitive shall be used to request a report on the status of a transaction.

3.5.5.2 Semantics

Report.request shall provide parameters as follows:

Report.request (transaction ID)

3.5.5.3 When Generated

Report.request is generated by any CFDP user at any time during the lifetime of any transaction.

3.5.5.4 Effect on Receipt

Receipt of Report.request shall cause the CFDP entity to return a Report.indication primitive to the CFDP user.

3.5.5.5 Additional Comments

None.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

3.5.6 Transaction.indication**3.5.6.1 Function**

The Transaction.indication primitive shall be used to indicate the Transaction identifier to the source CFDP user.

3.5.6.2 Semantics

Transaction.indication shall provide parameters as follows:

Transaction.indication (transaction ID)

3.5.6.3 When Generated

Transaction.indication shall be generated on receipt of a Put.request primitive.

3.5.6.4 Effect on Receipt

The effect on receipt of Transaction.indication by a CFDP user is undefined.

3.5.6.5 Additional Comments

The Transaction ID parameter is returned by the CFDP entity and provides the source CFDP user with a means of uniquely identifying the associated transaction thereafter.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

3.5.7 EOF-Sent.indication

3.5.7.1 Function

The EOF-Sent.indication primitive shall be used to notify the source CFDP user of the initial transmission of a transaction's EOF PDU.

3.5.7.2 Semantics

EOF-Sent.indication shall provide parameters as follows:

EOF-Sent.indication (transaction ID)

3.5.7.3 When Generated

EOF-Sent.indication shall be generated on initial transmission of an EOF PDU, at the conclusion of initial transmission of a transaction's Metadata and file data.

3.5.7.4 Effect on Receipt

The effect on receipt of EOF-Sent.indication by a CFDP user is undefined.

3.5.7.5 Additional Comments

Generation of EOF-Sent.indication is optional. The user may choose to base a flow control system in part on this mechanism, e.g., to refrain from submitting a new Put.request primitive until the EOF-Sent.indication resulting from the previous one has been received.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

3.5.8 Transaction-Finished.indication**3.5.8.1 Function**

The Transaction-Finished.indication primitive shall be used to indicate to the source or destination CFDP user that the transaction is complete and that the source CFDP user is authorized to modify or delete any retransmission buffer (file) that it was sharing with the protocol entity to conserve persistent storage space.

3.5.8.2 Semantics

Transaction-Finished.indication shall provide parameters as follows:

Transaction-Finished.indication	(transaction ID, [filestore responses], [status report], condition code, file status, delivery code)
---------------------------------	---

3.5.8.3 When Generated

Transaction-Finished.indication is generated on Notice of Completion of a file transmission procedure either at the source CFDP entity or, optionally, at the destination CFDP entity.

3.5.8.4 Effect on Receipt

The effect on receipt of Transaction-Finished.indication by an application is undefined.

3.5.8.5 Additional Comments

Transaction-Finished.indication is always generated by the source CFDP entity and can also be generated by the destination CFDP entity. The condition code indicates the condition under which the transaction was finished.

CCSDS RECOMMENDATION FOR CCSDS FILE DELIVERY PROTOCOL (CFDP)

3.5.9 Metadata-Recv.indication

3.5.9.1 Function

The Metadata-Recv.indication primitive shall be used to indicate to the destination CFDP user that the metadata associated with a transaction has been received.

3.5.9.2 Semantics

Metadata-Recv.indication shall provide parameters as follows:

Metadata-Recv.indication	(transaction ID, source CFDP entity ID, [source file name], [destination file name], [messages to user])
--------------------------	--

3.5.9.3 When Generated

Metadata-Recv.indication is generated on receipt of a Metadata PDU.

3.5.9.4 Effect on Receipt

The effect on receipt of Metadata-Recv.indication by the destination CFDP user is undefined.

3.5.9.5 Additional Comments

None.