

BS ISO 1823:2015



BSI Standards Publication

Rubber hose and hose assemblies for oil suction and discharge service — Specification

bsi.

...making excellence a habit.
AVA Documents™
Document Sharing Hub

National foreword

This British Standard is the UK implementation of ISO 1823:2015.

The UK participation in its preparation was entrusted to Technical Committee PRI/66, Rubber and plastics tubing, hoses and hose assemblies.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2015. Published by BSI Standards Limited 2015

ISBN 978 0 580 71578 5

ICS 75.200; 83.140.40

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 28 February 2015.

Amendments issued since publication

Date	Text affected
------	---------------

INTERNATIONAL STANDARD

BS ISO 1823:2015

ISO
1823

Second edition
2015-02-15

Rubber hose and hose assemblies for oil suction and discharge service — Specification

*Flexibles en caoutchouc pour chargement et déchargement des
produits pétroliers — Spécification*



Reference number
ISO 1823:2015(E)
Documents
Document Sharing Hub
© ISO 2015



COPYRIGHT PROTECTED DOCUMENT

© ISO 2015

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Classificaiton	2
4.1 General	2
4.2 Types	2
4.3 Classes	2
4.4 Grades	3
4.5 Pressure and designations	3
5 Materials and construction	4
5.1 Materials	4
5.1.1 Lining	4
5.1.2 Reinforcing plies	4
5.1.3 Wire helices	4
5.1.4 Internal and armouring wire helices	4
5.1.5 Cover	4
5.2 Construction	4
5.2.1 Type R: Electrically continuous	4
5.2.2 Type A: Electrically continuous	5
5.2.3 Type S: Electrically continuous or electrically discontinuous	5
5.2.4 Type L: Electrically continuous or electrically discontinuous	6
6 End connections	6
6.1 Nipples and flanges	6
6.2 Method of attaching end connections to the hose	7
6.3 Electrically discontinuous assemblies	7
6.4 Electrically continuous assemblies	7
7 Dimensions and tolerances	8
7.1 Dimensions	8
7.2 Length	8
8 Physical properties	9
8.1 Rubber compounds	9
8.2 Finished hose assemblies	9
9 Type tests	11
10 Frequency of testing	11
11 Test report	12
12 Marking	12
Annex A (informative) Information to be supplied by the purchaser	13
Annex B (informative) Recommendations for packaging and transportation of oil suction and discharge hose assemblies	14
Annex C (informative) Masses	15
Annex D (normative) Wet adhesion test	16
Annex E (normative) Hydrostatic test for suction and discharge hose assemblies	18
Annex F (normative) Test frequency for type and routine test	20
Annex G (informative) Test frequency for production test	21

Bibliography	22
---------------------------	-----------

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 45, *Rubber and rubber products*, Subcommittee SC 1, *Rubber and plastics hoses and hose assemblies*.

This second edition of ISO 1823 cancels and replaces ISO 1823-1:1997 and ISO 1823-2:1997. Considering the actual market situations, two classes (the lowest and highest aromatics content) and one grade for maximum working pressure have been added in [4.3](#) and [4.4](#), respectively.

Introduction

This International Standard specifies minimum requirements for the satisfactory performance of wire- or textile-reinforced rubber hose assemblies of both smooth and rough bore types for oil suction and discharge services. The hoses are commonly used for transferring crude oil and liquid petroleum products, other than liquefied petroleum gas and natural gas, to and from tanker and bunkering vessels or for similar duties ashore.

Specific details of the construction of hoses are not rigidly defined in this International Standard since it is felt that this could restrict the introduction of improved methods of construction. The hose assemblies have been classified and designated in terms of service pressure, which includes an allowance for surge pressure and which equates to the factory test pressure. To keep this specification in line with other documents, this factory test pressure is also defined as the maximum working pressure (see [Table 1](#)). It is the responsibility of the user to determine the appropriate working pressure, which will depend on the severity of the user's operating conditions and on the service life that is expected of the hose assembly.

It is necessary for the purchaser to provide certain information about the hose assembly and its intended use at the time of enquiry and/or order; this information is listed in [Annex A](#) (informative). Recommendations concerning packaging and transportation are given in [Annex B](#) (informative) and expected masses of hoses, in kilograms per metre of free length, are given in [Annex C](#) (informative).

Rubber hose and hose assemblies for oil suction and discharge service — Specification

1 Scope

This International Standard specifies the characteristics of four types of oil suction and discharge hose assemblies used for the conveyance of petroleum, including crude oils and other liquid petroleum products. Each type being divided into three classes depend on the aromatic contents. It is not suitable for liquefied petroleum gas and natural gas.

Hose assemblies to this International Standard can be used in the temperature range $-20\text{ }^{\circ}\text{C}$ to $80\text{ }^{\circ}\text{C}$.

The hoses specified are in the range of nominal size 50 to 500 and can be types of smooth bore, rough bore, armoured rough bore, and light weight.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 228, *Pipe threads where pressure-tight joints are not made on the threads*

ISO 1402, *Rubber and plastics hoses and hose assemblies — Hydrostatic testing*

ISO 1431-1, *Rubber, vulcanized or thermoplastic — Resistance to ozone cracking — Part 1: Static and dynamic strain testing*

ISO 1460, *Metallic coatings — Hot dip galvanized coatings on ferrous materials — Gravimetric determination of the mass per unit area*

ISO 1461, *Hot dip galvanized coatings on fabricated iron and steel articles — Specifications and test methods*

ISO 1817, *Rubber, vulcanized or thermoplastic — Determination of the effect of liquids*

ISO 2063, *Metallic and other inorganic coatings — Thermal spraying — Zinc, aluminium and their alloys*

ISO 4649, *Rubber, vulcanized or thermoplastic — Determination of abrasion resistance using a rotating cylindrical drum device*

ISO 7005-1, *Pipe flanges — Part 1: Steel flanges for industrial and general service piping systems*

ISO 7233, *Rubber and plastics hoses and hose assemblies — Determination of resistance to vacuum*

ISO 8031, *Rubber and plastics hoses and hose assemblies — Determination of electrical resistance and conductivity*

ISO 8033, *Rubber and plastics hoses — Determination of adhesion between components*

ISO 8330, *Rubber and plastics hoses and hose assemblies — Vocabulary*

ISO 10619-1, *Rubber and plastics hoses and tubing — Measurement of flexibility and stiffness — Part 1: Bending tests at ambient temperature*

ISO 15614-1, *Specification and qualification of welding procedures for metallic materials — Welding procedure test — Part 1: Arc and gas welding of steels and arc welding of nickel and nickel alloys*

BS 3592-1, *Steel wire for hose reinforcement — Part 1: Specification for coated round and flat steel wire for rubber hose reinforcement*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 8330 and the following apply.

3.1 electrically bonded hose assembly
hose assembly that uses a metallic wire connection to create a low-resistance electrical connection between the end connection

3.2 electrically discontinuous hose assembly
hose assembly that incorporates an electrical insulation between the end of the helical wire or/and wire cord reinforcement and on or both couplings

4 Classification

4.1 General

WARNING — Careful consideration needs to be given before the use of electrically discontinuous hoses for transferring liquids known to generate static charges. In no circumstances should more than one length of electrically discontinuous hose be used in an individual transfer pipeline and effective electrical continuity to earth from both ends of the electrically discontinuous hose should be maintained.

4.2 Types

Hose assemblies for this application are classified according to end-use as follows:

- **Type R**, rough bore hose assemblies for dock operation and intended for situations where a relatively stiff, heavy, and robust assembly can be used. The lining of the rubberized fabric is supported and reinforced by an internal (hot-dipped) zinc coated steel wire helix. Type R assemblies are electrically continuous;
- **Type A**, armoured rough bore hose assemblies for dock operation. In addition to an internal zinc coated steel wire helix, there shall be external helical armour of a similar material. Type A hoses are electrically continuous and can be lighter and more flexible than type R;
- **Type S**, smooth bore hose assemblies for dock operation where flexibility and lightness are important. Type S hose assemblies can be electrically continuous or electrically discontinuous (see Warning);
- **Type L**, hose assemblies for dock and general discharge service where greater flexibility, lower weight, and ease of handling are of primary consideration. Type L hose assemblies can be electrically continuous or electrically discontinuous. They are only suitable for discharge applications (see Warning).

4.3 Classes

Each type of hose assemblies shall be designated according to three classes, depending on the conveyance of petroleum products containing the maximum aromatics content:

- **Class 25**: For oil and gasoline service (suitable for below 25 % aromatics content);
- **Class 50**: For oil and gasoline service (up to and including 50 % max. aromatics content);
- **Class 100**: For oil and gasoline service (suitable for up to 100 % aromatics content).

NOTE For the determination of aromatics content, see ISO 3837.

4.4 Grades

Each class is further divided into five grades depending on the maximum working pressure:

- **Grade 5:** For maximum working pressure 0,5 MPa (5 bar);
- **Grade 7:** For maximum working pressure 0,7 MPa (7 bar);
- **Grade 10:** For maximum working pressure 1,0 MPa (10 bar);
- **Grade 15:** For maximum working pressure 1,5 MPa (15 bar);
- **Grade 20:** For maximum working pressure 2,0 MPa (20 bar).

4.5 Pressure and designations

Each type of hose assembly shall be designated according to the type letters R, A, S, or L, followed by the class figures, and followed by the grade figures which indicate maximum working pressure given in [Table 1](#).

Table 1 — Grade description, pressure and designation

Grade description	Maximum working pressure		Proof pressure test (maximum 5 min)		Designation ^a
	MPa	bar	MPa	bar	
5	0,5	5	0,75	7,5	R25-5 A50-5 S25-5 L50-5
7	0,7	7	1,05	10,5	R50-7 R100-7 A50-7 A100-7 S50-7 S100-7 L50-7 L100-7
10	1,0	10	1,50	15	R25-10 R50-10 R100-10 A50-10 A100-10 S25-10 S50-10 S100-10 L50-10 L100-10
15	1,5	15	2,25	22,5	R25-15 R50-15 R100-15 A50-15 A100-15 S25-15 S50-15 S100-15 L50-15 L100-15
20	2,0	20	3,00	30,0	R50-20 R100-20 S50-20 S100-20
^a Other combinations are available if required. See the second paragraph of Introduction.					

For the purposes of this International Standard, the maximum working pressure includes an allowance for surge pressures above the normal operating pressure.