BS ISO 20679:2025

BSI Standards Publication

Ships and marine technology — Marine environment protection — Testing of ship biofouling in-water cleaning systems

Documents
Document Sharing Hub

Full document details: BS ISO 20679:2025

National foreword

This British Standard is the UK implementation of ISO 20679:2025.

The UK participation in its preparation was entrusted to Technical Committee SME/32, Ships and marine technology - Steering committee.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2025
Published by BSI Standards Limited 2025

ISBN 978 0 539 27030 3

ICS 13.020.99; 47.020.99

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 January 2025.

Amendments/corrigenda issued since publication

Date	Text affected

Documents
Document Sharing Hub

Full document details: BS ISO 20679:2025

International Standard

ISO 20679

First edition
2025-01

Ships and marine technology — Marine environment protection — Testing of ship biofouling in-water cleaning systems

Navires et technologie maritime — Protection de l'environnement marin — Essais des systèmes de nettoyage des salissures biologiques sans sortir le navire de l'eau

Reference number
ISO 20679:2025(en)

© ISO 2025

Documents
Document Sharing Hub

Full document details: BS ISO 20679:2025

COPYRIGHT PROTECTED DOCUMENT

© ISO 2025

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Documents
Document Sharing Hub
Full document details: BS ISO 20679:2025

Contents

Page

Foreword ... **v**
Introduction ... **vi**
1 Scope ... **1**
2 Normative references ... **1**
3 Terms and definitions ... **1**
4 Fundamental information needed for testing of IWC systems ... **3**
4.1 Factors that can impact performance ... 3
4.2 Fundamental parameters ... 4
5 Test experimental design ... **6**
5.1 General ... 6
5.2 Classification of IWC system application for testing ... 8
5.3 Duration and extent of testing ... 9
5.3.1 General ... 9
5.3.2 Proactive systems ... 9
5.3.3 Reactive systems ... 9
6 Quantification of biofouling removal and prevention ... **10**
6.1 IWC systems ... 10
6.1.1 General ... 10
6.1.2 Proactive systems ... 10
6.1.3 Reactive systems ... 10
6.2 Fouling rating ... 10
6.3 Control and treated test locations ... 11
6.4 Biofouling survey sampling methods ... 12
6.4.1 General ... 12
6.4.2 Hull areas ... 12
6.4.3 Niche areas ... 13
6.4.4 Hull and niche areas ... 14
6.4.5 Proactive systems ... 14
6.5 Dive survey sampling method during low visibility ... 16
6.5.1 Hull areas ... 16
6.5.2 Niche areas ... 16
6.6 Environmental characteristics to quantify ... 17
7 Quantification of changes to water quality ... **17**
7.1 Water quality measures as proxies for broad environmental impacts ... 17
7.1.1 General ... 17
7.1.2 Proactive systems ... 17
7.1.3 Reactive systems ... 17
7.2 Water quality parameters to quantify ... 17
7.3 Water quality sample collection ... 19
7.4 Environmental characterization ... 21
8 Quantification of debris processing and effluent ... **21**
8.1 Overview ... 21
8.2 Sampling the debris processing unit ... 22
8.3 Water quality parameters to quantify ... 23
8.4 Solid waste disposal ... 24
9 Quantification of IWC impact on ship coatings ... **24**
10 Data management ... **24**
10.1 System for data management ... 24
10.1.1 General ... 24
10.1.2 Data quality objectives ... 25
10.1.3 Data quality indicators ... 25

© ISO 2025 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 20679:2025

10.2 Data recording and archiving ... 25
10.3 Data analysis ... 25
10.3.1 Overview ... 25
10.3.2 Quality assurance and quality control ... 26
10.3.3 Measurement uncertainty ... 26

11 Quality assessments ... 26
11.1 Fundamental principles ... 26
11.2 Technical audits ... 27
11.2.1 Overview ... 27
11.2.2 Technical system audit ... 27
11.2.3 Audit of data quality ... 27
11.3 Data quality assessment ... 27
11.4 Non-conforming work and corrective action ... 28
11.5 Audit reporting ... 28

12 Human health and environmental safety ... 28

13 Test report ... 29

Annex A (informative) **Example of biofouling surveys of various surface types ... 30**

Annex B (informative) **Optional method for additional determinations of IWC impacts on ship coatings ... 31**

Bibliography ... 33

© ISO 2025 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 20679:2025

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 8, *Ships and marine technology*, Subcommittee SC 2, *Marine environment protection*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO 2025 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 20679:2025

Introduction

Like all substrates placed in coastal waters, the wetted surfaces of ships are quickly colonized by a succession of diverse sessile or sedentary micro- and macro-organisms, collectively known as biofouling.[1][2][3] The adverse effects of biofouling on ships and their operations are well known and there is a long history of attempting various biofouling management approaches.[4]

Negative impacts of biofouling on the shipping industry include:

— reduced ship performance and fuel efficiency;[5][6][7][8]

— corrosion and decreased durability;[9][10]

— increased greenhouse gas emissions;[11][12]

— failure to meet associated legal/contractual requirements;[13][14]

— increased underwater noise;[15]

— unintended translocation of aquatic species.[16][17][18]

In recent decades, the importance of ship biofouling as a pathway for invasive aquatic species translocations has become increasingly apparent.[17][18][19][20][21] Entire biological communities can be moved around the world by oceangoing ships and a substantial number of species, including pathogens, can be introduced as a result.[22][23][24] While not all invasive aquatic species have immediate noticeable or significant impacts, a subset of invasive aquatic species have a broad range of effects on the aquatic environment and the communities reliant upon local ecosystem services.[25][26][27] Guidelines and regulations to prevent invasive aquatic species introductions via ship biofouling are beginning to emerge to protect environmental, economic, social, and cultural values (e.g. see References [12] [28] [29]).

The International Maritime Organization (IMO) defines antifouling systems (AFS) as various approaches used on a ship to control or prevent the attachment of unwanted organisms.[30] The primary AFS are coatings, applied during dry-docking to surfaces below the maximum waterline of ships, which are designed to either prevent macrofouling attachment (using biocides) or reduce adhesion (foul-release) to wetted surfaces.[31][32] In some areas (e.g. Baltic Sea), non-ablative or non-polishing hard coatings are used in combination with regular cleaning as a fouling prevention strategy.[33]

The service life of modern coatings for commercial ships is typically five years (e.g. see Reference [32] [34]). Despite substantial improvements over the past 40 years, surface coatings do not consistently prevent biofouling accumulation on all ship surfaces over the course of their service lives.[35][36] Accumulations tend to occur as coatings age[37][38] and when ships have extended stationary periods.[13][14][39][40]

Even when antifouling coatings are used, there are also substantial areas of ships' immersed surfaces that are more prone to biofouling[41][42][43][44] because they:

— cannot be painted (e.g. anodes);

— are prone to damage (e.g. bulbous bow, tug and fender points, areas below anchor chain);

— are challenging to coat (e.g. dry-dock blocking areas); or

— are sub-optimal for coating performance (e.g. gratings, rudders, propellers, and sea chests).

Given the existing limitations of coatings, especially during extended periods between dry-docking, in-water cleaning (IWC) of ship biofouling (within a coating's service life) is often required or advantageous.[12]

IWC of biofouling – used to either maintain or reset ship immersed surfaces to a hydrodynamically smooth state – is a common approach to increase ship performance and fuel efficiency between dry-dockings.[8][45] IWC is also recognized as beneficial for reducing both greenhouse gas emissions[11][12][46] and biosecurity risks.[47][48]

© ISO 2025 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 20679:2025

IWC systems typically involve the use of diver- or remotely-operated cleaning units (i.e. cleaning carts) that remove biofouling from hull surfaces.[49][50] IWC is generally described as either proactive or reactive.[47] Proactive IWC is the periodic removal or reduction of biofilm growth (i.e. microfouling or slime layer) on ship surfaces. Proactive IWC also removes newly settled or attached microscopic stages of macrofouling organisms, to ultimately minimize or prevent macrofouling growth.[47][51] Reactive IWC is typically used to remove already established macrofouling organisms.[47][52] Both proactive and reactive IWC can include debris capture, treatment and disposal.[48][52]

While IWC has the potential to provide significant ship operations and biosecurity benefits, there are two main IWC processes that can result in inadvertent environmental harm:

a) lack of, or incomplete, capture of dislodged debris by the cleaning unit; and

b) release of untreated, or incompletely treated, effluent from debris processing.[47][48]

Potential environmental impacts from these two IWC processes include:

— increased discharge of coating biocides and microplastics to ambient waters;[52][53][54][55]

— release of live biofouling organisms, their propagules, or pathogens, into local habitats;[24][52][54]

— diminished coating condition (e.g. dry film thickness [DFT] or scuffs and chips) that reduces antifouling performance and longevity.[45][56]

Given the potential for environmental harm, independent, transparent, and predictive testing of efficacy is needed to evaluate the performance of both proactive and reactive IWC systems. Such robust and standardized testing is critical for the responsible use of IWC systems and the success of biofouling-related policies and regulations.[48]

This document aims to provide standardized, science-based test procedures that produce the data (and level of confidence) needed by relevant stakeholders when assessing the development and use of IWC systems. This document is based on recent, related international efforts to develop IWC system testing protocols (e.g. see References [50] [57] [58]). It describes how to produce data and report on the efficacy and safety of IWC systems to clean various ship surfaces and for the capture and disposal of cleaning debris. The impartial data and reporting from testing under this document are intended to inform IWC service providers, ship operators, and relevant authorities on the performance of IWC. The procedures and methods in this document can also serve as a resource for technology developers, environmental regulators, and other stakeholders interested in the safe and effective use of IWC systems.

The methods and approaches presented in this document represent consensus among international technical experts on best scientific practices. However, it is also expected that some test methods will evolve or improve over time as collective knowledge of this complex issue grows. Performance and safety of IWC systems is context-dependent with many sources of variation across ships, environments, and associated biota. As a result, the use of this document does not guarantee that a specific IWC system will always, or under circumstances other than those used in testing, operate at the levels reported.

This document was developed so that all forms of IWC systems can be tested in a comprehensive and standardized way. However, this document also provides flexibility for conducting evaluations that are customized and appropriate for individual IWC system designs, operational requirements or limits, and providers' claims. It is expected that end-users will select appropriate aspects of this document to incorporate in any individual testing effort, depending on the specifics of the IWC system being evaluated, the function of the IWC system evaluation, and the resources available.

© ISO 2025 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 20679:2025

Documents
Document Sharing Hub

Ships and marine technology — Marine environment protection — Testing of ship biofouling in-water cleaning systems

1 Scope

This document provides detailed and rigorous procedures for the independent performance testing of all forms of ship in-water cleaning (IWC), including on all types of biofouling (i.e. biofilms/microfouling and macrofouling), all external submerged surfaces (i.e. hull and niche areas), and both proactive and reactive IWC systems with or without the capture, processing, and disposal of debris. This document also includes testing protocols and describes how to produce data and report on the efficacy and safety of IWC systems to clean various ship surfaces and for the capture and disposal of cleaning debris.

The development of specific IWC performance requirements, criteria, or standards is outside the scope of this document and is the responsibility of individual authorities, agencies, or administrations. Similarly, while some methods and approaches described in this document can apply to other ship biofouling management approaches, systems designed to kill or prevent biofouling on external surfaces without removal (i.e. without in-water cleaning), and systems that remove or treat biofouling on internal surfaces (e.g. seawater pipes) or external surfaces of intricate mechanical components (e.g. external parts of propeller shaft seal), are also outside the scope of this document.

2 Normative references

There are no normative references for this document.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at https://www.electropedia.org/

3.1
antifouling system
AFS
coating, paint, surface treatment, surface or device that is used on a *ship* (3.18) to control or prevent the attachment of organisms

3.2
antifouling coating
surface coating or paint designed to prevent, repel, or facilitate the detachment of *biofouling* (3.3) from hull and *niche areas* (3.16) that are typically or occasionally submerged

3.3
biofouling
accumulation of aquatic organisms such as microorganisms, plants, and animals on surfaces and structures immersed in or exposed to the aquatic environment

© ISO 2025 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 20679:2025

3.4
capture
process of containment, collection, and removal of *biofouling* (3.3) material, debris, and *waste substances* (3.20) from surfaces during cleaning in water or in drydock

3.5
cleaning system
equipment used for, or the process of, removal of *biofouling* (3.3) from the *ship* (3.18) surface, with or without *capture* (3.4)

3.6
data quality objective
qualitative and quantitative statement that clarifies study objectives, defines the appropriate types of data and specifies the tolerable levels of potential decision errors that will be used as the basis for establishing the quality and quantity of data needed to support decisions

3.7
dry film thickness
DFT
non-destructive means to measure the total coating thickness and wear on submerged ship surfaces through repeated measures using a digital DFT sensor

3.8
fouling rating
FR
allocation of a number for a defined inspection area of the *ship* (3.18) surface based on a visual assessment, including a description of *biofouling* (3.3) present and the percentage of *macrofouling* (3.13) coverage

3.9
hull area
largest proportion of *ship* (3.18) submerged surfaces, which are relatively flat or planar locations, have well-understood hydrodynamic conditions and employ common or traditional *biofouling* (3.3) management systems (e.g. *antifouling coating* (3.2))

3.10
independent testing organization
independent TO
appropriately independent (e.g. with no conflicts of interest), qualified, scientific contractor accepted to conduct third-party testing

3.11
invasive aquatic species
non-native or non-indigenous species to a particular ecosystem that can pose threats to human, animal, and plant life, economic and cultural activities, and the aquatic environment

3.12
in-water cleaning
IWC
intentional removal of *biofouling* (3.3) from a *ship's* (3.18) hull or *niche areas* (3.16) while in the water

3.13
macrofouling
biofouling (3.3) caused by the attachment and subsequent growth of visible plants and animals on structures and *ships* (3.18) exposed to water

Note 1 to entry: Macrofouling are large, distinct multicellular individual or colonial organisms visible to the human eye such as barnacles, tubeworms, mussels, fronds/filaments of algae, bryozoans, sea squirts, and other large attached, encrusting or mobile organisms.

© ISO 2025 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 20679:2025

3.14
microfouling
biofouling (3.3) caused by bacteria, fungi, microalgae, protozoans, and other microscopic organisms that create a biofilm

3.15
multicomponent in-water cleaning system
multicomponent IWC system
system reliant on two or more individual components to achieve the required *in-water cleaning* (3.12)

Note 1 to entry: The use of each component shall be specified in the system standard operating procedures (SOP), e.g. the use of a hand tool for addressing *niche areas* (3.16) after the use of the main cleaning unit on hull surfaces.

3.16
niche area
subset of the submerged surface areas on a *ship* (3.18) that can be more susceptible to *biofouling* (3.3) than the main hull owing to structural complexity, different or variable hydrodynamic forces, susceptibility to *antifouling coating* (3.2) wear or damage, or inadequate or no protection by *antifouling systems* (3.1)

3.17
proactive in-water cleaning
proactive IWC
periodic removal of *microfouling* (3.14) on *ship* (3.18) surfaces to prevent or minimize attachment of *macrofouling* (3.13)

3.18
ship
vessel of any type operating in the aquatic environment, including hydrofoil boats, air-cushion vehicles, submersibles, floating craft, fixed or floating platforms, floating storage units, and floating production storage and off-loading units

3.19
reactive in-water cleaning
reactive IWC
corrective action during which *biofouling* (3.3) is removed from a *ship's* (3.18) hull and *niche areas* (3.16), either in water with *capture* (3.4) or in drydock

3.20
waste
dissolved and particulate materials or debris that can be released or produced during cleaning or maintenance, and can include biocides, metals, organic substances, removed *biofouling* (3.3), pigments, microplastics, or other contaminants that could have a negative impact on the environment

3.21
waste processing
treatment designed to remove or deactivate any particulate, dissolved material, or debris *captured* (3.4) during any form of *in-water cleaning* (3.12)

Note 1 to entry: Treatment can be a single stage such as physical separation (e.g. settling tanks, filtration, flocculation), selective media binding of compounds of concern, or disinfection of biological constituents of concern (e.g. biocides, UV, ultrasound) or a multi-staged, combined treatment approach.

4 Fundamental information needed for testing of IWC systems

4.1 Factors that can impact performance

Numerous factors can impact IWC system performance and the means by which comprehensive, standardized testing is performed.[48][52] These include, but are not limited to:

— ship [e.g. type, design, coating(s), ship and coating ages, operational profile, and routes];

© ISO 2025 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 20679:2025

— biofouling (e.g. life history stage, type, coverage, location);

— environmental conditions (e.g. visibility, swell, current, ambient water quality);

— the IWC system (e.g. unique design features, operational requirements and limits, cleaning procedures); and

— IWC system operator training and experience.

4.2 Fundamental parameters

Testing IWC systems is most appropriate and informative when performed under real-world conditions. However, the cost and complexity of full-scale operations on ships can prohibit extensive experimental replication, controls, and the isolation of single factors to measure their impact on overall performance and safety. Given the complexity of these variables, it is not feasible to examine all possible factors (singularly or in combination) that can impact IWC system performance and safety. Therefore, a list of fundamental parameters that shall be either documented, characterized, or specifically tested for, as part of any independent evaluation, is provided in Table 1. The listed parameters allow for linking test results to performance under specifically known (or measured) ship, biofouling, environmental, and IWC system characteristics. The experimental design and specific performance parameters for IWC system testing are described in Clauses 5 to 9.

Reporting for these parameters falls into three general categories:

— Documenting: information that shall be provided either by the ship owner, operator, IWC system service provider, or all three, which appropriately describes test conditions;

— Monitoring: information that shall be observed, measured or collected (e.g. direct observations of cleaning mobilization, operations, demobilization and environmental test conditions) and reported by the independent testing organization (TO) conducting the testing; and

— Testing: factors that shall be directly targeted or manipulated as fundamental test variables (e.g. a direct test of IWC system claims).

Table 1 — Test parameters and data required to assess IWC system performance

Ship parameters	Documenting	Monitoring	Testing
Ship type/function, age, size, and design drawings, with any relevant modifications (including complexities and niche areas)	X		
Ship recent routes/voyages and operational history over at least the past 12 months (including dry-docking, long idle periods, lay-up, and repairs)	X		

X Designates data or information required through documenting, monitoring, or testing for each parameter listed.

[a] Proprietary, or commercially sensitive, information on specific IWC technologies or approaches can be held confidential, provided enough basic information on system specifications, design, function, and operations are available to allow for an adequate understanding of performance and safety.

[b] For example, testing the IWC system service provider's claims on coating type (biocidal or fouling release), age or damage, which can influence environmental results.

[c] For example, testing the IWC system service provider's claims on fouling type/level/location and results from recent/relevant in-water biofouling inspections.

[d] For example, testing within specifications or to limits, including fouling (e.g. type, stage, and coverage), ship (e.g. size, materials, curvature, niche areas), coating type and appropriateness for cleaning, and environmental parameters (e.g. currents and visibility).

[e] For example, testing within specifications or efficacy limits.

[f] For example, testing within specifications or limits.

© ISO 2025 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 20679:2025

Table 1 *(continued)*

Ship availability/access for either cleaning, testing, or both (including dates, ports, time at dock or anchorage, any access restrictions)	X		
Ship coating(s) type (or uncoated), age, expected service life, applied location, and history (including prior cleaning, damage, or repair)	X	X	X[b]
Ship fouling rating prior to testing (including type and percentage cover) and distribution on various surfaces		X	X[c]
Environmental parameters	**Documenting**	**Monitoring**	**Testing**
Water visibility/clarity		X	
Tides, currents, wind, and waves		X	
Water quality at location of testing and during testing, at minimum: (a) salinity, (b) temperature, (c) total suspended solids, (d) particle size distribution, (e) dissolved organic carbon, and (f) particulate organic carbon		X	
Ambient levels of biocides during testing, if applicable (e.g. background levels of copper and zinc) and other contaminants of interest (e.g. microplastics) in water column at location of testing		X	
IWC system parameters[a]	**Documenting**	**Monitoring**	**Testing**
IWC system design and function, and IWC mobilization, operations and demobilization	X		X
IWC system specifications, requirements and limits	X		X[d]
Mode of cleaning unit operations (e.g. diver-, remotely-, or autonomously-operated)	X	X	
Mode of cleaning unit attachment to, and movement on, ship surfaces	X	X	
Operator/diver skill and experience (as described by the IWC service provider)	X	X	

X Designates data or information required through documenting, monitoring, or testing for each parameter listed.

[a] Proprietary, or commercially sensitive, information on specific IWC technologies or approaches can be held confidential, provided enough basic information on system specifications, design, function, and operations are available to allow for an adequate understanding of performance and safety.

[b] For example, testing the IWC system service provider's claims on coating type (biocidal or fouling release), age or damage, which can influence environmental results.

[c] For example, testing the IWC system service provider's claims on fouling type/level/location and results from recent/relevant in-water biofouling inspections.

[d] For example, testing within specifications or to limits, including fouling (e.g. type, stage, and coverage), ship (e.g. size, materials, curvature, niche areas), coating type and appropriateness for cleaning, and environmental parameters (e.g. currents and visibility).

[e] For example, testing within specifications or efficacy limits.

[f] For example, testing within specifications or limits.

© ISO 2025 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 20679:2025