BS ISO 4437-3:2024

BSI Standards Publication

Plastics piping systems for the supply of gaseous fuels — Polyethylene (PE)

Part 3: Fittings

Documents
Document Sharing Hub

Full document details: BS ISO 4437-3:2024

National foreword

This British Standard is the UK implementation of ISO 4437-3:2024. It supersedes BS ISO 4437-3:2014, which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee PRI/88/2, Plastics piping for pressure applications.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2024
Published by BSI Standards Limited 2024

ISBN 978 0 539 06925 9

ICS 23.040.20; 23.040.50; 23.040.80; 75.200; 83.140.30

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 29 February 2024.

Amendments/corrigenda issued since publication

Date	Text affected

Documents
Document Sharing Hub

Full document details: BS ISO 4437-3:2024

International Standard

ISO 4437-3

Second edition
2024-02

Plastics piping systems for the supply of gaseous fuels — Polyethylene (PE) —

Part 3: Fittings

Systèmes de canalisations en plastique pour la distribution de combustibles gazeux — Polyéthylène (PE) —

Partie 3: Raccords

Reference number
ISO 4437-3:2024(en)

© ISO 2024

Documents
Document Sharing Hub

Full document details: BS ISO 4437-3:2024

COPYRIGHT PROTECTED DOCUMENT

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Documents
Document Sharing Hub

Full document details: BS ISO 4437-3:2024

Contents

Page

Foreword ... **v**
Introduction ... **vi**
1 Scope ... **1**
2 Normative references ... **2**
3 Terms and definitions ... **3**
3.1 Terms related to geometry ... 3
3.2 Terms related to material ... 4
3.3 Terms related to material characteristics ... 5
3.4 Terms related to service conditions ... 5
3.5 Terms related to joints ... 6
4 Symbols and abbreviated terms ... **6**
4.1 Symbols ... 6
4.2 Abbreviated terms ... 8
5 Material ... **9**
5.1 PE compound for fittings ... 9
5.2 Material for non-polyethylene parts ... 9
5.2.1 General ... 9
5.2.2 Metal parts ... 9
5.2.3 Sealing materials ... 9
5.2.4 Other materials ... 10
6 General characteristics ... **10**
6.1 Appearance ... 10
6.2 Colour ... 10
6.3 Design ... 10
6.4 Appearance of factory-made joints ... 10
6.5 Electrical characteristics for electrofusion fittings ... 10
7 Geometrical characteristics ... **11**
7.1 Measurement of dimensions ... 11
7.2 Dimensions of electrofusion socket fittings ... 11
7.2.1 Diameters and lengths of electrofusion sockets ... 11
7.2.2 Wall thicknesses ... 13
7.2.3 Out-of-roundness of the bore of a fitting (at any point) ... 13
7.2.4 Spigots ... 13
7.2.5 Other dimensions ... 13
7.3 Dimensions of electrofusion saddle fittings ... 13
7.4 Dimensions of spigot end fittings ... 14
7.4.1 Diameters and lengths ... 14
7.4.2 Wall thickness of the fusion end ... 16
7.4.3 Wall thickness of the fitting body ... 16
7.4.4 Other dimensions ... 16
7.5 Dimensions of socket fusion fittings ... 16
7.6 Design and dimensions of mechanical fittings ... 16
7.6.1 General ... 16
7.6.2 Mechanical fittings with polyethylene spigot ends ... 17
7.6.3 Mechanical fittings with polyethylene electrofusion sockets ... 17
7.6.4 Threads ... 17
8 Mechanical characteristics ... **17**
8.1 General ... 17
8.2 Requirements ... 17
8.3 Modifications of the fitting ... 20
8.4 Performance requirements ... 20

© ISO 2024 – All rights reserved

AVA Documents
Document Sharing Hub

Full document details: BS ISO 4437-3:2024

9 Physical characteristics ... **21**
9.1 Conditioning ... 21
9.2 Requirements ... 21
10 Performance requirements ... **22**
11 Technical information ... **22**
12 Marking ... **22**
12.1 General ... 22
12.2 Minimum required marking of fittings ... 23
12.3 Additional marking ... 23
12.4 Fusion system recognition ... 23
13 Delivery conditions ... **24**
Annex A (normative) **Socket fusion fittings** ... **25**
Annex B (informative) **Examples of typical terminal connections for electrofusion fittings** ... **27**
Annex C (normative) **Short-term pressure test method** ... **30**
Annex D (normative) **Tensile test for fitting/pipe assemblies** ... **32**
Annex E (informative) **Formulae for calculating the equivalent dimensions of non-metric electrofusion socket fitting series** ... **34**
Bibliography ... **35**

© ISO 2024 – All rights reserved

Documents
Document Sharing Hub

Full document details: BS ISO 4437-3:2024

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 138, *Plastics pipes, fittings and valves for the transport of fluids*, Subcommittee SC 4, *Plastics pipes and fittings for the supply of gaseous fuels*.

This second edition cancels and replaces the first edition (ISO 4437-3:2014), which has been technically revised.

The main changes are as follows:

— PE 100-RC type materials with enhanced resistance to slow crack growth (SCG) have been added;

— the nominal diameter range of the electrofusion socket fittings and spigot end fittings has been increased to 800 mm;

— the PE 80 20 °C/100 h control point has been changed to 10 MPa with a note to advise that 9 MPa is applicable if the ISO 9080 data set for a material indicates that a lower value is applicable;

— test methods have been updated and new methods have been added for PE 100-RC materials.

A list of all parts in the ISO 4437 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO 2024 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 4437-3:2024

Introduction

The ISO 4437 series specifies the requirements for a piping system and its components made from polyethylene (PE) compounds, which is intended to be used for the supply of gaseous fuels.

This document covers the characteristics of fittings.

Requirements and test methods for materials and components, other than fittings, are specified in ISO 4437-1, ISO 4437-2 and ISO 4437-4.

Characteristics for fitness for purpose of the system are covered in ISO 4437-5.

Recommended practice for design, handling and installation is given in ISO/TS 10839.

© ISO 2024 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 4437-3:2024

Plastics piping systems for the supply of gaseous fuels — Polyethylene (PE) —

Part 3: Fittings

1 Scope

This document specifies the characteristics of fusion fittings made from polyethylene (PE) as well as of mechanical fittings for piping systems in the field of the supply of gaseous fuels.

It also specifies the test parameters for the test methods referred to in this document.

In conjunction with ISO 4437-1, ISO 4437-2, ISO 4437-4 and ISO 4437-5, this document is applicable to PE pipes, fittings and valves, their joints, and joints with components of PE and other materials intended to be used under the following conditions:

a) a maximum operating pressure (MOP), up to and including 10 bar[1)], at a reference temperature of 20 °C for design purposes;

b) an operating temperature between −20 °C and 40 °C.

For operating temperatures between 20 °C and 40 °C, derating coefficients are defined in ISO 4437-5.

The ISO 4437 series covers a range of maximum operating pressures and gives requirements concerning colours.

It is the responsibility of the purchaser or specifier to make the appropriate selections from these aspects, taking into account their particular requirements and any relevant national regulations and installation practices or codes.

This document is applicable for fittings of the following types:

— electrofusion socket fittings;

— electrofusion saddle fittings;

— spigot end fittings (for butt fusion using heated tools and electrofusion socket fusion);

— socket fusion fittings;

— mechanical fittings.

NOTE 1 The fittings can be, for example, in the form of couplers, saddles, equal and reduced tees, reducers, elbows, bends or end caps.

NOTE 2 Fabricated fittings are normally not used for gas applications except for larger dimensions or in the absence of other solutions. Guidance can be found in ISO 4427-3:2019, Annex B.

1) 1 bar = 0,1 MPa = 10^5 Pa; 1 MPa = 1 N/mm^2.

© ISO 2024 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 4437-3:2024

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 7-1, *Pipe threads where pressure-tight joints are made on the threads — Part 1: Dimensions, tolerances and designation*

ISO 228-1, *Pipe threads where pressure-tight joints are not made on the threads — Part 1: Dimensions, tolerances and designation*

ISO 1133-1, *Plastics — Determination of the melt mass-flow rate (MFR) and melt volume-flow rate (MVR) of thermoplastics — Part 1: Standard method*

ISO 1167-1:2006, *Thermoplastics pipes, fittings and assemblies for the conveyance of fluids — Determination of the resistance to internal pressure — Part 1: General method*

ISO 1167-4, *Thermoplastics pipes, fittings and assemblies for the conveyance of fluids — Determination of the resistance to internal pressure — Part 4: Preparation of assemblies*

ISO 3126, *Plastics piping systems — Plastics components — Determination of dimensions*

ISO 4437-1, *Plastics piping systems for the supply of gaseous fuels — Polyethylene (PE) — Part 1: General*

ISO 4437-2:2024, *Plastics piping systems for the supply of gaseous fuels — Polyethylene (PE) — Part 2: Pipes*

ISO 4437-5, *Plastics piping systems for the supply of gaseous fuels — Polyethylene (PE) — Part 5: Fitness for purpose of the system*

ISO 11357-6, *Plastics — Differential scanning calorimetry (DSC) — Part 6: Determination of oxidation induction time (isothermal OIT) and oxidation induction temperature (dynamic OIT)*

ISO 12176-5, *Plastics pipes and fittings — Equipment for fusion jointing polyethylene systems — Part 5: Two-dimensional data coding of components and data exchange format for PE piping systems*

ISO 13950, *Plastics pipes and fittings — Automatic recognition systems for electrofusion joints*

ISO 13951, *Plastics piping systems — Test method for the resistance of plastic pipe/pipe or pipe/fitting assemblies to tensile loading*

ISO 13953, *Polyethylene (PE) pipes and fittings — Determination of the tensile strength and failure mode of test pieces from a butt-fused joint*

ISO 13954, *Plastics pipes and fittings — Peel decohesion test for polyethylene (PE) electrofusion assemblies of nominal outside diameter greater than or equal to 90 mm*

ISO 13955, *Plastics pipes and fittings — Crushing decohesion test for polyethylene (PE) electrofusion assemblies*

ISO 13956, *Plastics pipes and fittings — Decohesion test of polyethylene (PE) saddle fusion joints — Evaluation of ductility of fusion joint interface by tear test*

ISO 13957, *Plastics pipes and fittings — Polyethylene (PE) tapping tees — Test method for impact resistance*

ISO 16010, *Elastomeric seals — Material requirements for seals used in pipes and fittings carrying gaseous fuels and hydrocarbon fluids*

ISO 17778, *Plastics piping systems — Fittings, valves and ancillaries — Determination of gaseous flow rate/pressure drop relationships*

ISO 17885, *Plastics piping systems — Mechanical fittings for pressure piping systems — Specifications*

ISO 18488, *Polyethylene (PE) materials for piping systems — Determination of Strain Hardening Modulus in relation to slow crack growth — Test method*

© ISO 2024 – All rights reserved

Documents
Document Sharing Hub

Full document details: BS ISO 4437-3:2024

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at https://www.electropedia.org/

3.1 Terms related to geometry

3.1.1
nominal size
DN/OD
numerical designation of the size of a component related to the outside diameter

Note 1 to entry: It is a convenient round number approximately equal to the manufacturing dimension in millimetres (mm). It is not applicable to components designated by thread size.

3.1.2
nominal outside diameter
d_n
specified outside diameter assigned to a *nominal size* (3.1.1)

Note 1 to entry: Nominal outside diameter is expressed in millimetres.

3.1.3
mean outside diameter
d_{em}
value of the measurement of the outer circumference of the pipe or spigot end of a fitting in any cross-section divided by π (= 3,142), rounded to the next greater 0,1 mm

3.1.4
minimum mean outside diameter
$d_{em,min}$
minimum value for the *mean outside diameter* (3.1.3) as specified for a given *nominal size* (3.1.1)

3.1.5
maximum mean outside diameter
$d_{em,max}$
maximum value for the *mean outside diameter* (3.1.3) as specified for a given *nominal size* (3.1.1)

3.1.6
out-of-roundness
ovality
difference between the maximum and the minimum outside diameters in the same cross-section of a pipe or spigot

3.1.7
nominal wall thickness
e_n
numerical designation of the wall thickness of a component, which is a convenient round number, approximately equal to the manufacturing dimension in millimetres (mm)

Note 1 to entry: For thermoplastics components conforming to the ISO 4437 series, the value of the nominal wall thickness, e_n, is identical to the specified *minimum wall thickness at any point* (3.1.9).

© ISO 2024 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 4437-3:2024

3.1.8
wall thickness at any point
e
wall thickness at any point around the circumference of a component rounded to the next greater 0,1 mm

Note 1 to entry: The symbol for the wall thickness of a fitting or valve at any point is *E*.

3.1.9
minimum wall thickness at any point
e_{min}
minimum value for the *wall thickness at any point* (3.1.8) around the circumference of a component

3.1.10
tolerance
permitted variation of the specified value of a quantity, expressed as the difference between the permitted maximum and the permitted minimum value

3.1.11
standard dimension ratio
SDR
numerical designation of a *pipe series* (3.1.12), which is a convenient round number, approximately equal to the dimension ratio of the *nominal outside diameter* (3.1.2) and the *nominal wall thickness* (3.1.7)

3.1.12
pipe series
S
number for pipe designation

Note 1 to entry: The relationship between the pipe series, *S*, and the *standard dimension ratio (SDR)* (3.1.11) is given by the following formula, as specified in ISO 4065.

$$S = \frac{SDR - 1}{2}$$

3.2 Terms related to material

3.2.1
compound
homogenous extruded mixture of *base polymer* (3.2.4) (polyethylene) and additives (i.e. anti-oxidants, pigments, carbon black, UV-stabilizers and others) at a dosage level necessary for the processing and use of components

3.2.2
virgin material
compound (3.2.1) in a form such as granules that has not been subjected to use or processing other than that required for its manufacture and to which no reworked or recyclable materials have been added

3.2.3
reworked material
plastics materials from rejected unused products or trimmings that have been manufactured and retained within plants owned and operated by the same legal entity

3.2.4
base polymer
polymer produced by the material supplier for the manufacture of the *compound* (3.2.1)

© ISO 2024 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 4437-3:2024

3.3 Terms related to material characteristics

3.3.1
lower confidence limit of the predicted hydrostatic strength
σ_{LPL}
quantity, with the dimensions of stress, which represents the 97,5 % lower confidence limit of the predicted hydrostatic strength at temperature θ and time t

Note 1 to entry: It is expressed in megapascals (MPa).

3.3.2
minimum required strength
MRS
value of the *lower confidence limit of the predicted hydrostatic strength* (3.3.1) at 20 °C and 50 years, rounded down to the next smaller value of the R10 series or R20 series

Note 1 to entry: Only *compounds* (3.2.1) with an MRS of 8 MPa or 10 MPa are specified in this document.

Note 2 to entry: The R10 series and the R20 series conform to ISO 3.

Note 3 to entry: It is expressed in megapascals (MPa).

[SOURCE: ISO 12162:2009, 3.3, modified — Note 1 to entry has been removed and replaced with new Notes 1 to 3 to entry.]

3.3.3
design coefficient
C
coefficient with a value greater than 1 which takes into consideration service conditions as well as properties of the components of a piping system other than those represented in the lower confidence limit

3.3.4
melt mass-flow rate
MFR
value relating to the viscosity of the molten material at a specified temperature and load

Note 1 to entry: It is expressed in grams per 10 minutes (g/10 min).

3.4 Terms related to service conditions

3.4.1
gaseous fuel
fuel which is in gaseous state at a temperature of 15 °C at atmospheric pressure

Note 1 to entry: There are proposals to inject gases from renewable sources in natural gas networks, e.g. hydrogen (H_2). This is the subject of ongoing research.

3.4.2
maximum operating pressure
MOP
maximum effective pressure of the fluid in the piping system which is allowed in continuous use

Note 1 to entry: It is expressed in bar. It takes into account the physical and the mechanical characteristics of the components of a piping system. It is calculated using the following formula:

$$MOP = \frac{20 \times MRS}{C \times (SDR - 1)}$$

Note 2 to entry: Research on long-term performance prediction of polyethylene gas distribution systems shows a possible service life of at least 100 years; see References [13], [14] and [15].

© ISO 2024 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 4437-3:2024

3.4.3
reference temperature
temperature for which the piping system is designed

Note 1 to entry: It is used as the base for further calculation when designing a piping system or parts of a piping system for operating temperatures different from the reference temperature (see ISO 4437-5).

3.5 Terms related to joints

3.5.1
electrofusion socket fitting
polyethylene (PE) fitting which contains one or more integrated heating elements that are capable of transforming electrical energy into heat to realize a fusion joint with a spigot end or a pipe

3.5.2
electrofusion saddle fitting
polyethylene (PE) fitting which contains one or more integrated heating elements that are capable of transforming electrical energy into heat to realize a fusion joint onto a pipe

3.5.3
tapping tee
electrofusion saddle fitting (3.5.2) that contains a cutter to tap through the wall of the main pipe and remains in the body of this fitting

3.5.4
branch saddle
electrofusion saddle fitting (3.5.2) that requires an ancillary cutting tool for drilling a hole in the adjoining main pipe

3.5.5
spigot end fitting
polyethylene (PE) fitting where the outside diameter of the spigot end is equal to the *nominal outside diameter* (3.1.2) of the corresponding pipe

3.5.6
socket fusion fitting
polyethylene (PE) fitting designed to accept the insertion of a pipe or spigot end to realize a fusion joint between mating surfaces using the socket fusion process

3.5.7
mechanical fitting
fitting for assembling plastics pipes with each other or with a metal pipe or fitting, that includes one or more compression zones to provide pressure integrity, leak tightness and resistance to end loads

[SOURCE: ISO 17885:2021, 3.1.1]

4 Symbols and abbreviated terms

4.1 Symbols

For the purposes of this document, the following symbols apply.

© ISO 2024 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 4437-3:2024