BS ISO 532-2:2017

BSI Standards Publication

Acoustics — Methods for calculating loudness

Part 2: Moore-Glasberg method

Documents
Document Sharing Hub

Full document details: BS ISO 532-2:2017

National foreword

This British Standard is the UK implementation of ISO 532-2:2017.

The UK participation in its preparation was entrusted to Technical Committee EH/1, Acoustics.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2017
Published by BSI Standards Limited 2017

ISBN 978 0 580 81404 4

ICS 17.140.01

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 July 2017.

Amendments/corrigenda issued since publication

Date	Text affected

Documents
Document Sharing Hub

Full document details: BS ISO 532-2:2017

INTERNATIONAL STANDARD

ISO 532-2

First edition
2017-06

Acoustics — Methods for calculating loudness —

Part 2: Moore-Glasberg method

Acoustique — Méthode de calcul d'isosonie —

Partie 2: Méthode Moore-Glasberg

Reference number
ISO 532-2:2017(E)

Documents
Document Sharing Hub
© ISO 2017

Full document details: BS ISO 532-2:2017

COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

© ISO 2017 – All rights reserved

Documents
Document Sharing Hub

Full document details: BS ISO 532-2:2017

Contents

Page

Foreword ... **iv**
Introduction ... **v**
1 Scope ... **1**
2 Normative references ... **1**
3 Terms and definitions ... **1**
4 General ... **5**
5 Specifications of signals ... **5**
5.1 General ... 5
5.2 Complex tone ... 5
5.3 Noise consisting of bands of pink or white noise of defined width ... 5
5.4 Mixture of discrete sinusoidal components and bands of pink or white noise ... 6
5.5 Sound specified in terms of the sound pressure levels in 29 adjacent one-third-octave bands ... 6
6 Instrumentation ... **6**
7 Description of the method ... **7**
7.1 Introduction ... 7
7.2 Determination of sound spectrum at the tympanic membrane ... 7
7.2.1 General ... 7
7.2.2 Free field and diffuse field transfer functions for sound picked up by a single microphone ... 8
7.2.3 Earphones ... 8
7.2.4 Signal recorded at eardrum ... 8
7.2.5 Head and torso simulator ... 8
7.2.6 Interpolation and extrapolation ... 8
7.3 Determination of sound spectrum at the oval window ... 9
7.4 Transformation of sound spectrum into excitation pattern ... 10
7.5 Transformation of excitation pattern into specific loudness ... 13
7.5.1 Introduction ... 13
7.5.2 Reference excitation at the reference threshold of hearing ... 14
7.5.3 Gain of the cochlear amplifier for inputs with low sound pressure levels ... 14
7.5.4 Calculation of specific loudness from excitation when $E_{\mathrm{THRQ}}/E_0 \leq E/E_0$ ... 15
7.5.5 Calculation of specific loudness from excitation when $E_{\mathrm{THRQ}}/E_0 > E/E_0$ ... 15
7.5.6 Calculation of specific loudness from excitation when $E > 10^{10}$ ... 15
8 Calculation of loudness and loudness level ... **16**
8.1 Calculation of monaural and binaural loudness (diotic and dichotic stimuli) ... 16
8.2 Relationship between loudness level and loudness ... 17
8.3 Calculation of the reference threshold of hearing ... 18
9 Uncertainty of calculated loudness for stationary sounds ... **18**
10 Data reporting ... **19**
Annex A (informative) **Comments regarding binaural loudness** ... **20**
Annex B (informative) **Results for specific test signals** ... **21**
Annex C (informative) **Software for the calculation of loudness** ... **26**
Bibliography ... **27**

© ISO 2017 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 532-2:2017

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html

This document was prepared by Technical Committee ISO/TC 43, *Acoustics*.

A list of all parts in the ISO 532- series, published under the general title *Acoustics — Methods for calculating loudness*, can be found on the ISO website.

© ISO 2017 – All rights reserved
Documents
Document Sharing Hub
Full document details: BS ISO 532-2:2017

Introduction

Loudness and loudness level are two perceptual attributes of sound describing absolute and relative sensations of sound strength perceived by a person under specific listening conditions. Due to inherent individual differences among people, both loudness and loudness level have the nature of statistical estimators characterized by their respective measures of central tendency and dispersion determined for a specific sample of the general population.

The object of the ISO 532- series is to specify calculation procedures based on physical properties of sound for estimating loudness and loudness level of sound as perceived by persons with otologically normal hearing under specific listening conditions. Each procedure seeks single numbers that can be used in many scientific and technical applications to estimate the perceived loudness and loudness level of sound without conducting separate human observer studies for each application. Because loudness is a perceived quantity, the perception of which may vary among people, any calculated loudness value represents only an estimate of the average loudness as perceived by a group of individuals with otologically normal hearing

ISO 532-1 and ISO 532-2 specify two different methods for calculating loudness which may yield different results for given sounds. Since no general preference for one or the other method can presently be stated, it is up to the user to select the method which appears most appropriate for the given situation. Some major features of each of the methods are described below to facilitate the choice.

This document is limited to calculation of loudness and loudness level of stationary sounds and the calculations are based on the spectral properties of a sound. This calculation method is based on Moore-Glasberg loudness calculation algorithms [14-17]. It starts by converting a specified signal spectrum into a series of sinusoidal components representing that spectrum. This series is then transformed into a specific loudness pattern by applying four consecutive transformations, each of which is directly related to physiological and psychological characteristics of the human hearing system. Loudness is calculated from the specific loudness pattern.

This document describes the calculation procedures leading to estimation of loudness and loudness level and provides an executable computer program and code. The software provided with this document is entirely informative and provided for the convenience of the user. Use of the provided software is not required for conformance with this document.

The Moore-Glasberg method is limited to stationary sounds and can be applied to tones, broadband noises and complex sounds with sharp line spectral components. The method in this document differs from those in ISO 532:1975. Method A of ISO 532:1975 (Stevens loudness[18]) was removed as this method was not often used and its predictions were not accurate for sounds with strong tonal components. The method described in this document also improves the precision of calculated loudness in the low frequency range and allows for calculation of loudness under conditions where the sound differs at the two ears. It has been shown that this method provides a good match to the contours of equal loudness level as defined in ISO 226:2003 and the reference threshold of hearing as defined in ISO 389-7:2005.

The Zwicker method in ISO 532-1 can be applied for stationary and arbitrary non-stationary sounds. The method for stationary sounds in ISO 532-1 differs slightly from the methods included in the previous ISO 532:1975, method B, by specifying corrections for low frequencies and by restricting the description of the approach to numerical instructions only, thus allowing a unique software description. For reasons of continuity, the method given in ISO 532-1 is in accordance with ISO 226:1987 instead of the later revised version, ISO 226:2003.

NOTE Equipment or machinery noise emissions/immissions can also be judged by other quantities defined in various International Standards (see e.g. ISO 1996-1, ISO 3740, ISO 9612 and ISO 11200).

© ISO 2017 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 532-2:2017

Documents
Document Sharing Hub

Full document details: BS ISO 532-2:2017

Acoustics — Methods for calculating loudness —

Part 2: Moore-Glasberg method

1 Scope

This document specifies a method for estimating the loudness and loudness level of stationary sounds as perceived by otologically normal adult persons under specific listening conditions. It provides an algorithm for the calculation of monaural or binaural loudness for sounds recorded using a single microphone, using a head and torso simulator, or for sounds presented via earphones. The method is based on the Moore-Glasberg algorithm.

NOTE 1 Issues of binaural calculations are discussed in Annex A.

NOTE 2 Users who wish to study the details of the calculation method can review or implement the source code, which is entirely informative and provided with this document for the convenience of the user.

This method can be applied to tones, broadband noises and complex sounds with sharp line spectral components, for example transformer hum or fan noise.

NOTE 3 It has been shown (see Reference [15]) that this method provides a good match to the contours of equal loudness level as defined in ISO 226:2003 and the reference threshold of hearing as defined in ISO 389-7:2005.

The evaluation of the harmful effect of sound events is outside the scope of this document.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61260-1:2014, *Electroacoustics — Octave-band and fractional-octave-band filters — Part 1: Specifications*

IEC 61672-1:2013, *Electroacoustics — Sound level meters — Part 1: Specifications*

IEC/TS 60318-7, *Electroacoustics — Simulators of human head and ear — Part 7: Head and torso simulator for the measurement of hearing aids*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at http://www.iso.org/obp

— IEC Electropedia: available at http://www.electropedia.org/

© ISO 2017 – All rights reserved

Documents Document Sharing Hub
Full document details: BS ISO 532-2:2017

3.1
sound pressure level
L_p
ten times the logarithm to the base 10 of the ratio of the square of the sound pressure, p, to the square of a reference value, p_0, expressed in decibels

$$L_p = 10 \lg \frac{p^2}{p_0^2} \text{ dB}$$

where the reference value, p_0, in gases is 20 μPa

Note 1 to entry: Because of practical limitations of the measuring instruments, p^2 is always understood to denote the square of a frequency-weighted, frequency-band-limited or time-weighted sound pressure. If specific frequency and time weightings as specified in IEC 61672–1 and/or specific *frequency bands* (3.2) are applied, this should be indicated by appropriate subscripts, for example $L_{p,\mathrm{AS}}$ denotes the A-weighted sound pressure level with time weighting S (slow). Frequency weightings such as A-weighting should not be used when specifying sound pressure levels for the purpose of *loudness* (3.17) calculation using the current procedure.

Note 2 to entry: This definition is technically in accordance with ISO 80000-8:2007, 8.

3.2
frequency band
continuous set of frequencies lying between two specified limiting frequencies

Note 1 to entry: A frequency band is characterized by two values that define its position in the frequency spectrum, for instance its lower and upper cut-off frequencies.

Note 2 to entry: Frequency is expressed in Hz.

[SOURCE: IEC 60050-702:1992, 702-01-02]

3.3
filter
device or mathematical operation that, when applied to a complex signal, passes energy of signal components of certain frequencies while substantially attenuating energy of signal components of all other frequencies

3.4
cut-off frequency
lowest (f_l) or highest (f_h) frequency beyond which the response of the *filter* (3.3) to a sinusoidal signal does not exceed −3 dB relative to the maximum response measured between (f_l) and (f_h)

3.5
one-third-octave band
frequency band (3.2) with the centre frequency f_T and the width of one-third of an octave

Note 1 to entry: The subscript T instead of c is used to specify the centre frequency in the special case of a one-third-octave band.

Note 2 to entry: Width of one-third of an octave as specified in IEC 61260-1.

3.6
band-reject filter
filter (3.3) that rejects signal energy within a certain *frequency band* (3.2) and passes most of the signal energy outside of this frequency band

Note 1 to entry: A narrow band-reject filter is also called a notch filter.

3.7
band level
L_pb
sound pressure level (3.1) of sound contained within a restricted frequency band (b)

© ISO 2017 – All rights reserved
Documents
Document Sharing Hub
Full document details: BS ISO 532-2:2017

3.8
one-third-octave-band level
L_T
sound pressure level (3.1) of sound contained within a *frequency band* (3.2) with the width of one-third of an octave

3.9
sound spectrum
representation of the magnitudes (and sometimes of the phases) of the components of a complex sound as a function of frequency

3.10
spectrum density level
spectrum level
level of the limit, as the width of the *frequency band* (3.2) approaches zero, of the quotient of a specified quantity distributed within a frequency band, by the width of the band, expressed in decibels

Note 1 to entry: The words "spectrum level" should be preceded by a descriptive modifier describing the measured quantity.

Note 2 to entry: For illustration, the sound pressure spectrum level L_{ps} at the midband frequency is obtained practically by

$$L_{pbs} = 10\lg\left[\left(p_b^2 / \Delta f\right) / \left(p_0^2 / \Delta_0 f\right)\right]\text{dB}$$

where $p_b{}^2$ is the time-mean-square sound pressure measured through a *filter* (3.3) system, p_0 the reference sound pressure, Δf the bandwidth of the filter system, and $\Delta_0 f$ the reference bandwidth of 1 Hz. For computational purposes, with L_{pb} for the band *sound pressure level* (3.1) observed through the filter, the above relation becomes

$$L_{pbs} = L_{pb} - 10\lg\left[\Delta f / \Delta_0 f\right]\text{dB}$$

3.11
auditory filter
filter (3.3) within the human cochlea describing the frequency resolution of the auditory system, with characteristics that are usually estimated from the results of masking experiments

3.12
otologically normal person
person in a normal state of health who is free from all signs or symptoms of ear disease and from obstructing wax in the ear canals, and who has no history of undue exposure to noise, exposure to potentially ototoxic drugs or familial hearing loss

[SOURCE: ISO 226:2003, 3.1]

3.13
equivalent rectangular bandwidth of the auditory filter for otologically normal persons
ERB_n
auditory filter (3.11) bandwidth determined by measuring tone detection thresholds in wideband noise passed through band-reject (notch) filters of various bandwidths

Note 1 to entry: The subscript n indicates that the value applies for persons with otologically normal hearing.

Note 2 to entry: The multi-letter abbreviated term presented in italics and with a subscript is used here instead of a symbol to maintain an established notation and to avoid confusion.

Note 3 to entry: Bandwidth is measured in Hertz (Hz).

© ISO 2017 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 532-2:2017

3.14
equivalent rectangular bandwidth number scale
ERB_n-number scale
transformation of the frequency scale constructed so that an increase in frequency equal to one ERB_n leads to an increase of one unit on the ERB_n-number scale

Note 1 to entry: ERB_n is measured in Hertz (Hz).

Note 2 to entry: The unit of the ERB_n-number scale is the Cam. For example, the value of ERB_n for a centre frequency of 1 000 Hz is approximately 132 Hz, so an increase in frequency from 934 Hz to 1 066 Hz corresponds to a step of one Cam. The equation relating ERB_n-number to frequency is given in 7.4.

3.15
loudness level
sound pressure level (3.1) of a frontally incident, sinusoidal plane progressive wave, presented binaurally at a frequency of 1 000 Hz that is judged by otologically normal persons as being as loud as the given sound

Note 1 to entry: Loudness level is expressed in phons.

3.16
calculated loudness level
L_N
loudness level (3.15) calculated following the procedure of a predictive model

3.17
loudness
perceived magnitude of a sound, which depends on the acoustic properties of the sound and the specific listening conditions, as estimated by otologically normal persons

Note 1 to entry: Loudness is expressed in sones.

Note 2 to entry: Loudness depends primarily upon the *sound pressure level* (3.1) although it also depends upon the frequency, waveform, bandwidth, and duration of the sound.

Note 3 to entry: One sone is the loudness of a sound with a *loudness level* (3.15) of 40 phon.

Note 4 to entry: A sound that is twice as loud as another sound is characterized by doubling the number of sones.

3.18
calculated loudness
N
loudness (3.17) calculated following the procedure of a predictive model

3.19
excitation
E
output of an *auditory filter* (3.11) centred at a given frequency, specified in units that are linearly related to power

Note 1 to entry: An excitation of 1 unit is produced at the output of an auditory filter centred at 1 000 Hz by a tone with a frequency of 1 000 Hz with a *sound pressure level* (3.1) of 0 dB presented in a free field with frontal incidence.

3.20
excitation level
L_E
ten times the logarithm to the base 10 of the ratio of the *excitation* (3.19) at the output of an *auditory filter* (3.11) centred at the frequency of interest to the reference excitation E_0

$$L_E = 10\lg\frac{E}{E_0}\,\text{dB}$$

© ISO 2017 – All rights reserved
Documents
Document Sharing Hub
Full document details: BS ISO 532-2:2017