

Implementation of
ISO 6020-3:1994

Hydraulic fluid power — Mounting dimensions for single rod cylinders, 16 MPa (160 bar) series —

Part 3: Compact series with bores
from 250 mm to 500 mm

ICS 23.100.20

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

BSI
Documents

AVA

Document Sharing Hub

Committees responsible for this British Standard

The preparation of this British Standard was entrusted to Technical Committee MCE/18, Fluid power systems and components, upon which the following bodies were represented:

- Association of British Mining Equipment Companies
- British Compressed Air Society
- British Fluid Power Association
- British Hydromechanics Research Association
- British Iron and Steel Producers' Association
- British Steel Industry
- Department of Trade and Industry (National Engineering Laboratory)
- Ministry of Defence
- University of Bath

This British Standard, having been prepared under the direction of the Engineering Sector Board, was published under the authority of the Standards Board and comes into effect on 15 September 1995

© BSI 12-1999

The following BSI references relate to the work on this standard:
Committee reference MCE/18
Draft for comment 86/70440 DC

ISBN 0 580 24688 4

Amendments issued since publication

Amd. No.	Date	Comments

Contents

	Page
Committees responsible	Inside front cover
National foreword	ii
Foreword	iii
Text of ISO 6020-3	1

National foreword

This British Standard reproduces verbatim ISO 6020-3:1994 and implements it as the UK national standard.

This British Standard is published under the direction of the Engineering Sector Board whose Technical Committee MCE/18 has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international committee any enquiries on interpretation, or proposals for change, and keep UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

NOTE International and European Standards, as well as overseas standards, are available from Customer Services, BSI, 389 Chiswick High Road, London W4 4AL.

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, the ISO title page, pages ii to iv, pages 1 to 10, an inside back cover and a back cover.

This standard has been updated (see copyright date) and may have had amendments incorporated. This will be indicated in the amendment table on the inside front cover.

INTERNATIONAL STANDARD

ISO
6020-3

First edition
1994-09-01

Hydraulic fluid power — Mounting dimensions for single rod cylinders, 16 MPa (160 bar) series —

Part 3:

Compact series with bores from 250 mm to
500 mm

*Transmissions hydrauliques — Dimensions d'interchangeabilité des vérins
16 MPa (160 bar) à simple tige —*

Partie 3: Série compacte, alésages de 250 mm à 500 mm



Reference number
ISO 6020-3:1994(E)

Contents

	Page
Foreword	iii
Introduction	1
1 Scope	1
2 Normative references	1
3 Definitions	1
4 Dimensions	1
5 Bore sizes	1
6 Mounting styles	1
7 Piston rod characteristics	2
8 Identification statement	2
Annex A (informative) Bibliography	Inside back cover
Figure 1 — General dimensions	2
Figure 2 — MF5 — Head mounting, square flange	3
Figure 3 — MF6 — Cap mounting, square flange	4
Figure 4 — MP1 — Cap mounting, fixed clevis	5
Figure 5 — MP3 — Cap mounting, fixed eye	6
Figure 6 — MP5 — Cap mounting, fixed eye with spherical plain bearing	7
Figure 7 — MT1 — Head mounting, integral trunnion (male)	8
Figure 8 — MT2 — Cap mounting, integral trunnion (male)	9
Figure 9 — MT4 — Mounting with intermediate fixed or movable trunnions (male)	10
Table 1 — General dimensions and part sizes	2
Table 2 — Dimensions of head mountings, square flange	3
Table 3 — Dimensions of cap mountings, square flange	4
Table 4 — Dimensions of cap mountings, fixed clevis	5
Table 5 — Dimensions of cap mountings, fixed eye	6
Table 6 — Dimensions of cap mountings, fixed eye with spherical plain bearing	7
Table 7 — Dimensions of head mountings, integral trunnion (male)	8
Table 8 — Dimensions of cap mountings, integral trunnion (male)	9
Table 9 — Dimensions of mountings with intermediate fixed or movable trunnions (male)	10

Descriptors: Hydraulic fluid power, hydraulic equipment, hydraulic cylinders, single rod cylinders, fastening flanges, dimensions, mounting dimensions, interchangeability.