

Implementation of
ISO 6336-2:1996

Calculation of load capacity of spur and helical gears —

Part 2: Calculation of surface durability
(pitting)

ICS 21.200

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

BSI
Documents

AVA

Document Sharing Hub

Committees responsible for this British Standard

The preparation of this British Standard was entrusted to Technical Committee MCE/5, Gears, upon which the following bodies were represented:

- British Engineering Cutting Tools Association
- British Gear Association
- British Horological Federation
- British Horological Institute
- Engineering Equipment and Materials Users' Association
- Federation of Manufacturers of Construction Equipment and Cranes
- Gauge and Tool Makers' Association
- Institution of Mechanical Engineers
- Lloyds Register of Shipping
- London Underground Ltd.
- Ministry of Defence
- Power Generation Contractors' Association [PGCA (BEAMA Ltd.)]

This British Standard, having been prepared under the direction of the Engineering Sector Board, was published under the authority of the Standards Board and comes into effect on 15 November 1996

© BSI 03-2000

The following BSI references relate to the work on this standard:
Committee reference MCE/5
Draft for comment 89/75653 DC

ISBN 0 580 26750 4

Amendments issued since publication

Amd. No.	Date	Comments
10405	May 1999	Indicated by a sideline in the margin

Contents

	Page
Committees responsible	Inside front cover
National foreword	ii
Foreword	iii
Text of ISO 6336-2	1

National foreword

This British Standard reproduces verbatim ISO 6336-2:1996 and implements it as the UK national standard.

This British Standard is published under the direction of the Engineering Sector Board whose Technical Committee MCE/5 has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international committee any enquiries on interpretation, or proposals for change, and keep UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

NOTE International and European Standards, as well as overseas standards, are available from Customer Services, BSI, 389 Chiswick High Road, London W4 4AL.

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, the ISO title page, pages ii to iv, pages 1 to 26, an inside back cover and a back cover.

This standard has been updated (see copyright date) and may have had amendments incorporated. This will be indicated in the amendment table on the inside front cover.

INTERNATIONAL STANDARD

ISO
6336-2

First edition
1996-06-15

Calculation of load capacity of spur and helical gears —

Part 2:

Calculation of surface durability (pitting)

*Calcul de la capacité de charge des engrenages cylindriques à dentures
droite et hélicoïdale —*

Partie 2: Calcul de la résistance à la pression superficielle (piquage)



Contents

	Page
Foreword	iii
Introduction	1
1 Scope	1
2 Normative references	1
3 Pitting damage and safety factors	1
4 Basic formulae	2
5 Zone factor, Z_H , and single pair tooth contact factors, Z_B and Z_D	7
6 Elasticity factor, Z_E	13
7 Contact ratio factor, Z_ϵ	14
8 Helix angle factor, Z_β	16
9 Strength for contact stress	16
10 Life factor, Z_{NT} (for flanks)	17
11 Influences of the lubricant film, factors Z_L , Z_v and Z_R	19
12 Work hardening factor, Z_W	25
13 Size factor, Z_X	26
Annex A (informative) Bibliography	Inside back cover
Figure 1 — Graphic determination of the permissible contact stress for a limited life, in accordance with method B	6
Figure 2 — Zone factor, Z_H , for $\alpha_n = 20^\circ$	8
Figure 3 — Zone factor, Z_H , for $\alpha_n = 22,5^\circ$	9
Figure 4 — Zone factor, Z_H , for $\alpha_n = 25^\circ$	10
Figure 5 — Radii of curvature at the pitch point C and at the single pair tooth contact point B of the pinion and D of the wheel for determination of the pinion single pair tooth contact factor Z_B in accordance with equation (14), and of the wheel single pair tooth contact factor Z_D in accordance with equation (15) (only for external spur gears)	11
Figure 6 — Contract ratio factor Z_ϵ	15
Figure 7 — Helix angle factor, Z_β	16
Figure 8 — Life factor, Z_{NT} , for standard reference test gears	18
Figure 9 — Lubricant factor, Z_L	21
Figure 10 — Velocity factor, Z_v	22
Figure 11 — Roughness factor, Z_R	24
Figure 12 — Work hardening factor, Z_W	26
Table 1 — Elasticity factor, Z_E , for some material combinations	13
Table 2 — Life factor, Z_{NT}	19
Table 3 — Viscosity parameters	22

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liason with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the Technical Committees are circulated to the member bodies for voting. Publication as a International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard 6336-2 was prepared by Technical Committee ISO/TC 60, Gears, Subcommittee SC2, Gear capacity calculation.

ISO 6336 consists of the following parts, under the general title *Calculation of load capacity of spur and helical gears*:

- *Part 1: Basic principles, introduction and general influence factors;*
- *Part 2: Calculation of surface durability (pitting);*
- *Part 3: Calculation of tooth bending strength;*
- *Part 5: Strength and quality of materials.*

Annex A is for information only.

Introduction

Hertzian pressure, which serves as a basis for the calculation of contact stress, is the basic principle used in this part of ISO 6336 for the assessment of surface durability of cylindrical gears. It is a significant indicator of the stress generated during tooth flank engagement. However, it is not the sole cause of pitting, nor are the corresponding subsurface shear stresses. There are other contributory influences; for example, coefficient of friction, direction and magnitude of sliding and the influence of lubricant on distribution of pressure. Development has not yet advanced to the stage of directly including these in calculations of load-bearing capacity; however, allowance is made for them to some degree in the derating factors and choice of material property values.

In spite of shortcomings, Hertzian pressure is useful as a working hypothesis. This is attributable to the fact that, for a given material, limiting values of Hertzian pressure are preferably derived from fatigue tests on gear specimens; thus additional relevant influences are included in the values. Therefore, if the reference datum is located in the application range, Hertzian pressure is acceptable as a design basis for extrapolating from experimental data to values for gears of different dimensions.

Several methods have been approved for the calculation of the permissible contact stress and the determination of a number of factors (see ISO 6336-1).

1 Scope

This part of ISO 6336 specifies the fundamental formulae for use in the determination of the surface load capacity of cylindrical gears with involute internal or external teeth. It includes formulae for all influences on surface durability for which quantitative assessments can be made. It applies primarily to oil-lubricated transmissions, but may also be used to obtain approximate values for (slow-running) grease-lubricated transmissions, as long as sufficient lubricant is present in the mesh at all times.

The given formulae are valid for cylindrical gears with tooth profiles in accordance with the basic rack standardized in ISO 53. They may be used for teeth where the actual transverse contact ratio is less than $\varepsilon_{\alpha n} = 2,5$. The results are in good agreement with other methods for the range as indicated in the scope of ISO 6336-1.

The user of this part of ISO 6336 is cautioned that when the method specified is used for large helix angles and large pressure angles, the calculated results should be confirmed by experience as by method A.

These formulae cannot be directly applied for the assessment of types of gear tooth surface damage such as plastic yielding, scratching, scuffing or any other than that described in clause 3.

The load capacity determined by way of the permissible contact stress is called the “surface load capacity” or “surface durability”.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this part of ISO 6336. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this part of ISO 6336 are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 53:1974, *Cylindrical gears for general and heavy engineering — Basic rack*.

ISO 6336-1:1996, *Calculation of load capacity of spur and helical cylindrical gears — Part 1: Basic principles, introduction and general influence factors*.

ISO 6336-5:1996, *Calculation of load capacity of cylindrical gears — Part 5: Strength and quality of materials*.

3 Pitting damage and safety factors

If limits of the surface durability of the meshing flanks are exceeded, particles will break out of the flanks, leaving pits.

The extent to which such pits can be tolerated (in size and number) varies within wide limits, depending largely on the field of application. In some fields, extensive pitting can be accepted; in other fields any appreciable pitting is to be avoided.

The following definitions, relevant to average working conditions help in distinguishing between initial pitting and destructive pitting.

Linear or progressive increase of the total area of pits is unacceptable, however the effective tooth bearing area may be enlarged by initial pitting, and the rate of generation of pits may subsequently reduce (degressive pitting), or cease (arrested pitting). Such pitting is considered tolerable. In the event of dispute, the following rule is determinant.

Pitting involving the formation of pits which increase linearly or progressively with time under unchanged service conditions (linear or progressive pitting) is not acceptable. Damage assessment shall include the entire active area of all the tooth flanks. The number and size of newly developed pits in unhardened tooth flanks shall be taken into consideration. It is a frequent occurrence that pits are formed on just one or only a few of the surface hardened gear tooth flanks. In such circumstances, assessment shall be centred on the flanks actually pitted. Teeth suspected of being especially at risk should be marked for critical examination if a quantitative evaluation is required.

In special cases, a first rough assessment can be based on considerations of the entire quantity of wear debris. In critical cases, the condition of the flanks should be examined at least three times. The first examination should, however, only take place after at least 10^6 cycles of load. Further examination should take place after a period of service depending on the results of the previous examination.

If the deterioration by pitting is such that it puts human life in danger, or there is a risk of leading to some grave consequences, then pitting is not tolerable. Due to stress concentration effects, a pit of a diameter of 1 mm near the fillet of a through-hardened or case-hardened tooth of a gear may become the origin of a crack which could lead to tooth breakage; for this reason, such a pit shall be considered as intolerable (e.g. in aerospace transmissions).

Similar considerations are true for turbine gears. In general, during the long life (10^{10} to 10^{11} cycles) which is demanded of these gears, neither pitting nor unduly severe wear is tolerable. Such damage could lead to unacceptable vibrations and excessive dynamic loads. Appropriately generous safety factors should be included in the calculation, i.e. only a low probability of failure can be tolerated.

In contrast, pitting over 100 % of the working flanks can be tolerated for some slow-speed industrial gears with large teeth (e.g. module 25) made from low hardness steel where they will safely transmit the rated power for 10 to 20 years. Individual pits may be up to 20 mm in diameter and 8 mm deep. The apparently “destructive” pitting which occurs during the first two or three years of service normally slows down. The tooth flanks become smoothed and work hardened to the extent of increasing the surface Brinell hardness number by 50 % or more.

For such conditions, relatively low safety factors (in some cases less than one) can be chosen, with a correspondingly higher probability of tooth surface damage. A high factor of safety against tooth breakage is necessary.

Comments on the choice of safety factor S_H can be found in ISO 6336-1, subclause 4.1.3. It is recommended that the manufacturer and customer agree on the values of the minimum safety factor.

4 Basic formulae

NOTE 1 All symbols, terms and units are defined in ISO 6336-1.

The calculation of surface durability is based on the contact stress, σ_H at the pitch point or at the inner point of single pair tooth contact. The higher of the two values obtained is used to determine capacity (determinant). σ_H and the permissible contact stress, σ_{HP} , shall be calculated separately for wheel and pinion, σ_H shall be less than σ_{HP} . Three categories are recognized in the calculation of σ_H as follows.

a) Spur gears

1) Spur pinion: for a pinion, σ_H is usually calculated at the inner point of single pair tooth contact. In special cases, σ_H at the pitch point is greater and thus determinant.

2) Spur wheel: in the case of external teeth, σ_H is usually calculated at the pitch point. In special cases, particularly in the case of small transmission ratios (see 5.2), σ_H is greater at the inner point of single pair tooth contact of the wheel and is thus determinant. For internal teeth, σ_H is always calculated at the pitch point.

b) Helical gearing with overlap ratio $\varepsilon_\beta \geq 1$

σ_H is always calculated at the pitch point for pinion and wheel.

c) Helical gearing with overlap ratio $\varepsilon_\beta < 1$

In this case σ_H is determined by linear interpolation between the two limit values, i.e. σ_H for spur gears and σ_H for helical gears with $\varepsilon_\beta = 1$ in which the determination of σ_H for each is to be based on the numbers of teeth on the actual gears.

4.1 Contact stress σ_H

As stated, the contact stress is to be calculated on the basis of Hertzian pressure (see introduction).

4.1.1 Contact stress for the pinion

The total tangential load in the case of gear trains with multiple transmission paths, planetary gear systems, or split-path gear trains is not quite evenly distributed over the individual meshes (depending on design, tangential speed and manufacturing accuracy). This is to be taken into consideration by inserting a distribution factor K_γ to follow K_A in equation (1), to adjust the average tangential load per mesh as necessary.

$$\sigma_H = Z_B \sigma_{H0} \sqrt{K_A K_v K_{H\beta} K_{H\alpha}} \leq \sigma_{HP} \quad \dots (1)$$

$$\sigma_{H0} = Z_H Z_E Z_\epsilon Z_\beta \sqrt{\frac{F_t}{d_1 b} \frac{u+1}{u}} \quad \dots (2)$$

where

σ_{H0} is the nominal contact stress at the pitch point; this is the stress induced in flawless (error free) gearing by application of static nominal torque.

Z_B is the pinion single pair tooth contact factor (see 5.2). This converts contact stress at the pitch point to the contact stress at the inner point of single pair tooth contact on the pinion.

K_A is the application factor (see ISO 6336-1). It takes into account the load increment due to externally influenced variations of input or output torque.

K_v is the dynamic factor (see ISO 6336-1). It takes into account load increments due to internal dynamic effects.

$K_{H\beta}$ is the face load factor for contact stress (see ISO 6336-1). It takes into account uneven distribution of load over the facewidth, due to mesh misalignment caused by inaccuracies in manufacture, elastic deformations, etc.

$K_{H\alpha}$ is the transverse load factor for contact stress (see ISO 6336-1). It takes into account uneven load distribution in the transverse direction resulting, for example, from pitch deviation.

NOTE 2 See ISO 6336-1, subclause 4.1.10 for the sequence in which factors K_A , K_v , $K_{H\beta}$, $K_{H\alpha}$ are calculated.

σ_{HP} is the permissible contact stress (see 4.2.)

Z_H is the zone factor (see clause 5). It takes into account the flank curvatures at the pitch point and transforms tangential load at the reference cylinder to tangential load at the pitch cylinder.

Z_E is the elasticity factor (see clause 6). It takes into account specific properties of the material, moduli of elasticity E_1 , E_2 and Poisson's ratios ν_1 , ν_2 .

Z_ϵ is the contact ratio factor (see clause 7). It takes into account the influence of the effective length of the lines of contact.

Z_β is the helix angle factor (see clause 8). It takes into account influences of the helix angle, such as the variation of the load along the lines of contact.

F_t is the nominal tangential load, the transverse load tangential to the reference cylinder. The total tangential load per mesh shall be introduced for F_t in every case (even with $\varepsilon_{\alpha n} > 2$). See ISO 6336-1, subclause 4.2, for the definition of F_t and comments on particular characteristics of double-helical gearing.

b is the facewidth (for a double helix gear $b = 2 b_B$). The value b of mating gears is the smaller of the facewidths at the root circles of pinion and wheel ignoring any intentional transverse chamfers or tooth-end rounding. Neither unhardened portions of surface-hardened gear tooth flanks nor the transition zones shall be included.