BS ISO 6487:2012

BSI Standards Publication

Road vehicles — Measurement techniques in impact tests — Instrumentation

bsi.

...making excellence a habit.™

Document Sharing Hub

National foreword

This British Standard is the UK implementation of ISO 6487:2012. It supersedes BS ISO 6487:2002+A1:2008 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee AUE/7, Automobile occupant restraint systems.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2012.
Published by BSI Standards Limited 2012

ISBN 978 0 580 71179 4

ICS 43.020

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 October 2012.

Amendments issued since publication

Date	Text affected

Documents
Document Sharing Hub

Full document details: BS ISO 6487:2012

INTERNATIONAL STANDARD

ISO 6487

Fifth edition
2012-10-01

Road vehicles — Measurement techniques in impact tests — Instrumentation

Véhicules routiers — Techniques de mesurage lors des essais de chocs — Instrumentation

Reference number
ISO 6487:2012(E)

Documents
Document Sharing Hub

© ISO 2012

Full document details: BS ISO 6487:2012

COPYRIGHT PROTECTED DOCUMENT

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Documents
Document Sharing Hub
© ISO 2012 – All rights reserved

Full document details: BS ISO 6487:2012

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Performance requirements 4
4.1 CFC specifications and performance requirements 4
4.2 Phase delay time of a data channel 5
4.3 Time 5
4.4 Transducer transverse sensitivity ratio of a rectilinear transducer 6
4.5 Calibration 6
4.6 Environmental effects 8
4.7 Choice and designation of data channel 8
4.8 Choice of reference coordinate system 8
4.9 Impact velocity measurement 8
4.10 ATD temperature measurement 9

Annex A (informative) **Butterworth four-pole phaseless digital filter (including initial conditions treatment) algorithm** 10

Annex B (informative) **Recommendations for enabling requirements of the present International Standard to be met** 13

Annex C (informative) **Temperature measurement systems** 15

Bibliography 16

© ISO 2012 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 6487:2012

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 6487 was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 12, *Passive safety crash protection systems*.

This fifth edition cancels and replaces the fourth edition (ISO 6487:2002) and its Amendment 1:2008, subclauses 3.4, 3.9 and 3.13, 4.1, 4.2, 4.6.1, 4.6.2 and 4.6.3 of which have been technically revised.

Annexes A, B and C are for information only.

© ISO 2012 – All rights reserved
Documents
Document Sharing Hub
Full document details: BS ISO 6487:2012

Introduction

This edition of ISO 6487 is the result of a willingness to harmonize the previous edition, ISO 6487:2002, and SAE International's Recommended Practice, SAE J211-1 (JUL2007).

It presents a series of performance requirements concerning the whole measurement sequence of impact tests.

These requirements may not be altered by the user and all are obligatory for any agency conducting tests according to this International Standard. However, the method of demonstrating compliance with them is flexible and can be adapted to suit the needs of the particular equipment used by a testing agency.

This approach affects the interpretation of requirements. For example, there is a requirement to calibrate within the working range of the channel, i.e. between F_L and F_H/2,5. This cannot be interpreted literally, as low-frequency calibration of accelerometers requires large displacement inputs beyond the capacity of virtually any laboratory.

It is not intended that each requirement be taken as necessitating proof by a single test. Rather, it is intended that any agency proposing to conduct tests according to this International Standard guarantee that if a particular test could be and were to be carried out then their equipment would meet the requirements. This proof would be based on reasonable deductions from existing data, such as the results of partial tests.

On the basis of studies carried out by technical experts, no significant difference has been identified between the characteristics of the load transducer when measuring using static as opposed to dynamic calibration methods. This new edition helps to define the dynamic calibration method for force and moment data channels, in accordance with the current knowledge base and studies available.

The temperature of the anthropomorphic test device (ATD) used in a collision test needs to be monitored to confirm that it has been used within the acceptable temperature range prescribed for the whole ATD or body segment. The objective is to prevent temperature from being a variable that will influence the ATD response. The actual ATD temperature can be influenced by various factors, including ambient air, high-speed photography lighting, sunshine, heat dissipation from transducers and ATD in-board data acquisition systems. In order to respond to these objectives, the new edition specifies the performance requirements for the ATD temperature measurement.

To summarize, this International Standard enables users of impact test results to call up a set of relevant instrumentation requirements by merely specifying ISO 6487. Their test agency then has the primary responsibility for ensuring that the ISO 6487 requirements are met by their instrumentation system. The evidence on which they have based this proof assessment will be available to the user on request. In this way, fixed requirements, guaranteeing the suitability of the instrumentation for impact testing, can be combined with flexible methods of demonstrating compliance with those requirements.

Documents
Document Sharing Hub

© ISO 2012 – All rights reserved

Full document details: BS ISO 6487:2012

Documents
Document Sharing Hub

INTERNATIONAL STANDARD ISO 6487:2012(E)

Road vehicles — Measurement techniques in impact tests — Instrumentation

1 Scope

This International Standard gives requirements and recommendations for measurement techniques involving the instrumentation used in impact tests carried out on road vehicles. Its requirements are aimed at facilitating comparisons between results obtained by different testing laboratories, while its recommendations will assist such laboratories in meeting those requirements. It is applicable to instrumentation including that used in the impact testing of vehicle subassemblies. It does not include optical methods, which are the subject of ISO 8721.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2041, *Mechanical vibration, shock and condition monitoring — Vocabulary*

ISO 3784, *Road vehicles — Measurement of impact velocity in collision tests*

ISO 4130, *Road vehicles — Three-dimensional reference system and fiducial marks — Definitions*

ISO/TR 27957, *Road vehicles — Temperature measurement in anthropomorphic test devices — Definition of the temperature sensor locations*

SAE J211-1:2007, *Instrumentation for impact test — Part 1: Electronic instrumentation*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 2041 and the following apply.

3.1
data channel
all the instrumentation from, and including, a single transducer (or multiple transducers, the outputs of which are combined in some specified way) to, and including, any analysis procedures that may alter the frequency content or the amplitude content of data

3.2
transducer
first device in a data channel used to convert a physical quantity to be measured into a second quantity (such as an electrical voltage), which can be processed by the remainder of the channel

© ISO 2012 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 6487:2012