BS ISO 7870-6:2024

BSI Standards Publication

Control charts

Part 6: EWMA control charts for the process mean

Documents
Document Sharing Hub

Full document details: BS ISO 7870-6:2024

National foreword

This British Standard is the UK implementation of ISO 7870-6:2024. It supersedes BS ISO 7870-6:2016, which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee SS/4, Statistical Process Management.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2024
Published by BSI Standards Limited 2024

ISBN 978 0 539 23090 1

ICS 03.120.30

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 July 2024.

Amendments/corrigenda issued since publication

Date	Text affected

Documents
Document Sharing Hub

Full document details: BS ISO 7870-6:2024

International Standard

ISO 7870-6

Second edition
2024-07

Control charts —

Part 6: EWMA control charts for the process mean

Cartes de contrôle —

Partie 6: Cartes de contrôle EWMA pour la moyenne d'un processus

Reference number
ISO 7870-6:2024(en)

© ISO 2024

Documents
Document Sharing Hub

Full document details: BS ISO 7870-6:2024

COPYRIGHT PROTECTED DOCUMENT

© ISO 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Documents
Document Sharing Hub
Full document details: BS ISO 7870-6:2024

Contents

Page

Foreword ... **iv**
Introduction ... **v**
1 Scope ... **1**
2 Normative references ... **1**
3 Terms and definitions ... **1**
4 Symbols and abbreviated terms ... **2**
5 EWMA for inspection by variables ... **3**
5.1 General ... 3
5.2 Weighted average explained ... 3
5.3 Control limits for EWMA control chart ... 4
5.4 Construction of EWMA control chart ... 5
5.5 Example ... 7
6 Choice of the control chart ... **10**
6.1 Shewhart control chart versus EWMA control chart ... 10
6.2 Average run length ... 11
6.3 Choice of parameters for EWMA control chart ... 11
6.3.1 Choice of λ ... 11
6.3.2 Choice of L_z ... 12
6.3.3 Calculation for n ... 12
6.3.4 Example ... 13
7 Procedure for implementing the EWMA control chart ... **13**
8 Sensitivity of the EWMA to non-normality ... **14**
9 Advantages and limitations ... **14**
9.1 Advantages ... 14
9.2 Limitations ... 14
Annex A (informative) **Application of the EWMA control chart** ... **16**
Annex B (informative) **EWMA control chart for a proportion of nonconforming items** ... **20**
Annex C (informative) **EWMA control charts for a number of nonconformities** ... **22**
Bibliography ... **24**

© ISO 2024 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 7870-6:2024

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 69, *Applications of statistical methods*, Subcommittee SC 4, *Applications of statistical methods in product and process management*.

This second edition cancels and replaces the first edition (ISO 7870-6:2016), which has been technically revised.

A list of all parts in the ISO 7870 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO 2024 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 7870-6:2024

Introduction

Shewhart control charts are the most widespread statistical control methods used for controlling a process, but they are slow in signalling shifts of small magnitude in the process parameters. The exponentially weighted moving average[13] (EWMA) control chart makes possible faster detection of small to moderate shifts.

The Shewhart control chart is simple to implement and it rapidly detects shifts of major magnitude. However, it is fairly ineffective for detecting shifts of small or moderate magnitude. It happens quite often that the shift of the process is slow and progressive (in case of continuous processes in particular); this shift has to be detected very early in order to react before the process deviates seriously from its target value. There are two possibilities for improving the effectiveness of the Shewhart control charts with respect to small and moderate shifts.

— The simplest, but not the most economical possibility is to increase the subgroup size. This may not always be possible due to low production rate; time consuming or too costly testing. As a result, it may not be possible to draw samples of size more than 1.

— The second possibility is to take into account the results preceding the control under way in order to try to detect the existence of a shift in the production process. The Shewhart control chart takes into account only the information contained in the last sample observation and it ignores any information given by the entire sequence of points. This feature makes the Shewhart control chart relatively insensitive to small process shifts. Its effectiveness can be improved by taking into account the former results.

Where it is desired to detect slow, progressive shifts, it is preferable to use specific charts which take into account the past data and which are effective with a moderate control cost. Two very effective alternatives to the Shewhart control chart in such situations are

a) Cumulative sum (CUSUM) control chart. This chart is described in ISO 7870-4. The CUSUM control chart reacts more sensitively than the X-bar chart to a shift of the mean value in the range of half to two sigma. If one plots the cumulative sum of deviations of successive averages from a specified target, even minor, permanent shifts in the process mean will eventually lead to a sizable cumulative sum of deviations. Thus, this chart is particularly well-suited for detecting such small permanent shifts that may go undetected when using the X-bar chart.

b) Exponentially weighted moving average (EWMA) control chart which is covered by this document. This chart is presented like the Shewhart control chart; however, instead of placing on the chart the successive averages of the samples, one monitors a weighted average of the current average and of the previous averages.

EWMA control charts are generally used for detecting small shifts in the process mean. They will detect shifts of half sigma to two sigma much faster. They are, however, slower in detecting large shifts in the process mean. EWMA control charts can also be preferred when the subgroups are of size $n = 1$.

The joint use of an EWMA control chart with a small value of smoothing parameter (λ) and a Shewhart control chart has been recommended as a means of guaranteeing fast detection of both small and large shifts. The here considered EWMA control chart monitors only the process mean; monitoring the process variability requires the use of some other technique including special EWMA control charts.

The numbers in all tables and figures were calculated using the R-package SPC, (Knoth 2022), which makes use of the algorithm proposed by Crowder (1987).

The R-file containing the calculations can be downloaded on https://standards.iso.org/iso/7870/-6/ed-2/en.

© ISO 2024 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 7870-6:2024

Documents
Document Sharing Hub

Control charts —

Part 6: EWMA control charts for the process mean

1 Scope

This document covers EWMA control charts, originally proposed by Roberts (1959)[16], as a statistical process control technique to detect small shifts in the process mean. It makes possible the faster detection of small to moderate shifts in the process mean. In this chart, the process mean is evaluated in terms of exponentially weighted moving average of all previous observations or averages.

The EWMA control chart's application is worthwhile in particular when

— production rate is slow,

— a minor or moderate shift in the process mean is vital to be detected,

— sampling and inspection procedure is complex and time consuming,

— testing is expensive, and

— it involves safety risks.

NOTE EWMA control charts are applicable for both variables and attributes data. The given examples illustrate both types (see 5.5, Annex A, Annex B and Annex C).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3534-2, *Statistics — Vocabulary and symbols — Part 2: Applied statistics*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 3534-2 apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at https://www.electropedia.org/

3.1
run length
number of samples taken up to the point at which a signal occurs

3.2
average run length
ARL
Mathematical expectation of the run length

© ISO 2024 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 7870-6:2024

3.3
maximum run length
MAXRL
95 %-percentile of the run length

4 Symbols and abbreviated terms

μ_0	Target value for the mean of the process
U_μ, L_μ	Upper rejectable value of the mean, lower rejectable value of the mean
$\bar{x}_i$	Average of the sample i
R_i	Range of the sample i
n	Number of items in a sample (sample size)
z_i	EWMA value for the sample i
z_0	Initial value of EWMA series $\{z_i\}$
λ	The smoothing parameter
L_z	Factor to establish the control limit for z_i
s	Estimate of the standard deviation σ
σ	Standard deviation of the distribution of X (the random variable to be monitored)
σ_0	In-control standard deviation
$\sigma_{\bar{x}}$	Standard deviation of the averages of n individual observations; $\sigma_{\bar{x}} = \sigma / \sqrt{n}$
σ_z	Standard deviation of z_i when i tends towards infinity
δ	Shift in the mean from the target value μ_0, expressed in number of standard deviations
δ_1	Maximum acceptable shift in the mean from μ_0, expressed in number of standard deviations
p	Proportion of nonconforming items of the process
p_0	Target value for the proportion of nonconforming items of the process
p_1	Upper refusable value of the proportion of nonconforming items
p_i	Proportion of nonconforming items in the ith sample
c	Mean number of nonconformities
c_0	Target value for the mean number of nonconformities
c_1	Refusable mean of nonconformities
c_i	Number of nonconformities in the ith sample
U_{CL}	Upper control limit
L_{CL}	Lower control limit

© ISO 2024 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 7870-6:2024

ARL Average Run Length

ARL_0 Average Run Length of the process in control

ARL_1 Average Run Length of the process with shift

CL Centre line

MAXRL Maximum Run Length

5 EWMA for inspection by variables

5.1 General

An EWMA control chart plots exponentially weighted moving averages of past and current data in which the values being averaged are assigned weights that decrease exponentially from the present into the past, see Figure 1. Consequently, the average values are influenced more by recent process performance. The exponentially weighted moving average is defined as Formula (1):

$$z_i = \lambda x_i + (1 - \lambda)\, z_{i-1} \tag{1}$$

Where $0 < \lambda \leq 1$ is a constant and the starting value (required with the first sample at $i = 1$) is the process target, so that $z_0 = \mu_0$.

NOTE 1 When the EWMA control chart is used with rational subgroups of size $n > 1$ then x_i is simply replaced with $\bar{x}_i$.

NOTE 2 μ_0 can be estimated by the average of preliminary data.

The EWMA control chart becomes an $\bar{X}$ chart for $\lambda = 1$.

5.2 Weighted average explained

To demonstrate that the EWMA is a weighted average of all previous observations or averages, the right-hand side of Formula (1) in 5.1 can be substituted with z_{i-1} to obtain Formula (2):

$$\begin{aligned} z_i &= \lambda x_i + (1-\lambda)[\lambda x_{i-1} + (1-\lambda) z_{i-2}] \\ &= \lambda x_i + \lambda(1-\lambda) x_{i-1} + (1-\lambda)^2 z_{i-2} \end{aligned} \tag{2}$$

Continuing to substitute recursively for z_{i-j}, where $j = 2, 3, \ldots$, we obtain Formula (3):

$$z_i = \lambda \sum_{j=0}^{i-1} (1-\lambda)^j x_{i-j} + (1-\lambda)^i z_0 \tag{3}$$

For $i = 1$, $z_1 = \lambda x_1 + (1 - \lambda)\mu_0$.

The weights, $\lambda(1 - \lambda)^j$, decrease geometrically with the age of the observation or average. Furthermore, the weights sum to unity:

$$\lambda \sum_{j=0}^{i-1} (1-\lambda)^j + (1-\lambda)^i = \lambda \left[\frac{1-(1-\lambda)^i}{1-(1-\lambda)} \right] + (1-\lambda)^i = 1 \tag{4}$$

If $\lambda = 0{,}25$, then the weight assigned to the current average is 0,25 and the weights given to the preceding averages are 0,187 5; 0,140 6; 0,105 5 and so forth. These weights are shown in Figure 1. Because these weights decline geometrically, the EWMA is sometimes called a geometric moving average (GMA), which is the original name of the control chart[16].

© ISO 2024 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO 7870-6:2024