



BSI Standards Publication

Information technology — Metadata registries (MDR)

Part 32: Metamodel for concept system registration

National foreword

This British Standard is the UK implementation of [ISO/IEC 11179-32:2023](#). Together with [BS ISO/IEC 11179-31:2023](#) and [BS ISO/IEC 11179-3:2023](#), it supersedes [BS ISO/IEC 11179-3:2013+A1:2020](#) which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee IST/40, Data management and interchange.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2023
Published by BSI Standards Limited 2023

ISBN 978 0 539 13690 6

ICS 35.040.50

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 28 February 2023.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

INTERNATIONAL STANDARD

ISO
11179-32

First edition
2023-01-16

Information technology — Metadata registries (MDR) —

Part 32: Metamodel for concept system registration

*Technologies de l'information — Registres de métadonnées (RM) —
Partie 32: Métamodèle pour l'enregistrement de systèmes de concepts*



Reference number
ISO 11179-32:2023(E)

AVA Documents
Document Sharing Hub
© ISO 2023



COPYRIGHT PROTECTED DOCUMENT

© ISO 2023, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Abbreviated terms	4
5 Conformance	5
5.1 Overview of conformance	5
5.2 Degree of conformance	5
5.2.1 General	5
5.2.2 Strictly conforming implementations	5
5.2.3 Conforming implementations	6
5.3 Conformance by feature	6
5.4 Registry conformance	6
5.4.1 Standard registry profiles	6
5.4.2 Conformance labels	6
5.5 Implementation conformance statement (ICS)	7
5.6 Obligation	7
6 Relationship to ISO/IEC 11179-3	7
6.1 Metamodel for a metadata registry	7
6.2 Specification of the metamodel	7
6.3 Use of UML Class diagrams and textual description	8
6.4 Package dependencies	8
6.5 Subclassing the Constraint_Set class	9
6.6 Relationship to Classification region in ISO/IEC 11179-3:2023	9
7 Concept_System package	9
7.1 Overview of the Concept_System package	9
7.2 Concept System metamodel region	9
7.2.1 Overview	9
7.2.2 Classes in the Concept System metamodel region	10
7.2.3 Associations of the Concept System metamodel region	18
8 Binary_Relations package	21
8.1 Overview of Binary_Relations package	21
8.2 Binary Relations metamodel region	21
8.2.1 Overview	21
8.2.2 Classes in the Binary Relations metamodel region	21
8.2.3 Datatypes in the Binary_Relation metamodel region	22
Annex A (informative) Consolidated Class Hierarchy	24
Annex B (informative) Concept System Examples	25
Annex C (informative) Mapping ISO/IEC 11179-3:2023 Classification_Scheme to ISO/IEC 11179-32:2023 Concept_System	54
Bibliography	55

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see <https://patents.iec.ch>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by Joint Technical Committee ISO/IEC/JTC 1, *Information technology*, Subcommittee SC 32, *Data management and interchange*.

A list of all parts in the ISO/IEC 11179 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

Introduction

[ISO/IEC 11179-3](#) specifies the structure of a Metadata Registry (MDR) and provides a metamodel for registry common facilities. That metamodel is intended to be extended by other parts of [ISO/IEC 11179](#) for specific purposes.

This first edition of [ISO/IEC 11179-32](#), is part of a restructuring of [ISO/IEC 11179-3:2013](#), which has now been broken into multiple parts. This document provides a metamodel for registering metadata about concept systems and binary relations in a Metadata Registry (MDR), as extensions to the registry metamodel specified in [ISO/IEC 11179-3](#).

In [Clauses 7](#) and [8](#), this document uses:

- **bold** font to highlight terms which represent metadata objects specified by the metamodel;
- normal text for terms which represent concepts defined in [Clause 3](#).

EXAMPLE **Concept** ([7.2.2.1](#)) is a class each instance of which models a concept.

This page deliberately left blank

Information technology — Metadata registries (MDR) —

Part 32: Metamodel for concept system registration

1 Scope

This document provides a specification for an extension to a metadata registry (MDR), as specified in [ISO/IEC 11179-3:2023](#), in which metadata that describes concept systems can be registered.

The specification in this document, together with the relevant clauses of the specification in [ISO/IEC 11179-3](#), provides the ability to record the following metadata:

- concept systems and associated concepts;
- relations among concepts in a concept system;
- assertions about concepts in a concept system.

The metamodel in this document is intended to support the full description of a concept system, including ontologies.

Where there is a requirement to register an ontology where the details are defined elsewhere, consider using [ISO/IEC 19763-3^{\[8\]}](#) instead.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

[ISO/IEC 11179-3:2023](#), *Information technology — Metadata registries (MDR) — Part 3: Metamodel for registry common facilities*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in [ISO/IEC 11179-3](#) and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org/>

3.1

concept

unit of knowledge created by a unique combination of characteristics

Note 1 to entry: Concepts are not necessarily bound to particular natural languages. They are, however, influenced by the social or cultural background which often leads to different categorizations.

Note 2 to entry: This is the concept “concept” as used and designated by the term “concept” in terminology work. It is a very different concept from that designated by other domains such as industrial automation or marketing.

Note 3 to entry: A concept is independent of its representation.

[SOURCE: ISO 1087:2019, 3.2.7, modified — Reference to definition of *characteristics* removed. Note 3 to entry added.]

3.2

concept system

system of concepts

set of *concepts* (3.1) structured in one or more related domains according to the *concept relations* (3.3) among its concepts

[SOURCE: ISO 1087:2019, 3.2.28]

3.3

relation

concept relation

sense in which *concepts* (3.1) may be connected, via constituent *relation roles* (3.4)

EXAMPLE Causality is a relation with two constituent roles: cause and effect.

Note 1 to entry: The related concepts may be general or individual concepts.

3.4

relation role

role (3.5) that a *concept* (3.1) plays in a *relation* (3.3)

3.5

role

specified responsibilities

3.6

link

member of a *relation* (3.3)

3.7

link end

end of a *link* (3.6), identifying the *relation role* (3.4) played by a *concept* (3.1) in the link

3.8

binary relation

relation (3.3) with *arity* (3.9) equal to 2 (i.e. whose members all have two ends)

Note 1 to entry: Most common semantic relations are binary, e.g. “equals”, “less than”, “greater than”, “is part of”, etc. An example of a relation which is not binary is “betweenness” (e.g. A is between B and C.).

3.9

arity

number of arguments that a function takes

3.10

reflexivity

characterization of a *binary relation* (3.8) as reflexive, irreflexive or antireflexive

Note 1 to entry: A binary relation, R, is reflexive if for all x, R(x,x) is true. Equality is an example of a reflexive relation.

Note 2 to entry: A binary relation, R, is irreflexive if it is not reflexive. i.e., R(x,x) is not necessarily true for all x.

Note 3 to entry: A binary relation, R, is antireflexive if for all x, R(x,x) is false. Inequality is an example of an antireflexive relation. An antireflexive relation is also irreflexive, but antireflexive is a more specific characterization.

3.11

symmetry

characterization of a *binary relation* (3.8) as symmetric, asymmetric or antisymmetric

Note 1 to entry: A binary relation, R , is symmetric if for all x, y : $R(x,y)$ implies $R(y,x)$.

EXAMPLE 1 Symmetric relations include: “equals”, “not equals”, “within-2-miles-of”, etc.

Note 2 to entry: Symmetry does not imply *reflexivity* (3.18).

EXAMPLE 2 the “inequality” relation is symmetric, but antireflexive.

Note 3 to entry: A binary relation, R , is asymmetric if for all x,y : $R(x,y)$ does not imply $R(y,x)$.

EXAMPLE 3 Asymmetric relations include: “less than”, “likes”, “father of”, etc.

Note 4 to entry: A binary relation, R , is anti-symmetric if for all x,y : $R(x,y)$ implies not $R(y,x)$. An antisymmetric relation is also asymmetric, but antisymmetric is a more specific characterization.

EXAMPLE 4 “less than” is an antisymmetric relation.

Note 5 to entry: An asymmetric relation is not necessarily antisymmetric.

EXAMPLE 5 Less than or equals.

3.12

transitivity

characterization of a *binary relation* (3.8) as: transitive, intransitive or antitransitive

Note 1 to entry: A binary relation, R , is transitive, if for all x,y,z : $R(x,y)$ and $R(y,z)$ implies $R(x,z)$. Examples of transitive relations include equality, less than and less than or equals.

Note 2 to entry: A binary relation, R , is intransitive if it is not transitive i.e. $R(x,y)$ and $R(y,z)$ does not imply $R(x,z)$.

Note 3 to entry: A binary relation, R , is antitransitive if for all x,y,z : $R(x,y)$ and $R(y,z)$ implies not $R(x,z)$.

Note 4 to entry: An antitransitive relation is also intransitive, but antitransitive is a more specific characterization.

3.13

object

anything perceivable or conceivable

Note 1 to entry: Objects can be material (e.g. “engine”, “sheet of paper”, “diamond”), immaterial (e.g. “conversion ratio”, “project plan”) or imagined (e.g. “unicorn”, “scientific hypothesis”).

[SOURCE: ISO 1087:2019, 3.1.1]

3.14

property

feature of an *object* (3.13)

EXAMPLE 1 “Being made of wood” as a property of a given “table”.

EXAMPLE 2 “Belonging to person A” as a property of a given “pet”.

EXAMPLE 3 “Having been formulated by Einstein” as a property of the equation “ $E = mc^2$ ”.

EXAMPLE 4 “Being compassionate” as a property of a given “person”.

EXAMPLE 5 “Having a given cable” as a property of a given “computer mouse”.

Note 1 to entry: One or more objects can have the same property.

[SOURCE: ISO 1087:2019, 3.1.3]

3.15

characteristic

abstraction of a *property* ([3.14](#))

EXAMPLE “Having a cable for connecting with a computer” as a characteristic of the concept “cord mouse”.

Note 1 to entry: Characteristics are used for describing *concepts* ([3.6](#)).

[SOURCE: ISO 1087:2019, 3.2.1]

3.16

notation

formal syntax and associated semantics for the representation of information

EXAMPLE UML,[\[5\]](#)[\[6\]](#)[\[7\]](#) MOF, OCL, OWL[\[11\]](#)/RDF,[\[12\]](#) SKOS,[\[13\]](#) CGIF,[\[9\]](#) XCL,[\[9\]](#) XTM[\[17\]](#) or [ISO/IEC 11404](#)[\[4\]](#)

Note 1 to entry: A formal syntax consists of a set of symbols and the rules for their use.

Note 2 to entry: Formal syntax is often intended for machine processing.

[SOURCE: ISO/IEC 11179-3:2023, 3.2.36]

3.17

assertion

sentence or proposition in logic which is asserted (or assumed) to be true

3.18

cardinality

number of elements in a set

Note 1 to entry: cf. *multiplicity* ([3.19](#))

Note 2 to entry: Adapted from [ISO/IEC 19501:2005](#),[\[5\]](#) Glossary.

3.19

multiplicity

specification of the range of allowable *cardinalities* ([3.18](#)) that a set may assume

Note 1 to entry: Multiplicity specifications may be given for roles within *associations* ([ISO/IEC 11179-3:2023](#), 3.1.5)

Note 2 to entry: A multiplicity is a (possibly infinite) subset of the nonnegative integers

Note 3 to entry: Adapted from [ISO/IEC 19501:2005](#),[\[5\]](#) Glossary.

3.20

taxonomy

type of hierarchy which deals with generalization/specialization relationships

Note 1 to entry: cf. *meronymy* ([3.21](#))

3.21

meronymy

type of hierarchy which deals with part-whole relationships

Note 1 to entry: cf. *taxonomy* ([3.20](#))

4 Abbreviated terms

CD	Conceptual Domain
CL [9]	Common Logic
CLIF [9]	Common Logic Interchange Format

OWL[11]	Web Ontology Language
OWL-DL	OWL Description Logic
RDF[12]	Resource Description Framework
SKOS[13]	Simple Knowledge Organization System
UML[5][6][7]	Unified Modeling Language
URI	Uniform Resource Identifier
W3C[15]	World Wide Web Consortium
XCL[9]	eXtended Common Logic markup language
XML[16]	eXtensible Markup Language
XTM[17]	XML Topic Maps

5 Conformance

5.1 Overview of conformance

Conformance rules for a Metadata Registry are specified in [ISO/IEC 11179-3:2023](#), Clause 4. The clause “Degree of Conformance” is repeated here for convenience. The subsequent subclauses extend the rules from [ISO/IEC 11179-3](#).

5.2 Degree of conformance

5.2.1 General

The distinction between “strictly conforming” and “conforming” implementations is necessary to address the simultaneous needs for interoperability and extensions. This document describes specifications that promote interoperability. Extensions are motivated by needs of users, vendors, institutions and industries, and:

- a) are not directly specified by this document;
- b) are specified and agreed to outside this document;
- c) may serve as trial usage for future editions of this document.

A strictly conforming implementation can be limited in usefulness but is maximally interoperable with respect to this document. A conforming implementation can be more useful but can be less interoperable with respect to this document.

5.2.2 Strictly conforming implementations

A strictly conforming implementation:

- a) shall support all mandatory, optional and conditional classes, attributes, datatypes and associations;
- b) shall not use, test, access or probe for any extension features nor extensions to classes, attributes, datatypes, associations or any combination thereof;
- c) shall not recognize, nor act on, nor allow the production of classes, attributes, datatypes, associations or any combination thereof that are dependent on any unspecified, undefined or implementation-defined behaviour.

NOTE The use of extensions to the metamodel can cause undefined behaviour.

5.2.3 Conforming implementations

A conforming implementation:

- a) shall support all mandatory, optional and conditional classes, attributes, datatypes and associations;
- b) as permitted by the implementation, may use, test, access or probe for extension features or extensions to classes, attributes, datatypes, associations or any combination thereof;
- c) may recognize, act on or allow the production of classes, attributes, datatypes, associations or any combination thereof that are dependent on implementation-defined behaviour.

NOTE 1 All strictly conforming implementations are also conforming implementations.

NOTE 2 The use of extensions to the metamodel can cause undefined behaviour.

5.3 Conformance by feature

Conformance claims may be made to [Clause 7](#) and optionally [Clause 8](#), or to specific features within these clauses. Those clauses are also dependent upon one or more other clauses of [ISO/IEC 11179-3](#), so conformance to all or part of those clauses shall be understood to imply conformance also to relevant provisions specified in one or more of the clauses in [ISO/IEC 11179-3](#).

A conformance statement shall specify exactly the features supported and not supported.

5.4 Registry conformance

5.4.1 Standard registry profiles

This document specifies the following standard profiles in addition to those specified in [ISO/IEC 11179-3:2023](#), 4.4.2.

- **Concept System Registry:** Implements [Clause 7](#) in addition to all provisions of the “Basic Registry” profile of [ISO/IEC 11179-3:2023](#), 4.4.2;
- **Concept System and Binary Relations Registry:** Implements [Clauses 7](#) and [8](#) in addition to all provisions of the “Basic Registry” profile of [ISO/IEC 11179-3:2023](#), 4.4.2;
- **Concept System Registry with mapping:** Implements [Clause 7](#) in addition to all provisions of the “Basic Registry with mapping” profile of [ISO/IEC 11179-3:2023](#), 4.4.2;
- **Concept System and Binary Relations Registry with mapping:** Implements [Clauses 7](#) and [8](#) in addition to all provisions of the “Basic Registry with mapping” profile of [ISO/IEC 11179-3:2023](#), 4.4.2.

5.4.2 Conformance labels

Conformance to the profiles specified in [5.4.1](#) may be claimed using the following labels, respectively:

- [ISO/IEC 11179-32:2023](#) Concept System Registry;
- [ISO/IEC 11179-32:2023](#) Concept System and Binary Relations Registry;
- [ISO/IEC 11179-32:2023](#) Concept System Registry with mapping;
- [ISO/IEC 11179-32:2023](#) Concept System Registry and Binary Relations with mapping.

5.5 Implementation conformance statement (ICS)

An implementation claiming conformance to this document shall include an Implementation Conformance Statement stating:

- a) whether it conforms or strictly conforms;
- b) which clauses are or are not supported;
- c) what extensions, if any, are supported or used.

A standard profile may be referenced, if applicable.

EXAMPLE Product Z strictly conforms to [ISO/IEC 11179-32:2023](#) Concept System Registry with Mapping.

5.6 Obligation

Properties and relationships specified in this document are one of: Mandatory, Conditional or Optional. The obligation is not explicitly stated but is to be inferred from the multiplicity of the property or relationship, and the presence or absence of a condition. In addition, a Registration Authority can specify additional constraints to be applied to particular **Administered_Items** (see [ISO/IEC 11179-3:2023](#), 9.4.2), using **Constraint_Sets** (see [ISO/IEC 11179-3:2023](#), 9.4.6). See [6.5](#).

For the purpose of conformance:

- a) Mandatory properties and relationships shall exist and shall conform to the provisions of this document.
- b) Anything specified as Conditional within this document shall be treated as Mandatory if the associated condition is satisfied and shall otherwise be not present.
- c) Optional properties and relationships are not required to exist, but if they do exist, they shall conform to the provisions of this document.

Such obligation is enforced if and only if the Registration Status of the associated registry items is Recorded or higher (see [ISO/IEC 11179-3:2023](#), 9.4.6.3 and [ISO/IEC 11179-6:2023](#), [\[3\]](#) 4.4).

6 Relationship to ISO/IEC 11179-3

6.1 Metamodel for a metadata registry

A metamodel is a model that describes other models. A metamodel provides a mechanism for understanding the precise structure and components of the specified models, which are needed for the successful sharing of the models by users, software facilities or both.

[ISO/IEC 11179-3](#) uses a metamodel to describe the information model of a metadata registry. The registry in turn will be used to describe and model other data, for example about enterprise, public administration or business applications. The registry metamodel is specified as a conceptual data model, i.e., one that describes how relevant information is structured in the natural world. In other words, it is how the human mind is accustomed to thinking of the information.

6.2 Specification of the metamodel

The conventions used in specifying the metamodel are described in [ISO/IEC 11179-3:2023](#), 5.3. Many of the classes specified in this document inherit from **Item**, which is specified in [ISO/IEC 11179-3:2023](#), 6.4.2.1. As **Items**, instances of these classes may be identified, registered, administered, named, defined and classified.

6.3 Use of UML Class diagrams and textual description

This document uses both text and UML class diagrams to describe the metamodel. Both are normative and are intended to be complementary. However, if a conflict exists between what is specified in UML and what is specified in text, the text takes precedence until a correction is made to make them consistent. Further, if a conflict exists between a formal definition and other normative text, the formal definition takes precedence until a correction is made to make them consistent.

A consolidated UML class hierarchy is included as [Annex A](#).

While the model diagrams are presented in UML notation, this document does not assume nor endorse any specific system environment, database management system, database design paradigm, system development methodology, data definition language, command language, system interface, user interface, computing platform or any technology required for implementation.

6.4 Package dependencies




Figure 1 — Package dependencies

[Figure 1](#) illustrates the dependencies among the packages. The **Concept_System** and **Binary_Relations** packages are specified in this document. All the other packages are specified in [ISO/IEC 11179-3:2023](#).

The lines in the figure illustrate dependencies in the direction of the arrow. In order to implement a package that has dependencies, the packages on which it is dependent shall also be implemented. The dependencies are of three types:

- Subclassing from classes in another package, e.g. **Relation** ([7.2.2.3](#)) in the **Concept_System** package is subclassed from the **Concept** class in the **Basic and Core** package ([ISO/IEC 11179-3:2023](#), 6.4.2.2), and **Concept_Constraint_Set** ([7.2.2.8](#)) in the **Concept_System** package is subclassed from the **Constraint_Set** class in the **Registration** package ([ISO/IEC 11179-3:2023](#), 9.4.6).
- Relationship between classes, e.g. **Registered_Item** in the **Registration** package ([ISO/IEC 11179-3:2023](#), 9.4.1) has a relationship with **Reference_Document** in the **Basic_and_Core** package ([ISO/IEC 11179-3:2023](#), 6.3.8).

- c) Some attributes use a predefined datatype or a class from another package as a datatype, e.g. the **contact** attribute of the **Stewardship_Record** class in the **Registration** package (ISO/IEC 11179-3:2023, 9.4.7) uses the **Contact** class of the **Basic_and_Core** package (ISO/IEC 11179-3:2023, 6.3.5) as a datatype.

Conformance options are specified in [Clause 5](#) and standard conformance profiles in [5.3](#).

6.5 Subclassing the Constraint_Set class

This document extends the **Constraint_Set** class (ISO/IEC 11179-3:2023, 9.4.6) by specifying subclasses to support constraints specified in this document. See [Figure 2](#).




Figure 2 — Subclassing Constraint_Set

Concept_Constraint_Set is specified in [7.2.2.8](#).

Relation_Constraint_Set is specified in [7.2.2.9](#).

Any registry implementation shall provide a mechanism to enforce these constraints.

6.6 Relationship to Classification region in ISO/IEC 11179-3:2023

There are some overlaps in functionality between the **Concept_System** package specified in this document and the **Classification** package specified in ISO/IEC 11179-3:2023, Clause 10. [Annex C](#) provides a mapping between the two facilities and an explanation for the duplication.

7 Concept_System package

7.1 Overview of the Concept_System package

The **Concept_System** package consists of a single metamodel region, the Concept System metamodel region.

7.2 Concept System metamodel region

7.2.1 Overview

The Concept System metamodel region is illustrated in [Figure 3](#). The purpose of this metamodel region is to describe concepts (abstract units of knowledge), represented by instances of **Concept** ([7.2.2.1](#)), and the various relations, represented by instances of **Relation** ([7.2.2.3](#)), which hold among the concepts. Support for more advanced concept systems, such as ontologies with formal semantics is provided through the use of assertions, represented by instances of **Assertion** ([7.2.2.5](#)). [Annex B](#) provides examples using SKOS, ORM, OWL and CLIF.




Figure 3 — Concept system metamodel region

7.2.2 Classes in the Concept System metamodel region

7.2.2.1 Concept class

7.2.2.1.1 Direct superclass

Concept is a subclass of **Item** (ISO/IEC 11179-3:2023, 6.4.2.1), allowing instances to be identified, registered, administered, named, defined and classified.

7.2.2.1.2 Description of Concept

Concept is part of the Core metamodel and is specified in ISO/IEC 11179-3:2023, 6.4.2.2. Additional associations are specified in this metamodel region.

Concept is a class, each instance of which models a concept, a unit of knowledge created by a unique combination of characteristics. A concept is independent of representation.

Concept is a superclass of both **Relation** ([7.2.2.3](#)) and **Relation_Role** ([7.2.2.4](#)). These specializations are disjoint, and the specialization hierarchy is incomplete.

7.2.2.1.3 Associations of Concept

As a subclass of **Item**, **Concept** inherits **Item**'s associations ([ISO/IEC 11179-3:2023](#), 6.4.2.1.2). This metamodel region specifies the following associations:

- **concept_system_membership** ([7.2.3.1](#));
- **concept_source** ([7.2.3.2](#));
- **assertion_about_concept** ([7.2.3.7](#));
- **link_end_concept** ([7.2.3.11](#)).

7.2.2.1.4 Attributes of Concept

The attributes of **Concept** are specified in [ISO/IEC 11179-3:2023](#), 6.4.2.2.4.

7.2.2.2 Concept_System class

7.2.2.2.1 Direct superclass

Concept_System is a subclass of **Item** ([ISO/IEC 11179-3:2023](#), 6.4.2.1), allowing instances to be identified, registered, administered, named, defined and classified.

7.2.2.2.2 Description of Concept_System

Concept_System is a class, each instance of which models a concept system, a set of concepts structured according to the relations among them.

A minimal concept system can simply be a collection of concepts. A more elaborate concept system could be a collection of concepts organized into a taxonomy or meronomy specified by means of various relations (e.g. semantic relations) among the concepts.

NOTE 1 Examples of concept systems are included in [Annex B](#).

NOTE 2 If a concept system is available in multiple notations, it is good practice to register the concept system only once and to use reference documents to record the various notations.

7.2.2.2.3 Associations of Concept_System

A **Concept_System** has the following associations:

- **concept_system_membership** ([7.2.3.1](#));
- **concept_source** ([7.2.3.2](#));
- **concept_system_reference** ([7.2.3.3](#));
- **concept_system_importation** ([7.2.3.4](#));
- **assertion_inclusion** ([7.2.3.6](#)).

7.2.2.2.4 Attributes of Concept_System

See [Table 1](#).

Table 1 — Attributes of Concept_System

Attribute name	Multiplicity	Datatype	Description
notation	0..1	Notation (ISO/IEC 11179-3:2023 , 6.2.7)	Definition: notation used in specification of this concept system. Comment: Examples of such notations include XCL Common Logic (ISO/IEC 24707) or OWL-DL XML notation (Ontology Web Language from W3C).
source_uri	0..1	String (ISO/IEC 11179-3:2023 , 6.2.11)	Definition: URI that enables access to the concept system Provides access to details of the concept system that are external to the registry.

7.2.2.3 Relation class

7.2.2.3.1 Direct superclass

Relation is a subclass of **Concept** (specified in [ISO/IEC 11179-3:2023](#), 6.4.2.2). **Concept** in turn is a subclass of **Item** (specified in [ISO/IEC 11179-3:2023](#), 6.4.2.1), allowing instances to be identified, registered, administered, named, defined and classified.

7.2.2.3.2 Description of Relation

Relation is a class, each instance of which models a relation, a sense in which concepts may be connected via constituent relation roles.

Relation is a superclass of the **Binary_Relation** class which is described in [8.2.2.2](#).

Any relation is also a concept in its own right (and hence **Relation** is a subclass of **Concept**). A unary relation is just a concept and should be registered as such. Only relations with arity 2 or greater can be registered as **Relations**.

A reflexive relation (i.e. one which refers to itself) needs to be modelled using an **Assertion**.

NOTE 1 A **Relation** is a subset of the powerset of $R \times UD$, for some role set R , where UD is the universe of discourse.

NOTE 2 An n -ary **Relation** on sets $A_1, \dots, A_n$ is a set of ordered n -tuples $\langle a_1, \dots, a_n \rangle$ where a_i is an element of A_i for all i , i between 1 and n . Thus, an n -ary **Relation** on sets $A_1, \dots, A_n$ is a subset of Cartesian product $A_1 \times \dots \times A_n$. Membership of an n -tuple in the **Relation** is specified through **Assertions**, the simplest form of which is a **Link** representing exactly one tuple of the **Relation**. In this metamodel, **Relations** are defined over sets of **Concepts**.

NOTE 3 In this metamodel, unordered n -tuples are used with named **Relation_Roles** rather than positional elements of the n -tuple. The ordering can optionally be specified using the **ordinal** attribute on **Relation_Role**.

7.2.2.3.3 Associations of Relation

As a subclass of **Concept**, **Relation** inherits **Concept**'s associations. **Relation** has the following additional associations:

- **relation_role_set** ([7.2.3.5](#));
- **relation_link** ([7.2.3.9](#));
- **assertion_of_predicate** ([7.2.3.8](#)).

7.2.2.3.4 Attributes of Relation

See [Table 2](#).