

Information technology — Telecommunications and information exchange between systems — Private integrated services network —

**Part 1: Reference configuration for
PISN Exchanges (PINX)**

ICS 35.110

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

BSI
Documents

AVA

Document Sharing Hub

Committees responsible for this British Standard

The preparation of this British Standard was entrusted by the Information Systems Technology Standards Policy Committee (IST/-) to Technical Committee IST/6, upon which the following bodies were represented:

- British Computer Society
- British Telecommunications plc
- CCTA (the Government Centre for Information Systems)
- Digital Equipment Co. Ltd.
- IBM United Kingdom Ltd.
- Institution of Electrical Engineers
- International Computers Limited
- Joint Information Systems Committee
- Logica UK Ltd.
- Nine Tiles Computer Systems Ltd.
- Rank Xerox Ltd.

This British Standard, having been prepared under the direction of the Information Systems Technology Standards Policy Committee, was published under the authority of the Standards Board and comes into effect on 15 January 1995

© BSI 04-2000

The following BSI references relate to the work on this standard:
Committee reference IST/6
Draft for comment 92/68700 DC

ISBN 0 580 23674 9

Amendments issued since publication

Amd. No.	Date	Comments
9671	November 1997	Indicated by a sideline in the margin

Contents

	Page
Committee responsible	Inside front cover
National foreword	ii
Foreword	iii
Text of ISO/IEC 11579-1	1

National foreword

This British Standard reproduces verbatim ISO/IEC 11579-1:1994 together with Technical Corrigendum No. 1:1996 and implements it as the UK national standard.

This British Standard is published under the direction of the Information Systems Technology Standards Policy Committee whose Technical Committee IST/6 has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international committee any enquiries on interpretation, or proposals for change, and keep UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

NOTE International and European Standards, as well as overseas standards, are available from Customer Services, BSI, 389 Chiswick High Road, London W4 4AL.

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, the ISO/IEC title page, pages ii to iv, pages 1 to 9 and a back cover.

This standard has been updated (see copyright date) and may have had amendments incorporated. This will be indicated in the amendment table on the inside front cover.

**Information technology —
Telecommunications and information
exchange between systems — Private
integrated services network —**

Part 1:

Reference configuration for PISN Exchanges
(PINX)

*Technologies de l'information — Télécommunications et échange
d'information entre systèmes — Réseau privé avec intégration de
services —*

Partie 1: Configuration de référence pour échanges de PISN (PINX)



Reference number
ISO/IEC 11579-1:1994(E)

Contents

	Page
Foreword	iii
Introduction	1
1 Scope	1
2 Normative references	1
3 Symbols and abbreviations	2
4 Definitions	2
5 PINX reference configuration	2
5.1 Terminal equipment (TE)	3
5.2 Private termination system functional grouping (PTS)	3
5.3 Switching functional grouping (SW)	3
5.4 Mapping functional grouping (MP)	3
5.5 Public ISDN access termination functional grouping (PIAT)	3
5.6 Inter-PINX connection control functional grouping (ICC)	3
5.7 Call control functional grouping (CC)	3
5.8 Scenario management	3
6 Reference points (RP)	4
6.1 C reference point	4
6.2 Q reference point	4
6.3 S reference point	4
6.4 T reference point	4
7 Use of the PINX reference configuration	4
7.1 Multiple instances of Q reference point	4
7.2 Multiple instances of C reference point	4
7.3 Multiple IVN interfaces	4
7.4 Shared interface use	4
Annex A (informative) Termination of signalling information flows	6
Annex B (informative) Public ISDN/PISN interworking scenarios	6
Annex C (informative) Example of a PISN employing multiple instances of Q reference points	7
Annex D (informative) Example for the application of the PINX reference configuration to a PISN	9
Figure 1 — PINX reference configuration	3
Figure 2 — Multiple instances of Q reference points	5
Figure 3 — Multiple instances of C reference point	5
Figure 4 — Shared use of an interface to a public ISDN	5
Figure A.1 — Application of the PINX reference configuration to protocol termination	6
Figure B.1 — Overlay scenario	6
Figure B.2 — Concatenation scenario	7
Figure C.1 — Example for the application of the PINX reference configuration to a PISN with multiple instances of Q reference point and with shared interface use	8
Figure D.1 — Application of the PINX reference configuration to a PISN	9