

Information technology — Configuration of Customer Premises Cabling (CPC) for applications —

Part 1: ISDN basic access

ICS 33.080

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW



Document Sharing Hub

National foreword

This British Standard reproduces verbatim ISO/IEC 14709-1:1997 and implements it as the UK national standard.

The UK participation in its preparation was entrusted to Technical Committee IST/39, Interconnection of IT Equipment, Cabling, Microprocessors, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international/European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this committee can be obtained on request to its secretary.

Cross-references

The British Standards which implement international or European publications referred to in this document may be found in the BSI Standards Catalogue under the section entitled “International Standards Correspondence Index”, or by using the “Find” facility of the BSI Standards Electronic Catalogue.

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, the ISO/IEC title page, pages ii to iv, pages 1 to 16 and a back cover.

This standard has been updated (see copyright date) and may have had amendments incorporated. This will be indicated in the amendment table on the inside front cover.

This British Standard, having been prepared under the direction of the DISC Board, was published under the authority of the Standards Board and comes into effect on 15 November 1997

© BSI 04-2000

ISBN 0 580 27863 8

Amendments issued since publication

Amd. No.	Date	Comments

Contents

	Page
National foreword	Inside front cover
Foreword	iv
Text of ISO/IEC 14709-1	1

INTERNATIONAL STANDARD

ISO/IEC 14709-1

First edition
1997-09-01

Information technology — Configuration of Customer Premises Cabling (CPC) for applications —

Part 1: Integrated Services Digital Network (ISDN) basic access

*Technologies de l'information — Configuration du câblage dans les locaux
d'utilisateurs (CPC) pour les applications —*

*Partie 1: Accès de base au réseau numérique à intégration de services
(RNIS)*



Contents

	Page
Foreword	iv
Introduction	1
1 Scope	1
2 Normative references	1
3 Definitions	1
4 Abbreviations and symbols	2
4.1 Abbreviations	2
4.2 Symbols	2
5 Design requirements	3
5.1 General	3
5.2 Insertion loss	3
5.3 Longitudinal conversion loss	3
5.4 Round trip delay	3
5.5 Power feeding	3
5.6 Electromagnetic environment	4
5.7 Spurs	4
5.8 Near-end crosstalk loss (NEXT)	4
6 Configurations	4
6.1 General	4
6.2 The point-to-point configuration	5
6.3 The short passive bus configuration	6
6.4 The extended passive bus configuration	7
6.5 The Y-configuration	7
6.6 The star configuration	8
6.7 Implementation over structured cabling systems	8
7 Minimum requirements for cabling components	11
7.1 General	11
7.2 Cables	11
7.3 Terminal cords	11
7.4 Terminating resistors	12
7.5 Outlets and joint boxes	12
7.6 Cross-connect products/patch cords	12
8 Cabling qualification	12
8.1 General	12
8.2 Spurs	13
8.3 Cabling integrity	13
8.4 D.c. loop resistance	13
8.5 D.c. lead resistance unbalance	13
8.6 Insulation resistance	13
8.7 Insertion loss	13
8.8 Round trip delay	14
8.9 Characteristic impedance	14
8.10 Near end crosstalk (NEXT) loss	14
8.11 Impulsive noise	14
8.12 Bit error rates	14
8.13 Longitudinal conversion loss	14
Annex A (informative) Bibliography	15
Annex B (informative) Examples of maximum distances for specific common cables	16
Figure 1 — Round trip delay requirements	4

	Page
Figure 2 — Point-to-point configuration	5
Figure 3 — Short passive bus	6
Figure 4 — Extended passive bus	7
Figure 5 — Y-configuration	8
Figure 6 — NT location in the generic cabling structure	9
Figure 7 — ISDN structured cabling adapter	10
Figure 8 — ISDN structured cabling multipoint adapter	10
Figure 9 — ISDN structured cabling multipoint adapters in series	11
Table 1 — Maximum insertion loss for each configuration	3
Table 2 — Pin assignments	12
Table B.1 — Examples of recommended maximum distances for typical installations	16

Descriptors: Data processing, information interchange, telecommunications, ISDN, public network, buildings, premises, communication cables, cabling, specifications.

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 14709-1 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 25, *Interconnection of information technology equipment*.

ISO/IEC 14709 consists of the following parts, under the general title *Information technology — Configuration of Customer Premises Cabling (CPC) for applications*:

- *Part 1: Integrated Services Digital Network (ISDN) basic access*;
- *Part 2: Integrated Services Digital Network (ISDN) primary access*;

Annex A and Annex B of this part of ISO/IEC 14709 are for information only.