

**Information
technology —
Telecommunications
and information
exchange between
systems —
Private Integrated
Services Network —
Specification,
functional model and
information flows —
Call interception
additional network
feature**

ICS 33.040.40; 35.110

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

BSI
Documents

AVA

Document Sharing Hub

National foreword

This British Standard reproduces verbatim ISO/IEC 15053:1997 and implements it as the UK national standard.

The UK participation in its preparation was entrusted to Technical Committee IST/6, Data communications, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international/European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this committee can be obtained on request to its secretary.

From 1 January 1997, all IEC publications have the number 60000 added to the old number. For instance, IEC 27-1 has been renumbered as IEC 60027-1. For a period of time during the change over from one numbering system to the other, publications may contain identifiers from both systems.

Cross-references

The British Standards which implement international or European publications referred to in this document may be found in the BSI Standards Catalogue under the section entitled “International Standards Correspondence Index”, or by using the “Find” facility of the BSI Standards Electronic Catalogue.

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, the ISO/IEC title page, pages ii to iv, pages 1 to 30 and a back cover.

This standard has been updated (see copyright date) and may have had amendments incorporated. This will be indicated in the amendment table on the inside front cover.

Amendments issued since publication

Amd. No.	Date	Comments

This British Standard, having been prepared under the direction of the DISC Board, was published under the authority of the Standards Board and comes into effect on 15 December 1997

© BSI 04-1999

ISBN 0 580 28848 X

Contents

	Page
National foreword	Inside front cover
Foreword	iv
Text of ISO/IEC 15053	1

INTERNATIONAL STANDARD

ISO/IEC 15053

First edition
1997-05-15

Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Specification, functional model and information flows — Call interception additional network feature

*Technologies de l'information — Télécommunications et échange
d'information entre systèmes — Réseau privé à intégration de services —
Spécification, modèle fonctionnel et flux d'informations — Facilité de réseau
additionnelle d'interception d'appel*



Reference number
ISO/IEC 15053:1997(E)

Contents

	Page
Foreword	iv
Introduction	1
1 Scope	1
2 Conformance	1
3 Normative references	1
4 Definitions	2
4.1 External definitions	2
4.2 Other definitions	2
5 List of acronyms	3
6 ANF-CINT stage 1 specification	3
6.1 Description	3
6.1.1 General description	3
6.1.2 Qualifications on applicability to telecommunication services	3
6.2 Procedures	3
6.2.1 Provision/withdrawal	3
6.2.2 Normal procedures	3
6.2.3 Exceptional procedures	4
6.3 Interactions with other supplementary services and ANFs	4
6.3.1 Calling Line Identification Presentation (CLIP)	4
6.3.2 Connected Line Identification Presentation (COLP)	4
6.3.3 Calling/Connected Line Identification Restriction (CLIR)	5
6.3.4 Calling Name Identification Presentation (CNIP)	5
6.3.5 Connected Name Identification Presentation (CONP)	5
6.3.6 Calling/Connected Name Identification Restriction (CNIR)	5
6.3.7 Call Diversion (CFU, CFB, CFNR, CD)	5
6.3.8 Do Not Disturb (DND)	5
6.3.9 Do Not Disturb Override (DNDO)	5
6.3.10 Call Completion to Busy Subscriber (CCBS)	5
6.3.11 Call Completion on No Reply (CCNR)	5
6.3.12 Call Offer (CO)	5
6.3.13 Call Intrusion (CI)	5
6.3.14 Call Transfer (CT)	5
6.3.15 Path Replacement (PR)	5
6.3.16 Advice Of Charge (AOC/S/D/E)	5
6.3.17 Recall (RE)	5
6.4 Interworking considerations	6
6.5 Overall SDL	6
7 ANF-CINT stage 2 specification	6
7.1 Functional model	6
7.1.1 Functional model description	6
7.1.2 Description of functional entities	6
7.1.3 Relationship of functional model to basic call functional model	6
7.2 Information flows	10
7.2.1 Definition of information flows	10
7.2.2 Relationship of information flows to basic call information flows	13
7.2.3 Information flow sequences	14
7.3 Functional entity actions	20
7.3.1 Functional entity actions of FE1	21
7.3.2 Functional entity actions of FE2	21
7.3.3 Functional entity actions of FE3	21

	Page
7.3.4 Functional entity actions of FE4	22
7.3.5 Functional entity actions of FE5	22
7.3.6 Functional entity actions of FE6	22
7.4 Functional entity behaviour	22
7.4.1 Behaviour of FE1	22
7.4.2 Behaviour of FE2	23
7.4.3 Behaviour of FE3	25
7.4.4 Behaviour of FE4	26
7.4.5 Behaviour of FE5	26
7.4.6 Behaviour of FE6	29
7.5 Allocation of functional entities to physical equipment	29
7.6 Interworking considerations	30
Figure 1 — ANF-CINT, overall SDL	7
Figure 2 — Functional model for ANF-CINT	10
Figure 3 — Example relationship between model for ANF-CINT and basic call	11
Figure 4 — Information flow sequence — successful invocation of interception immediate	15
Figure 5 — Information flow sequence — successful invocation of interception delayed	16
Figure 6 — Information flow sequence — failure of interception immediate	17
Figure 7 — Information flow sequence — failure of interception delayed	18
Figure 8 — Information flow sequence — calling user clearing during interception delayed	19
Figure 9 — Information flow sequence — called user answers during interception delayed	20
Figure 10 — Information flow sequence — FE4 disables call interception	21
Figure 11 — ANF-CINT, SDL for functional entity FE1	22
Figure 12 — ANF-CINT, SDL for functional entity FE2	24
Figure 13 — ANF-CINT, SDL for functional entity FE3	25
Figure 14 — ANF-CINT, SDL for functional entity FE4	27
Figure 15 — ANF-CINT, SDL for functional entity FE5	28
Figure 16 — ANF-CINT, SDL for functional entity FE6	29
Table 1 — Content of rb_INFORM1	11
Table 2 — Content of ra_INFORM2	11
Table 3 — Content of rd_INFORM4	12
Table 4 — Content of re_INFORM5	12
Table 5 — Content of rd_INFORM6, rb_INFORM6	13
Table 6 — Content of ra_INFORM7	13
Table 7 — Content of rc_INTERCEPT_CONDITION	13
Table 8 — Scenarios for the allocation of FEs to physical equipment	30

Descriptors: Data processing, information interchange, telecommunications, network interconnection, telecommunication network, private network, ISDN, data transmission, signal processing.

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 15053 was prepared by ECMA (as ECMA-220) and was adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

Introduction

This International Standard is one of a series of standards defining services and signalling protocols applicable to Private Integrated Services Networks. The series uses the ISDN concepts as developed by ITU-T (formerly CCITT) and is also within the framework of standards for open systems interconnection as defined by ISO.

This International Standard specifies the Call Interception additional network feature.

The International Standard is based upon the practical experience of ECMA member companies and the results of their active and continuous participation in the work of ISO/IEC JTC 1, ITU-T, ETSI and other international and national standardization bodies. It represents a pragmatic and widely based consensus.

There is currently no equivalent service specified by ITU-T or ETSI for public ISDNs.

1 Scope

This International Standard specifies Additional Network Feature Call Interception (ANF-CINT), which is applicable to various basic services supported by Private Integrated Services Networks (PISN). Basic services are specified in ISO/IEC 11574.

ANF-CINT is an additional network feature which enables calls that cannot be completed due to certain conditions to be redirected to a pre-defined intercepted-to user.

ANF specifications are produced in three stages, according to the method described in CCITT Rec. I.130. This International Standard contains the stage 1 and stage 2 specifications of ANF-CINT. The stage 1 specification (clause 6) specifies the feature as seen by users of PISNs. The stage 2 specification (clause 7) identifies the functional entities involved in the feature and the information flows between them.

2 Conformance

In order to conform to this International Standard, a stage 3 standard shall specify signalling protocols and equipment behaviour that are capable of being used in a PISN which supports the feature specified in this International Standard. This means that, to claim conformance, a stage 3 standard is required to be adequate for the support of those aspects of clause 6 (stage 1) and clause 7 (stage 2) which are relevant to the interface or equipment to which the stage 3 standard applies.

3 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO/IEC 11571:1994, *Information technology — Telecommunications and information exchange between systems — Numbering and sub-addressing in private integrated services networks*.

ISO/IEC 11574:1994, *Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Circuit-mode 64 kbit/s bearer services — Service description, functional capabilities and information flows*.

ISO/IEC 11579-1:1994, *Information technology — Telecommunications and information exchange between systems — Private Integrated Services Network — Part 1: Reference configuration for PISN Exchanges (PINX)*.

CCITT Rec. I.112:1988, *Vocabulary of terms for ISDNs*.

CCITT Rec. I.130:1988, *Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN*.

CCITT Rec. I.210:1988, *Principles of telecommunication services supported by an ISDN and the means to describe them*.

CCITT Rec. I.221:1988, *Common specific characteristics of services*.

CCITT Rec. Z.100:1988, *Specification and description language*.

4 Definitions

For the purposes of this International Standard, the following definitions apply.

4.1 External definitions

This International Standard uses the following terms defined in other documents:

- Basic Service (CCITT Rec. I.210)
- Connection (CCITT Rec. I.112)
- Network Determined User Busy (CCITT Rec. I.221)
- Private Integrated Services Network (PISN) (ISO/IEC 11579-1)
- Private Integrated Services Network Exchange (PINX) (ISO/IEC 11579-1)
- PISN Number (ISO/IEC 11571)
- Service (CCITT Rec. I.112)
- Signalling (CCITT Rec. I.112)
- Supplementary Service (CCITT Rec. I.210)
- User Determined User Busy (CCITT Rec. I.221)
- User (except in the context of ANF-CINT user) (ISO/IEC 11574)

This International Standard refers to the following basic call functional entities (FEs) defined in ISO/IEC 11574:

- Call Control (CC)
- Call Control Agent (CCA).

This International Standard refers to the following basic call inter-FE relationships defined in ISO/IEC 11574:

- r1
- r2
- r3

This International Standard refers to the following basic call information flows defined in ISO/IEC 11574:

- Disconnect request/indication
- Setup request/indication
- Setup response/confirmation
- Report request/indication
- Release request/indication

4.2 Other definitions

Additional Network Feature

a capability, over and above that of a basic service, provided by a PISN, but not directly to a PISN user

ANF-CINT user

an entity, within a PISN, that requests ANF-CINT

busy

a property of a user for whom either a Network Determined User Busy or a User Determined User Busy condition exists

call, basic call

an instance of the use of a basic service

called user

the user to which a call is directed prior to invocation of ANF-CINT

intercepted-to user

the user to which the intercepted call is directed

interception cause

a condition that can lead to call interception

interception delayed

the redirection of a call to an alternative destination as a result of remaining too long in an alerting or waiting on busy state

interception immediate

the redirection of a call to an alternative destination as a result of detecting a condition that prevents the call reaching an alerting or waiting on busy state

waiting on busy

a call state in which a call is awaiting answer at a user that is busy on another call

NOTE This can arise, for example, as a result of the use of supplementary service Call Offer (SS-CO) during call establishment. A call that is waiting on busy can be transferred.

5 List of acronyms

ANF	Additional Network Feature
ANF-CINT	Additional Network Feature Call Interception
CC	Call Control (functional entity)
CCA	Call Control Agent (functional entity)
CD	Call Deflection
CFB	Supplementary Service Call Forwarding Busy
CFNR	Supplementary Service Call Forwarding No Reply
CFU	Supplementary Service Call Forwarding Unconditional
CLIR	Calling/Connected Line Identification Restriction
CNIP	Calling Name Identification Presentation
CNIR	Calling/Connected Name Identification Restriction
FE	Functional Entity
ISDN	Integrated Services Digital Network
PINX	Private Integrated Services Network Exchange
PISN	Private Integrated Services Network
SDL	Specification and Description Language
SS	Supplementary Service
TE	Terminal Equipment

6 ANF-CINT stage 1 specification

6.1 Description

6.1.1 General description

ANF-CINT is invoked by an ANF-CINT user for an unanswered or unsuccessful call, allowing the call to be routed to a special destination in the PISN. The special destination may be dependent on the interception cause.

The conditions leading to invocation of ANF-CINT are considered as implementation options. Examples of factors that can be taken in account are:

- the source of the call (e.g., the geographic location of the calling user, the network from which the call has entered the PISN);
- the particular interception cause;
- the type of connection (e.g. the originating user is an attendant);
- the call destination;

— time of the day.

6.1.2 Qualifications on applicability to telecommunication services

Call Interception is applicable to all basic services defined in ISO/IEC 11574.

6.2 Procedures

6.2.1 Provision/withdrawal

ANF-CINT shall be PISN instigated. The conditions under which interception is invoked shall be an implementation matter. Also, parameters and values offered by a PISN shall be an implementation matter. A PISN may offer more or less parameters than the one specified below.

Parameters may apply separately to each different condition for which interception is to be invoked.

Parameter	Value
Intercepted-to number (Note)	— PISN number

NOTE This parameter is not needed for conditions where the intercepted-to number is determined on a call by call basis e.g. the number of the user that transferred the call.

6.2.2 Normal procedures

6.2.2.1 Activation/deactivation/registration/interrogation

The feature shall be permanently activated.

Registration and interrogation shall not apply.

6.2.2.2 Invocation and operation

ANF-CINT shall be invoked for a call if a certain condition, determined by the PISN implementation, is met. Also the parameters with the invocation request shall be determined by the PISN implementation. Examples of interception causes include:

- timeout in waiting on busy condition
- busy user
- closed user group rejection
- do not disturb activated
- incoming barred destination
- invalid number
- no compatible user at destination
- network congestion
- no reply (i.e. timeout during alerting)
- called user access out of service
- route restriction (i.e. calling user not authorized for the route)
- timeout in waiting on busy condition after transfer

- no reply after transfer (i.e. timeout during alerting after transfer)
- upper limit of number of diversions reached
- upper limit of transit counter reached
- mobile user location not known
- mobile user no longer registered
- mobile terminal not responding
- invalid call diversion destination
- timeout after call hold.

On acceptance of invocation of ANF-CINT, the PISN shall perform redirection towards the intercepted-to user. If interception is invoked because of detecting a condition that prevents the call reaching an alerting or waiting on busy state (interception immediate) the PISN shall complete the release of the call towards the called user immediately. If interception is invoked as a result of remaining too long in an alerting or waiting on busy state (interception delayed) the PISN shall not release the call towards the called user until the call to the intercepted-to user enters an alerting or waiting on busy state. The called user can accept the call during this period.

As an implementation option for interception delayed, the PISN may retain the call towards the called user until the intercepted-to user answers the call. Further procedures in this case are outside the scope of this International Standard.

6.2.2.2.1 Intercepted-to user notification

The intercepted-to user shall be given a notification that the call has been intercepted. This notification shall include:

- the interception cause,
- the called user number/name if available.

6.2.2.2.2 Calling user notifications

The calling user shall be given the notification that the call has been intercepted with the appropriate interception cause. In case of multiple call interceptions, the calling user shall be notified of the first interception and of any subsequent interceptions from intercepted-to users at which an alerting or waiting on busy state has been reached.

For single interception, the intercepted-to user's number and, if available, the intercepted-to user's name shall be sent to the calling user if CLIR/CNIR is not invoked by the intercepted-to user.

For multiple interception, the number and, if available, name of the final intercepted-to user shall be sent to the calling user if CLIR and CNIR respectively has not been invoked by the final intercepted-to user. In addition, if an alerting or waiting on busy state is reached at an intermediate intercepted-to user the number and, if available, name of that intercepted-to user may be sent to the calling user if there is no possibility of CLIR and CNIR respectively being invoked by that intercepted-to user.

6.2.3 Exceptional procedures

6.2.3.1 Activation/deactivation/registration/interrogation

Not applicable.

6.2.3.2 Invocation and operation

If the number of the intercepted-to user is unavailable (e.g. due to number presentation restriction or interworking), the user who would have been given the number shall receive an indication of the reason why no number is given.

In the case of interception delayed, if the intercepted call cannot be completed to the intercepted-to user, then the PISN shall clear the intercepted-to leg of the call and continue to alert or wait on busy at the called user. In this case the calling user shall not be given any notification.

In the case of interception immediate, if the intercepted call cannot be completed to the intercepted-to user, then the PISN shall clear the call, unless it is able to redirect the call to a new intercepted-to user. If the call is cleared, the calling user shall be sent an indication that the call has been intercepted.

6.3 Interactions with other supplementary services and ANFs

Interactions with other supplementary services and ANFs for which PISN standards were available at the time of publication of this International Standard are specified below.

6.3.1 Calling Line Identification Presentation (CLIP)

No interaction.

6.3.2 Connected Line Identification Presentation (COLP)

No interaction.