



BSI Standards Publication

Linux Standard Base (LSB)

Part 1-5: Imaging specification

National foreword

This British Standard is the UK implementation of ISO/IEC 23360-1-5:2021.

The UK participation in its preparation was entrusted to Technical Committee IST/5, Programming languages, their environments and system software interfaces.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2021
Published by BSI Standards Limited 2021

ISBN 978 0 539 04909 1

ICS 35.080

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 October 2021.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

INTERNATIONAL
STANDARD

ISO/IEC
23360-1-5

First edition
2021-10

Linux Standard Base (LSB) —
Part 1-5:
Imaging specification



Reference number
ISO/IEC 23360-1-5:2021(E)

AVA Documents
Document Sharing Hub
© ISO/IEC 2021

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see patents.iec.ch).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by the Linux Foundation as Linux Standard Base (LSB): Imaging specification and drafted in accordance with its editorial rules. It was assigned to Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 22, *Programming languages, their environments and system software interfaces*, and adopted by National Bodies.

This first edition of ISO/IEC 23360-1-5 cancels and replaces ISO/IEC 23360-1:2006, which has been technically revised.

This document is based on “The GNU Free Documentation License, version 1.1”. The license is available at <https://www.gnu.org/licenses/old-licenses/fdl-1.1.html>.

A list of all parts in the ISO/IEC 23660 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

Contents

Foreword	iii
Introduction.....	v
I Introductory Elements	1
1 Scope.....	2
2 Normative References.....	3
3 Requirements	4
3.1 Relevant Libraries	4
4 Terms and Definitions.....	5
5 Documentation Conventions.....	7
6 PPD Format Extensions.....	8
II Printing Libraries	12
7 Libraries.....	13
7.1 Interfaces for libcups	13
7.2 Data Definitions for libcups	15
7.3 Interface Definitions for libcups.....	29
7.4 Interfaces for libcupsimage	49
7.5 Data Definitions for libcupsimage.....	50
7.6 Interface Definitions for libcupsimage	53
III Printing Commands.....	56
8 Printing Commands	57
8.1 Commands and Utilities.....	57
8.2 Command Behavior	57
IV Execution Environment.....	63
9 File System Hierarchy	64
V Scanning Libraries	65
10 Libraries	66
10.1 Interfaces for libsane	66
10.2 Data Definitions for libsane	66
VI Package Format and Installation	75
11 Software Installation.....	76
11.1 Package Dependencies	76
Annex A Alphabetical Listing of Interfaces by Library.....	77
A.1 libsane.....	77
A.2 libcups.....	77
A.3 libcupsimage.....	79

Introduction

The LSB defines a binary interface for application programs that are compiled and packaged for LSB-conforming implementations on many different hardware architectures. A binary specification must include information specific to the computer processor architecture for which it is intended. To avoid the complexity of conditional descriptions, the specification has instead been divided into generic parts which are augmented by one of several architecture-specific parts, depending on the target processor architecture; the generic part will indicate when reference must be made to the architecture part, and vice versa.

This document should be used in conjunction with the documents it references. This document enumerates the system components it includes, but descriptions of those components may be included entirely or partly in this document, partly in other documents, or entirely in other reference documents. For example, the section that describes system service routines includes a list of the system routines supported in this interface, formal declarations of the data structures they use that are visible to applications, and a pointer to the underlying referenced specification for information about the syntax and semantics of each call. Only those routines not described in standards referenced by this document, or extensions to those standards, are described in the detail. Information referenced in this way is as much a part of this document as is the information explicitly included here.

The specification carries a version number of either the form $x.y$ or $x.y.z$. This version number carries the following meaning:

1. The first number (x) is the major version number. Versions sharing the same major version number shall be compatible in a backwards direction; that is, a newer version shall be compatible with an older version. Any deletion of a library results in a new major version number. Interfaces marked as deprecated may be removed from the specification at a major version change.
2. The second number (y) is the minor version number. Libraries and individual interfaces may be added, but not removed. Interfaces may be marked as deprecated at a minor version change. Other minor changes may be permitted at the discretion of the LSB workgroup.
3. The third number (z), if present, is the editorial level. Only editorial changes should be included in such versions.

Since this specification is a descriptive Application Binary Interface, and not a source level API specification, it is not possible to make a guarantee of 100% backward compatibility between major releases. However, it is the intent that those parts of the binary interface that are visible in the source level API will remain backward compatible from version to version, except where a feature marked as "Deprecated" in one release may be removed from a future release. Implementors are strongly encouraged to make use of symbol versioning to permit simultaneous support of applications conforming to different releases of this specification.

LSB is a trademark of the Linux Foundation. Developers of applications or implementations interested in using the trademark should see the Linux Foundation Certification Policy for details.

I Introductory Elements

1 Scope

The Linux Standard Base (LSB) defines a system interface for compiled applications and a minimal environment for support of installation scripts. Its purpose is to enable a uniform industry standard environment for high-volume applications conforming to the LSB.

These specifications are composed of two basic parts: a common part describing those parts of the interface that remain constant across all implementations of the LSB, and an architecture-specific part describing the parts of the interface that vary by processor architecture. Together, the common part and the relevant architecture-specific part for a single hardware architecture provide a complete interface specification for compiled application programs on systems that share a common hardware architecture.

The LSB contains both a set of Application Program Interfaces (APIs) and Application Binary Interfaces (ABIs). APIs may appear in the source code of portable applications, while the compiled binary of that application may use the larger set of ABIs. A conforming implementation provides all of the ABIs listed here. The compilation system may replace (e.g. by macro definition) certain APIs with calls to one or more of the underlying binary interfaces, and may insert calls to binary interfaces as needed.

The LSB is primarily a binary interface definition. Not all of the source level APIs available to applications may be contained in this specification.

This is the Imaging module of the Linux Standard Base (LSB). This module provides the fundamental system interfaces, libraries, and runtime environment upon which conforming applications and libraries requiring the LSB Imaging module depend.

Interfaces described in LSB Imaging are mandatory except where explicitly listed otherwise. Interfaces described in the LSB Imaging module supplement those described in the LSB Core module. They do not depend on other LSB modules.

2 Normative References

The specifications listed below are referenced in whole or in part by the LSB Imaging specification. Such references may be normative or informative; a reference to specification shall only be considered normative if it is explicitly cited as such. The LSB Imaging specification may make normative references to a portion of these specifications (that is, to define a specific function or group of functions); in such cases, only the explicitly referenced portion of the specification is to be considered normative.

Table 2-1 Normative References

Name	Title	URL
CUPS API Reference	CUPS 1.2 API Reference	http://www.cups.org/documentation.php/doc-1.2/
Filesystem Hierarchy Standard	Filesystem Hierarchy Standard (FHS) 3.0	http://refspecs.linuxbase.org/fhs
ISO C (1999)	ISO/IEC 9899:1999 - Programming Languages -- C	
PPD Specification	PostScript Printer Description File Format Specification version 4.3	http://partners.adobe.com/public/developer/en/ps/5003.PPD_Spec_v4.3.pdf
PPD Specification Update	Update to PPD Specification Version 4.3	http://partners.adobe.com/public/developer/en/ps/5645.PPD_Update.pdf
SANE Standard Version 1.04	SANE Standard Version 1.04	http://www.sane-project.org/html/

3 Requirements

3.1 Relevant Libraries

The libraries listed in Table 3-1 shall be available on a Linux Standard Base system, with the specified runtime names. This list may be supplemented or amended by an architecture-specific specification.

Table 3-1 Standard Library Names

Library	Runtime Name
libcups	libcups.so.2
libcupsimage	libcupsimage.so.2
libsane	libsane.so.1

These libraries will be in an implementation-defined directory which the dynamic linker shall search by default.

4 Terms and Definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 2382, ISO 80000-2, and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

4.1

archLSB

Some LSB specification documents have both a generic, architecture-neutral part and an architecture-specific part. The latter describes elements whose definitions may be unique to a particular processor architecture. The term archLSB may be used in the generic part to refer to the corresponding section of the architecture-specific part.

4.2

Binary Standard, ABI

The total set of interfaces that are available to be used in the compiled binary code of a conforming application, including the run-time details such as calling conventions, binary format, C++ name mangling, etc.

4.3

Implementation-defined

Describes a value or behavior that is not defined by this document but is selected by an implementor. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence of the value or behavior. An application that relies on such a value or behavior cannot be assured to be portable across conforming implementations. The implementor shall document such a value or behavior so that it can be used correctly by an application.

4.4

Shell Script

A file that is read by an interpreter (e.g., awk). The first line of the shell script includes a reference to its interpreter binary.

4.5

Source Standard, API

The total set of interfaces that are available to be used in the source code of a conforming application. Due to translations, the Binary Standard and the Source Standard may contain some different interfaces.

4.6

Undefined

Describes the nature of a value or behavior not defined by this document which results from use of an invalid program construct or invalid data input. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence or validity of the value or behavior. An application that relies on any particular value or behavior cannot be assured to be portable across conforming implementations.

4.7

Unspecified

Describes the nature of a value or behavior not specified by this document which results from use of a valid program construct or valid data input. The value or behavior may vary among implementations that conform to this document. An application should not rely on the existence or validity of the value or behavior. An application that relies on any particular value or behavior cannot be assured to be portable across conforming implementations.

In addition, for the portions of this specification which build on IEEE Std 1003.1-2001, the definitions given in *IEEE Std 1003.1-2001, Base Definitions, Chapter 3* apply.

5 Documentation Conventions

Throughout this document, the following typographic conventions are used:

`function()`

the name of a function

command

the name of a command or utility

CONSTANT

a constant value

parameter

a parameter

variable

a variable

Throughout this specification, several tables of interfaces are presented. Each entry in these tables has the following format:

name

the name of the interface

(symver)

An optional symbol version identifier, if required.

[refno]

A reference number indexing the table of referenced specifications that follows this table.

For example,

forkpty(GLIBC_2.0) [SUSv4]

refers to the interface named `forkpty()` with symbol version `GLIBC_2.0` that is defined in the reference indicated by the tag `SUSv4`.

Note: For symbols with versions which differ between architectures, the symbol versions are defined in the architecture specific parts of of this module specification only. In the generic part, they will appear without symbol versions.

6 PPD Format Extensions

The Postscript Printer Description (PPD) format is used in a text file to describe device capabilities for a printing device. PPD files shall conform to the format described by PPD Specification and PPD Specification Update. In addition, several extensions to the standard attribute list are recognized, as listed below. The "cupsVersion" attribute is required in a compliant PPD, while the other attributes are optional.

cupsColorProfile

This string attribute specifies an sRGB-based color profile consisting of gamma and density controls and a 3x3 CMY color transform matrix.

The attribute has the following parameter usage:

*cupsColorProfile Resolution/MediaType: "density gamma m00 m01 m02 m10 m11 m12 m20 m21 m22"

The Resolution and MediaType values may be "-" to act as a wildcard. Otherwise, they must match one of the Resolution or MediaType attributes defined in the PPD file.

The density and gamma values define the gamma and density adjustment function such that (in terms of C math):

$$f(x) = \text{density} * \text{pow}(x, \text{gamma})$$

The m00 through m22 values define a 3x3 transformation matrix for the CMY color values. The density function is applied after the CMY transformation:

m00	m01	m02	m10	m11	m12	m20	m21	m22
-----	-----	-----	-----	-----	-----	-----	-----	-----

cupsFax

This boolean attribute specifies whether the PPD defines a facsimile device. The default is false.

cupsFilter

The attribute has the following parameter usage:

*cupsFilter: "source/type cost program"

This string attribute provides a conversion rule from the given source type to the printer's native format using the filter "program". A source type is specified according to the conventions of the MIME specification, using "type/subtype" nomenclature, and may refer to a standard MIME type or a CUPS-specific MIME type using the prefix "vnd.cups-" in the subtype. If a printer supports the source type directly, the special filter program "-" may be specified. The cost is an arbitrary positive integer, used to calculate the relative impact a print job has on system load.

cupsManualCopies

This boolean attribute notifies the RIP filters that the destination printer does not support copy generation in hardware. The default value is false.

cupsModelNumber

This integer attribute specifies a printer-specific model number. This number can be used by a filter program to adjust the output for a specific model of printer.

cupsVersion

The attribute has the following parameter usage:

*cupsVersion: "major.minor"

This required attribute describes which version of the CUPS PPD file extensions was used. Currently it must be the string "1.0" or "1.1". The strings "1.2" and "1.3" represent newer versions of the CUPS PPD API that are not covered in this version of the specification, and are currently not allowed, although they may be found in non-conforming PPDs which use a newer version of the CUPS PPD specification.

FoomaticIDs

The attribute has the following parameter usage:

*FoomaticIDs printer driver

The parameters correspond to the IDs in the Foomatic database for the printer and driver, respectively.

FoomaticNoPageAccounting

This boolean attribute tells foomatic-rip whether or not to insert accounting information into the PostScript data stream. By default, foomatic-rip will insert this information.

FoomaticRIPCommandLine

The attribute has the following parameter usage:

*FoomaticRIPCommandLine "code"

This attribute defines the command line in the "code" parameter for the renderer that is called by foomatic-rip. The command must take PostScript on standard input and provide the job data stream in the printer's native language on standard output. The command must exit with status 0 if the conversion was successful and exit with another status if an error occurs. The "code" parameter may contain option setting wildcards, as described below under "FoomaticRIPOption".

FoomaticRIPDefault

The attribute has the following parameter usage:

*FoomaticRIPDefaultOptionName value

This attribute sets a default for a Foomatic option. The name of the attribute should contain the name of the option appended to "FoomaticRIPDefault", with the desired default value as the only parameter.

This option is only used to provide numeric options in the PPD, which are not supported by the Adobe spec, via enumerated options, and should not be used except for that purpose.

FoomaticRIPOption

The attribute has the following parameter usage:

*FoomaticRIPOption name: type style spot [order]

This attribute sets options for the command line specified in the "FoomaticRIPCommandLine" attribute. The "name" parameter specifies the option name, the "type" parameter specifies the option type, the "style"

parameter specifies one of "CmdLine", "JCL", "PS", or "Composite", and the "spot" parameter specifies a letter, which is prepended with a "%" and used in the "FoomaticRIPCommandLine" attribute to indicate where the option should go in the command line. The optional "order" parameter indicates an order number for one-choice options.

FoomaticRIPOptionAllowedChars

The attribute has the following parameter usage:

*FoomaticRIPOptionAllowedChars name: "code"

This option sets a list of allowed characters in a string option. The "name" parameter identifies the option, while the "code" parameter is a list of allowed characters.

FoomaticRIPOptionAllowedRegExp

The attribute has the following parameter usage:

*FoomaticRIPOptionAllowedRegExp name: "code"

This option causes the option named by "name" to be validated by the Perl-style regular expression in "code".

FoomaticRIPOptionMaxLength

The attribute has the following parameter usage:

*FoomaticRIPOptionMaxLength name: length

For string or password options, this attribute sets a maximum length which can be returned. The "name" parameter identifies the option, and the "length" parameter is the maximum number of characters allowed.

FoomaticRIPOptionPrototype

The attribute has the following parameter usage:

*FoomaticRIPOptionPrototype name: "code"

For string, password, or simulated numeric options, this attribute sets a code prototype to be inserted into the output. This works for options where the FoomaticRIPOption "style" parameter is set to CmdLine, JCL, or PS. The value of the option can be represented with the string "%s" in the "code" parameter.

FoomaticRIPOptionRange

The attribute has the following parameter usage:

*FoomaticRIPOptionRange name: min max

This attribute adds a minimum and maximum limit to numeric options (that are simulated by Foomatic via enumerated options). The "name" parameter identifies the option, while the "min" and "max" parameters set the minimum and maximum allowed values, respectively, for the option.

FoomaticRIPOptionSetting

The attribute has the following parameter usage:

*FoomaticRIPOptionSetting name=choice: "code"

This attribute adds code to an option, identified by "name", with a FoomaticRIPOption "style" parameter set to Composite. It inserts options for other options that are members of the Composite option "name".

FoomaticRIPPostPipe

The attribute has the following parameter usage:

*FoomaticRIPPostPipe "code"

This attribute defines the command line in the "code" parameter for the job output command used by foomatic-rip in standalone mode. The command should take printer-native data on standard input. The "code" parameter should include the preceding shell pipe symbol ("|").

II Printing Libraries

7 Libraries

7.1 Interfaces for libcups

Table 7-1 defines the library name and shared object name for the libcups library

Table 7-1 libcups Definition

Library:	libcups
SONAME:	libcups.so.2

The behavior of the interfaces in this library is specified by the following specifications:

[CUPS 1.2] CUPS API Reference

[LSB] This Specification

7.1.1 CUPS Convenience ABI

7.1.1.1 Interfaces for CUPS Convenience ABI

An LSB conforming implementation shall provide the generic functions for CUPS Convenience ABI specified in Table 7-2, with the full mandatory functionality as described in the referenced underlying specification.

Table 7-2 libcups - CUPS Convenience ABI Function Interfaces

cupsAddDest [LSB]	cupsAddOption [LSB]	cupsCancelJob [LSB]	cupsDoAuthentication [CUPS 1.2]
cupsDoFileRequest [CUPS 1.2]	cupsEncodeOptions [CUPS 1.2]	cupsEncryption [LSB]	cupsFreeDests [LSB]
cupsFreeJobs [LSB]	cupsFreeOptions [LSB]	cupsGetDefault [LSB]	cupsGetDefault2 [CUPS 1.2]
cupsGetDest [LSB]	cupsGetDests [LSB]	cupsGetDests2 [CUPS 1.2]	cupsGetFd [CUPS 1.2]
cupsGetFile [CUPS 1.2]	cupsGetJobs [LSB]	cupsGetJobs2 [CUPS 1.2]	cupsGetOption [LSB]
cupsGetPPD [LSB]	cupsGetPPD2 [CUPS 1.2]	cupsGetPassword [LSB]	cupsLangEncoding [LSB]
cupsLangFlush [LSB]	cupsLangFree [LSB]	cupsLangGet [LSB]	cupsLastError [LSB]
cupsMarkOptions [LSB]	cupsParseOptions [LSB]	cupsPrintFile [LSB]	cupsPrintFile2 [CUPS 1.2]
cupsPrintFiles [LSB]	cupsPrintFiles2 [CUPS 1.2]	cupsPutFd [CUPS 1.2]	cupsPutFile [CUPS 1.2]
cupsServer [LSB]	cupsSetDests [LSB]	cupsSetDests2 [CUPS 1.2]	cupsSetEncryption [LSB]
cupsSetPasswordCB [LSB]	cupsSetServer [LSB]	cupsSetUser [LSB]	cupsTempFd [LSB]

cupsUser [LSB]	httpBlocking [CUPS 1.2]	httpCheck [CUPS 1.2]	httpClearCookie [CUPS 1.2]
httpClearFields [CUPS 1.2]	httpClose [CUPS 1.2]	httpConnect [CUPS 1.2]	httpConnectEncrypt [CUPS 1.2]
httpDecode64_2 [CUPS 1.2]	httpDelete [CUPS 1.2]	httpEncode64_2 [CUPS 1.2]	httpEncryption [CUPS 1.2]
httpError [CUPS 1.2]	httpFlush [CUPS 1.2]	httpGet [CUPS 1.2]	httpGetCookie [CUPS 1.2]
httpGetDateString [CUPS 1.2]	httpGetDateTime [CUPS 1.2]	httpGetField [CUPS 1.2]	httpGetHostByName [CUPS 1.2]
httpGetSubField [CUPS 1.2]	httpGets [CUPS 1.2]	httpHead [CUPS 1.2]	httpInitialize [CUPS 1.2]
httpMD5 [CUPS 1.2]	httpMD5Final [CUPS 1.2]	httpMD5String [CUPS 1.2]	httpOptions [CUPS 1.2]
httpPost [CUPS 1.2]	httpPut [CUPS 1.2]	httpReconnect [CUPS 1.2]	httpSetCookie [CUPS 1.2]
httpSetField [CUPS 1.2]	httpStatus [CUPS 1.2]	httpTrace [CUPS 1.2]	httpUpdate [CUPS 1.2]
httpWait [CUPS 1.2]	ippAddBoolean [CUPS 1.2]	ippAddBooleans [CUPS 1.2]	ippAddCollection [CUPS 1.2]
ippAddCollections [CUPS 1.2]	ippAddDate [CUPS 1.2]	ippAddInteger [CUPS 1.2]	ippAddIntegers [CUPS 1.2]
ippAddRange [CUPS 1.2]	ippAddRanges [CUPS 1.2]	ippAddResolution [CUPS 1.2]	ippAddResolutions [CUPS 1.2]
ippAddSeparator [CUPS 1.2]	ippAddString [CUPS 1.2]	ippAddStrings [CUPS 1.2]	ippDateToTime [CUPS 1.2]
ippDelete [CUPS 1.2]	ippDeleteAttribute [CUPS 1.2]	ippErrorString [CUPS 1.2]	ippFindAttribute [CUPS 1.2]
ippFindNextAttribute [CUPS 1.2]	ippLength [CUPS 1.2]	ippNew [CUPS 1.2]	ippPort [CUPS 1.2]
ippRead [CUPS 1.2]	ippReadFile [CUPS 1.2]	ippReadIO [CUPS 1.2]	ippSetPort [CUPS 1.2]
ippTimeToDate [CUPS 1.2]	ippWrite [CUPS 1.2]	ippWriteFile [CUPS 1.2]	ippWriteIO [CUPS 1.2]
ppdClose [LSB]	ppdCollect [LSB]	ppdConflicts [LSB]	ppdEmit [LSB]
ppdEmitFd [LSB]	ppdEmitJCL [LSB]	ppdErrorString [LSB]	ppdFindAttr [LSB]
ppdFindChoice [LSB]	ppdFindMarkedChoice [LSB]	ppdFindNextAttr [LSB]	ppdFindOption [LSB]
ppdIsMarked [LSB]	ppdLastError [LSB]	ppdMarkDefaults [LSB]	ppdMarkOption [LSB]

ppdOpen [LSB]	ppdOpenFd [LSB]	ppdOpenFile [LSB]	ppdPageLength [LSB]
ppdPageSize [LSB]	ppdPageWidth [LSB]	ppdSetConformance [LSB]	

An LSB conforming implementation shall provide the generic deprecated functions for CUPS Convenience ABI specified in Table 7-3, with the full mandatory functionality as described in the referenced underlying specification.

Note: These interfaces are deprecated, and applications should avoid using them. These interfaces may be withdrawn in future releases of this specification.

Table 7-3 libcups - CUPS Convenience ABI Deprecated Function Interfaces

httpConnect [CUPS 1.2]			
------------------------	--	--	--

7.2 Data Definitions for libcups

This section defines global identifiers and their values that are associated with interfaces contained in libcups. These definitions are organized into groups that correspond to system headers. This convention is used as a convenience for the reader, and does not imply the existence of these headers, or their content. Where an interface is defined as requiring a particular system header file all of the data definitions for that system header file presented here shall be in effect.

This section gives data definitions to promote binary application portability, not to repeat source interface definitions available elsewhere. System providers and application developers should use this ABI to supplement - not to replace - source interface definition specifications.

This specification uses the ISO C (1999) C Language as the reference programming language, and data definitions are specified in ISO C format. The C language is used here as a convenient notation. Using a C language description of these data objects does not preclude their use by other programming languages.

7.2.1 cups/cups.h

```
#define _CUPS_CUPS_H_
#define CUPS_VERSION_MAJOR 1
#define CUPS_VERSION_MINOR 1
#define CUPS_VERSION 1.0123
#define CUPS_VERSION_PATCH 23
#define cupsLangDefault() cupsLangGet(NULL)

typedef enum {
    CUPS_AUTO_ENCODING = -1,
    CUPS_US_ASCII = 0,
    CUPS_ISO8859_1 = 1,
    CUPS_ISO8859_2 = 2,
    CUPS_ISO8859_3 = 3,
    CUPS_ISO8859_4 = 4,
    CUPS_ISO8859_5 = 5,
    CUPS_ISO8859_6 = 6,
    CUPS_ISO8859_7 = 7,
    CUPS_ISO8859_8 = 8,
    CUPS_ISO8859_9 = 9,
    CUPS_ISO8859_10 = 10,
    CUPS_UTF8 = 11,
```

```

        CUPS_ISO8859_13 = 12,
        CUPS_ISO8859_14 = 13,
        CUPS_ISO8859_15 = 14,
        CUPS_WINDOWS_874 = 15,
        CUPS_WINDOWS_1250 = 16,
        CUPS_WINDOWS_1251 = 17,
        CUPS_WINDOWS_1252 = 18,
        CUPS_WINDOWS_1253 = 19,
        CUPS_WINDOWS_1254 = 20,
        CUPS_WINDOWS_1255 = 21,
        CUPS_WINDOWS_1256 = 22,
        CUPS_WINDOWS_1257 = 23,
        CUPS_WINDOWS_1258 = 24,
        CUPS_KOI8_R = 25,
        CUPS_KOI8_U = 26
    } cups_encoding_t;
typedef struct cups_lang_s {
    struct cups_lang_s *next;
    int used;
    cups_encoding_t encoding;
    char language[16];
    cups_array_t *strings;
} cups_lang_t;
typedef enum {
    HTTP_ENCRYPT_IF_REQUESTED = 0,
    HTTP_ENCRYPT_NEVER = 1,
    HTTP_ENCRYPT_REQUIRED = 2,
    HTTP_ENCRYPT_ALWAYS = 3
} http_encryption_t;
typedef struct {
    char *name;
    char *value;
} cups_option_t;
typedef struct {
    char *name;
    char *instance;
    int is_default;
    int num_options;
    cups_option_t *options;
} cups_dest_t;
typedef enum {
    HTTP_WAITING = 0,
    HTTP_OPTIONS = 1,
    HTTP_GET = 2,
    HTTP_GET_SEND = 3,
    HTTP_HEAD = 4,
    HTTP_POST = 5,
    HTTP_POST_RECV = 6,
    HTTP_POST_SEND = 7,
    HTTP_PUT = 8,
    HTTP_PUT_RECV = 9,
    HTTP_DELETE = 10,
    HTTP_TRACE = 11,
    HTTP_CLOSE = 12,
    HTTP_STATUS = 13
} http_state_t;
typedef enum {
    HTTP_ERROR = -1,
    HTTP_CONTINUE = 100,
    HTTP_SWITCHING_PROTOCOLS = 101,
    HTTP_OK = 200,
    HTTP_CREATED = 201,
    HTTP_ACCEPTED = 202,
    HTTP_NOT_AUTHORITATIVE = 203,
    HTTP_NO_CONTENT = 204,
    HTTP_RESET_CONTENT = 205,

```

```

HTTP_PARTIAL_CONTENT = 206,
HTTP_MULTIPLE_CHOICES = 300,
HTTP_MOVED_PERMANENTLY = 301,
HTTP_MOVED_TEMPORARILY = 302,
HTTP_SEE_OTHER = 303,
HTTP_NOT_MODIFIED = 304,
HTTP_USE_PROXY = 305,
HTTP_BAD_REQUEST = 400,
HTTP_UNAUTHORIZED = 401,
HTTP_PAYMENT_REQUIRED = 402,
HTTP_FORBIDDEN = 403,
HTTP_NOT_FOUND = 404,
HTTP_METHOD_NOT_ALLOWED = 405,
HTTP_NOT_ACCEPTABLE = 406,
HTTP_PROXY_AUTHENTICATION = 407,
HTTP_REQUEST_TIMEOUT = 408,
HTTP_CONFLICT = 409,
HTTP_GONE = 410,
HTTP_LENGTH_REQUIRED = 411,
HTTP_PRECONDITION = 412,
HTTP_REQUEST_TOO_LARGE = 413,
HTTP_URI_TOO_LONG = 414,
HTTP_UNSUPPORTED_MEDIATYPE = 415,
HTTP_UPGRADE_REQUIRED = 426,
HTTP_SERVER_ERROR = 500,
HTTP_NOT_IMPLEMENTED = 501,
HTTP_BAD_GATEWAY = 502,
HTTP_SERVICE_UNAVAILABLE = 503,
HTTP_GATEWAY_TIMEOUT = 504,
HTTP_NOT_SUPPORTED = 505
} http_status_t;
typedef enum {
    HTTP_0_9 = 9,
    HTTP_1_0 = 100,
    HTTP_1_1 = 101
} http_version_t;
typedef enum {
    HTTP_KEEPALIVE_OFF = 0,
    HTTP_KEEPALIVE_ON = 1
} http_keepalive_t;
typedef enum {
    HTTP_ENCODE_LENGTH = 0,
    HTTP_ENCODE_CHUNKED = 1
} http_encoding_t;
typedef enum {
    IPP_JOB_PENDING = 3,
    IPP_JOB_HELD = 4,
    IPP_JOB_PROCESSING = 5,
    IPP_JOB_STOPPED = 6,
    IPP_JOB_CANCELLED = 7,
    IPP_JOB_ABORTED = 8,
    IPP_JOB_COMPLETED = 9
} ipp_jstate_t;
typedef struct {
    int id;
    char *dest;
    char *title;
    char *user;
    char *format;
    ipp_jstate_t state;
    int size;
    int priority;
    time_t completed_time;
    time_t creation_time;
    time_t processing_time;
} cups_job_t;

```

```

typedef struct _cups_array_s cups_array_t;

typedef struct _http_s http_t;
extern int cupsAddDest(const char *name, const char *instance,
                      int num_dests, cups_dest_t * *dests);
extern int cupsAddOption(const char *name, const char *value,
                        int num_options, cups_option_t * *options);
extern int cupsCancelJob(const char *printer, int job);
extern int cupsDoAuthentication(http_t * http, const char *method,
                               const char *resource);
extern ipp_t *cupsDoFileRequest(http_t * http, ipp_t * request,
                               const char *resource,
                               const char *filename);
extern void cupsEncodeOptions(ipp_t * ipp, int num_options,
                             cups_option_t * options);
extern http_encryption_t cupsEncryption(void);
extern void cupsFreeDest(int num_dests, cups_dest_t * dests);
extern void cupsFreeJobs(int num_jobs, cups_job_t * jobs);
extern void cupsFreeOptions(int num_options, cups_option_t *
options);
extern const char *cupsGetDefault(void);
extern const char *cupsGetDefault2(http_t * http);
extern cups_dest_t *cupsGetDest(const char *name, const char
*instance,
                               int num_dests, cups_dest_t * dests);
extern int cupsGetDests(cups_dest_t * *dests);
extern int cupsGetDests2(http_t * http, cups_dest_t * *dests);
extern http_status_t cupsGetFd(http_t * http, const char *resource,
                              int fd);
extern http_status_t cupsGetFile(http_t * http, const char
*resource,
                               const char *filename);
extern int cupsGetJobs(cups_job_t * *jobs, const char *dest, int
myjobs,
                      int completed);
extern int cupsGetJobs2(http_t * http, cups_job_t * *jobs,
                       const char *dest, int myjobs, int completed);
extern const char *cupsGetOption(const char *name, int num_options,
                                cups_option_t * options);
extern const char *cupsGetPPD(const char *printer);
extern const char *cupsGetPPD2(http_t * http, const char *printer);
extern const char *cupsGetPassword(const char *prompt);
extern const char *cupsLangEncoding(cups_lang_t * lang);
extern void cupsLangFlush(void);
extern void cupsLangFree(cups_lang_t * lang);
extern cups_lang_t *cupsLangGet(const char *language);
extern ipp_status_t cupsLastError(void);
extern int cupsMarkOptions(ppd_file_t * ppd, int num_options,
                          cups_option_t * options);
extern int cupsParseOptions(const char *arg, int num_options,
                          cups_option_t * *options);
extern int cupsPrintFile(const char *printer, const char *filename,
                        const char *title, int num_options,
                        cups_option_t * options);
extern int cupsPrintFile2(http_t * http, const char *printer,
                          const char *filename, const char *title,
                          int num_options, cups_option_t * options);
extern int cupsPrintFiles(const char *printer, int num_files,
                        const char **files, const char *title,
                        int num_options, cups_option_t * options);
extern int cupsPrintFiles2(http_t * http, const char *printer,
                          int num_files, const char **files,
                          const char *title, int num_options,
                          cups_option_t * options);
extern http_status_t cupsPutFd(http_t * http, const char *resource,
                              int fd);

```

```

extern http_status_t cupsPutFile(http_t * http, const char
*resource,
                                const char *filename);
extern const char *cupsServer(void);
extern void cupsSetDests(int num_dests, cups_dest_t * dests);
extern int cupsSetDests2(http_t * http, int num_dests,
                        cups_dest_t * dests);
extern void cupsSetEncryption(http_encryption_t e);
extern void cupsSetPasswordCB(const char *(*cb) (const char *));
extern void cupsSetServer(const char *server);
extern void cupsSetUser(const char *user);
extern int cupsTempFd(char *filename, int len);
extern const char *cupsUser(void);

```

7.2.2 cups/http.h

```

#define HTTP_MAX_URI      1024
#define HTTP_MAX_BUFFER  2048
#define HTTP_MAX_HOST     256
#define HTTP_MAX_VALUE   256

typedef enum http_auth_e {
    HTTP_AUTH_NONE,
    HTTP_AUTH_BASIC,
    HTTP_AUTH_MD5,
    HTTP_AUTH_MD5_SESS,
    HTTP_AUTH_MD5_INT,
    HTTP_AUTH_MD5_SESS_INT,
    HTTP_AUTH_NEGOTIATE
} http_auth_t;
typedef enum http_field_e {
    HTTP_FIELD_UNKNOWN,
    HTTP_FIELD_ACCEPT_LANGUAGE,
    HTTP_FIELD_ACCEPT_RANGES,
    HTTP_FIELD_AUTHORIZATION,
    HTTP_FIELD_CONNECTION,
    HTTP_FIELD_CONTENT_ENCODING,
    HTTP_FIELD_CONTENT_LANGUAGE,
    HTTP_FIELD_CONTENT_LENGTH,
    HTTP_FIELD_CONTENT_LOCATION,
    HTTP_FIELD_CONTENT_MD5,
    HTTP_FIELD_CONTENT_RANGE,
    HTTP_FIELD_CONTENT_TYPE,
    HTTP_FIELD_CONTENT_VERSION,
    HTTP_FIELD_DATE,
    HTTP_FIELD_HOST,
    HTTP_FIELD_IF_MODIFIED_SINCE,
    HTTP_FIELD_IF_UNMODIFIED_SINCE,
    HTTP_FIELD_KEEP_ALIVE,
    HTTP_FIELD_LAST_MODIFIED,
    HTTP_FIELD_LINK,
    HTTP_FIELD_LOCATION,
    HTTP_FIELD_RANGE,
    HTTP_FIELD_REFERER,
    HTTP_FIELD_RETRY_AFTER,
    HTTP_FIELD_TRANSFER_ENCODING,
    HTTP_FIELD_UPGRADE,
    HTTP_FIELD_USER_AGENT,
    HTTP_FIELD_WWW_AUTHENTICATE,
    HTTP_FIELD_MAX
} http_field_t;
typedef enum http_uri_status_e {
    HTTP_URI_OVERFLOW,
    HTTP_URI_BAD_ARGUMENTS,
    HTTP_URI_BAD_RESOURCE,

```

```

    HTTP_URI_BAD_PORT,
    HTTP_URI_BAD_HOSTNAME,
    HTTP_URI_BAD_USERNAME,
    HTTP_URI_BAD_SCHEME,
    HTTP_URI_BAD_URI,
    HTTP_URI_OK,
    HTTP_URI_MISSING_SCHEME,
    HTTP_URI_UNKNOWN_SCHEME,
    HTTP_URI_MISSING_RESOURCE
} http_uri_status_t;
typedef enum http_uri_coding_e {
    HTTP_URI_CODING_NONE,
    HTTP_URI_CODING_USERNAME,
    HTTP_URI_CODING_HOSTNAME,
    HTTP_URI_CODING_RESOURCE,
    HTTP_URI_CODING_MOST,
    HTTP_URI_CODING_QUERY,
    HTTP_URI_CODING_ALL
} http_uri_coding_t;
typedef union _http_addr_u {
    struct sockaddr addr;
    struct sockaddr_in ipv4;
    struct sockaddr_in6 ipv6;
    struct sockaddr_un un;
    char pad[256];
} http_addr_t;
typedef struct http_addrlist_s {
    struct http_addrlist_s *next;
    http_addr_t addr;
} http_addrlist_t;
extern void httpBlocking(http_t * http, int b);
extern int httpCheck(http_t * http);
extern void httpClearCookie(http_t * http);
extern void httpClearFields(http_t * http);
extern void httpClose(http_t * http);
extern http_t *httpConnect(const char *host, int port);
extern http_t *httpConnectEncrypt(const char *host, int port,
    http_encryption_t encryption);
extern char *httpDecode64_2(char *out, int *outlen, const char *in);
extern int httpDelete(http_t * http, const char *uri);
extern char *httpEncode64_2(char *out, int outlen, const char *in,
    int inlen);
extern int httpEncryption(http_t * http, http_encryption_t e);
extern int httpError(http_t * http);
extern void httpFlush(http_t * http);
extern int httpGet(http_t * http, const char *uri);
extern const char *httpGetCookie(http_t * http);
extern const char *httpGetDateString(time_t t);
extern time_t httpGetDateTime(const char *s);
extern const char *httpGetField(http_t * http, http_field_t field);
extern struct hostent *httpGetHostByName(const char *name);
extern char *httpGetSubField(http_t * http, http_field_t field,
    const char *name, char *value);
extern char *httpGets(char *line, int length, http_t * http);
extern int httpHead(http_t * http, const char *uri);
extern void httpInitialize(void);
extern char *httpMD5(const char *, const char *, const char *, char
    *);
extern char *httpMD5Final(const char *, const char *, const char *,
    char *);
extern char *httpMD5String(const unsigned char *, char *);
extern int httpOptions(http_t * http, const char *uri);
extern int httpPost(http_t * http, const char *uri);
extern int httpPut(http_t * http, const char *uri);
extern int httpReconnect(http_t * http);
extern void httpSetCookie(http_t * http, const char *cookie);

```

```
extern void httpSetField(http_t * http, http_field_t field,
                        const char *value);
extern const char *httpStatus(http_status_t status);
extern int httpTrace(http_t * http, const char *uri);
extern http_status_t httpUpdate(http_t * http);
extern int httpWait(http_t * http, int msec);
```

7.2.3 cups/ipp.h

```
#define IPP_MAX_NAME      256
#define IPP_MAX_LENGTH    32767
#define IPP_PORT          631
#define IPP_MAX_VALUES    8
#define CUPS_ADD_CLASS    CUPS_ADD_MODIFY_CLASS
#define CUPS_ADD_PRINTER  CUPS_ADD_MODIFY_PRINTER
#define IPP_ERROR_JOB_CANCELLED IPP_ERROR_JOB_CANCELED
#define IPP_JOB_CANCELLED  IPP_JOB_CANCELED
#define IPP_VERSION       "\001\001"

typedef enum {
    IPP_OK = 0,
    IPP_OK_SUBST = 1,
    IPP_OK_CONFLICT = 2,
    IPP_OK_IGNORED_SUBSCRIPTIONS = 3,
    IPP_OK_IGNORED_NOTIFICATIONS = 4,
    IPP_OK_TOO_MANY_EVENTS = 5,
    IPP_OK_BUT_CANCEL_SUBSCRIPTION = 6,
    IPP_REDIRECT_OTHER_SITE = 768,
    IPP_BAD_REQUEST = 1024,
    IPP_FORBIDDEN = 1025,
    IPP_NOT_AUTHENTICATED = 1026,
    IPP_NOT_AUTHORIZED = 1027,
    IPP_NOT_POSSIBLE = 1028,
    IPP_TIMEOUT = 1029,
    IPP_NOT_FOUND = 1030,
    IPP_GONE = 1031,
    IPP_REQUEST_ENTITY = 1032,
    IPP_REQUEST_VALUE = 1033,
    IPP_DOCUMENT_FORMAT = 1034,
    IPP_ATTRIBUTES = 1035,
    IPP_URI_SCHEME = 1036,
    IPP_CHARSET = 1037,
    IPP_CONFLICT = 1038,
    IPP_COMPRESSION_NOT_SUPPORTED = 1039,
    IPP_COMPRESSION_ERROR = 1040,
    IPP_DOCUMENT_FORMAT_ERROR = 1041,
    IPP_DOCUMENT_ACCESS_ERROR = 1042,
    IPP_ATTRIBUTES_NOT_SETTABLE = 1043,
    IPP_IGNORED_ALL_SUBSCRIPTIONS = 1044,
    IPP_TOO_MANY_SUBSCRIPTIONS = 1045,
    IPP_IGNORED_ALL_NOTIFICATIONS = 1046,
    IPP_PRINT_SUPPORT_FILE_NOT_FOUND = 1047,
    IPP_INTERNAL_ERROR = 1280,
    IPP_OPERATION_NOT_SUPPORTED = 1281,
    IPP_SERVICE_UNAVAILABLE = 1282,
    IPP_VERSION_NOT_SUPPORTED = 1283,
    IPP_DEVICE_ERROR = 1284,
    IPP_TEMPORARY_ERROR = 1285,
    IPP_NOT_ACCEPTING = 1286,
    IPP_PRINTER_BUSY = 1287,
    IPP_ERROR_JOB_CANCELLED = 1288,
    IPP_MULTIPLE_JOBS_NOT_SUPPORTED = 1289,
    IPP_PRINTER_IS_DEACTIVATED = 1290
} ipp_status_t;
typedef enum ipp_tag_e {
```