



BSI Standards Publication

Information technology — UPnP device architecture

Part 19-10: Solar Protection Blind Device Control
Protocol — Two Way Motion Motor Service

National foreword

This British Standard is the UK implementation of ISO/IEC 29341-19-10:2011.

The UK participation in its preparation was entrusted to Technical Committee ICT/1, Information systems co-ordination.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2023
Published by BSI Standards Limited 2023

ISBN 978 0 580 73530 1

ICS 35.200

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 March 2023.

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------



ISO/IEC 29341-19-10

Edition 1.0 2011-10

INTERNATIONAL STANDARD



**Information technology – UPnP device architecture –
Part 19-10: Solar Protection Blind Device Control Protocol – Two Way Motion
Motor Service**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

J

ICS 35.200

ISBN 978-2-88912-690-3

CONTENTS

1	Overview and Scope.....	3
2	Service Modeling Definitions.....	3
2.1	Service Type	3
2.2	State Variables.....	4
2.2.1	OperationMode	5
2.2.2	ServiceLocked	5
2.2.3	Position	5
2.2.4	PositionArgType	5
2.2.5	Relationships between State Variables.....	6
2.3	Eventing and Moderation	6
2.4	Actions.....	6
2.4.1	(Void) Open().....	7
2.4.2	(Void) Close()	8
2.4.3	(Void) Stop().....	9
2.4.4	(String) GetOperationMode(RetVal).....	10
2.4.5	(Void) SetOperationMode(String)	10
2.4.6	(Void) IsLocked(Boolean).....	11
2.4.7	(Void) Lock().....	11
2.4.8	(Void) UnLock()	12
2.4.9	(Float) GetPosition(RetVal)	13
2.4.10	(Void) SetPosition(I1).....	13
2.4.11	(String) GetPositionArgType(RetVal).....	14
2.4.12	Non-Standard Actions Implemented by a UPnP Vendor	15
2.4.13	Relationships between Actions.....	15
2.4.14	Common Error Codes	15
2.5	Theory of Operation.....	15
3	XML Service Description	17
4	Test	20
	Table 1: State Variables	4
	Table 1.1: allowedValueList for <u>OperationMode</u>	4
	Table 1.2: DefaultValue for <u>OperationMode</u>	4
	Table 1.5: allowedValueRange for <u>Position</u>	4
	Table 1.6: DefaultValue for <u>Position</u>	4
	Table 1.7: allowedValueList for <u>PositionArgType</u>	5
	Table 1.8: DefaultValue for <u>PositionArgType</u>	5
	Table 2: Event Moderation	6
	Table 3: Actions.....	7
	Table 4.1: Arguments for <u>Open</u>	7
	Table 4.2: Arguments for <u>Close</u>	8
	Table 4.3: Arguments for <u>Stop</u>	9

Table 4.4: Arguments for [GetOperationMode](#)10

Table 4.5: Arguments for [SetOperationMode](#)10

Table 4.6: Arguments for [IsLocked](#)11

Table 4.7: Arguments for [Lock](#)11

Table 4.8: Arguments for [UnLock](#)12

Table 4.9: Arguments for [GetPosition](#)13

Table 4.10: Arguments for [SetPosition](#)13

Table 4.11: Arguments for [GetPositionArgType](#)14

Table 5: Common Error Codes15

INFORMATION TECHNOLOGY – UPNP DEVICE ARCHITECTURE –

Part 19-10: Solar Protection Blind Device Control Protocol – Two Way Motion Motor Service

FOREWORD

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
- 4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
- 6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.
- 7) All users should ensure that they have the latest edition of this publication.
- 8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
- 9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 10) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 29341-19-10 was prepared by UPnP Forum Steering committee¹, was adopted, under the fast track procedure, by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

The list of all currently available parts of the ISO/IEC 29341 series, under the general title *Information technology – UPnP device architecture*, can be found on the IEC web site.

This International Standard has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

¹ UPnP Forum Steering committee, UPnP Forum, 3855 SW 153rd Drive, Beaverton, Oregon 97006 USA. See also "Introduction".

IMPORTANT – The “colour inside” logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this publication using a colour printer.

1 Overview and Scope

This service definition is compliant with the UPnP Device Architecture version 1.0.

This service-type enables the following functions:

- Driving a motor between two fixed end limits.
- Reaching any position written in percentage of the full run (optional).
- Returning the actual blind position written in percentage of the full run (optional).

This service template does not address:

- Any motorization whose run is not bounded.
- Any speed control.

2 Service Modeling Definitions

2.1 Service Type

The following service type identifies a service that is compliant with this template:

urn:schemas-UPnP-org:service:*TwoWayMotionMotor:1*.