BS ISO/IEC 30143:2020

BSI Standards Publication

Internet of Things (IoT) — Underwater acoustic sensor network (UWASN) — Application profiles

Documents
Document Sharing Hub

Full document details: BS ISO/IEC 30143:2020

National foreword

This British Standard is the UK implementation of ISO/IEC 30143:2020.

The UK participation in its preparation was entrusted to Technical Committee IOT/1, Internet of Things.

A list of organizations represented on this committee can be obtained on request to its committee manager.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2020
Published by BSI Standards Limited 2020

ISBN 978 0 539 14016 3

ICS 35.110

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 June 2020.

Amendments/corrigenda issued since publication

Date	Text affected

Documents
Document Sharing Hub

Full document details: BS ISO/IEC 30143:2020

ISO/IEC 30143

Edition 1.0 2020-06

INTERNATIONAL STANDARD

colour inside

Internet of Things (IoT) – Underwater acoustic sensor network (UWASN) – Application profiles

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 35.110

ISBN 978-2-8322-8485-8

Warning! Make sure that you obtained this publication from an authorized distributor.

Documents
Document Sharing Hub

Full document details: BS ISO/IEC 30143:2020

CONTENTS

FOREWORD 5
INTRODUCTION 6
1 Scope 7
2 Normative references 7
3 Terms and definitions 7
4 Abbreviated terms 8
5 Overview of UWASN application profiles 8
5.1 Introduction to application profiles 8
5.2 Benefits of application profiles 8
6 Design process of UWASN application profiles 8
6.1 General 8
6.2 Criteria for the design process of UWASN application profiles 9
6.3 Design process steps for UWASN application profiles 9
7 Requirements for the design process of UWASN application profiles 9
7.1 General 9
7.2 User requirements of UWASN application profiles 10
7.3 General requirements of UWASN application profiles 10
7.4 Functional requirements of UWASN application profiles 11
7.5 Constrained requirements of UWASN application profiles 12
7.5.1 General 12
7.5.2 Connectivity 13
7.5.3 UWA-GW 13
7.5.4 UWA-DTN-GW 13
7.5.5 Housing case 13
7.5.6 Fouling cleaner 13
7.5.7 Node deployment 13
7.5.8 Battery 14
8 Modelling techniques for designing UWASN application profiles 14
8.1 General 14
8.2 Use case model 14
8.2.1 General 14
8.2.2 Elements of use case diagram 14
8.2.3 Relationships 15
8.3 Sequence diagram model 16
8.3.1 General 16
8.3.2 Elements of sequence diagram 16
8.4 Class diagram model 18
8.4.1 General 18
8.4.2 Elements of class diagram 18
9 Guidelines for the implementation of UWASN application profiles 19
9.1 Layered design approach for developing UWASN application profiles 19
9.2 Specific architecture for implementing UWASN application profiles 20
9.3 Framework for implementing UWASN application profiles 21
9.3.1 User interface 21
9.3.2 System calculation unit 22
9.3.3 Surface devices 22

AVA Documents
Document Sharing Hub
Full document details: BS ISO/IEC 30143:2020

9.3.4 Sensor node 22
9.4 Functional operations for implementing UWASN application profiles 23
10 Specialized maintenance for UWASN application profiles 24
Annex A (informative) Application profile example 26
A.1 Fish farming 26
A.1.1 General 26
A.1.2 Guidelines for designing UWASN fish farming application 26
A.1.3 Requirements for the design process of UWASN fish farming application 27
A.1.4 Modelling techniques for designing UWASN fish farming application 30
A.1.5 Guidelines for the implementation process of UWASN fish farming application 32
Bibliography 38

Figure 1 – Actor representation examples 14
Figure 2 – Use case representation examples 15
Figure 3 – System boundary representation example 15
Figure 4 – Use case model for UWASN application profiles 16
Figure 5 – Object symbol in a sequence diagram 16
Figure 6 – Execution box symbol in a sequence diagram 17
Figure 7 – Lifeline representation in a sequence diagram 17
Figure 8 – Sequence diagram modelling for UWASN application profiles 17
Figure 9 – Representation of different sections in class diagram 18
Figure 10 – Class diagram modelling for UWASN application profiles 19
Figure 11 – Layer design approach 20
Figure 12 – UWASN specific architectural model 21
Figure 13 – Framework of UWASN application profiles 23
Figure 14 – Operation design approach 24
Figure A.1 – Use case model for fish farming application 31
Figure A.2 – Sequence diagram model for fish farming application 32
Figure A.3 – Layered design approach of fish farming application 33
Figure A.4 – Specific fish farming architecture 34
Figure A.5 – Framework for fish farming application 35
Figure A.6 – Operation design process for fish farming application 36

Table 1 – Steps for the design process of UWASN application profiles 9
Table 2 – User requirements of UWASN application profiles 10
Table 3 – General requirements for UWASN application profiles 10
Table 4 – Functional requirements for UWASN application profiles 11
Table 5 – Constrained requirements for UWASN application profiles 12
Table 6 – Relationship and symbols of use case diagram 15
Table 7 – Components for implementing UWASN application profiles 23
Table 8 – Operation process of UWASN application profiles 24
Table 9 – Key factors for monitoring UWASN application profiles 25
Table 10 – Components used for the maintenance of UWASN application profiles 25

AVA Documents
Document Sharing Hub

Full document details: BS ISO/IEC 30143:2020

Table A.1 – Steps for designing UWASN fish farming application 27
Table A.2 – User requirements for the design process of UWASN fish farming application 27
Table A.3 – General requirements for the design process of UWASN fish farming application 28
Table A.4 – Functional requirements for the design process of UWASN fish farming application 29
Table A.5 – Constrained requirements for the design process of UWASN fish farming application 30
Table A.6 – Operation design process of UWASN fish farming application 36
Table A.7 – Key components to monitor in fish farming application 37
Table A.8 – Components used for the maintenance of UWASN fish farming application 37

Documents
Document Sharing Hub

Full document details: BS ISO/IEC 30143:2020

INTERNET OF THINGS (IoT) – UNDERWATER ACOUSTIC SENSOR NETWORK (UWASN) – APPLICATION PROFILES

FOREWORD

1) ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

2) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees and ISO member bodies.

3) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC National Committees and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.

4) In order to promote international uniformity, IEC National Committees and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO, IEC or ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.

5) ISO and IEC do not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. ISO or IEC are not responsible for any services carried out by independent certification bodies.

6) All users should ensure that they have the latest edition of this publication.

7) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC National Committees or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.

8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

9) Attention is drawn to the possibility that some of the elements of this ISO/IEC publication may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 30143 was prepared by subcommittee 41: Internet of Things and related technologies, of ISO/IEC joint technical committee 1: Information technology.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
JTC1-SC41/150/FDIS	JTC1-SC41/161/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

Documents
Document Sharing Hub

Full document details: BS ISO/IEC 30143:2020

INTRODUCTION

Water covers approximately 70 % of the surface of the Earth. Modern technologies introduce new methods to monitor the body of water such as pollution monitoring and detection. Underwater data gathering techniques require exploring the water environment, which can be most effectively performed by underwater acoustic sensor networks (UWASNs). Applications developed for the UWASNs can record underwater climate, detect and control water pollution, monitor marine biology, discover natural resources, detect pipeline leakages, monitor and find underwater intruders, perform strategic surveillance, and so on.

In order to build and apply the UWASN technology, the most suitable methods for managing the network have been developed based on the already proposed ISO/IEC 30140 series. This document describes the application profiles outline and requirements appropriate to the UWASN under the constraints of underwater physical environment.

The ISO/IEC 30140 series provides general requirements, reference architecture (RA) including the entity models and high-level interface guidelines supporting interoperability among UWASNs in order to provide the essential UWASN construction information to help and guide architects, developers and implementers of UWASNs.

This document provides the guidelines for designing and developing the UWASN application. It also provides other information such as the components required for developing UWASN application, modelling techniques for UWASN application and UWASN application profiles example.

Various technical standards derived from the R&D results of the technical areas under the UWASN and underwater communication fields not covered by the ISO/IEC 30140 series are continuously proposed and developed.

Documents
Document Sharing Hub

Full document details: BS ISO/IEC 30143:2020

INTERNET OF THINGS (IoT) – UNDERWATER ACOUSTIC SENSOR NETWORK (UWASN) – APPLICATION PROFILES

1 Scope

This document provides the guidelines for designing and developing new applications in the underwater environment such as fish farming, environment monitoring, harbour security, etc. This document also:

- provides the components required for developing the application;
- provides instructions for modelling the application with examples;
- helps the user to understand the communication between the elements in the application for modelling the communication between elements;
- guides the user with the design process of underwater applications.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.1
application profile
set of documents which provides the effective guidance to develop a particular application

3.2
component
representation of an actor in a UWASN application profile

3.3
element
<of use case model> object used to connect the devices and networks in the underwater environment

EXAMPLE actors, use cases, relationships

3.4
element
<of sequence diagram model> essential part used to connect the devices and networks in the underwater environment

EXAMPLE class, execution place, lifeline

Documents
Document Sharing Hub

Full document details: BS ISO/IEC 30143:2020

3.5
element
<of class diagram model> class, object or method used for the communication between the devices and networks in the underwater environment

4 Abbreviated terms

RF	radio frequency
UUV	unmanned underwater vehicle
UWASN	underwater acoustic sensor network
UWA-GW	underwater acoustic gateway
UWA-SNode	underwater acoustic sensor node
UWA-CH	underwater acoustic cluster head
UWA-CH-id	underwater acoustic cluster head identity
UWA-SNode-id	underwater acoustic sensor node identity
UWA-DTN-GW	underwater DTN gateway
UWA-FN	underwater acoustic fundamental network

5 Overview of UWASN application profiles

5.1 Introduction to application profiles

In UWASN, the application profiles comprise of a group of components, approaches and guidelines for a specific application.

5.2 Benefits of application profiles

An application profile is a layout or outline for users. Application profiles can help users as suggested below:

– utilizing them to depict how applications are deployed, arranged and managed in submerged conditions;
– providing required components for building up new UWASN applications effectively;
– providing the basic information for planning;
– reducing the learning curve;
– standardizing the development work; and
– providing the general requirements and functional requirements for developing the application.

6 Design process of UWASN application profiles

6.1 General

The primary goal of the design process is to give guidance for developing underwater applications (See Annex A). The design process of UWASN application profiles provides the following information:

– purpose of UWASN application;
– overview of UWASN application;
– user requirements for the design process of UWASN application;
– general requirements for the design process of UWASN application;

Documents
Document Sharing Hub
Full document details: BS ISO/IEC 30143:2020

– functional requirements for the design process UWASN application;
– constrained requirements for the design process of UWASN application;
– consideration for the design process of UWASN application.

6.2 Criteria for the design process of UWASN application profiles

The criteria considered for the design process of the UWASN application profiles include but are not limited to the following:

– limitation in bandwidth;
– localization;
– limited battery power;
– deployment of devices;
– reliability;
– scalability;
– quality of service;
– distance of transmission;
– propagation delay;
– device configuration;
– device maintenance;
– self-management.

6.3 Design process steps for UWASN application profiles

Table 1 shows the steps for the design process of UWASN application profiles.

Table 1 – Steps for the design process of UWASN application profiles

Design process steps	Description
Step 1: User requirements analysis	The user requirements for a particular UWASN application are collected.
Step 2: General requirements analysis	The general requirements for particular UWASN application are collected.
Step 3: Functional requirements analysis	The functional requirements for a particular UWASN application are collected.
Step 4: Constrained requirements analysis	The constrained requirements for a particular UWASN application are collected.
Step 5: Design process	The design process of UWASN application profile needs the modelling techniques for designing the application such as case modelling, sequence diagram modelling and class diagram modelling.
Step 6: Implementation guideline process	The implementation process consists of installation, deployment, configuration, performing operation and testing.
Step 7: Specialized maintenance	The specialized maintenance for underwater applications is considered. For example, node reclamation (change battery/recharging), fouling cleaner, housing case, etc.

7 Requirements for the design process of UWASN application profiles

7.1 General

Clause 7 discusses the various requirements such as user requirements, general requirements, functional requirements and constrained requirements for the design process of UWASN application profiles (See Annex A).

AVA Documents
Document Sharing Hub

Full document details: BS ISO/IEC 30143:2020

7.2 User requirements of UWASN application profiles

Table 2 shows the user requirements for UWASN application profiles.

Table 2 – User requirements of UWASN application profiles

User requirements	Description
Durability	Durability refers to the time period for which a product or system can meet its service and performance requirements.
System performance	System performance refers to the effectiveness of a system, which includes response time, throughput, latency, availability, etc.
Low cost	Low cost includes the total cost of the system, which includes the cost of procurement, installation, usage and disposal.
Efficiency	Efficiency of a system can be identified using various factors such as response time, number of tasks completed in a stipulated time, etc.
Adaptability	Adaptability refers to the extent to which a system adapts to the change in its working environment.
Reliability	Reliability refers to the hardware or software or other application related items; its performance is consistently monitored by the users. It can be considered while buying or using the product.
Usability	Usability can be defined as the ease of use with respect to the system. This includes measures such as learnability, efficiency, memorability, etc.
Availability	Availability refers to the percentage of time that the system is available and working according to the requirements.
Maintainability	Maintainability refers to the ability to make variations in the system quickly and cost effectively.
Security	Security refers to the ability of the system (1) to resist unauthorized usage and (2) to continue providing services to the legitimate users in case of attacks.
Portability	Portability can be defined as the ability of a system to run under different computing environments such as hardware, software, operating systems, etc.
Reusability	Reusability refers to the ability of a system to make reuse of existing components in new applications.

7.3 General requirements of UWASN application profiles

Table 3 shows the general requirements for UWASN application profiles.

Table 3 – General requirements for UWASN application profiles

General requirements	Description
Capability of discovery	The UWA-SNode shall use discovery capability mechanism to identify other nodes connected inside the UWASN system.
Connectivity support to different network	Integration shall be supported by different networks for avoiding complexity.
Routing techniques	The best routing algorithm is performed by the device known as router, used for passing the message from source to destination. This technique can also reduce the cost in UWASN.
Security	A standard security system shall be used to prevent attacks from illegal users.
Service quality	Service quality refers to a network capability to attain maximum bandwidth and deals with the various performance elements of network, which include latency, error rate, etc.
Scalability	If the number of devices increases, the UWASN system shall use the scalability support.
Dynamic adaptation	Due to the mobility of UUV and UWA-SNode, the UWASN shall use dynamic adaptation techniques.

AVA Documents
Document Sharing Hub

General requirements	Description
Deployment	Easy deployment techniques shall be used for the deployment of UWA-SNodes in the underwater environment.
Battery life time management	In UWASN, the battery life time management shall be used to increase the battery life time of underwater devices.
Localization	Localization techniques shall be used to find the location of UWA-SNodes, UUVs, etc.
Time synchronization	Time synchronization shall be used to synchronize the time of all sensor nodes used in UWASN.
Network management	Network management shall be used to manage the whole applications such as fish farming, environment monitoring, etc.
Wired/wireless communication	Wired or wireless communication shall be established based on the requirements.
Privacy	Any information cannot be provided for all. So, this function shall be used for maintaining privacy.
Packet loss reducing	Various techniques shall be used to minimize the packet loss in UWASN.

7.4 Functional requirements of UWASN application profiles

Table 4 shows the functional requirements for UWASN application profiles.

Table 4 – Functional requirements for UWASN application profiles

Functional requirements	Description
Data processing	Data processing is used for performing the operations such as classifying, retrieving, transforming, etc.
Device management	Device management is used for the management of components such as UWA-SNode, UWA-GW, etc.
Data acquisition	The data acquisition function is used for measuring the physical characteristics of water such as temperature, dissolved oxygen, pH value, etc.
Validation process	The validation process is used for application quality management, such as whether the application meets its requirements or services.
Integration	This is used to integrate different components to perform the required functions.
Data communication	Communication module and efficient protocols are required for long-range and short-range communication.
Data storage	The amount and type of data stored in UWA-SNode, UWA-CH, etc.
Identification	The UWA-SNode needs a unique identifiable address.
Self-localization	The UWA-SNode, UWA-CH and UUV needs the ability to identify their location.
Data security	In UWASN the functions like key distribution, data integrity and authentication are used to increase the security level.
Key distribution	The shared key mechanism can be used between the nodes such as UUV, UWA-SNode, UWA-CH, etc. to increase the reliability of communication.
Integrity	The integrity mechanism is used to increase the confidentiality while sending and receiving data.
Authentication	The authentication mechanism is used to ensure whether the messages are generated from the authenticated user or not.
Network recovery	The network recovery functions are used to reconnect the network when the connection is broken.
Device recovery	The devices such as UWA-SNodes, UUVs, etc. consist of all the information related to environment. If some failures occur in the device, the device recovery function shall be used.
Battery capacity	To identify the maximum amount of power availability in underwater devices such as UWA-SNodes, UUVs, etc. the battery capacity function is needed.

AVA Documents
Document Sharing Hub