BS ISO/IEC 7811-7:2014

BSI Standards Publication

Identification cards — Recording technique

Part 7: Magnetic stripe — High coercivity, high density

bsi.

...making excellence a habit.™

Document Sharing Hub

Full document details: BS ISO/IEC 7811-7:2014

National foreword

This British Standard is the UK implementation of ISO/IEC 7811-7:2014.

The UK participation in its preparation was entrusted to Technical Committee IST/17, Cards and personal identification.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2014. Published by BSI Standards Limited 2014

ISBN 978 0 580 80374 1

ICS 35.240.15

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 September 2014.

Amendments issued since publication

Date	Text affected

Documents
Document Sharing Hub

Full document details: BS ISO/IEC 7811-7:2014

INTERNATIONAL STANDARD

ISO/IEC 7811-7

Second edition
2014-09-01

Identification cards — Recording technique —

Part 7: Magnetic stripe — High coercivity, high density

Cartes d'identification — Technique d'enregistrement —

Partie 7: Bandeau magnétique — Haute coercitivité, haute densité

Reference number
ISO/IEC 7811-7:2014(E)

Documents
Document Sharing Hub
© ISO/IEC 2014

Full document details: BS ISO/IEC 7811-7:2014

COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

© ISO/IEC 2014 – All rights reserved

Documents
Document Sharing Hub

Full document details: BS ISO/IEC 7811-7:2014

Contents

Page

Foreword ... **iv**

1 Scope ... **1**

2 Conformance ... **1**

3 Normative references ... **1**

4 Terms and definitions ... **2**

5 Physical characteristics of the identification card ... **4**
5.1 Magnetic stripe area warpage ... 4
5.2 Surface distortions ... 4

6 Physical characteristics of the magnetic stripe ... **5**
6.1 Height and surface profile of the magnetic stripe area ... 5
6.2 Surface roughness ... 7
6.3 Adhesion of stripe to card ... 7
6.4 Wear of magnetic stripe from read/write head ... 7
6.5 Resistance to chemicals ... 8

7 Performance characteristics for the magnetic material ... **8**
7.1 General ... 8
7.2 Testing and operating environment ... 8
7.3 Signal amplitude requirements for magnetic media ... 8

8 Encoding technique ... **10**

9 Encoding specification ... **11**
9.1 Angle of recording ... 11
9.2 Nominal bit density ... 12
9.3 Flux transition spacing variation ... 12
9.4 Signal amplitude requirements ... 12
9.5 Bit configuration ... 12
9.6 Direction of recording ... 13
9.7 Leading and trailing clock bits ... 13

10 Data structure ... **13**
10.1 Track format ... 13
10.2 Coding for error detection and correction ... 15

11 Decoding ... **18**

12 Location of encoded tracks ... **19**

Annex A (informative) **Compatibility of magnetic stripes (ISO/IEC 7811-6 and ISO/IEC 7811-7)** ... **20**

Annex B (informative) **Magnetic stripe abrasivity** ... **21**

Annex C (informative) **Static magnetic characteristics** ... **22**

Annex D (informative) **Reed-Solomon code references** ... **25**

© ISO/IEC 2014 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO/IEC 7811-7:2014

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 17, *Cards and personal identification.*

This second edition cancels and replaces the first edition (ISO/IEC 7811-7:2004) of which it constitutes a major revision with the following changes.

— The primary standard cards held by Q-Card are used to calibrate the manufacture of secondary reference cards. Other primary standard cards held by PTB and Card testing International (CTI) are used as backup to replace cards held by Q-Card as they wear out.

— Delete reference to character sets in the Scope since none are used in this International Standard.

  — List of major differences has been moved from the Introduction to Annex A.

  — The supplier of secondary reference cards has changed from PTB to Q-Card.

ISO/IEC 7811 consists of the following parts, under the general title *Identification cards — Recording technique:*

— *Part 1: Embossing*

— *Part 2: Magnetic stripe — Low coercivity*

— *Part 6: Magnetic stripe — High coercivity*

— *Part 7: Magnetic stripe — High coercivity, high density*

— *Part 8: Magnetic stripe — High coercivity of 51,7 kA/m (650 Oe)*

— *Part 9: Tactile identifier mark*

Notes in this International Standard are only used for giving additional information intended to assist in the understanding or use of the International Standard and do not contain provisions or requirements to which it is necessary to conform in order to be able to claim compliance with this International Standard.

© ISO/IEC 2014 – All rights reserved
AVA Documents
Document Sharing Hub
Full document details: BS ISO/IEC 7811-7:2014

INTERNATIONAL STANDARD ISO/IEC 7811-7:2014(E)

Identification cards — Recording technique —

Part 7: Magnetic stripe — High coercivity, high density

1 Scope

This part of ISO/IEC 7811 is one of a series of International Standards describing the characteristics for identification cards as defined in the definitions clause and the use of such cards for international interchange.

This part of ISO/IEC 7811 specifies requirements for a high coercivity magnetic stripe (including any protective overlay) on an identification card and encoding technique. It takes into consideration both human and machine aspects and states minimum requirements.

Coercivity influences many of the quantities specified in this part of ISO/IEC 7811 but is not itself specified. The main characteristic of the high coercivity magnetic stripe is its improved resistance to erasure. This is achieved with minimal probability of damage to other magnetic stripes by contact while retaining read compatibility with magnetic stripes as defined in ISO/IEC 7811-2.

This standard provides for a card capacity of approximately 10 times that of a card conforming to ISO/IEC 7811-6. The number of tracks has been increased to six, each track being approximately half the width of tracks conforming to ISO/IEC 7811-6, located so that readers designed to read these high density tracks will also be able to read cards conforming to ISO/IEC 7811-2 and ISO/IEC 7811-6. Data is encoded in 8 bit bytes using the MFM encoding technique. Data framing is used to limit error propagation and error correction techniques further improve reliability of reading.

It is the purpose of this series of International Standards to provide criteria to which cards shall perform. No consideration is given within these International Standards to the amount of use, if any, experienced by the card prior to test. Failure to conform to specified criteria should be negotiated between the involved parties.

ISO/IEC 10373-2 specifies the test procedures used to check cards against the parameters specified in this part of ISO/IEC 7811.

NOTE Numeric values in the SI and/or Imperial measurement system in this part of ISO/IEC 7811 might have been rounded off and therefore are consistent with, but not exactly equal to, each other. Either system can be used, but the two should not be intermixed or reconverted. The original design was made using the Imperial measurement system.

2 Conformance

A prerequisite for conformance with this part of ISO/IEC 7811 is conformance with ISO/IEC 7810. An identification card is in conformance with this part of ISO/IEC 7811 if it meets all mandatory requirements specified herein. Default values apply if no others are specified.

3 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 4287-1, *Surface roughness — Terminology — Part 1: Surface and its parameters*

Documents
Document Sharing Hub

© ISO/IEC 2014 – All rights reserved

Full document details: BS ISO/IEC 7811-7:2014

ISO/IEC 7810, *Identification cards — Physical characteristics*

ISO/IEC 10373-1, *Identification cards — Test methods — Part 1: General characteristics*

ISO/IEC 10373-2, *Identification cards — Test methods — Part 2: Cards with magnetic stripes*

4 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 7810 and the following apply.

4.1
primary standard
set of reference cards established by Physikalisch-Technische Bundesanstalt (PTB) and maintained by PTB, Q-Card, and WG1 secretariat that represent the values of UR and IR designated RM7811-6

4.2
secondary standard
reference card designated RM7811-6 that is related to the primary standard as stated in the calibration certificate supplied with each card

Note 1 to entry: Secondary standards can be ordered from Q-Card, 301 Reagan St., Sunbury, PA 17801, USA. The source of secondary standards will be maintained at least until 2018.

4.3
unused un-encoded card
card possessing all the components required for its intended purpose, which has not been subjected to any personalization or testing operation, and which has been stored in a clean environment with no more than 48 h exposure to day-light at temperatures between 5 °C to 30 °C and humidity between 10 % to 90 % without experiencing thermal shock

4.4
unused encoded card
card according to 4.3 that has only been encoded with all the data required for its intended purpose (e.g. magnetic encoding, embossing, electronic encoding)

4.5
returned card
card according to 4.4 after it has been issued to the card holder and returned for the purpose of testing

4.6
flux transition
location of the greatest rate of change with distance of the magnetization

4.7
reference current
I_R
minimum recorded current amplitude under the given test conditions that causes, on the reference card, a readback signal amplitude equal to 80 % of the reference signal amplitude U_R, at a density of 20 flux transitions per mm (508 flux transitions per inch) as shown in Figure 6

4.8
reference flux level
F_R
flux level in the test head that corresponds to the reference current I_R

4.9
test recording currents
two recording currents defined by: I_{min} = recording current corresponding to 2,2 F_R and I_{max} = recording current corresponding to 2,5 F_R

© ISO/IEC 2014 – All rights reserved
Documents
Document Sharing Hub
Full document details: BS ISO/IEC 7811-7:2014

4.10
individual signal amplitude
U_i
base-to-peak amplitude of a single readback voltage signal

4.11
average signal amplitude
U_A
sum of the absolute values of the amplitude of each signal peak (U_i) divided by the number of signal peaks (n) for a given track over the length of the magnetic stripe area

4.12
reference signal amplitude
U_R
maximum value of the average signal amplitude of a reference card corrected to the primary standard

4.13
physical recording density
number of flux transitions per unit length recorded on a track

4.14
bit density
number of data bits stored per unit of length (bits/mm or bpi)

4.15
bit cell
distance for a data bit nominally the reciprocal of the bit density (see Figure 8)

4.16
average bit cell
B_a
product of bit cell length and sum of the actual distances for all flux transition intervals on a track divided by the sum of the nominal distances for all flux transition intervals on the track

4.17
local average bit cell
B_{a6}
comparison reference for a given flux transition interval equal to the nominal L1 distance multiplied by the sum of the actual distances for the previous six flux transition intervals divided by the sum of the nominal distances for the previous six flux transition intervals

$$L1 \times (\Sigma \text{ actual})/(\Sigma \text{ nominal})$$

4.18
demagnetization current
I_d
D C current value that reduces the average signal amplitude to 80 % of the reference signal amplitude (U_R) on a secondary reference card that has been encoded at a density of 40 ft/mm (1 016 ftpi) at a current of I_{min}

4.19
L_1
short distance between adjacent flux transitions nominally equal to 1 times the bit cell

4.20
L_2
medium distance between adjacent flux transitions nominally equal to 1,5 times the bit cell

© ISO/IEC 2014 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO/IEC 7811-7:2014

4.21
L_3
long distance between adjacent flux transitions nominally equal to 2 times the bit cell

4.22
FSC
frame synchronization character

4.23
CRC
cyclic redundancy check

4.24
CP
column parity

4.25
U_F
magnitude of the individual element at 20 flux transitions per mm frequency of the Fourier spectrum for a given track over the length of the magnetic stripe area

5 Physical characteristics of the identification card

The identification card shall conform to the specification given in ISO/IEC 7810.

WARNING — The attention of card issuers is drawn to the fact that information held on the magnetic stripe may be rendered ineffective through contamination by contact with dirt and certain commonly used chemicals including plasticizers. It should also be noted that any printing or screening placed on top of the magnetic stripe must not impair the function of the magnetic stripe.

5.1 Magnetic stripe area warpage

Application of a 2,2 N (0.5 lbf) load evenly distributed on the front face opposite the magnetic stripe shall bring the entire stripe within 0,08 mm (0.003 in) of the rigid plate.

5.2 Surface distortions

There shall be no surface distortions, irregularities or raised areas on both the front and the back of the card in the area shown in Figure 1 that might interfere with the contact between the magnetic head and magnetic stripe.

© ISO/IEC 2014 – All rights reserved
Documents
Document Sharing Hub
Full document details: BS ISO/IEC 7811-7:2014



Figure 1 — Distortion-free area on card with magnetic stripe

If a raised signature panel area is located on the front or back of the card, then it shall be no closer to the top edge of the card than 19,05 mm (0.750 in).

NOTE Raised areas and distortions on other areas of the card may cause card transport problems with magnetic stripe processing equipment resulting in reading or writing errors.

6 Physical characteristics of the magnetic stripe

6.1 Height and surface profile of the magnetic stripe area

The magnetic stripe area is located on the back of the card as shown in Figure 2.



Figure 2 — Location of magnetic material

© ISO/IEC 2014 – All rights reserved

Documents
Document Sharing Hub
Full document details: BS ISO/IEC 7811-7:2014