

Information technology — Open systems interconnection — Network Service Definition

ICS 35.100.30

National foreword

This British Standard reproduces verbatim ISO/IEC 8348:1996 and implements it as the UK national standard. It supersedes BS ISO/IEC 8348:1993 which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee IST/6, Data communications, which has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international/European committee any enquiries on the interpretation, or proposals for change, and keep the UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

A list of organizations represented on this committee can be obtained on request to its secretary.

Cross-references

The British Standards which implement international or European publications referred to in this document may be found in the BSI Standards Catalogue under the section entitled “International Standards Correspondence Index”, or by using the “Find” facility of the BSI Standards Electronic Catalogue.

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, the ISO/IEC title page, pages ii to v, a blank page, pages 1 to 60, an inside back cover and a back cover.

The BSI copyright notice displayed throughout this document indicates when the document was last issued.

This British Standard, having been prepared under the direction of the DISC Board, was published under the authority of the Standards Board and comes into effect on 15 August 1998

© BSI 07-1999

ISBN 0 580 30310 1

Amendments issued since publication

Amd. No.	Date	Comments
10502	July 1999	Indicated by a sideline

INTERNATIONAL STANDARD

ISO/IEC
8348

Third edition
1996-09-15

AMENDMENT 1
1998-12-15

Information technology — Open systems interconnection — Network Service Definition

*Technologies de l'information — Interconnexion des systèmes ouverts —
Définition du service de réseau —*



Reference number
ISO/IEC 8348:1996/Amd 1:1998(E)

AVA Documents
Document Sharing Hub

Contents

	<i>Page</i>
SECTION 1 – GENERAL	1
1 Scope.....	1
2 Normative references	1
2.1 Identical Recommendations International Standards	1
2.2 Paired Recommendations International Standards equivalent in technical content	2
2.3 Additional references	2
3 Definitions.....	2
3.1 Basic reference model definitions	2
3.2 Service conventions definitions	3
3.3 Network Service definitions.....	3
3.4 Network addressing definitions	3
3.5 Network layer architecture definitions.....	4
4 Abbreviations	4
5 Conventions.....	5
5.1 General conventions.....	5
5.2 Parameters.....	5
5.3 NC endpoint identification convention	5
6 Overview and general characteristics.....	5
7 Types and classes of Network Service	6
SECTION 2 – DEFINITION OF THE CONNECTION-MODE SERVICE	6
8 Features of the connection-mode Network Service	6
9 Model of the connection-mode Network Service.....	7
9.1 Model of the connection-mode Network Layer Service	7
9.2 Model of a Network Connection.....	7
10 Quality of the connection-mode Network Service	11
10.1 Determination of QOS	11
10.2 Definition of QOS-parameters	12
11 Sequence of primitives	15
11.1 Relation of primitives at the two NC end points	15
11.2 Sequence of primitives at one NC endpoint.....	15
12 Connection establishment phase	18
12.1 Function	18
12.2 Types of primitives and parameters	18
12.3 Sequence of primitives.....	26

© ISO/IEC 1996

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland

13	Connection release phase	26
13.1	Function	26
13.2	Types of primitive and parameters	27
13.3	Sequence of primitives when releasing an established NC	28
13.4	Sequence of primitives in an NS user rejection of an NC establishment attempt	30
13.5	Sequence of primitives in an NS provider rejection of an NC establishment attempt	30
14	Data transfer phase	31
14.1	Data transfer	31
14.2	Receipt confirmation service	31
14.3	Expedited data transfer service	33
14.4	Reset service	34
SECTION 3 – DEFINITION OF THE CONNECTIONLESS-MODE SERVICE		37
15	Features of the connectionless-mode Network Service	37
16	Model of the connectionless-mode Network Service	37
16.1	Model of the connectionless-mode Network Layer Service	37
16.2	Model of a network connectionless-mode transmission	37
17	Quality of the connectionless-mode Network Service	39
17.1	Determination of QOS	39
17.2	Definition of network connectionless-mode QOS-parameters	39
17.3	Route selection considerations	40
18	Sequence of primitives	40
19	Data transfer	41
19.1	Function	41
19.2	Types of primitives and parameters	41
19.3	Sequence of primitives	42
Annex A – Network Layer Addressing		43
A.1	General	43
A.2	Scope	43
A.3	Concepts and terminology	43
A.4	Principles for creating the OSI Network addressing scheme	46
A.5	Network address definition	47
A.6	Character based DSP allocation	54
A.7	Reference publication formats	54
A.8	Network entity titles	55
Annex B – Rationales for the material in Annex A		56
B.1	IDI formats (see A.5.2.1.2)	56
B.2	Reservation of AFI values 00-F and FF	57
B.3	Derivation of the preferred encodings	57
Annex C – Facilities for conveying service characteristics in the connectionless-mode Network Service		58
C.1	Introduction	58
C.2	Function	58
C.3	Types of primitives and parameters	59
C.4	Service characteristics	59
C.5	Types of primitives and parameters	60

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 8348 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 21, *Open Systems Interconnection, data management and open distributed processing*, in collaboration with ITU-T. The identical text is published as ITU-T Recommendation X.213.

This third edition cancels and replaces the second edition (ISO/IEC 8348:1993), which has been technically revised. It also incorporates Amendment 5:1994.

Annex A forms an integral part of this International Standard. Annexes B and C are for information only.

Introduction

This Recommendation | International Standard is one of a set of Recommendations and International Standards produced to facilitate the interconnection of computer systems. It is related to other Recommendations and International Standards in the set as defined by the Reference Model of Open Systems Interconnection (OSI). The OSI Reference Model (ITU-T Rec. X.200 | ISO/IEC 7498-1) subdivides the area of standardization for interconnection into a series of layers of specification, each of a manageable size.

This Recommendation | International Standard defines the Service provided by the Network Layer to the Transport Layer at the boundary between the Network and Transport Layers of the Reference Model. It provides for the designers of Transport protocols a definition of the Network Service existing to support the Transport protocol and for the designers of Network protocols a definition of the services to be made available through the action of the Network protocol over the underlying service. This relationship is illustrated in Figure Intro. 1.




Figure Intro. 1 – Relationship of the Network Service to OSI Network and Transport protocols

The use of the word “Network” to name the “Network” Layer of the OSI Reference Model should be distinguished from the use of the word “network” to denote a communications network as conventionally understood. To facilitate this distinction, the term “subnetwork” is used for a collection of physical equipment, commonly called a “network” (see Rec. X.200 | ISO/IEC 7498-1). Subnetworks may be either public networks or privately supplied networks. In the case of public networks, their properties may be determined by separate Recommendations such as Recommendation X.21 for a circuit-switched network or Recommendation X.25 for a packet-switched network.

Throughout the set of OSI Recommendations and International Standards the term “Service” refers to the abstract capability provided by one layer of the OSI Reference Model to the layer above it. Thus, the Network Service defined in this Recommendation | International Standard is a conceptual architectural Service, independent of administrative divisions.

NOTE – It is important to distinguish the specialized use of the term “Service” within the set of OSI Recommendations and International Standards from its use elsewhere to describe the provision of a service by an organization (such as the provision of a service, as defined in other Recommendations, by an Administration).

Any particular subnetwork may or may not support the OSI Network Service. The OSI Network Service may be provided by a combination of one or more subnetworks and optional additional functions between or outside these subnetworks.

INFORMATION TECHNOLOGY – OPEN SYSTEMS INTERCONNECTION – NETWORK SERVICE DEFINITION

SECTION 1 – GENERAL

1 Scope

This Recommendation | International Standard defines the OSI Network Service in terms of:

- a) the primitive actions and events of the Service;
- b) the parameters associated with each primitive action and event, and the form which they take;
- c) the interrelationship between, and the valid sequences of, these actions and events.

The principal objectives of this Recommendation | International Standard are

- 1) To specify the characteristics of a conceptual Network Service and thus, supplement the Reference Model in guiding the development of Network Layer protocols.
- 2) To encourage convergence of the capabilities offered by providers of subnetworks.
- 3) To provide a basis for the individual enhancement of existing heterogeneous subnetworks to a common subnetwork-independent Network Service to enable them to be concatenated for the purpose of providing global communication. (Such concatenation may involve optional additional functions which are not defined in this Recommendation | International Standard.) A definition of the quality of service is an important element of this Recommendation | International Standard.
- 4) To provide a basis for the development and implementation of subnetwork-independent Transport Layer protocols decoupled from the variability of underlying public and private subnetworks and their specific interface requirements.

This Recommendation | International Standard does not specify individual implementations or products nor does it constrain the implementation of entities and interfaces within a system.

There is no conformance of equipment to this Recommendation | International Standard. Instead, conformance is achieved through implementation of conforming OSI Network protocols which fulfill the Network Service defined in this Recommendation | International Standard.

2 Normative references

The following Recommendations and International Standards contain provisions which, through reference in this text, constitute provisions of this Recommendation | International Standard. At the time of publication, the editions indicated were valid. All Recommendations and International Standards are subject to revision, and parties to agreements based on this Recommendation | International Standard are encouraged to investigate the possibility of applying the most recent edition of the Recommendations and International Standards listed below. Members of the IEC and ISO maintain registers of currently valid International Standards. The Telecommunication Standardization Bureau of the ITU maintains a list of currently valid ITU-T Recommendations.

2.1 Identical Recommendations | International Standards

- ITU-T Recommendation X.200 (1994) | ISO/IEC 7498-1:1994, *Information technology – Open Systems Interconnection – Basic Reference Model: The Basic Model*.
- ITU-T Recommendation X.210 (1993) | ISO/IEC 10731:1994, *Information technology – Open Systems Interconnection – Basic Reference Model: Conventions for the definition of OSI services*.

2.2 Paired Recommendations | International Standards equivalent in technical content

- ITU-T Recommendation X.224 (1993), *Protocol for providing the OSI connection-mode transport service.*

ISO/IEC 8073:1992, *Information technology – Telecommunications and information exchange between systems – Open Systems Interconnection – Protocol for providing the connection-mode transport service.*

2.3 Additional references

- CCITT Recommendation E.163 (1988), *Numbering plan for the international telephone service.*
- CCITT Recommendation E.164 (1991), *Numbering plan for the ISDN era.*
- CCITT Recommendation F.69 (1988), *Plan for telex destination codes.*
- CCITT Recommendation T.50 (1992), *International Reference Alphabet (IRA) – Information technology – 7-bit coded character set for information interchange.*
- CCITT Recommendation X.121 (1992), *International numbering plan for public data networks.*
- CCITT Recommendation X.300, (1988), *General principles for interworking between public networks and between public networks and other networks for the provision of data transmission services.*
- ISO/IEC 646:1991, *Information technology – ISO 7-bit coded character set for information interchange.*
- ISO 2375:1985, *Data processing – Procedure for registration of escape sequences.*
- ISO 3166:1993, *Codes for the representation of names of countries.*
- ISO 6523:1984, *Data interchange – Structures for the identification of organizations.*
- ISO 8648:1988, *Information processing systems – Open Systems Interconnection – Internal organization of the Network Layer.*
- Internet Standard 00002, *Assigned Numbers.*

3 Definitions

For the purposes of this Recommendation | International Standard, the following definitions apply.

3.1 Basic reference model definitions

This Recommendation | International Standard is based on the concepts developed in the Basic Reference Model for Open Systems Interconnection and makes use of the following terms defined in ITU-T Rec. X.200 | ISO/IEC 7498-1:

- expedited Network-Service-data-unit;
- Network-address;
- Network Connection;
- Network-entity;
- Network-protocol control information;
- Network-protocol data unit;
- Network Layer;
- Network-relay;
- Network-routing;
- Network Service;
- Network-Service-access-point;
- Network-Service-access-point-address;
- Network-Service-data-unit;
- OSI environment;
- subnetwork;
- title.

3.2 Service conventions definitions

This Recommendation | International Standard also makes use of the following terms defined in ITU-T Rec. X.210 | ISO/IEC 10731, as they apply to the Network Layer:

- a) confirm;
- b) indication;
- c) Network Service user;
- d) Network Service provider;
- e) primitive;
- f) request;
- g) response.

3.3 Network Service definitions

For the purpose of this Recommendation | International Standard, the following definitions also apply:

3.3.1 calling NS user: An NS user that initiates an NC establishment request.

3.3.2 called NS user: An NS user with whom a calling NS user wishes to establish an NC.

NOTE – Calling NS users and called NS users are defined with respect to a single NC. An NS user can be both a calling and a called NS user simultaneously.

3.3.3 generic address: An address which identifies a set of NSAPs rather than a single specific NSAP.

3.3.4 Network Connection: An association established by a Network Layer between two NS users for the transfer of data, which provides explicit identification of a set of Network data transmissions and agreement concerning the services to be provided by the set.

NOTE – This definition clarifies that given in ITU-T Rec. X.200 | ISO/IEC 7498-1.

3.3.5 Network connection-mode Data Transmission: The transfer of an NSDU from a source NSAP to a destination NSAP within the context of an NC that has previously been established.

3.3.6 Network connectionless-mode Data Transmission: The transmission of an NSDU from a source NSAP to a destination NSAP or group of destination NSAPs outside the context of an NC and without any requirement to maintain any logical relationship among multiple invocations.

3.3.7 Network connectionless-mode Multicast Transmission: The transmission of an NSDU from a source NSAP to a set of destination NSAPs.

3.4 Network addressing definitions

Annex A, describing network addressing makes use of the following terms as defined below:

3.4.1 DTE address: Information used to identify a point of attachment to a public data network.

3.4.2 subnetwork point of attachment: A point at which a real end system, interworking unit, or real subnetwork is attached to a real subnetwork, and a conceptual point at which a subnetwork service is offered within an end or intermediate system.

3.4.3 subnetwork point of attachment address: Information used in the context of a particular real subnetwork to identify a subnetwork point of attachment; or information used in the context of a particular subnetwork to identify the conceptual point within an end or intermediate system at which the subnetwork service is offered. This term is used interchangeably with the (equivalent) shortened form *subnetwork address*.

3.4.4 network protocol address information: Information encoded in a Network protocol data unit to carry the semantics of a Network service access point address. (This is known as an “address signal” or as the “coding of an address signal” in the public network environment.)

3.4.5 naming domain: A context within which a name allocated by a naming authority is unambiguous. Where the name is an address, the context within which the name is allocated is called an *addressing domain*.

3.4.6 global network addressing domain: An addressing domain consisting of all of the Network service access point addresses in the OSI environment.

3.4.7 network addressing domain: A subset of the global network addressing domain consisting of all of the Network service access point addresses allocated by one or more addressing authorities.

3.4.8 naming authority: That which allocated names from a specified naming domain, and which ensures that names so allocated are unambiguous. Where the naming authority allocates addresses, it is called an *addressing authority*.

3.4.9 network addressing authority: An addressing authority that assigns and administers Network service access point addresses within one or more network addressing domains.

3.4.10 abstract syntax: A notation which enables data types to be defined, and values of those types specified, without determining the way in which they will be represented (encoded) for transfer by protocols.

3.4.11 group Network address: An address that identifies a set of zero or more Network service access points; these may belong to multiple Network entities, in different end systems.

3.4.12 individual Network address: An address that identifies a single NSAP.

NOTE – Where the distinction between a group Network address and an individual Network address is not important, the term **NSAP address** is used.

3.5 Network layer architecture definitions

This Recommendation | International Standard makes use of the following terms defined in CCITT Rec. X.300 and ISO 8648.

- a) subnetwork;
- b) real subnetwork;
- c) subnetwork service;
- d) real end system;
- e) interworking unit;
- f) intermediate system;
- g) relay entity.

4 Abbreviations

For the purposes of this Recommendation | International Standard, the following abbreviations apply:

AFI	Authority and Format Identifier
CC	Country Code
COR	Confirmation of Receipt
DCC	Data Country Code
DSP	Domain Specific Part
ENSDU	Expedited Network-Service-data-unit
ICD	International Code Designator
IDI	Initial Domain Identifier
IDP	Initial Domain Part
ISDN	Integrated Services Digital Network
N	Network
NC	Network Connection
NL	Network Layer
NPAI	Network Protocol Addressing Information
NPDU	Network Protocol Data Unit
NS	Network Service
NSAP	Network-Service-access-point
NSDU	Network-Service-data-unit
OSI	Open Systems Interconnection
PSTN	Public Switched Telephone Network

PTT	Postal, Telephone and Telegraph
QOS	Quality of Service
RPF	Reference Publication Format
SNPA	Subnetwork Point of Attachment

5 Conventions

5.1 General conventions

This Service Definition uses the descriptive conventions given by ITU-T Rec. X.210 | ISO/IEC 10731.

The layer service model, service primitives, and time-sequence diagrams taken from those conventions are entirely abstract descriptions; they do not represent a specification for implementation.

5.2 Parameters

Service primitives, used to represent service-user/service-provider interactions (see ITU-T Rec. X.210 | ISO/IEC 10731), convey parameters which indicate information available in the user/provider interaction.

The parameters which apply to each group of Network Service primitives are set out in tables in clauses 12 to 14 and 19. Each “X” in the tables indicates that the primitive labeling the column in which it falls may carry the parameter labeling the row in which it falls.

Some entries are further qualified by items in brackets. These may be:

- a) an indication that the parameter is conditional in some way:
 - (C) indicates that the parameter is not present on the primitive for every NC; the parameter definition describes the conditions under which the parameter is present or absent;
- b) a parameter specific constraint:
 - (=) indicates that the value supplied in an indication or confirm primitive is always identical to that supplied in the corresponding request or response primitive occurring at the peer NSAP;
- c) an indication that some note applies to the entry:
 - (Note x) indicates that the referenced note contains additional information pertaining to the parameter and its use.

In any particular interface, not all parameters need be explicitly stated. Some may be implicitly associated with the NSAP at which the primitive is issued.

5.3 NC endpoint identification convention

If an NS user needs to distinguish among several NCs at the same NSAP, then a local NC endpoint identification mechanism must be provided. All primitives issued at such an NSAP would be required to use this mechanism to identify NCs. Such an implicit identification is not described as a parameter of the service primitives in this Service Definition.

NOTE – The implicit NC endpoint identification must not be confused with the address parameters of the N-CONNECT primitives (see 12.2).

6 Overview and general characteristics

The Network Service provides for the transparent transfer of data (i.e. NS-user-data) between NS users. It makes invisible to these NS users the way in which supporting communications resources are utilized to achieve this transfer.

In particular, the Network Service provides for the following:

- a) *Independence of underlying transmission media* – The Network Service relieves NS users from all concerns regarding how various subnetworks are used to provide the Network Service. The Network Service hides from the NS user differences in the transfer of data over heterogeneous subnetworks, other than quality of service.

- b) *End-to-end transfer* – The Network Service provides for transfer of NS-user-data between NS users in end systems. All routing and relaying functions are performed by the NS provider including the case where several similar or dissimilar transmission resources are used in tandem or in parallel.
- c) *Transparency of transferred information* – The Network Service provides for the transparent transfer of octet-aligned NS-user-data and/or control information. It does not restrict the content, format or coding of the information, nor does it ever need to interpret its structure or meaning.
- d) *Quality of service selection* – The Network Service makes available to NS users a means to request and to agree to the quality of service for the transfer of NS-user-data. Quality of service is specified by means of QOS-parameters representing characteristics such as throughput, transit delay, accuracy, and reliability.
- e) *NS-user-addressing* – The Network Service utilizes a system of addressing (NSAP addressing and group Network addressing) which allows NS users to refer unambiguously to one another.

7 Types and classes of Network Service

There are two types of Network Service:

- a) a connection-mode service (defined in Section 2); and
- b) a connectionless-mode service (defined in Section 3).

For a given instance of communication, the mode of service provided to all NS users is the same (i.e. connection-mode or connectionless-mode). Choice of provision of the connectionless-mode Network Service or the connection-mode Network Service is made in accordance with ITU-T Rec. X.200 | ISO/IEC 7498-1.

When referring to this Service Definition, an NS user or NS provider shall state which type(s) of service it expects to use or provide.

There are no distinct classes of Network Service defined.

However, for the connection-mode service, two Network Layer Services, Receipt Confirmation and Expedited Data Transfer, are NS provider-options.

A service which is an NS provider-option is one which an NS provider can choose either to provide or not to provide for a particular NC. In circumstances where the NS provider chooses not to provide a provider-option service, it will not be available in the Network Service. If the provider-option Receipt Confirmation or Expedited Data Transfer is provided, it shall be as defined in 14.1 to 14.3.

SECTION 2 – DEFINITION OF THE CONNECTION-MODE SERVICE

8 Features of the connection-mode Network Service

The connection-mode Network Service offers the following features to an NS user:

- a) The means to establish an NC with another NS user for the purpose of transferring NS-user-data in the form of NSDUs. More than one NC may exist between the same pair of NS users.
- b) The establishment of an agreement between the two NS users and the NS provider for a certain QOS associated with each NC.
- c) The means of transferring NSDUs in sequence on an NC. The transfer of NSDUs, which consist of an integer number of octets, is transparent, in that the boundaries of NSDUs and the contents of NSDUs are preserved unchanged by the Network Service, and there are no constraints on the NSDU content imposed by the Network Service.
- d) The means by which the receiving NS user may flow control the rate at which the sending NS user may send NSDUs.
- e) In some circumstances, the means of transferring separate expedited NSDUs in sequence (see clause 7). Expedited NSDUs are limited in length and their transmission is subject to a different flow control from normal data across the NSAP.
- f) The means by which the NC can be returned to a defined state and the activities of the two NS users synchronized by use of a reset service.

- g) In some circumstances, the means for the NS user to confirm the receipt of an NSDU (see clause 7).
- h) The unconditional, and therefore possibly destructive, release of an NC by either of the NS users or by the NS provider.

9 Model of the connection-mode Network Service

9.1 Model of the connection-mode Network Layer Service

This Service Definition uses the abstract model for a layer service defined in clause 4 of ITU-T Rec. X.210 | ISO/IEC 10731. The model defines the interactions between the NS users and the NS provider which take place at the two NSAPs. Information is passed between the NS user and the NS provider by service primitives, which may convey parameters.

9.2 Model of a Network Connection

Between the two endpoints of an NC, there exists a flow control function which relates the behaviour of the NS user at one end receiving NS-user-data to the ability of the NS user at the other end to send NS-user-data. As a means of specifying this flow control feature and its relationship with other capabilities provided by the Network Service, the queue model of an NC, described in the following subclauses, is used.


This queue model of an NC is discussed only to aid in the understanding of the end-to-end service features perceived by users of the Network Service. It is not intended to serve as a substitute for a precise, formal description of the Network Service, nor as a complete specification of all allowable sequences of NS primitives (allowable primitive sequences are specified in clause 11 – also, see Note below.) In addition, this model does not attempt to describe all the functions or operations of Network Layer entities (including relay entities) which are used to provide the Network Service. No attempt to specify or constrain Network Service implementations is implied.

In interpreting this service definition, statements in clauses 12 to 14 concerning the properties of individual primitives have precedence over the general statements in this clause.

NOTE – In addition to the interaction between service primitives described by this model, there may be constraints applied locally on the ability to invoke primitives, as well as service procedures defining particular sequencing constraints on some primitives.

9.2.1 Queue model concepts

The queue model represents the operation of an NC in the abstract by a pair of queues linking the two NSAPs. There is one queue for each direction of information flow (see Figure 1).



TISO0300-92/d02

Figure 1 – Queue model of a Network Connection

Each queue represents a flow control function in one direction of transfer. The ability of an NS user to add objects to a queue will be determined by the behaviour of the NS user removing objects from that queue and the state of the queue. Objects are entered or removed from the queue, either as the result of interactions at the two NSAPs, or as the result of NS provider initiatives.

The pair of queues is considered to be available for each potential NC.

The objects which may be placed in a queue as a result of interactions at an NSAP (see clauses 12 to 14) are:

- a) connect objects (associated with N-CONNECT primitives and all of their parameters);
- b) octets of normal NS-user-data (associated with an N-DATA primitive);
- c) indications of end-of-NSDU (associated with completion of an N-DATA primitive);
- d) expedited NSDUs (associated with N-EXPEDITED-DATA primitives and all their parameters);
- e) data acknowledgment objects (associated with N-DATA-ACKNOWLEDGE primitives);
- f) reset objects (associated with N-RESET primitives and their parameters);
- g) disconnect objects (associated with N-DISCONNECT primitives and all their parameters).

NOTE – The description of flow control (see 9.2.3) requires a less abstract description than that used for describing sequences of primitives in clauses 11 to 14. While primitives are defined to be indivisible, for purposes of this queue model, information associated with N-DATA primitives is conceptually subdivided into a sequence of octets of NS-user-data followed by an end-of-NSDU indication. This does not imply any particular subdivision in any real interface.

The objects which may be placed in a queue as a result of NS provider initiatives (see clauses 12 to 14) are:

- 1) reset objects (associated with N-RESET primitives and all their parameters);
- 2) synchronization mark objects (see 9.2.4);
- 3) disconnect objects (associated with N-DISCONNECT primitives and all their parameters).

The queues are defined to have the following general properties:

- i) a queue is empty until a connect object has been entered and can be returned to this state, with loss of its contents, by the NS provider (see 9.2.4 and 9.2.5);
- ii) objects may be entered into a queue as a result of the actions of the source NS user, subject to control by the NS provider; objects may also be entered into a queue by the NS provider;
- iii) objects are removed from the queue under the control of the receiving NS user;
- iv) objects are normally removed under the control of the NS user in the same order that they were entered (however see 9.2.3);
- v) a queue has a limited capacity, but this capacity is not necessarily either fixed or determinable.

9.2.2 NC establishment

A pair of queues is associated with an NC between two NSAPs when the NS provider receives an N-CONNECT request primitive at one of the NSAPs and a connect object is entered into one of the queues. From the standpoint of one of the NS users of the NC, the queues remain associated with the NC until a disconnect object (associated with an N-DISCONNECT primitive) is either entered or removed from a queue at that NSAP.

If NS user A denotes the NS user who initiates NC establishment (resulting in a connect object being entered into the queue from NS user A to NS user B), then no object other than a disconnect object may be entered into the queue from A to B until after the connect object associated with the N-CONNECT confirm has been removed. In the queue from NS user B to NS user A, objects can be entered only after a connect object associated with an N-CONNECT response from NS user B has been entered; it is possible for a disconnect object to be placed in the queue from B to A instead of a connect object to release the NC.

The properties exhibited by the queues while the NC exists represent the agreements reached among the NS users and the NS provider during the NC establishment procedure concerning quality of service and the use of the receipt and expedited data transfer services.

9.2.3 Data transfer operations

Flow control on the NC is represented in this queue model by the management of the queue capacity, allowing objects of certain types to be added to the queues. The conditions affecting entry of reset and disconnect objects are described in item b) below and in 9.2.4 and 9.2.5. The flow control relationship between the other types of objects is summarized by Table 1.

Table 1 – Flow control relationships between queue model objects

The addition of object x may prevent further addition of object y	Octets of NS-user-data or end-of-NSDU	Expedited NSDU	Data acknowledgment
Octets of normal NS-user-data or end-of-NSDU	Yes	Yes	No
Expedited NSDU	No	Yes	No
Data acknowledgment	No	No	No

Once in the queue, the NS provider may manipulate pairs of adjacent objects, resulting in:

- Change of order* – The order of any pair of objects may be reversed, if and only if, the following object is of a type defined to be able to advance ahead of the preceding object. No object is defined to be able to advance ahead of another object of the same type.
- Deletion* – Any object may be deleted if, and only if, the following object is defined to be destructive with respect to the preceding object. If necessary, the last object in the queue will be deleted to allow a destructive object to be entered. Destructive objects may therefore always be added to the queue. Disconnect objects are defined to be destructive with respect to all other objects. Reset objects are defined to be destructive with respect to all other objects except connect and disconnect objects.

The relationships between objects which may be manipulated as described in a) and b) above are summarized in Table 2.

Whether the NS provider performs actions resulting in change of order and deletion or not will depend upon the behaviour of the NS users and the agreed QOS for the NC. In general, if an NS user does not cause objects to be removed from a queue, the NS provider shall, after some unspecified period of time, perform all permitted actions of types a) and b).

9.2.4 Reset operations

The invocation of a reset procedure is represented in the two queues as follows:

- Invocation of a reset procedure by the NS provider is represented by the introduction into each queue of a reset object followed by a synchronization mark object.
- A reset procedure invoked by an NS user is represented by the addition of a reset object to one queue. In this case, the NS provider will insert a reset object followed by a synchronization mark object into the other queue.

The completion of a reset procedure by the issuance of an N-RESET response by an NS user results in a reset object being placed in the queue from the responding NS user.

A synchronization mark object cannot be removed from a queue by an NS user; a queue appears empty to an NS user when a synchronization mark object is the next object in it. Unless destroyed by a disconnect object, a synchronization mark object remains in the queue until the next object following it in the queue is a reset object. Both the synchronization mark object and the following reset object are then deleted by the NS provider.

NOTE – Associated with the invocation of a reset procedure are restrictions on the issuance of certain other types of primitives. These restrictions will result in restrictions on the entry of certain object types into the queue until the reset procedure is complete.

9.2.5 NC release

The insertion into a queue of a disconnect object, which may occur at any time, represents the initiation of an NC release procedure. The release procedure may be destructive with respect to other objects in the two queues and eventually results in the emptying of the queues and the disassociation of the queues with the NC.

The insertion of a disconnect object may also represent the rejection of an NC establishment attempt or the failure to complete NC establishment. In such cases, if a connect object representing an N-CONNECT request primitive is deleted by a disconnect object, then the disconnect object is also deleted. The disconnect object is not deleted when it deletes any other object, including the case where it deletes a connect object representing an N-CONNECT response.

Table 2 – Ordering relationships between queue model objects

Following object x is defined with respect to preceding object y	Connect	Octets of normal NS user-data	End-of- NSDU	Expedited NSDU	Data acknowledgment	Reset	Synchronization mark	Disconnect
Connect	N/A	–	N/A	–	–	–	N/A	DES
Octets of normal NS user-data	N/A	–	–	AA	AA	DES	N/A	DES
End-of-NSDU	N/A	–	N/A	AA	AA	DES	N/A	DES
Expedited NSDU	N/A	–	–	–	AA	DES	N/A	DES
Data acknowledgment	N/A	–	–	AA	–	DES	N/A	DES
Reset	N/A	–	N/A	–	–	DES	–	DES
Synchronization mark	N/A	–	–	–	–	DES	N/A	DES
Disconnect	N/A	N/A	N/A	N/A	N/A	N/A	N/A	DES
AA Indicates that object x is defined to be able in advance ahead of the preceding object y. DES Indicates that object x is defined to be destructive with respect to the preceding object y. – Indicates that object x is neither destructive with respect to object y nor able to advance ahead of object y. N/A Indicates that object x will not occur in a position succeeding object y in a valid state of a queue.								

10 Quality of the connection-mode Network Service

The term Quality of Service (QOS) refers to certain characteristics of an NC as observed between the NC endpoints. QOS describes aspects of an NC which are attributable solely to the NS provider; it can only be properly determined in the absence of NS user behaviour (which is beyond the control of the NS provider) which specifically constrains or impairs the performance of the Network Service.

A value of QOS applies to an entire NC. When determined or measured at both ends of an NC, the QOS observed by the NS users at the two ends of the NC is the same. This is true even in the case of an NC spanning several subnetworks where each subnetwork offers different services.

10.1 Determination of QOS

QOS is described in terms of QOS-parameters. The definition of each of these QOS-parameters specifies the way in which the QOS-parameter's value is measured or determined, making reference where appropriate, to primitive events of the NS.

NOTES

1 It is important to distinguish the use of the term "QOS-parameters" from the more general term "parameters" as defined in 5.2 and used throughout this Service Definition. A "QOS-parameter" refers to a specific aspect or component of the QOS for an NC. As described below, a particular QOS-parameter may or may not be related to a parameter defined as part of a Network Service primitive.

2 For purposes of accuracy and/or convenience, the definition and measurement formula for some QOS-parameters includes a component attributable to the NS user(s). In such cases, to evaluate the QOS attributable solely to the NS provider, this NS user-dependent component must be factored out.

3 The definition of NS QOS-parameters in terms which provide a means for measurement should not be understood to imply that QOS monitoring or that verification of stated QOS value is, or must be, performed by the NS provider or by the NS users.

It is in terms of the NS QOS-parameters that information about QOS is exchanged among the NS provider and NS users.

Information about the QOS requirements of the NS users may be used by the NS provider for purposes such as protocol selection, route determination, and allocation of resources. Information about the QOS available from the NS provider may be used by NS users for purposes such as selecting QOS enhancement mechanisms and determining the QOS values provided to NS users at higher layers.

The NS QOS-parameters can be divided into two categories as follows:

- 1) those whose values are "conveyed" between peer NS users by means of the NS provider during the Establishment phase of an NC. As part of this conveyance, a three-party "negotiation" among the NS users and the NS provider for the purpose of agreeing upon a particular QOS-parameter value may take place; and
- 2) those whose values are not "conveyed" or "negotiated" among the NS users and the NS provider; for these QOS-parameters, however, information about the values which is useful to the NS provider and each NS user may be made known by local means.

The NS QOS-parameters are defined in 10.2.1 to 10.2.12 below.

The set of NS QOS-parameters that belong to the first category, and the procedures and constraints that apply to conveying and negotiating those QOS-parameters, are specified in 12.2.7. Once the NC is established, and throughout the lifetime of the NC, the agreed values for these QOS-parameters are not "renegotiated" at any point, and there is no guarantee that the originally negotiated values will be maintained. The NS user should also be aware that, once an NC is established, changes in QOS on the NC are not explicitly signaled in the NS.

For QOS-parameters in the second category, the values for a particular NC are not negotiated, nor are they directly conveyed from NS user to NS user. As a local matter, however, there may be means by which the values of one or more of these QOS-parameters are known and utilized by the NS provider and each NS user. Despite the local nature of particular NS user/NS provider interactions which may occur for the purposes of exchanging QOS-parameter information, the characteristics of an NC which the QOS-parameters describe are applicable and can be observed on a complete NC, end-to-end basis. Thus, in order to give a full characterization of the properties of NCs, the definitions of the entire set of QOS-parameters which apply to the NS, including those classified in category 2, are included in this Service Definition. Other aspects related to category 2 parameters, such as the circumstances of their availability and use, as well as other QOS issues, such as the relationship to OSI management, and multi-layer QOS relationships, are the subjects of other OSI QOS-related specifications.

NOTE 4 – For non-negotiated QOS-parameters associated with the Data Transfer phase of an NC, when specified, a value of such a QOS-parameter applies to both directions of transfer on the NC.

10.2 Definition of QOS-parameters

QOS-parameters can be classified as:

- a) QOS-parameters which express Network Service performance, as shown in Table 3.
- b) QOS-parameters that express other Network Service characteristics, as shown in Table 4.

NOTE – Some QOS-parameters are defined in terms of the issuance of Network Service primitives. Reference to a primitive in 10.2.1 through 10.2.12 refers to the complete execution of that service primitive at the appropriate NSAP.

Table 3 – Classification of performance QOS-parameters

Phase	Performance criterion	
	Speed	Accuracy/reliability
NC establishment	NC establishment delay	NC establishment failure probability (misconnection/NC refusal)
Data transfer	Throughput	Residual error rate (corruption, duplication/loss) NC resilience
	Transit delay	Transfer failure probability
NC release	NC release delay	NC release failure probability

Table 4 – QOS-parameters not associated with performance

NC protection
NC priority
Maximum acceptable cost

10.2.1 NC establishment delay

NC establishment delay is the maximum acceptable delay between an N-CONNECT request and the corresponding N-CONNECT confirm primitive.

NOTE – This delay includes a component, attributable to the called NS user, which is the time between the N-CONNECT indication primitive and the N-CONNECT response primitive.

10.2.2 NC establishment failure probability

NC establishment failure probability is the ratio of total NC establishment failures to total NC establishment attempts in a measurement sample.

NC establishment failure is defined to occur when a requested NC is not established within the specified maximum acceptable time period as a result of NS provider behaviour such as misconnection, NC refusal, or excessive delay. NC establishment attempts which fail as a result of NS user behaviour such as error, NC refusal, or excessive delay are excluded in calculating NC establishment failure probability.

10.2.3 Throughput

Throughput is defined, for each direction of transfer, in terms of a sequence of at least two successfully transferred NSDUs presented continuously to the NS provider at the maximum rate the NS provider can continuously sustain, and unconstrained by flow control applied by the receiving NS user.

Given such a sequence of n NSDUs, where n is greater than or equal to 2, the throughput is defined to be the smaller of:

- a) the number of NS-user-data octets contained in the last $n - 1$ NSDUs divided by the time between the first and last N-DATA requests in the sequence; and

- b) the number of NS-user-data octets contained in the last $n - 1$ NSDUs divided by the time between the first and last N-DATA indications in the sequence.

Successful transfer of the octets in a transmitted NSDU is defined to occur when the octets are delivered to the intended receiving NS user without error, in the proper sequence, and prior to release of the NC by the receiving NS user.

Throughput is specified separately for each direction of transfer. Each throughput specification will specify both the desired “target” value and the minimum acceptable value (i.e. the “lowest quality acceptable”) for the NC. (See also 12.2.7.)

10.2.4 Transit delay

Transit delay is the elapsed time between an N-DATA request and the corresponding N-DATA indication. Elapsed time values are calculated only on NSDUs that are successfully transferred.

Successful transfer of an NSDU is defined to occur when the NSDU is transferred from the sending NS user to the intended receiving NS user without error, in the proper sequence, and prior to release of the NC by the receiving NS user.

Specification of transit delay will define a pair of values: the desired “target” value and the maximum acceptable (i.e. the “lowest quality acceptable”) value. (See also 12.2.7.) The specified values will be averages and will be based on an NSDU size of 128 octets.

The pair of transit delay values specified for an NC applies to both directions of transfer. That is, the transit delay in each direction is expected to be no worse than that specified.

The transit delay for an individual NSDU may be increased if the receiving NS user exercises flow control. Such occurrences are excluded in calculating both average and maximum transit delay values.

10.2.5 Residual error rate

Residual error rate is the ratio of total incorrect, lost, and duplicate NSDUs to total NSDUs transferred across the NS boundary during a measurement period. The relationship among these quantities is defined, for a particular NS user pair, as shown in Figure 2.




Figure 2 – Components of residual error rate