

Implementation of ISO/IEC 8802-3 : 1993

**Information technology —
Local and metropolitan area
networks**

**Part 3. Carrier sense multiple access with
collision detection (CSMA/CD) access
method and physical layer specifications**

UDC 681.3 : 621.39

National foreword

This British Standard reproduces verbatim ISO/IEC 8802-3 : 1993 and implements it as the UK national standard.

BS ISO/IEC 8802-3 : 1993 supersedes BS ISO/IEC 8802-3 : 1992, which is withdrawn.

This British Standard is published under the direction of the Information Systems Technology Standards Policy Committee whose Technical Committee IST/6 has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international committee any enquiries on interpretation, or proposals for change, and keep UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

NOTE. International and European Standards, as well as overseas standards, are available from Customer Services, Publications, BSI, Linford Wood, Milton Keynes, MK14 6LE.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

INTERNATIONAL STANDARD

ISO/IEC
8802-3

ANSI/IEEE
Std 802.3

Fourth edition
1993-07-08

Information technology — Local and metropolitan area networks —

Part 3:

**Carrier sense multiple access with collision detection
(CSMA/CD) access method and physical layer
specifications**

Technologie de l'information — Réseaux locaux et métropolitains —

*Partie 3: Accès multiple par surveillance du signal et détection de collision et
spécifications pour la couche physique*



Reference number
ISO/IEC 8802-3:1993 (E)
ANSI/IEEE
Std 802.3-1993 Edition

AVA Documents
Document Sharing Hub

The Institute of Electrical and Electronics Engineers, Inc.
345 East 47th Street, New York, NY 10017-2394, USA

Copyright © 1993 by the
Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 1993
Printed in the United States of America

ISBN 1-55937-324-5

*No part of this publication may be reproduced in any form,
in an electronic retrieval system or other wise,
without the prior written permission of the publisher.*

July 8, 1993

SH16337

Information technology— Local and metropolitan area networks—

Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications

Sponsor

**Technical Committee on Computer Communications
of the
IEEE Computer Society**

Abstract: This Local and Metropolitan Area Network standard, ISO/IEC 8802-3 : 1993 [ANSI/IEEE Std 802.3, 1993 Edition], specifies the media access control characteristics for the Carrier Sense Multiple Access with Collision Detection (CSMA/CD) access method. It also specifies the media, Medium Attachment Unit (MAU) and physical layer repeater unit for 10 Mb/s baseband and broadband systems, and it provides a 1 Mb/s baseband implementation. Specifications for MAU types 10BASE5, 10BASE2, FOIRL (fiber optic inter-repeater link), 10BROAD36, 1BASE5, and 10BASE-T are included. System considerations for multisegment 10 Mb/s baseband networks are provided. Layer and sublayer interface specifications are aligned to the ISO Open Systems Interconnection Basic Reference Model and 8802 models. The 8802-3 internal model is defined and used.

Keywords: data processing, information interchange, local area networks, mode of data transmission, network interconnection, models



Adopted as an International Standard by the
International Organization for Standardization
and by the
International Electrotechnical Commission



Published by
The Institute of Electrical and Electronics Engineers, Inc.



International Standard ISO/IEC 8802-3 : 1993

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and nongovernmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75% of the national bodies casting a vote.

In 1985, IEEE Standard 802.3-1985 was adopted by ISO Technical Committee 97, *Information processing systems*, as draft International Standard ISO/DIS 8802-3. Following the procedures described above, the Standard was subsequently approved by ISO and published as ISO 8802-3 : 1989, incorporating ISO 8802-3/DAD 1 which had resulted from the adoption by ISO in 1987 of ANSI/IEEE Std 802.3a.

A further revision was subsequently approved by ISO/IEC JTC 1 in 1990, incorporating ISO/IEC 8802-3/Amendments 2 and 5.

A third edition, published in 1992, incorporated ISO/IEC 8802-3/Amendments 3 and 4.

This fourth edition cancels and replaces ISO/IEC 8802-3 : 1992 and incorporates ISO/IEC 8802-3/Amendment 6, *Maintenance Ballot*; Amendment 7, *Layer management*; and Amendment 9, *System considerations for multisegment 10 Mb/s baseband networks and Twisted-pair medium attachment unit (MAU) and baseband medium, type 10BASE-T*. These amendments were approved in 1992.

For the purpose of assigning organizationally unique identifiers, the Institute of Electrical and Electronics Engineers, Inc., USA, has been designated by the ISO Council as the Registration Authority. Communications on this subject should be addressed to

· Registration Authority for ISO/IEC 8802-3
c/o The Institute of Electrical and Electronics Engineers, Inc.
445 Hoes Lane
P.O. Box 1331
Piscataway, NJ 08855-1331
USA

During the preparation of this International Standard, information was gathered on patents upon which application of this standard might depend. Relevant patents were identified as belonging to Xerox Corporation. However, ISO and IEC cannot give authoritative or comprehensive information about evidence, validity or scope of patent and like rights. The patent-holder has stated that licenses will be granted under reasonable terms and conditions and communications on this subject should be addressed to


Xerox Corporation
P.O. Box 1600
Stamford, CT 06904
USA



International Organization for Standardization/International Electrotechnical Commission
Case postale 56 • CH-1211 Genève 20 • Switzerland

Foreword to International Standard ISO/IEC 8802-3 : 1993

This standard is part of a family of standards for Local and Metropolitan Area Networks. The relationship between this standard and the other members of the family is shown below. (The numbers in the figure refer to ISO standard numbers.)



This family of standards deals with the Physical and Data Link layers as defined by the ISO Open Systems Interconnection Basic Reference Model (ISO 7498 : 1984). The access standards define four types of medium access technologies and associated physical media, each appropriate for particular applications or system objectives. Other types are under investigation.

The standards defining these technologies are as follows:

- (1) ISO/IEC 8802-3 [ANSI/IEEE Std 802.3, 1993 Edition], a bus utilizing CSMA/CD as the access method,
- (2) ISO/IEC 8802-4 [ANSI/IEEE Std 802.4-1990], a bus utilizing token passing as the access method,
- (3) ISO/IEC 8802-5 [ANSI/IEEE Std 802.5-1992], a ring utilizing token passing as the access method,
- (4) ISO 8802-7, a ring utilizing slotted ring as the access method.

ISO 8802-2 [ANSI/IEEE Std 802.2-1989], *Logical Link Control protocol*, is used in conjunction with the medium access standards.

ISO/IEC 10038 [ANSI/IEEE Std 802.1D, 1993 Edition], *Media access control (MAC) bridges*, specifies an architecture and protocol for the interconnection of IEEE 802 LANs below the MAC service boundary.

The reader of this document is urged to become familiar with the complete family of standards.

The main body of this standard serves for both the ISO/IEC 8802-3 and ANSI/IEEE Std 802.3 standards. ISO/IEC and IEEE each have unique foreword sections. The Annex applies to the IEEE standard only. The Appendixes serve as useful reference material to both standards.

ANSI/IEEE Std 802.3, 1993 Edition

IEEE Standards documents are developed within the Technical Committees of the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Board. Members of the committees serve voluntarily and without compensation. They are not necessarily members of the Institute. The standards developed within IEEE represent a consensus of the broad expertise on the subject within the Institute as well as those activities outside of IEEE which have expressed an interest in participating in the development of the standard.

Use of an IEEE Standard is wholly voluntary. The existence of an IEEE Standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE Standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard. Every IEEE Standard is subjected to review at least once every five years for revision or reaffirmation. When a document is more than five years old, and has not been reaffirmed, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE Standard.

Comments for revision of IEEE Standards are welcome from any interested party, regardless of membership affiliation with IEEE. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments.

Interpretations: Occasionally questions may arise regarding the meaning of portions of standards as they relate to specific applications. When the need for interpretations is brought to the attention of IEEE, the Institute will initiate action to prepare appropriate responses. Since IEEE Standards represent a consensus of all concerned interests, it is important to ensure that any interpretation has also received the concurrence of a balance of interests. For this reason IEEE and the members of its technical committees are not able to provide an instant response to interpretation requests except in those cases where the matter has previously received formal consideration.

Comments on standards and requests for interpretations should be addressed to:


Secretary, IEEE Standards Board
345 East 47th Street
New York, NY 10017
USA

IEEE Standards documents are adopted by the Institute of Electrical and Electronics Engineers without regard to whether their adoption may involve patents on articles, materials, or processes. Such adoptions does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the standards documents.

Foreword to ANSI/IEEE Std 802.3, 1993 Edition

(This Foreword is not a part of this International Standard or of ANSI/IEEE 802.3, 1993 Edition.)

This standard is part of a family of standards for local and metropolitan area networks. The relationship between the standard and other members of the family is shown below. (The numbers in the figure refer to IEEE standard numbers.)



This family of standards deals with the Physical and Data Link layers as defined by the International Organization for Standardization (ISO) Open Systems Interconnection Basic Reference Model (ISO 7498 : 1984). The access standards define several types of medium access technologies and associated physical media, each appropriate for particular applications or system objectives. Other types are under investigation.

The standards defining these technologies are as follows:

- IEEE Std 802[†]: Overview and Architecture. This standard provides an overview to the family of IEEE 802 standards. This document forms part of the 802.1 scope of work.
- IEEE Std 802.1B: LAN/MAN Management. Defines an Open System Interconnection (OSI) management-compatible architecture, and services and protocol elements for use in a LAN/MAN environment for performing remote management.
- ISO/IEC 10038 : 1993 [ANSI/IEEE Std 802.1D] MAC Bridging. Specifies an architecture and protocol for the interconnection of IEEE 802 LANs below the MAC service boundary.
- IEEE Std 802.1E: System Load Protocol. Specifies a set of services and protocol for those aspects of management concerned with the loading of systems on IEEE 802 LANs.
- ISO 8802-2 [ANSI/IEEE Std 802.2]: Logical Link Control
- ISO/IEC 8802-3 [ANSI/IEEE Std 802.3]: CSMA/CD Access Method and Physical Layer Specifications

[†]The 802 Architecture and Overview Specification, originally known as IEEE Std 802.1A, has been renumbered as IEEE Std 802. This has been done to accommodate recognition of the base standard in a family of standards. References to IEEE Std 802.1A should be considered as references to IEEE Std 802.

- ISO/IEC 8802-4 [ANSI/IEEE Std 802.4]: Token Bus Access Method and Physical Layer Specifications
- ISO/IEC 8802-5 [ANSI/IEEE Std 802.5]: Token Ring Access Method and Physical Layer Specifications
- IEEE Std 802.6: Metropolitan Area Network Access Method and Physical Layer Specifications
- IEEE Std 802.10: Interoperable Local Area Network Security, *Currently Contains Secure Data Exchange (SDE)*

In addition to the family of standards the following is a recommended practice for a common technology:

- IEEE Std 802.7: IEEE Recommended Practice for Broadband Local Area Networks

The reader of this document is urged to become familiar with the complete family of standards.

Conformance Test Methodology

Another standards series, identified by the number 1802, has been established to identify the conformance test methodology documents for the 802 family of standards. This makes the correspondence between the various 802 standards and their applicable conformance test requirements readily apparent. Thus the conformance test documents for 802.3 are numbered 1802.3, the conformance test documents for 802.5 will be 1802.5, and so on. Similarly, ISO will use 18802 to number conformance test standards for 8802 standards.

ISO/IEC 8802-3 : 1993 (ANSI/IEEE Std 802.3, 1993 Edition)

This edition of the standard defines 10 Mb/s baseband and broadband implementations and a 1 Mb/s baseband implementation of the Physical Layer using the CSMA/CD access method. It is anticipated that future editions of the standard may provide additional implementations of the physical layer to support different needs (for example, media, and data rates).

This standard contains state-of-the-art material. The area covered by this standard is undergoing evolution. Revisions are anticipated to this standard within the next few years to clarify existing material, to correct possible errors, and to incorporate new related material.

Readers wishing to know the state of revisions should contact

Secretary
IEEE Standards Board
Institute of Electrical and Electronics Engineers, Inc
PO Box 1331, 445 Hoes Lane
Piscataway, NJ 08855-1331
USA

The IEEE 802.3 Working Group acknowledges and appreciates that many concepts embodied in this standard are based largely upon the CSMA/CD access method earlier described in *The Ethernet* specification as written jointly by individuals from Xerox Corporation, Digital Equipment Corporation, and Intel Corporation. Appreciation is also expressed to Robert M. Metcalfe and David R. Boggs for their pioneering work in establishing the original concepts.

Participants

When the IEEE 802.3 Working Group approved the original standard (ANSI/IEEE Std 802.3-1985) in 1983, it had the following membership:

Donald C. Loughry, Chair

Phil L. Arst
Robert F. Bridge
Charles Brill
G. J. Clancy
John Davidson
Ralph DeMent
Hank (H. N.) Dorris
Judith Estrin
Richard Fabbri
Ingrid Fromm
Milton C. Harper
Bryan Hoover
George D. Jelatis
Harold W. Katz

Donald E. Kotas
William P. Lidinsky
Laurie Lindsey
William D. Livingston
Andy Luque
Daniel Maltbie
Jerry McDowell
C. Kenneth Miller
Robert L. Morrell
Wendell Nakamine
W. P. Neblett
James Nelson
Thomas L. Phinney
David Potter

Robert S. Printis
Gary S. Robinson
Robert Rosenthal
Gary Stephens
Daniel P. Stokesberry
Ken. F. Sumner
Daniel Sze
Victor J. Tarassov
P. E. Wainwright
Lyle Weiman
Hugh E. White
Choa-Ping Wu
Nick Zades
Mo R. Zonoun

Additional individuals who contributed actively in the development of the original standard (ANSI/IEEE Std 802.3-1985) throughout its elaboration were

Juan Bulnes
Ron Crane
Dane Elliot
Alan Flatman
Maris Graube
Guy Harkins

Dean Lindsay
Then. T. Liu
Robert Moles
Tony Lauck
Joseph St. Amand
Richard Seifert
Nathan Tobol

Mark Townsend
Roger Van Brunt
Bo Vicklund
Chris Wargo
Richard Williams
Ron Yara

The ECMA TC24 Committee on Communication Protocols also provided helpful input in the development of this standard.

When the IEEE 802.3 Working Group approved ANSI/IEEE Std 802.3a-1988 (Section 10) in November 1984, it had the following membership:

Donald C. Loughry, Chair

Alan Flatman, Chair, Type 10BASE2 Task Force

Menachem Abraham
R. V. Balakrishnan
William Belknap
Charles Brill
Juan Bulnes
Stephen Cooper
Ronald Crane
John Davidson
Mark Devon
Phil Edholm
Gregory Ennis
Judy Estrin
Richard Fransen
Ingrid Fromm
Robert Galin
Rich Graham

Guy Harkins
Greg Hopkins
Joe Kennedy
Hiroshi Kobayashi
Tony Lauck
William Livingston
Hugh Logan
Leland Long
Andy Luque
Daniel Maltbie
Steven Moustakas
Wendell Nakamine
Lloyd Oliver
Aidan Paul
David Potter
Eugene Reilly

Joseph Rickert
Gary Robinson
Robert Rosenthal
Joseph St. Amand
Walter Schreuer
Stephen Soto
Gary Spencer
Robert Summers
Pat Thaler
Geoff Thompson
Wendell Turner
David White
Lawrence White
Rich Williams
Ronald Yara
Mo Zonoun

The following persons were on the balloting committee that approved ANSI/IEEE Std 802.3-1985 for submission to the IEEE Standards Board:

W. Adams
R. Appleby
G. Arnold
Y. Baeg
E. Beauregard
J. Becker
E. Bergaimini
Boorstyn
A. Carrato
G. Carson
S. Chakradarti
S. Chandra
F. Chang
C. Chao
C. Chen
P. Chen
K. Chon
R. Chow
G. Clinque
I. Cotton
D. Cox
R. DeJardins
D. Dickel
C. Eldridge
P. Enslow
J. Fendirch
M. Figuerea
D. Fisher
J. Fletcher
W. Franta
R. Gagliano
D. Gan
M. Graube
M. Greene
R. Gustin
K. Harbaugh
G. Harkins

R. Harrington
H. Heilborn
L. Heselton
D. Hislop
C. Hobbs
S. Hollander
P. Hutton
P. Induiago
T. Ishida
J. Jelemenshy
O. Kahn
S. Kak
K. Katzeff
C. Kessler
D. Kirschen
R. Kolm
T. Kuki
R. Kunkel
W. Lai
V. Lasker
N. Lau
R. Laughlin
F. Lim
T. Liu
J. Loo
K. Loughner
D. Loughry
T. Louhenkillbi
D. Manchester
M. Marco
D. Matters
D. McInode
D. Michels
L. Moraes
D. Morriss
J. Murayama
R. Nelson
D. Ofsevit

C. Ostereicher
M. Papa
S. Peter
D. Phuoc
T. Phinney
G. Power
A. Reddi
M. Repko
F. Restivo
L. Rich
D. Rine
R. Rosenthal
P. Ruosadri
S. Samoylenko
B. Sashi
A. Sauer
N. Schneidewind
O. Serlin
D. Shepard
D. Sloyer
H. Solomon
G. Stephens
C. Stillebroer
K. Sumner
E. Sykas
A. Tantawi
D. Tether
J. Tourret
K. Tu
D. Umbaugh
J. Vorhies
A. Weissberger
W. Wenker
T. Wicklund
T. Wolf
F. Wolff
R. Youg

The following persons were on the balloting committee that approved ANSI/IEEE Std 802.3a-1988 (Section 10) for submission to the IEEE Standards Board:

Marshall Abrams
John Adams
William B. Adams
S. R. Ahuja
Kit Athul
William Ayen
Yong-Myung Baeg
Wesley A. Ballenger, Jr.
Edwardo W. Bergamini
Henk F. Boley
Betty Brannick
George S. Carson
Po Chen
L. Y. Cheung
Kilnam Chon
T. Ricky Chow
David Cohen
Allen F. Conrad
Ira W. Cotton
Robert S. Crowder
Michel Diaz
Mitchell G. Duncan
Philip H. Enslow, Jr.
Judith Estrin
John W. Fendrich
Harvey A. Freeman
Patrick Gonia
Ambuj Goyal
Michael D. Graebner
Maris Graube
Nobuhiro Hamada
Joseph L. Hammond

Keith W. Harbaugh
S. M. Harris
J. Scott Haugdahl
Sharon Healy
C. W. Hobbs
Jim P. Hong
Paul L. Hutton
Richard Liff
George D. Jelatis
Guy Juanole
Siegel L. Junker
Karl H. Kellermayr
Mladen Kezunovic
Samuel Kho
David Kollm
Sastri L. Kota
Hirayr M. Kudyan
Takahiko Kuki
Lee LaBarre
Wai-Sum Lai
Valerie Lasker
Lanse M. Leach
Edward Y. S. Lee
Stephen E. Levin
F. C. Lim
Don C. Loughry
Joseph F. P. Luhukay
Wo-Shun Luk
Marco Marsan
Joseph Massi
Darrell B. McIndoe
Patrick S. McIntosh

Marco Meli
David S. Millman
Aditya N. Mishra
Richard J. Moff
David E. Morgan
Mike Morganti
Kinji Mori
D. J. Morris
H. T. Mouftah
Dale A. Murray
Ruth Nelson
J. Duane Northcutt
Charles Ostereicher
David Ofsevit
Young Oh
George Parowski
Thomas L. Phinney
Nikitas Pimopoulos
David Potter
John Potvcek
Gary S. Robinson
Marya Repko
Robert Rosenthal
Gian Paolo Rossi
David J. Rypka
S. I. Samoylenko
Norman F. Schneidewind
Oscar Sepulveda
Omri Serlin
D. Sheppard
R. M. Simmons
David W. Sloyer

When the IEEE Standards Board approved ANSI/IEEE Std 802.3-1988 on June 9, 1988, and ANSI/IEEE Std 802.3a-1988 (Section 10) on October 20, 1988, it had the following membership:

Donald C. Fleckenstein, Chair

Andrew G. Salem, Secretary

Marco Migliaro, Vice Chair

Arthur A. Blaisdell
Fletcher J. Buckley
James M. Daly
Stephen R. Dillon
Eugene P. Fogarty
Jay Forster*
Thomas L. Hannan
Kenneth D. Hendrix
Theodore W. Hissey, Jr.

John W. Horch
Jack M. Kinn
Frank D. Kirschner
Frank C. Kitzantides
Joseph L. Koepfinger*
Irving Kolodny
Edward Lohse
John E. May, Jr.
Lawrence V. McCall

L. Bruce McClung
Donald T. Michael*
Richard E. Mosher
L. John Rankine
Gary S. Robinson
Frank L. Rose
Helen M. Wood
Karl H. Zaininger
Donald W. Zipse

*Member emeritus

ANSI/IEEE Std 802.3-1988 and ANSI/IEEE Std 802.3a-1988 were approved by the American National Standards Institute on January 12, 1989.

When the IEEE 802.3 Working Group approved ANSI/IEEE Std 802.3c-1985 (9.1–9.8) in July 1985, it had the following membership:

Donald C. Loughry, *Chair*
Geoffrey O. Thompson, *Chair, Repeater Task Force*

Menachem Abraham
Keith Albright
R. V. Balakrishnan
William Belknap
Richard Bennett
Charles Brill
Juan Bulnes
Stephen Cooper
Paul Eastman
Phil Edholm
Gregory Ennis
Alan Flatman
Richard Franses
Ingrid Fromm
Robert Galin
Sharad Gandhi
Rich Graham
Richard Gumpertz

Hacene Hariti
Guy Harkins
Fred Huang
Stephen Janshego
Donald Johnson
Kwi-Yung Jung
Paul Kellam
Joe Kennedy
Hiroshi Kobayashi
Lee LaBarre
Tony Lauck
John Laynor
William Livingston
Terry Lockyer
James Lucas
Andy Luque
Daniel Maltbie
Steven Moustakas
Lloyd Oliver

Aidan Paul
David Potter
Eric Rawson
Joseph Rickert
Gary Robinson
Timothy Rock
David Roos
Robert Rosenthal
Joseph St. Amand
Walter Schreuer
Semir Sirazi
David Smith
Stephen Soto
Robert Summers
Pat Thaler
Wendell Turner
Marc Warshaw
Ronald Yara

The following persons were on the balloting committee that approved ANSI/IEEE Std 802.3c-1985 (9.1–9.8) for submission to the IEEE Standards Board:

Marshall Abrams
John Adams
William B. Adams
S. R. Ahuja
P. D. Amer
Kit Athul
William Ayen
Yong-Myung Baeg
Wesley A. Ballenger, Jr.
Edwardo W. Bergamini
H. F. Boley
Paul W. Campbell, Jr.
George S. Carson
Po Chen
L. Y. Cheung
Kilnam Chon
T. Ricky Chow
W. F. Chow
David Cohen
Allen F. Conrad
Robert S. Crowder
Michel Diaz
Philip H. Enslow, Jr.
Judith Estrin
John W. Fendrich
Harvey A. Freeman
R. J. Gagliano
Patrick Gonja
Ambuj Goyal
Michael D. Graebner
Maris Graube
Nobushiro Hamada
Joseph L. Hammond
S. M. Harris
J. Scott Haugdahl
C. W. Hobbs
Jim P. Hong
Paul L. Hutton

Richard Iliff
George D. Jelatis
E.D. Jensen
Guy Juanole
Karl H. Kellermayr
Mladen Kozunovic
Samuel Kho
David Kollm
Sastri L. Kota
Hirayr M. Kudyan
Takahiko Kuki
Lee LaBarre
Wai-Sum Lai
Lanse M. Leach
Stephen E. Levin
F. C. Lim
William Livingston
Don C. Loughry
Joseph F. P. Luhukay
Meli Marco
Marco Marsan
Joseph Massi
Darrell B. McIndoe
Patrick S. McIntosh
David S. Millman
Aditya N. Mishra
David E. Morgan
Mike Morganti
Kinji Mori
D. J. Morris
H. T. Mouftah
Dale A. Murray
Ruth Nelson
J. Duane Northcutt
Charles Oestereicher
Young Oh
George Parowski
Thomas L. Phinney
David Potter

John Potvcek
Gary S. Robinson
Marya Repko
Robert Rosenthal
Gian Paolo Rossi
David J. Rypka
S. I. Samoylenko
Norman F. Schneidewind
Oscar Sepulveda
Omri Serlin
D. Sheppard
R. M. Simmons
L. Sintonen
David W. Sloyer
Stephen Soto
Fred Strauss
Bart W. Stuck
Tatsuya Suda
Efstathios D. Sykas
Daniel T. W. Sze
Ahmed N. Tantau
Mario Tokoro
H. C. Torng
Donald F. Towsley
Wei-Tek Tsai
M. Tsuchiya
Richard Tung
Stanko Turk
L. David Umbaugh
James Vorhies
Pearl S. C. Wang
Don Weir
Alan J. Weissberger
William J. Wenker
Earl J. Whitaker
Michael Willett
Tsong-Ho Wu
Oren Yuen

When the IEEE Standards Board approved ANSI/IEEE Std 802.3c-1985 (9.1–9.8) on December 12, 1985, it had the following membership:

John E. May, *Chair*

Sava I. Sherr, *Secretary*

John P. Riganati, *Vice Chair*

James H. Beall
Fletcher J. Buckley
Rene Castenschiold
Edward Chelotti
Edward J. Cohen
Paul G. Cummings
Donald C. Fleckenstein

Jay Forster
Daniel L. Goldberg
Kenneth D. Hendrix
Irvin N. Howell
Jack Kinn
Joseph L. Koepfinger*
Irving Kolodny
R. F. Lawrence

Lawrence V. McCall
Donald T. Michael*
Frank L. Rose
Clifford O. Swanson
J. Richard Weger
W. B. Wilkens
Charles J. Wylie

*Member emeritus

ANSI/IEEE Std 802.3c-1985 was approved by the American National Standards Institute on June 4, 1986.

When the IEEE 802.3 Working Group approved ANSI/IEEE Std 802.3d-1987 (9.9), it had the following membership:

Donald C. Loughry, *Chair*
Steven Moustakas, *Chair, Task Force*

Menachem Abraham
Keith Albright
Keith Amundsen
Jean-Pierre Astorg
R. V. Balakrishnan
Richard Bennett
Charles Brill
Juan Bulnes
Robert Campbell
Luigi Canavese
Albert Claessen
Peter Dawe
Peter Desaulniers
Raymond Duley
Jeff Ebeling
Gianfranco Enrico
Alan Flatman
Richard Fransen
Ingrid Fromm
Robert Galin
Mark Gerhold
Adi Golbert
Rich Graham
Rich Gumpertz
Hacene Hariti

Lloyd Hasley
Hawming Haung
Charles Hoffner
Michael Hughes
Donald Johnson
Mze Johnson
Kwi-Yung Jung
Matt Kaltenbach
Paul Kellam
Scott Kesler
Hiroshi Kobayashi
Hidetune Kurokawa
Lee LaBarre
Ed Lare
Wayne Lindquist
Terry Lockyer
Don Loughry
James Lucas
Andy Luque
Lloyd Oliver
Aidan Paul
Roy Pierce
Eric Rawson
Joseph Rickert
Gary Robinson

Timothy Rock
David Roos
Walter Schruer
Semir Sirazi
David Smith
Robert Summers
Pat Thaler
Geoff Thompson
Nathan Tobol
Carlos Tomaszewski
Wendell Turner
Joseph Wiencko
Bruce Williams

OBSERVERS

Allen Cherin
John Decramer
Paul Eastman
Shinji Emori
Jiro Kashio
Michael Lee
Luciano Marchitto
Jim Montrose
Peter Tarrant

The IEC TC83 Committee on Information Technology Equipment also provided very helpful input to the development of the FOIRL Standard (9.9).

The following persons were on the balloting committee that approved ANSI/IEEE Std 802.3d-1987 (9.9) for submission to the IEEE Standards Board:

William B. Adams	M. Kezunovic	Gary S. Robinson
S. R. Ahuja	Samuel Kno	Robert Rosenthal
Kit Athul	S. E. Kille	Gian Paolo Rossi
William Ayen	David Kollm	David J. Rypka
Eduardo W. Bergamini	Takahiko Kuki	S. I. Samaylenko
Paul W. Campbell, Jr.	Lee LaBarre	Norman F. Schneidewind
George S. Carson	Wai-Sum Lai	Omri Serlin
Po Chen	Lanse M. Leach	D. Sheppard
L. Y. Cheung	Edward Y. Lee	Ron Simmons
Kilnam Chon	R. C. Lightburn	J. B. Sinclair
W. F. Chow	F. C. Lim	L. Sintonen
Michael Coden	William D. Livingston	Tom Stack
A. F. Conrad	Don C. Loughry	Carel M. Stillebroer
Robert S. Crowder	Joseph F. P. Luhukay	Fred Strauss
Michel Diaz	Wo-Shun Luk	Tatsuya Suda
N. I. Dimopoulos	Marco Ajmone Marsan	P. Sugar
M. G. Duncan	Joseph Massi	Efstathios D. Sykas
Philip H. Enslow, Jr.	Marco Meli	Daniel T. W. Sze
Judith Estrin	Darrel B. McIndoe	Ahmed N. Tantawi
John W. Fendrich	P. S. McIntosh	H. C. Torng
Harvey A. Freeman	David S. Millman	D. F. Towsley
Patrick S. Gonia	Aditya N. Mishra	Wei-Tek Tsai
R. L. Gordon	David E. Morgan	Stanko Turk
A. Goyal	Mike Morganti	L. David Umbaugh
M. D. Graebner	Kanji Mori	J. T. Vorhies
Maris Graube	David Morris	Pearl S. C. Wang
Joseph L. Hammond	H. H. T. Mouftah	Don Weir
Stephen Harris	Dale N. Murray	Alan J. Weissburger
J. Scott Haugdahl	R. R. Nelson	W. J. Wenker
C. W. Hobbs	J. D. Northcut	Earl J. Whitaker
Paul Hutton	Charles Oestereicher	Bryan Whittle
Richard Illif	Young Oh	Michael Willett
E. D. Jenson	George Parowski	David C. Wood
Guy Juanole	Thomas L. Phinney	Tsong-Hu Wu
Karl H. Kellermayr	J. M. Potucek	Oren Yuen
	Marya Repko	

When the IEEE Standards Board approved ANSI/IEEE Std 802.3d-1987 (9.9) on December 12, 1985, it had the following membership:

Donald C. Fleckenstein, Chair

Andrew G. Salem, Secretary

Marco Migliaro, Vice Chair

James H. Beall	Leslie R. Kerr	Donald T. Michael*
Dennis Bodson	Jack Kinn	L. John Rankine
Marshall L. Cain	Irving Kolodny	John P. Riganati
James M. Daly	Joseph L. Koepfinger*	Gary S. Robinson
Stephen R. Dillon	Edward Lohse	Frank L. Rose
Eugene P. Fogarty	John May	Robert E. Rountree
Jay Forster	Lawrence V. McCall	William R. Tackaberry
Kenneth D. Hendrix	L. Bruce McClung	William B. Wilkens
Irvin N. Howell		Helen M. Wood

*Member emeritus

ANSI/IEEE Std 802.3d-1987 was approved by the American National Standards Institute on February 9, 1989.

When the IEEE 802.3 Working Group approved ANSI/IEEE Std 802.3b-1985 (Section 11), it had the following membership:

Donald C. Loughry, Chair
Menachem Abraham, Chair, Type 10BROAD36 Task Force

Keith Albright
R. V. Balakrishnan
William Belknap
Richard Bennett
Charles Brill
Juan Bulnes
Stephen Cooper
Ronald Crane
John Davidson
Mark Devon
Paul Eastman
Phil Edholm
Gregory Ennis
Judy Estrin
Alan Flatman
Richard Fransen
Ingrid Fromm
Robert Galin
Sharad Gandhi
Rich Graham
Richard Gumpertz
Hacene Hariti
Guy Harkins
Gregory Hopkins

Fred Huang
Stephen Janshego
Donald Johnson
Kwi-Yung Jung
Paul Kellam
Joe Kennedy
Hiroshi Kobayashi
Lee LaBarre
Ed Lare
Tony Lauck
John Laynor
William Livingston
Terry Lockyer
Hugh Logan
Leland Long
James Lucas
Andy Luque
Daniel Maltbie
Joseph Mazor
Steven Moustakas
Narayan Murthy
Wendell Nakamine
Lloyd Oliver

Aidan Paul
David Potter
Eric Rawson
Eugene Reilly
Joseph Rickert
Anthony Rizzolo
Gary Robinson
Timothy Rock
David Roos
Robert Rosenthal
Joseph St. Amand
Walter Schreuer
Semir Sirazi
David Smith
Stephen Soto
Gary Spencer
Robert Summers
Pat Thaler
Geoff Thompson
Nathan Tobol
Wendell Turner
Marc Warshaw
David White
Mo Zonoun

The following persons were on the balloting committee that approved ANSI/IEEE Std 802.3b-1985 (Section 11) for submission to the IEEE Standards Board:

Marshall Abrams
John Adams
William B. Adams
S. R. Ahuja
Kit Athul
William Ayen
Yong-Myung Baeg
Wesley A. Ballenger, Jr.
Edwardo W. Bergamini
Henk F. Boley
George S. Carson
Po Chen
L. Y. Cheung
Kilnam Chon
T. Ricky Chow
David Cohen
Allen F. Conrad
Ira W. Cotton
Robert S. Crowder
Michel Diaz
Mitchell G. Duncan
Philip H. Enslow, Jr.
Judith Estrin
John W. Fendrich
Harvey A. Freeman
Patrick Gonia
Ambuj Goyal
Michael D. Graebner
Maris Graube
Nobuhiro Hamada
Joseph L. Hammond
Keith W. Harbaugh
S. M. Harris
J. Scott Haugdahl
Sharon Healy
C. W. Hobbs
Jim P. Hong
Paul L. Hutton
Richard Iliff
George D. Jelatis

E. Douglas Jensen
Guy Juanole
Siegel L. Junker
Karl H. Kellermayr
Mladen Kezunovic
Samuel Kho
David Kollm
Sastri L. Kota
Hirayr M. Kudyan
Takahiko Kuki
Lee LaBarre
Wai-Sum Lai
Valerie Lasker
Lanse M. Leach
Edward Y. S. Lee
Stephen E. Levin
F. C. Lim
Donald C. Loughry
Joseph F. P. Luhukay
Wo-Shun Luk
Marco Marsan
Joseph Massi
Darrell B. McIndoe
Patrick S. McIntosh
Marco Meli
David S. Millman
Aditya N. Mishra
Richard J. Moff
David E. Morgan
Mike Morganti
Kinji Mori
D. J. Morris
H. T. Mouftah
Dale A. Murray
Ruth Nelson
J. Duane Northcutt
Charles Oestereicher
David Ofsevit
Young Oh

George Parowski
Thomas L. Phinney
Nikitas Pimopoulos
David Potter
John Potvcek
Gary S. Robinson
Marya Repko
Robert Rosenthal
Gian Paolo Rossi
David J. Rypka
S. I. Samoylenko
Norman F. Schneidewind
Oscar Sepulveda
Omri Serlin
D. Sheppard
R. M. Simmons
David W. Sloyer
Stephen Soto
Tom Stack
Carel M. Stillebroer
Fred Strauss
Bart W. Stuck
Tatsuya Suda
Peter Sugar
Efsthios D. Sykas
Daniel T. W. Sze
Ahmed N. Tantaui
Mario Tokoro
H. C. Torng
Donald F. Towsley
Wei-Tek Tsai
M. Tsuchiya
Richard Tung
Stanko Turk
L. David Umbaugh
James Vorhies
Pearl S. C. Wang
Don Weir
Alan J. Weissberger
William J. Wenker

Earl J. Whitaker
Bryan S. Whittle

Michael Willett
Donald Wittman

George R. Wood
Tsong-Ho Wu

When the IEEE Standards Board approved ANSI/IEEE Std 802.3b-1985 (Section 11) on September 19, 1985, it had the following membership:

John E. May, *Chair*

Sava I. Sherr, *Secretary*

John P. Riganati, *Vice Chair*

James H. Beall
Fletcher J. Buckley
Rene Castenschiold
Edward Chelotti
Edward J. Cohen
Paul G. Cummings
Donald C. Fleckenstein

Jay Forster
Daniel L. Goldberg
Kenneth D. Hendrix
Irvin N. Howell
Jack Kinn
Joseph L. Koepfinger*
Irving Kolodny
R. F. Lawrence

Lawrence V. McCall
Donald T. Michael*
Frank L. Rose
Clifford O. Swanson
J. Richard Weger
W. B. Wilkens
Charles J. Wylie

*Member emeritus

ANSI/IEEE Std 802.3b-1985 was approved by the American National Standards Institute on February 28, 1986.

When the IEEE 802.3 Working Group approved ANSI/IEEE Std 802.3e-1987 (Section 12) in November 1986, it had the following membership:

Donald C. Loughry, *Chair*
Robert Galin, *Chair, Type 1BASE5 Task Force*

Menachem Abraham
Keith Albright
Keith Amundsen
Jean-Pierre Astorg
R. V. Balakrishnan
Ian Barker
Charles Brill
Juan Bulnes
Robert Campbell
Luigi Canavese
Albert Claessen
Michael Coden
Bill Cronin
Peter Dawe
Peter Desaulniers
Raymond Duley
Jeff Ebeling
Gianfranco Enrico
Alan Flatman
Richard Fransen
Mark Gerhold
Adi Golbert

Rich Graham
Richard Gumpertz
Hacene Hariti
Lloyd Hasley
Haw Ming Haung
Charles Hoffner
Michael Hughes
Donald Johnson
Mize Johnson
Kwi-Yung Jung
Matt Kaltenbach
Paul Kellam
Scott Kesler
Hiroshi Kobayashi
Hidetsune Kurokawa
Michael Lee
Lee LaBarre
Terry Lockyer
James Lucas
Andy Luque
Luciano Marchitto
Steven Moustakas

Lloyd Oliver
Roy Pierce
Bill Poston
Eric Rawson
Joseph Rickert
Gary Robinson
Timothy Rock
David Roos
Ed Sakaguchi
Walter Schreuer
Semir Sirazi
David Smith
Robert Summers
Peter Tarrant
Mark Taylor
Pat Thaler
Geoff Thompson
Nathan Tobol
Carlos Tomaszewski
Jayshree Ullal
Joseph Wiencko
Bruce Williams

The following persons were on the balloting committee that approved ANSI/IEEE Std 802.3e-1987 (Section 12) for submission to the IEEE Standards Board:

Marshall D. Abrams
William B. Adams
S. R. Ahuja
P. D. Amer
Kit Athul
William Ayen
Eduardo W. Bergamini
H. F. Boley
Paul W. Campbell, Jr.
George S. Carson
Po Chen
L. Y. Cheung
Kilnam Chon
W. F. Chow
Michael Coden
A. F. Conrad
Ira Cotton
D. E. Crotty
Robert S. Crowder
Michel Diaz
N. I. Dimopoulos
M. G. Duncan
P. M. Elliot
Philip H. Enslow, Jr.
Judith Estrin
John W. Fendrich
G. A. Foggiano
Harvey A. Freeman
Robert J. Gagliano
T. F. Gannon III
Patrick S. Gonias
R. L. Gordon
A. Goyal
M. D. Graebner
Maris Graube
Joseph L. Hammond
Stephen Harris
J. Scott Haugdahl
C. W. Hobbs
Paul Hutton

Richard Iliff
E. D. Jenson
Guy Juanole
S. L. Junker
Karl H. Kellermayr
M. Kezunovic
Samuel Kho
S. E. Kille
David Kollm
Takahiko Kuki
Lee LaBarre
Wai-Sum Lai
Lansea M. Leach
Edward Y. Lee
S. E. Levin
R. C. Lightburn
F. C. Lim
William D. Livingston
Don C. Loughry
Joseph F. P. Luhukay
Wo-Shun Luk
Marco Ajmone Marsan
Joseph Massi
Marco Meli
Darrel B. McIndoe
P. S. McIntosh
David S. Millman
Aditya N. Mishra
David E. Morgan
Mike Morganti
Kanji Mori
David Morris
H. H. T. Mouftah
Dale N. Murray
R. R. Nelson
J. D. Northcut
Charles Oestereicher
Young Oh
George Parowski
Thomas L. Phinney
David Potter

J. M. Potucek
Marya Repko
Gary S. Robinson
Robert Rosenthal
Gian Paolo Rossi
David J. Rypka
S. I. Samaylenko
Norman F. Schneidewind
Omri Serlin
D. Sheppard
Ron Simmons
J. B. Sinclair
L. Sintonen
Stephen H. Soto
Tom Stack
Carel M. Stillebroer
Fred Strauss
Bart W. Stuck
Tatsuya Suda
P. Sugar
Efsthathios D. Sykas
Daniel T. W. Sze
Ahmed N. Tantawi
H. C. Torng
D. F. Towsley
Wei-Tek Tsai
Masahiro Tsuchiya
Stanko Turk
L. David Umbaugh
J. T. Vorhies
Pearl S. C. Wang
Don Weir
Alan J. Weissburger
W. J. Wenker
Earl J. Whitaker
Bryan Whittle
Michael Willett
David C. Wood
Tsong-Hu Wu
Oren Yuen

When the IEEE Standards Board approved ANSI/IEEE Std 802.3e-1987 (Section 12) on June 11, 1987, it had the following membership:

Donald C. Fleckenstein, *Chair*

Marco W. Migliaro, *Vice Chair*

Andrew G. Salem, *Secretary*

James H. Beall
Dennis Bodson
Marshall L. Cain
James M. Daly
Stephen R. Dillon
Eugene P. Fogarty
Jay Forster
Kenneth D. Hendrix
Irvin N. Howell

Leslie R. Kerr
Jack Kinn
Irving Kolodny
Joseph L. Koepfinger*
Edward Lohse
John May
Lawrence V. McCall
L. Bruce McClung
Donald T. Michael*

L. John Rankine
John P. Riganati
Gary S. Robinson
Frank L. Rose
Robert E. Rountree
Sava I. Sherr*
William R. Tackaberry
William B. Wilkens
Helen M. Wood

*Member emeritus

ANSI/IEEE Std 802.3e-1987 was approved by the American National Standards Institute on December 15, 1987.

When the IEEE 802.3 Working Group approved ANSI/IEEE Std 802.3h-1990 (Section 5), it had the following membership:

Donald C. Loughry, Chair
Andy J. Luque, Chair, Layer Management Task Force

Menachem Abraham
John R. Agee
Richard Anderson
Ekkehard Antz
Keith Amundsen
Susie Armstrong
R. V. Balakrishnan
Mark Bohrer
Richard Brand
Thomas Butler
Luca Cafiero
Robert R. Campbell
Luigi Canavese
Jacques Christ
Michael Coden
Robert Conte
Bill Cronin
Peter Cross
John DeCramer
Ian Crayford
Nabil Damouny
Sanjay Dhawan
Raymond S. Duley
Paul Eastman
Richard Ely
Gianfranco Enrico
Norman Erbacher
Steve Evitts
Alan V. Flatman
Ingrid Fromm
Mel Gable
Bob Galin
Mark Gerhold
Rich Graham
Andreas Gulle
Richard Gumpertz
Clive Hallatt
Kevin Hamilton
Benny Hanigal
Lloyd Hasley

W. B. Hatfield
Stephen Haughey
Carl G. Hayssen
Ariel Hendel
Chip Hicks
William Hingston
Charles Hoffner
Ernie Jensen
Clarence Joh
Dieter W. Junkers
Donald C. Johnson
Mize Johnson
Scott Kesler
Bob Kilgore
Yongbum Kim
Bill Kind
John Kincaid
Tadayoshi Kitayama
Paul Kopera
David Kung
Michael Lee
Richard Lena
Yoseph Linde
Wayne Lindquist
T. D. Lockyer
James A. Lucas
Ian Lyon
Kenneth MacLeod
Luciano Marchitto
Charles Marsh
Bob Matthys
Steven Moustakas
Narayan Murthy
Darcy Nelson
Bob Norton
Mike O'Connor
Chris Oliver
Lloyd Oliver
Kazuyuki Ozawa

Keith Onodera
Tony Peatfield
Peter Rautenberg
Bill Reysen
Gary Robinson
Steven Robinson
Moni Samaan
Fred Sammartino
Stan Sassower
F. Sarles
Ronald Schmidt
Tom Schmitt
Frederick Scholl
Ron Shani
Semir Sirazi
Joseph Skorupa
David A. Smith
Bob Smith
Steve Smith
Robert Snyder
Graham Starkins
David E. Stein
Peter Tarrant
Mark Taylor
Patricia Thaler
Douglas Thompson
Geoffrey O. Thompson
Nathan Tobol
Carlos Tomaszewski
Herbert Uhl
Steven Ulrich
John Visser
William Wager
Joseph A. Wiencko, Jr.
Bruce Williams
Richard Williams
Roger Wilmarth
Mike Wincn
Mark Wingrove
Nobushige Yokota

The following persons were on the balloting committee that approved ANSI/IEEE Std 802.3h-1990 for submission to the IEEE Standards Board:

William Adams
Kit Athul
William E. Ayen
Ali Bahrololoomi
George S. Carson
Chih-Tsai M. Chen
Michael H. Coden
R. A. Conser
R. S. Crowder
Andrew Davidson
Luis F. M. De Moraes
N. I. Dimopoulos
Mitchell Duncan
John E. Emrich
John W. Fendrich
Harold C. Folts
Harvey Freeman
Ingrid Fromm
D. G. Gan
Patrick Gonia
Julio Gonzalez Sanz
Michael Graebner

Maris Graube
Joseph L. Hammond
Stephen Harris
J. Scott Haugdahl
C.W.L. Hobbs
Chris Hsieh
Richard J. Iliff
Raj Jain
M. Kezunovic
Samuel Kho
Tom Kurihara
Lee Labarre
Anthony B. Lake
Mike Lawler
Jaiyong Lee
F. C. Lim
Randolph S. Little
William Livingston
Joseph Loo
Donald C. Loughry
Andy J. Luque
Kelly C. McDonald

Darrell B. McIndoe
Richard H. Miller
David S. Millman
Aditya Mishra
John E. Montague
M. A. F. Morganti
Kinji Mori
D. J. Morris
M. T. Mouftah
Arne A. Nilsson
Charles Oestereicher
Young Oh
Thomas L. Phinney
Rafat Pirzada
Udo Pooch
Robert S. Printis
Marya S. Repko
John P. Riganati
Gary S. Robinson
N. F. Schneidewind
Manfred H. Seifert
D. A. Sheppard

Glen Sherwood
R. M. Simmons
Leo Sintonen
Harry P. Solomon
Robert K. Southard
John Spragins
C. M. Stillebroer

Frank J. Strauss
E. D. Sykas
A. N. Tantawi
Nathan Tobol
Twi-Tek Tsai
David L. Umbaugh
T. A. Varetoni

James Vorhies
Don Weir
A. P. Wheeler
Earl J. Whitaker
D. C. Wood
George B. Wright
Oren Yuen

When the IEEE Standards Board approved ANSI/IEEE Std 802.3h-1990 on September 28, 1990, it had the following membership:

Marco W. Migliaro, *Chairman*

James M. Daly, *Vice Chairman*

Andrew G. Salem, *Secretary*

Dennis Bodson
Paul L. Borrill
Fletcher J. Buckley
Allen L. Clapp
Stephen R. Dillon
Donald C. Fleckenstein
Jay Forster*
Thomas L. Hannan

Kenneth D. Hendrix
John W. Horch
Joseph L. Koepfinger*
Irving Kolodny
Michael A. Lawler
Donald J. Loughry
John E. May, Jr.

Lawrence V. McCall
L. Bruce McClung
Donald T. Michael*
Stig Nilsson
Roy T. Oishi
Gary S. Robinson
Terrance R. Whittemore
Donald W. Zipse

*Member Emeritus

ANSI/IEEE Std 802.3h-1990 was approved by the American National Standards Institute on March 11, 1991.

When the IEEE 802.3 Working Group approved ANSI/IEEE Std 802.3i-1990 (Sections 13 and 14), it had the following membership:

Donald C. Loughry, *Chair**

Patricia Thaler, *Chair, Type 10BASE-T Task Force*†

Menachem Abraham
Luc Adriaenssens
John R. Agee
Keith Amundsen
Richard Anderson
Stephen J. Anderson
Ekkehard Antz
Susie Armstrong
R. V. Balakrishnan
Roberto Bertoldi
Dave Bethune
Mark Bohrer
Richard Brand
Thomas Butler
Luca Cafiero
Robert R. Campbell
Luigi Canavese
Michael Coden
Kevin Cone
Robert Conte
Neil Coote
Ian Crayford
Bill Cronin
Peter Cross
Joe Curcio
Nabil Damouny
Mark Darby
John DeCramer
Tazio M. Denicolo
Sanjay Dawan

Paul (Skip) Ely
Richard Ely
Norman Erbacher
Steve Evitts
Eldon Feist
Alan V. Flatman
Ingrid Fromm
Mel Gable
Robert Galin
Mark Gerhold
Andreas Gulle
Richard Gumpertz
Clive Hallatt
Benny Hanigal
W. B. Hatfield
Stephen Haughey
Carl G. Hayssen
Ernie Jensen
Clarence Joh
Donald C. Johnson
Mize Johnson
Imra Juhaisz
Dieter W. Junkers
Joel S. Kalman
Rainer Kaps
Bob Kilgore
Yongbum Kim
John Kincaid
Bill Kind
Tadayoshi Kitayama

Steven Koller
Paul Kopera
Leonid Koshevoy
Ted Kummert
David Kung
Michael Lebar
Michael Lee
Richard Lefkowitz
Richard Lena
Yoseph Linde
T. D. Lockyer
Andy J. Luque
Kenneth MacLeod
Luciano Marchitto
Charles Marsh
Steven Moustakas
Narayan Murthy
Darcy Nelson
Bob Norton
Mike O'Connor
Chris Oliver
Lloyd Oliver
Keith Onodera
Kazuyuki Ozawa
Charles Palanzo
Tony Peatfield
Peter Rautenberg
Bill Reysen
Gary Robinson
Steven Robinson

Patricia Thaler, *Current Chair

†**Richard Anderson, *Current Chair***

Paul F. Russo
Moni Samaan
F. Sarles
Stan Sassower
Ronald Schmitt
Tom Schmitt
Frederick Scholl
Ron Shani
Joseph Skorupa
David A. Smith

Bob Smith
Steve Smith
Robert Snyder
Graham Starkins
David E. Stein
Peter Tarrant
Mark Taylor
Douglas Thompson
Geoffrey Thompson
Nathan Tobol

Carlos Tomaszewski
Herbert Uhl
John Visser
William Wager
Joseph Wiencko, Jr.
Richard Williams
Roger Wilmarth
Mike Wincn
Mark Wingrove
Nobushige Yokota

The following persons were on the balloting committee for ANSI/IEEE Std 802.3i-1990:

Bandula W. Abesundara
William B. Adams
Don Aelmore
Hasan S. Alkhatib
Jonathan Allan
Sule Arslander
Kit Athul
Michael Atkinson
William E. Ayen
Yong Myung Baeg
Subhash Bhatia
Asa O. Bishop
Alan L. Bridges
Richard Caasi
Mehmet U. Caglayan
Anthony L. Carrato
George S. Carson
Brian J. Casey
George C. Chachis
Chih-Tsai Chen
Gerald W. Cichanowski
Michael H. Coden
Keith Collins
Rodney A. Conser
Robert Crowder
Jose A. Cueto
F. Deravi
Ashwani K. Dhawan
Siyi Terry Dong
Mitchell G. Duncan
Andrew M. Dunn
Sourav Dutta
Ted Dzik
Hans Eklund
John E. Emrich
Richard G. Estock
Changxin Fan
John W. Fendrich
John N. Ferguson
Samuel Fineberg
Ernest L. Fogle
Harold C. Folts
Sandra J. Forney
Harvey A. Freeman
Ingrid Fromm
Eithan Froumine
Robert Gagliano
Isaac Ghansah
Patrick Gonia
Michael D. Graebner
Maris Graube
Abraham Grund
Crag Guarnieri
Sandor V. Halasz
Joseph L. Hammond
Clark M. Hay
Lee A. Hollaar
Marsha D. Hopwood
Anne B. Horton
Genesio L. Hubscher
Wing Huen

Bob Jacobsen
Raj Jain
Gerrit K. Janssen
Jack R. Johnson
Reijo Juvonen
Richard H. Karpinski
Julian Kateley
Gary C. Kessler
Samuel Kho
Jens Kolind
Vijaya Konangi
Peter Kornerup
Jon Kramp
Stephen B. Kruger
Thomas M. Kurihara
Anthony B. Lake
Lak Ming Lam
Glen Langdon
Mike Lawler
Lanse M. Leach
John E. Lecky
Jai-Yong Lee
Michael E. Lee
Lewis E. Leinenweber
Kin Fun Le
F. C. Lim
Ping Lin
Randolph S. Little
William D. Livingston
Mauro Lolli
Wayne M. Loucks
Donald Loughry
Nam C. Low
Andy J. Luque
Carl R. Manson
Eduardo G. Marmol
Gerald M. Masson
Richard McBride
Kelly C. McDonald
William McDonald
Darrell B. McIndoe
Richard H. Miller
David S. Millman
C. B. M. Mishra
Wen Hsien Lim Moh
John E. Montague
Kinji Mori
Gerald Moseley
H. H. T. Mouftah
K. R. S. Murthy
Charles E. Neblock
Ruth Nelson
Arne A. Nilsson
Donal O'Mahony
Frederic Oakland
Charles Oestereicher
Attila Ozgit
Richard J. Paroline
Thomas E. Phillips
Art J. Pina
Rafat Pirzada
Udo W. Pooch

Hardy J. Pottinger
Andris Putnins
Thad L. D. Regulinski
Francisco J. Retivo
John R. Riganati
Saber Rizk
Philip T. Robinson
Gary S. Robinson
Robert Rosenthal
Daniel Rosich
Floyd E. Ross
Victor Rozentouler
Chiseki Sagawa
Mark S. Sanders
Ravi Sankar
Julio Gonzalez Sanz
Ambatipudi Sastry
Vidyadhar S. Savant
Manoj Kunar Saxena
Lorne Schachter
Norman Schneidewind
Jeffrey R. Schwab
A. D. Sheppard
Glen Sherwood
William T. Smith
I. A. Soceanu
Robert K. Southard
Charles Spurgeon
Michael Stephenson
Fred J. Strauss
Efsthathios D. Sykas
Roy S. Sylter
Gregory M. Sylvain
Daniel Sze
Nhi P. Ta
Hassan Tabaie
Hao Tang
Ahmed N. Tantawi
Steven R. Taylor
James N. Thomas
Geoffrey O. Thompson
Nathal Tobol
Robert Tripi
L. David Umbaugh
Thomas A. Varetoni
James T. Vorhies
Barry Vornbrock
Clarence M. Weaver
Donald F. Weir
Alan J. Weissberger
Raymond Wenig
William J. Wenker
Earl J. Whitaker
Thomas P. Wigen
Michael Willett
Paul A. Willis
George B. Wright
Jen-Kun Yang
Oren Yuen
William H. Yundt
Zhao Wei

When the IEEE Standards Board approved ANSI/IEEE Std 802.3i-1990 on September 28, 1990, it had the following membership:

Marco W. Migliaro, *Chairman*

James M. Daly, *Vice Chairman*

Andrew G. Salem, *Secretary*

Dennis Bodson
Paul L. Borrill
Fletcher J. Buckley
Allen L. Clapp
Stephen R. Dillon
Donald C. Fleckenstein
Jay Forster*
Thomas L. Hannan

Kenneth D. Hendrix
John W. Horch
Joseph L. Koepfinger*
Irving Kolodny
Michael A. Lawler
Donald J. Loughry
John E. May, Jr.

Lawrence V. McCall
L. Bruce McClung
Donald T. Michael*
Stig Nilsson
Roy T. Oishi
Gary S. Robinson
Terrance R. Whittemore
Donald W. Zipse

*Member Emeritus

ANSI/IEEE Std 802.3i-1990 was approved by the American National Standards Institute on March 11, 1991.

Contents

SECTION	PAGE
1. Introduction	31
1.1 Overview	31
1.1.1 Basic Concepts	31
1.1.2 Architectural Perspectives	31
1.1.3 Layer Interfaces	32
1.1.4 Application Areas	33
1.2 Notation	33
1.2.1 State Diagram Conventions	33
1.2.2 Service Specification Method and Notation	34
1.2.3 Physical Layer and Media Notation	35
1.2.4 Physical Layer Message Notation	35
1.3 References	35
1.4 Definitions	36
2. MAC Service Specification	37
2.1 Scope and Field of Application	37
2.2 Overview of the Service	37
2.2.1 General Description of Services Provided by the Layer	37
2.2.2 Model Used for the Service Specification	37
2.2.3 Overview of Interactions	37
2.2.4 Basic Services and Options	37
2.3 Detailed Service Specification	38
2.3.1 MA_DATA.request	38
2.3.2 MA_DATA.indication	38
3. Media Access Control Frame Structure	41
3.1 Overview	41
3.1.1 MAC Frame Format	41
3.2 Elements of the MAC Frame	41
3.2.1 Preamble Field	41
3.2.2 Start Frame Delimiter (SFD) Field	42
3.2.3 Address Fields	42
3.2.4 Destination Address Field	43
3.2.5 Source Address Field	43
3.2.6 Length Field	43
3.2.7 Data and PAD Fields	43
3.2.8 Frame Check Sequence Field	43
3.3 Order of Bit Transmission	44
3.4 Invalid MAC Frame	44
4. Media Access Control	45
4.1 Functional Model of the Media Access Control Method	45
4.1.1 Overview	45
4.1.2 CSMA/CD Operation	45
4.1.3 Relationships to LLC Sublayer and Physical Layer	47
4.1.4 CSMA/CD Access Method Functional Capabilities	47
4.2 CSMA/CD Media Access Control Method (MAC): Precise Specification	48
4.2.1 Introduction	48
4.2.2 Overview of the Procedural Model	48
4.2.3 Frame Transmission Model	54
4.2.4 Frame Reception Model	55
4.2.5 Preamble Generation	56
4.2.6 Start Frame Sequence	57
4.2.7 Global Declarations	57
4.2.8 Frame Transmission	59
4.2.9 Frame Reception	63
4.2.10 Common Procedures	65
4.3 Interfaces to/from Adjacent Layers	66

SECTION	PAGE
4.3.1	Overview 66
4.3.2	Services Provided by the MAC Sublayer..... 66
4.3.3	Services Required from the Physical Layer 67
4.4	Specific Implementations 68
4.4.1	Compatibility Overview 68
4.4.2	Allowable Implementations 69
5.	Layer Management..... 71
5.1	Introduction..... 71
5.1.1	Systems Management Overview 71
5.1.2	Layer Management Model 72
5.2	Management Facilities 73
5.2.1	Introduction 73
5.2.2	MAC Sublayer Management Facilities 73
5.2.3	Physical Layer Management Facilities 77
5.2.4	Layer Management Model 77
6.	PLS Service Specifications..... 83
6.1	Scope and Field of Application 83
6.2	Overview of the Service 83
6.2.1	General Description of Services Provided by the Layer 83
6.2.2	Model Used for the Service Specification 83
6.2.3	Overview of Interactions 83
6.2.4	Basic Services and Options 84
6.3	Detailed Service Specification 84
6.3.1	Peer-to-Peer Service Primitives..... 84
6.3.2	Sublayer-to-Sublayer Service Primitives 85
7.	Physical Signaling (PLS) and Attachment Unit Interface (AUI) Specifications 87
7.1	Scope 87
7.1.1	Definitions 87
7.1.2	Summary of Major Concepts..... 88
7.1.3	Application..... 88
7.1.4	Modes of Operation 88
7.1.5	Allocation of Function 88
7.2	Functional Specification 88
7.2.1	PLS–PMA (DTE–MAU) Interface Protocol..... 89
7.2.2	PLS Interface to MAC and Management Entities..... 94
7.2.3	Frame Structure 95
7.2.4	PLS Functions 96
7.3	Signal Characteristics..... 98
7.3.1	Signal Encoding 98
7.3.2	Signaling Rate 102
7.3.3	Signaling Levels 102
7.4	Electrical Characteristics 103
7.4.1	Driver Characteristics..... 103
7.4.2	Receiver Characteristics 104
7.4.3	AUI Cable Characteristics 108
7.5	Functional Description of Interchange Circuits 108
7.5.1	General..... 108
7.5.2	Definition of Interchange Circuits..... 109
7.6	Mechanical Characteristics 111
7.6.1	Definition of Mechanical Interface 111
7.6.2	Line Interface Connector 111
7.6.3	Contact Assignments 113
8.	Medium Attachment Unit and Baseband Medium Specifications, Type 10BASE5 115
8.1	Scope 115
8.1.1	Overview 115
8.1.2	Definitions 116

8.1.3	Application Perspective: MAU and MEDIUM Objectives.....	116
8.2	MAU Functional Specifications.....	117
8.2.1	MAU Physical Layer Functions.....	118
8.2.2	MAU Interface Messages.....	120
8.2.3	MAU State Diagrams.....	121
8.3	MAU–Medium Electrical Characteristics.....	121
8.3.1	MAU-to-Coaxial Cable Interface.....	121
8.3.2	MAU Electrical Characteristics.....	125
8.3.3	MAU–DTE Electrical Characteristics.....	126
8.3.4	MAU–DTE Mechanical Connection.....	126
8.4	Characteristics of the Coaxial Cable.....	126
8.4.1	Coaxial Cable Electrical Parameters.....	126
8.4.2	Coaxial Cable Properties.....	127
8.4.3	Total Segment DC Loop Resistance.....	128
8.5	Coaxial Trunk Cable Connectors.....	128
8.5.1	Inline Coaxial Extension Connector.....	129
8.5.2	Coaxial Cable Terminator.....	129
8.5.3	MAU-to-Coaxial Cable Connector.....	129
8.6	System Considerations.....	130
8.6.1	Transmission System Model.....	130
8.6.2	Transmission System Requirements.....	131
8.6.3	Labeling.....	134
8.7	Environmental Specifications.....	134
8.7.1	General Safety Requirements.....	134
8.7.2	Network Safety Requirements.....	134
8.7.3	Electromagnetic Environment.....	135
8.7.4	Temperature and Humidity.....	136
8.7.5	Regulatory Requirements.....	136
9.	Repeater Unit for 10 Mb/s Baseband Networks.....	137
9.1	Overview.....	137
9.2	Definitions.....	137
9.3	References.....	138
9.4	Compatibility Interface.....	138
9.4.1	AUI Compatibility.....	139
9.4.2	Direct Cable Compatibility.....	139
9.4.3	Link Segment Compatibility.....	139
9.5	Basic Functions.....	139
9.5.1	Repeater Set Network Properties.....	139
9.5.2	Signal Amplification.....	140
9.5.3	Signal Symmetry.....	140
9.5.4	Signal Retiming.....	140
9.5.5	Data Handling.....	140
9.5.6	Collision Handling.....	140
9.5.7	Electrical Isolation.....	141
9.6	Detailed Repeater Functions and State Diagrams.....	141
9.6.1	State Diagram Notation.....	141
9.6.2	Data and Collision Handling.....	146
9.6.3	Preamble Regeneration.....	146
9.6.4	Fragment Extension.....	146
9.6.5	MAU Jabber Lockup Protection.....	146
9.6.6	Auto-Partitioning/Reconnection (Optional).....	146
9.7	Electrical Isolation.....	149
9.7.1	Environment A Requirements.....	149
9.7.2	Environment B Requirements.....	149
9.8	Reliability.....	149
9.9	Medium Attachment Unit and Baseband Medium Specification for a Vendor-Independent FOIRL.....	149
9.9.1	Scope.....	149
9.9.2	FOMAU Functional Specifications.....	151

SECTION	PAGE
9.9.3 FOMAU Electrical Characteristics	159
9.9.4 FOMAU/Optical Medium Interface.....	159
9.9.5 Characteristics of the Optical Fiber Cable Link Segment	160
9.9.6 System Requirements	161
9.9.7 Environmental Specifications	162
10. Medium Attachment Unit and Baseband Medium Specifications, Type 10BASE2	165
10.1 Scope	165
10.1.1 Overview	165
10.1.2 Definitions	166
10.1.3 Application Perspective: MAU and Medium Objectives	167
10.2 References.....	167
10.3 MAU Functional Specifications.....	167
10.3.1 MAU Physical Layer Functional Requirements.....	168
10.3.2 MAU Interface Messages	170
10.3.3 MAU State Diagrams	172
10.4 MAU–Medium Electrical Characteristics	172
10.4.1 MAU-to-Coaxial Cable Interface	172
10.4.2 MAU Electrical Characteristics.....	174
10.4.3 MAU–DTE Electrical Characteristics	175
10.5 Characteristics of Coaxial Cable System	175
10.5.1 Coaxial Cable Electrical Parameters	175
10.5.2 Coaxial Cable Physical Parameters	175
10.5.3 Total Segment DC Loop Resistance	177
10.6 Coaxial Trunk Cable Connectors	177
10.6.1 In-Line Coaxial Extension Connector	178
10.6.2 Coaxial Cable Terminator	178
10.6.3 MAU-to-Coaxial Cable Connection	178
10.7 System Considerations	178
10.7.1 Transmission System Model.....	178
10.7.2 Transmission System Requirements	179
10.8 Environmental Specifications	181
10.8.1 Safety Requirements.....	181
10.8.2 Electromagnetic Environment.....	181
10.8.3 Regulatory Requirements	182
11. Broadband Medium Attachment Unit and Broadband Medium Specifications, Type 10BROAD36	183
11.1 Scope	183
11.1.1 Overview	183
11.1.2 Definitions	185
11.1.3 MAU and Medium Objectives	186
11.1.4 Compatibility Considerations	186
11.1.5 Relationship to PLS and AUI	186
11.1.6 Mode of Operation	186
11.2 MAU Functional Specifications.....	187
11.2.1 MAU Functional Requirements.....	187
11.2.2 DTE PLS to MAU and MAU to DTE PLS Messages.....	189
11.2.3 MAU State Diagrams	190
11.3 MAU Characteristics	194
11.3.1 MAU- to-Coaxial Cable Interface	194
11.3.2 MAU Frequency Allocations	198
11.3.3 AUI Electrical Characteristics.....	198
11.3.4 MAU Transfer Characteristics	199
11.3.5 Reliability.....	205
11.4 System Considerations	205
11.4.1 Delay Budget and Network Diameter.....	205
11.4.2 MAU Operation with Packets Shorter than 512 Bits	206
11.5 Characteristics of the Coaxial Cable System	206
11.5.1 Electrical Requirements	206

SECTION	PAGE
11.5.2 Mechanical Requirements.....	207
11.5.3 Delay Requirements.....	207
11.6 Frequency Translator Requirements for the Single-Cable Version.....	207
11.6.1 Electrical Requirements	207
11.6.2 Mechanical Requirements.....	208
11.7 Environmental Specifications	208
11.7.1 Safety Requirements.....	208
11.7.2 Electromagnetic Environment.....	208
11.7.3 Temperature and Humidity	208
12. Physical Signaling, Medium Attachment, and Baseband Medium Specifications, Type 1BASE5	209
12.1 Introduction.....	209
12.1.1 Overview	209
12.1.2 Scope	209
12.1.3 Definitions	209
12.1.4 General Characteristics	211
12.1.5 Compatibility.....	211
12.1.6 Objectives of Type 1BASE5 Specifications.....	211
12.2 Architecture.....	211
12.2.1 Major Concepts	211
12.2.2 Application Perspective.....	213
12.2.3 Packet Structure	213
12.3 DTE Physical Signaling (PLS) Specification	214
12.3.1 Overview	214
12.3.2 Functional Specification.....	214
12.4 Hub Specification	221
12.4.1 Overview	221
12.4.2 Hub Structure	222
12.4.3 Hub PLS Functional Specification	222
12.5 Physical Medium Attachment (PMA) Specification.....	227
12.5.1 Overview	227
12.5.2 PLS-PMA Interface	227
12.5.3 Signal Characteristics.....	227
12.6 Medium Dependent Interface (MDI) Specification	235
12.6.1 Line Interface Connector	235
12.6.2 Connector Contact Assignments	235
12.6.3 Labeling	235
12.7 Cable Medium Characteristics	236
12.7.1 Overview	236
12.7.2 Transmission Parameters	236
12.7.3 Coupling Parameters	236
12.7.4 Noise Environment.....	238
12.8 Special Link Specification	238
12.8.1 Overview	238
12.8.2 Transmission Characteristics	238
12.8.3 Permitted Configurations	238
12.9 Timing.....	239
12.9.1 Overview	239
12.9.2 DTE Timing	239
12.9.3 Medium Timing	239
12.9.4 Special Link Timing	239
12.9.5 Hub Timing.....	239
12.10 Safety.....	240
12.10.1 Isolation	240
12.10.2 Telephony Voltages	240
13. System Considerations for Multisegment 10 Mb/s Baseband Networks.....	241
13.1 Overview.....	241
13.2 Definitions	241

SECTION	PAGE
13.3 Transmission System Model.....	241
14. Twisted-Pair Medium Attachment Unit (MAU) and Baseband Medium, Type 10BASE-T	245
14.1 Scope	245
14.1.1 Overview	245
14.1.2 Definitions	245
14.1.3 Application Perspective.....	247
14.1.4 Relationship to PLS and AUI	248
14.2 MAU Functional Specifications.....	248
14.2.1 MAU Functions	249
14.2.2 PMA Interface Messages.....	250
14.2.3 MAU State Diagrams	252
14.3 MAU Electrical Specifications.....	256
14.3.1 MAU-to-MDI Interface Characteristics	257
14.3.2 MAU-to-AUI Specification	265
14.4 Characteristics of the Simplex Link Segment.....	266
14.4.1 Overview	266
14.4.2 Transmission Parameters.....	266
14.4.3 Coupling Parameters	267
14.4.4 Noise Environment.....	267
14.5 MDI Specification.....	268
14.5.1 MDI Connectors.....	268
14.5.2 Crossover Function.....	269
14.6 System Considerations	270
14.7 Environmental Specifications	270
14.7.1 General Safety.....	270
14.7.2 Network Safety.....	270
14.7.3 Environment.....	271
14.8 MAU Labeling	271
14.9 Timing Summary	271

FIGURES

Fig 1-1	LAN Standard Relationship to the ISO Open Systems Interconnection (OSI) Reference Model	32
Fig 1-2	State Diagram Notation Example	33
Fig 1-3	Service Primitive Notation	34
Fig 2-1	Service Specification Relation to the LAN Model.....	37
Fig 3-1	MAC Frame Format	41
Fig 3-2	Address Field Format	42
Fig 4-1	MAC Sublayer Partitioning, Relationship to the ISO Open Systems Interconnection (OSI) Reference Model	46
Fig 4-2	CSMA/CD Media Access Control Functions	48
Fig 4-3	Relationship Among CSMA/CD Procedures	50
Fig 4-4	Control Flow Summary	
	(a) TransmitFrame	51
	(b) ReceiveFrame	52
Fig 4-5	Control Flow: MAC Sublayer	53
Fig 5-1	Relationship Between the Various Management Entities and Layer Entities According to the ISO Open Systems Interconnection (OSI) Reference Model.....	72
Fig 6-1	Service Specification Relationship to the IEEE 802.3 CSMA/CD LAN Model	83
Fig 7-1	Physical Layer Partitioning, Relationship to the ISO Open Systems Interconnection (OSI) Reference Model	87
Fig 7-2	Generalized MAU Model.....	89
Fig 7-3	PLS Reset and Identify Function	91
Fig 7-4	PLS Mode Function	92
Fig 7-5	PLS Output Function.....	93
Fig 7-6	PLS Input Function.....	97
Fig 7-7	PLS Error Sense Function	98
Fig 7-8	PLS Carrier Sense Function	99

Fig 7-9	Interface Function for MAU with Conditioning	100–101
Fig 7-10	Examples of Manchester Waveforms	102
Fig 7-11	Differential Output Voltage, Loaded.....	104
Fig 7-12	Generalized Driver Waveform	105
Fig 7-13	Common-Mode Output Voltage	105
Fig 7-14	Driver Fault Conditions	106
Fig 7-15	Common-Mode Input Test	107
Fig 7-16	Receiver Fault Conditions	107
Fig 7-17	Common-Mode Transfer Impedance	109
Fig 7-18	Connector Locking Posts	111
Fig 7-19	Connector Slide Latch.....	112
Fig 7-20	Connector Hardware and AUI Cable Configuration	112
Fig 8-1	Physical Layer Partitioning, Relationship to the ISO Open Systems Interconnection (OSI) Reference Model	115
Fig 8-2	Interface Function: Simple MAU Without Isolate Capability	122
Fig 8-3	Interface Function: Simple MAU with Isolate Capability	123
Fig 8-4	Jabber Function.....	124
Fig 8-5	Recommended Driver Current Signal Levels	125
Fig 8-6	Typical Coaxial Trunk Cable Signal Waveform	125
Fig 8-7	Maximum Coaxial Cable Transfer Impedance	127
Fig 8-8	Coaxial Tap Connector Configuration Concepts	130
Fig 8-9	Typical Coaxial Tap Connection Circuit	131
Fig 8-10	Maximum Transmission Path	132
Fig 8-11	Minimal System Configuration	132
Fig 8-12	Minimal System Configuration Requiring a Repeater Set	132
Fig 8-13	An Example of a Large System with Maximum Transmission Paths	133
Fig 8-14	An Example of a Large Point-to-Point Link System (5140 ns)	133
Fig 9-1	Repeater Set, Coax-to-Coax Configuration	137
Fig 9-2	Repeater Unit State Diagram	144
Fig 9-3	Transmit Timer State Diagram for Port X	145
Fig 9-4	Tw2 State Diagram	145
Fig 9-5	MAU Jabber Lockup Protection State Diagram.....	145
Fig 9-6	Partitioning State Diagram for Port X.....	148
Fig 9-7	Schematic of the Vendor-Independent FOIRL and Its Relationship to the Repeater Unit	151
Fig 9-8	FOMAU Transmit, Receive, and Collision Functions State Diagram	157
Fig 9-9	FOMAU Jabber Function State Diagram	158
Fig 9-10	Low Light Level Detection Function State Diagram	158
Fig 10-1	Physical Layer Partitioning, Relationship to the ISO Open Systems Interconnection (OSI) Reference Model	165
Fig 10-2	MAU Interface Function	168
Fig 10-3	Jabber Function State Diagram	170
Fig 10-4	Driver Current Signal Levels	173
Fig 10-5	Coaxial Trunk Cable Signal Waveform	173
Fig 10-6	Maximum Coaxial Cable Transfer Impedance	176
Fig 10-7	Examples of Insulated Connector Cover	177
Fig 10-8	Maximum Transfer Path	179
Fig 10-9	The Minimum System Configuration.....	179
Fig 10-10	The Minimum System Configuration Requiring a Repeater Set	180
Fig 10-11	An Example of a Large Hybrid System.....	180
Fig 11-1	Physical Layer Partitioning, Relationship to the ISO Open Systems Interconnection (OSI) Reference Model	183
Fig 11-2	Broadband Cable Systems	184
Fig 11-3	Transmit Function Requirements	187
Fig 11-4	MAU State Diagram	192–193
Fig 11-5	MAU Jabber State Diagram	194
Fig 11-6	Packet Format and Timing Diagram (AUI to Coaxial Cable Interface)	196
Fig 11-7	Spectrum Mask for RF Data Signal	197
Fig 11-8	Transmit Out-of-Band Power Attenuation	197
Fig 11-9	Packet Format at Modulator Input	200

FIGURES	PAGE
Fig 11-10	Scrambler..... 201
Fig 11-11	Differential Encoder..... 201
Fig 11-12	Descrambler..... 202
Fig 11-13	No Collision Timing Diagram (Coax to AUI)..... 203
Fig 11-14	Collision Timing Diagram (RF Data to RF Collision Enforcement)..... 204
Fig 11-15	Collision Timing Diagram (Coaxial Cable Interface to AUI Circuit CI)..... 204
Fig 11-16	Timing at AUI for Zero-Length Coax..... 205
Fig 12-1	1BASE5 Relationship to the ISO Open Systems Interconnection (OSI) Reference Model and the IEEE 802.3 CSMA/CD LAN Model 210
Fig 12-2	Single Hub Network 212
Fig 12-3	Network With Two Levels of Hubs..... 212
Fig 12-4	Network With Four Levels of Hubs 213
Fig 12-5	Station Physical Signaling, Relationship to the ISO OSI Reference Model and the IEEE 802.3 CSMA/CD LAN Model..... 215
Fig 12-6	DTE PLS Output Function 217
Fig 12-7	DTE PLS Input Function 218
Fig 12-8	DTE PLS Error Sense Function 218
Fig 12-9	DTE PLS Carrier Sense Function 219
Fig 12-10	Examples of Manchester Waveforms 220
Fig 12-11	Examples of Collision Presence Waveforms 220
Fig 12-12	Hub Relationship to the OSI Reference Model and the IEEE 802.3 CSMA/CD LAN Model 221
Fig 12-13	Hub PLS Upward Transfer Function..... 224
Fig 12-14	Hub PLS Jabber Function for Port X..... 225
Fig 12-15	Hub PLS Downward Transfer Function 226
Fig 12-16	Physical Medium Attachment, Relationship to the OSI Reference Model and the IEEE 802.3 CSMA/CD LAN Model 228
Fig 12-17	Simulated Light Load 228
Fig 12-18	Simulated Heavy Load 229
Fig 12-19	Differential Output Voltage, Nominal Duration BT/2 229
Fig 12-20	Differential Output Voltage, Duration BT..... 229
Fig 12-21	Transmitter Waveform for Idle 231
Fig 12-22	Start-of-Idle Test Load #1..... 231
Fig 12-23	Start-of-Idle Test Load #2..... 231
Fig 12-24	Transmitter Impedance Balance 231
Fig 12-25	Common-Mode Output Voltage 232
Fig 12-26	Transmitter Common-Mode Tolerance 232
Fig 12-27	Common-Mode Impulse Test 233
Fig 12-28	Receiver Signal Envelope..... 233
Fig 12-29	Receiver Common-Mode Rejection 234
Fig 12-30	DTE and Hub Connector..... 235
Fig 12-31	Cable Connector 235
Fig 12-32	Cable Balance Test..... 237
Fig 13-1	Maximum Transmission Path with Three Coaxial Cable Segments 243
Fig 13-2	Example of Maximum Transmission Path Using Coaxial Cable Segments, 10BASE-T Link Segments, and Fiber Optic Link Segments..... 243
Fig 13-3	Example of Maximum Transmission Path with Three Repeater Sets, Four Link Segments (Two are 100 m 10BASE-T and Two are 1 km Fiber) 244
Fig 14-1	10BASE-T Relationship to the ISO Open Systems Interconnection (OSI) Reference Model and the IEEE 802.3 CSMA/CD LAN Model 246
Fig 14-2	Twisted-Pair Link 247
Fig 14-3	MAU Transmit, Receive, Loopback, and Collision Presence Functions State Diagram 253
Fig 14-4	<i>signal_quality_error</i> Message Test Function State Diagram 254
Fig 14-5	Jabber Function State Diagram 255
Fig 14-6	Link Integrity Test Function State Diagram 256
Fig 14-7	Twisted-Pair Model 257
Fig 14-8	Differential Output Voltage Test 258
Fig 14-9	Voltage Template 258
Fig 14-10	Transmitter Waveform for Start of TP_IDL..... 260

FIGURES	PAGE
Fig 14-11 Start-of-TP_IDL Test Load	260
Fig 14-12 Transmitter Waveform for Link Test Pulse	261
Fig 14-13 Transmitter Impedance Balance and Common-Mode Rejection Test Circuit	262
Fig 14-14 Common-Mode Output Voltage Test Circuit	262
Fig 14-15 Transmitter Fault Tolerance Test Circuit	263
Fig 14-16 Receiver Differential Input Voltage—Narrow Pulse	264
Fig 14-17 Receiver Differential Input Voltage—Wide Pulse	264
Fig 14-18 Receiver Common-Mode Rejection Test Circuit	265
Fig 14-19 Common-Mode Impulse Test Circuit	265
Fig 14-20 MAU MDI Connector	268
Fig 14-21 Twisted-Pair Link Segment Connector	268
Fig 14-22 Crossover Function	
(a) External Crossover Function	269
(b) MAU-Embedded Crossover Function	269

TABLES

Table 8-1 Generation of Collision Presence Signal	119
Table 9-1 Maximum Allowable Timing Budget Contributions to the FOIRL System Timing Budget	162
Table 10-1 Generation of Collision Presence Signal	169
Table 11.2-1 Single-Cable Frequency Allocations (Frequencies in MHz)	198
Table 11.2-2 Dual-Cable Frequency Allocations (Frequencies in MHz)	199
Table 11.4-1 Broadband Dual-Cable Systems—Physical Layer Delay Budget	206
Table 11.5-1 Cable System Electrical Requirements	207
Table 11.6-1 Frequency Translator Requirements	207
Table 13-1 Delays for Network Media Segments	241
Table 14-1 Voltage Template Values for Fig 14-9	259
Table 14-2 Maximum Timing Parameters	272

ANNEX

Additional Reference Material	273
-------------------------------------	-----

APPENDIXES

A. System Guidelines	275
A1. Baseband System Guidelines and Concepts	275
A1.1 Overall System Objectives	275
A1.2 Analog System Components and Parameter Values	275
A1.3 Minimum Frame Length Determination	276
A1.4 System Jitter Budgets	278
A2. System Parameters and Budgets for 1BASE5	280
A2.1 Delay Budget	280
A2.2 Minimum Frame Length Determination	281
A2.3 Jitter Budget	282
A3. Example Crosstalk Computation for Multiple Disturbances	283
A4. 10BASE-T	284
A4.1 System Jitter Budget	284
A4.2 Filter Characteristics	285
A4.3 Notes for Conformance Testing	285
B. State Diagram, MAC Sublayer	287
B1. Introduction	287
B2. CSMA/CD Media Access Control State Machine Overview	287
B2.1 Transmit Component Overview	287
B2.2 Transmit Component Event Descriptions	287
B2.3 Transmit Component Action Descriptions	289
B2.4 Transmit Component State Descriptions	289
B3. Receive Component Overview	290
B3.1 Receive Component Event Descriptions	290

APPENDIXES	PAGE
B3.2 Receive Component Action Descriptions	290
B3.3 Receive Component State Descriptions	291
C. Application Context, Selected Medium Specifications.....	292
C1. Introduction.....	292
C2. Type 10BASE5 Applications.....	292
C3. Type 10BASE2 Applications.....	293
C4. Type FOIRL Applications	293
D. Receiver Wavelength Design Considerations	294

APPENDIX FIGURES

Fig A1	Maximal System Configuration Bit Budget Apportionments.....	276
Fig A2	Typical Signal Waveforms	279
Fig A3	Worst-Case Signal Waveform Variations	279
Fig A4	MDNEXT Cumulative Probability Distribution.....	284
Fig B1	Transmit Component State Diagram.....	287
Fig B2	Receive Component State Diagram.....	290

APPENDIX TABLES

Table B1	Transmit Component State Transition.....	288
Table B2	Receive Component State Transition.....	290

Information technology—Local and metropolitan area networks—

Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications

1. Introduction

1.1 Overview

1.1.1 Basic Concepts. The Carrier Sense Multiple Access with Collision Detection (CSMA/CD) media access method is the means by which two or more stations share a common transmission medium. To transmit, a station waits (defers) for a quiet period on the medium (that is, no other station is transmitting) and then sends the intended message in bit-serial form. If, after initiating a transmission, the message collides with that of another station, then each transmitting station intentionally sends a few additional bytes to ensure propagation of the collision throughout the system. The station remains silent for a random amount of time (backoff) before attempting to transmit again. Each aspect of this access method process is specified in detail in subsequent sections of this standard.

This is a comprehensive standard for Local Area Networks employing CSMA/CD as the access method. This standard is intended to encompass several media types and techniques for signal rates of from 1 Mb/s to 20 Mb/s. This edition of the standard provides the necessary specifications for 10 Mb/s baseband and broadband systems, a 1 Mb/s baseband system, and a Repeater Unit.

1.1.2 Architectural Perspectives. There are two important ways to view local area network design corresponding to

- (1) *Architecture.* Emphasizing the logical divisions of the system and how they fit together.
- (2) *Implementation.* Emphasizing actual components, their packaging and interconnection.

This standard is organized along architectural lines, emphasizing the large-scale separation of the system into two parts: the Media Access Control (MAC) sublayer of the Data Link Layer, and the Physical Layer. These layers are intended to correspond closely to the lowest layers of the ISO Model for Open Systems Interconnection (see Fig 1-1). See ISO 7498:1984 [10].¹ The Logical Link Control (LLC) sublayer and MAC sublayer together encompass the functions intended for the Data Link Layer as defined in the OSI model.

1.1.2.1 An architectural organization of the standard has two main advantages:

- (1) *Clarity.* A clean overall division of the design along architectural lines makes the standard clearer.
- (2) *Flexibility.* Segregation of medium-dependent aspects in the Physical Layer allows the LLC and MAC sublayers to apply to a family of transmission media.

Partitioning the Data Link Layer allows various media access methods within the family of Local Area Network standards.

¹ The numbers in brackets correspond to those of the references listed in 1.3; when preceded by A, they correspond to those listed in the Annex.




Fig 1-1
LAN Standard Relationship to the ISO Open Systems Interconnection (OSI) Reference Model

The architectural model is based on a set of interfaces that may be different from those emphasized in implementations. One critical aspect of the design, however, shall be addressed largely in terms of the implementation interfaces: compatibility.

1.1.2.2 Two important compatibility interfaces are defined within what is architecturally the Physical Layer.

- (1) *Medium-Dependent Interface (MDI)*. To communicate in a compatible manner, all stations shall adhere rigidly to the exact specification of physical media signals defined in Section 8 (and beyond) in this standard, and to the procedures that define correct behavior of a station. The medium-independent aspects of the LLC sublayer and the MAC sublayer should not be taken as detracting from this point; communication by way of the ISO 8802-3 [IEEE 802.3] Local Area Network requires complete compatibility at the Physical Medium interface (that is, the coaxial cable interface).
- (2) *Attachment Unit Interface (AUI)*. It is anticipated that most DTEs will be located some distance from their connection to the coaxial cable. A small amount of circuitry will exist in the Medium Attachment Unit (MAU) directly adjacent to the coaxial cable, while the majority of the hardware and all of the software will be placed within the DTE. The AUI is defined as a second compatibility interface. While conformance with this interface is not strictly necessary to ensure communication, it is highly recommended, since it allows maximum flexibility in intermixing MAUs and DTEs. The AUI may be optional or not specified for some implementations of this standard that are expected to be connected directly to the medium and so do not use a separate MAU or its interconnecting AUI cable. The PLS and PMA are then part of a single unit, and no explicit AUI specification is required.

1.1.3 Layer Interfaces. In the architectural model used here, the layers interact by way of well defined interfaces, providing services as specified in Sections 2 and 6. In general, the interface requirements are as follows:

- (1) The interface between the MAC sublayer and the LLC sublayer includes facilities for transmitting and receiving frames, and provides per-operation status information for use by higher-layer error recovery procedures.
- (2) The interface between the MAC sublayer and the Physical Layer includes signals for framing (carrier sense, transmit initiation) and contention resolution (collision detect), facilities for passing a pair of serial bit streams (transmit, receive) between the two layers, and a wait function for timing.

These interfaces are described more precisely in 4.3. Additional interfaces are necessary to allow higher level network management facilities to interact with these layers to perform operation, maintenance, and planning functions. Network management functions will be discussed in Section 5.

1.1.4 Application Areas. The applications environment for the Local Area Network is intended to be commercial and light industrial. Use of CSMA/CD LANs in home or heavy industrial environments, while not precluded, is not considered within the scope of this standard.

1.2 Notation

1.2.1 State Diagram Conventions. The operation of a protocol can be described by subdividing the protocol into a number of interrelated functions. The operation of the functions can be described by state diagrams. Each diagram represents the domain of a function and consists of a group of connected, mutually exclusive states. Only one state of a function is active at any given time (see Fig 1-2).




Fig 1-2
State Diagram Notation Example

Each state that the function can assume is represented by a rectangle. These are divided into two parts by a horizontal line. In the upper part the state is identified by a name in capital letters. The lower part contains the name of any ON signal that is generated by the function. Actions are described by short phrases and enclosed in brackets.

All permissible transitions between the states of a function are represented graphically by arrows between them. A transition that is global in nature (for example, an exit condition from all states to the IDLE or RESET state) is indicated by an open arrow. Labels on transitions are qualifiers that must be fulfilled before the transition will be taken. The label UCT designates an unconditional transition. Qualifiers described by short phrases are enclosed in parentheses.

State transitions and sending and receiving of messages occur instantaneously. When a state is entered and the condition to leave that state is not immediately fulfilled, the state executes continuously, sending the messages and executing the actions contained in the state in a continuous manner.

Some devices described in this standard (e.g., repeaters) are allowed to have two or more ports. State diagrams capable of describing the operation of devices with an unspecified number of ports, required qualifier notation that allows testing for conditions at multiple ports. The notation used is a term that includes a description in parentheses of which ports must meet the term for the qualifier to be satisfied (e.g., ANY and ALL). It is also necessary to provide for term-assignment statements that assign a name to a port that satisfies a qualifier. The following convention is used to describe a term-assignment statement that is associated with a transition:

- (1) The character “.” (colon) is a delimiter used to denote that a term assignment statement follows.
- (2) The character “←” (left arrow) denotes assignment of the value following the arrow to the term preceding the arrow.

The state diagrams contain the authoritative statement of the functions they depict; when apparent conflicts between descriptive text and state diagrams arise, the state diagrams are to take precedence. This does not override, however, any explicit description in the text that has no parallel in the state diagrams.

The models presented by state diagrams are intended as the primary specifications of the functions to be provided. It is important to distinguish, however, between a model and a real implementation. The models are optimized for simplicity and clarity of presentation, while any realistic implementation may place heavier emphasis on efficiency and suitability to a particular implementation technology. It is the functional behavior of any unit that must match the standard, not its internal structure. The internal details of the model are useful only to the extent that they specify the external behavior clearly and precisely.

1.2.2 Service Specification Method and Notation. The service of a layer or sublayer is the set of capabilities that it offers to a user in the next higher (sub)layer. Abstract services are specified here by describing the service primitives and parameters that characterize each service. This definition of service is independent of any particular implementation (see Fig 1-3).




Fig 1-3
Service Primitive Notation

Specific implementations may also include provisions for interface interactions that have no direct end-to-end effects. Examples of such local interactions include interface flow control, status requests and indications, error notifications, and layer management. Specific implementation details are omitted from this service specification both because they will differ from implementation to implementation and because they do not impact the peer-to-peer protocols.

1.2.2.1 Classification of Service Primitives. Primitives are of two generic types:

- (1) **REQUEST.** The request primitive is passed from layer N to layer N-1 to request that a service be initiated.

- (2) **INDICATION.** The indication primitive is passed from layer N-1 to layer N to indicate an internal layer N-1 event that is significant to layer N. This event may be logically related to a remote service request, or may be caused by an event internal to layer N-1.

The service primitives are an abstraction of the functional specification and the user-layer interaction. The abstract definition does not contain local detail of the user/provider interaction. For instance, it does not indicate the local mechanism that allows a user to indicate that it is awaiting an incoming call. Each primitive has a set of zero or more parameters, representing data elements that shall be passed to qualify the functions invoked by the primitive. Parameters indicate information available in a user/provider interaction; in any particular interface, some parameters may be explicitly stated (even though not explicitly defined in the primitive) or implicitly associated with the service access point. Similarly, in any particular protocol specification, functions corresponding to a service primitive may be explicitly defined or implicitly available.

1.2.3 Physical Layer and Media Notation. Users of this standard need to reference which particular implementation is being used or identified. Therefore, a means of identifying each implementation is given by a simple, three-field, type notation that is explicitly stated at the beginning of each relevant section. In general, the Physical Layer type is specified by these fields:

<data rate in Mb/s> <medium type> <maximum segment length (× 100 m)>

For example, the standard contains a 10 Mb/s baseband specification identified as “TYPE 10BASE5,” meaning a 10 Mb/s baseband medium whose maximum segment length is 500 m. Each successive Physical Layer specification will state its own unique TYPE identifier along similar lines.

1.2.4 Physical Layer Message Notation. Messages generated within the Physical Layer, either within or between PLS and the MAU (that is, PMA circuitry), are designated by an italic type to designate either form of physical or logical message used to execute the physical layer signaling process (for example, *input_idle* or *mau_available*).

1.3 References

- [1] CISPR Publication 22 (1985), Limits and Methods of Measurement of Radio Interference Characteristics of Information Technology Equipment.²
- [2] IEC Publication 96-1, Radio-frequency cables, Part 1: General requirements and measuring methods.³
- [3] IEC Publication 96-1A, 1st Supplement to Radio-frequency cables, Part 1: Appendix Section 5.4, Terminated triaxial test method for transfer impedance up to 100 MHz.
- [4] IEC Publication 169-8 and -16, Radio-frequency connectors, Part 8: Radio-frequency coaxial connectors with inner diameter of outer conductor 6.5 mm (0.256 in) with bayonet lock—Characteristic impedance 50 ohms (Type BNC); Part 16: Radio-frequency coaxial connectors with inner diameter of outer conductor 7 mm (0.276 in) with screw coupling—Characteristic impedance 50 ohms (75 ohms) (Type N).
- [5] IEC Publication 380, Safety of electrically energized office machines.
- [6] IEC Publication 435, Safety of data processing equipment.

²CISPR documents are available from the International Electrotechnical Commission, 3 rue de Varembe, Case Postale 131, CH 1211, Genève 20, Switzerland/Suisse. CISPR documents are also available in the United States from the Sales Department, American National Standards Institute, 11 West 42nd Street, 13th Floor, New York, NY 10036, USA.

³IEC publications are available from IEC Sales Department, Case Postale 131, 3 rue de Varembe, CH-1211, Genève 20, Switzerland/Suisse. IEC publications are also available in the United States from the Sales Department, American National Standards Institute, 11 West 42nd Street, 13th Floor, New York, NY 10036, USA.

- [7] IEC Publication 807-2, Rectangular connectors for frequencies below 3 MHz, Part 2: Detail specification for a range of connectors with round contacts—Fixed solder contact types.
- [8] IEC Publication 950, Safety of Information Technology Equipment, Including Electrical Business Equipment.
- [9] ISO 2382-9 : 1984, Data processing—Vocabulary—Part 09: Data communication.⁴
- [10] ISO 7498 : 1984, Information processing systems—open systems interconnection—Basic reference model.
- [11] IEC Publication 60, High-voltage test techniques.
- [12] IEC Publication 68, Environmental testing.
- [13] IEC Publication 793-1, Optical fibres, Part 1: Generic specification.
- [14] IEC Publication 793-2, Optical fibres, Part 2: Product specifications.⁵
- [15] IEC Publication 794-1, Optical fibre cables, Part 1: Generic specification.
- [16] IEC Publication 794-2, Optical fibres cables, Part 2: Product specifications.
- [17] IEC Publication 825, Radiation safety of laser products, equipment classification, requirements, and user's guide.
- [18] IEC Publication 874-1, Connectors for optical fibres and cables, Part 1: Generic specification.
- [19] IEC Publication 874-2, Connectors for optical fibres and cables, Part 2: Sectional specification for fibre optic connector type F-SMA.
- [20] ISO/IEC 7498-4 : 1989, Information processing systems—Open Systems Interconnection—Basic Reference Model—Part 4: Management Framework.
- [21] ISO 8877 : 1987, Information processing systems—Interface connector and contact assignments for ISDN basic access interface located at reference points S and T.

Local and national standards such as those supported by ANSI, EIA, IEEE, MIL, NFPA, and UL are not a formal part of the ISO/IEC 8802-3 standard. Reference to such local or national standards may be useful resource material and are identified by a bracketed number beginning with the letter A and located in Annex A.

1.4 Definitions. The definitions used in this standard are consistent with ISO 2382-9:1984 [9]. A more specific Part 25, pertaining to LAN systems, is in development.

⁴ISO publications are available from the ISO Central Secretariat, Case Postale 56, 1 rue de Varembé, CH-1211, Genève 20, Switzerland/Suisse. ISO publications are also available in the United States from the Sales Department, American National Standards Institute, 11 West 42nd Street, 13th Floor, New York, NY 10036, USA.

⁵ Subsection 9.9 is to be read with the understanding that the following changes to IEC Publication 793-2 [14] have been requested:

- (1) Correction of the numerical aperture tolerance in Table III to ± 0.015 .
- (2) Addition of another bandwidth category, of ≥ 150 MHz referred to 1 km, for the type A1b fiber in Table III.

2. MAC Service Specification

2.1 Scope and Field of Application. This section specifies the services provided by the Media Access Control (MAC) sublayer to the Logical Link Control (LLC) sublayer for the ISO [IEEE] Local Area Network standard (see Fig 2-1). The services are described in an abstract way and do not imply any particular implementation, or any exposed interface. There is not necessarily a one-to-one correspondence between the primitives and the formal procedures and interfaces described in 4.2 and 4.3.




Fig 2-1
Service Specification Relation to the LAN Model

2.2 Overview of the Service

2.2.1 General Description of Services Provided by the Layer. The services provided by the MAC sublayer allow the local LLC sublayer entity to exchange LLC data units with peer LLC sublayer entities. Optional support may be provided for resetting the MAC sublayer entity to a known state.

2.2.2 Model Used for the Service Specification. The model used in this service specification is identical to that used in 1.2.

2.2.3 Overview of Interactions

MA_DATA.request
MA_DATA.indication

2.2.4 Basic Services and Options. The MA_DATA.request and MA_DATA.indication service primitives described in this section are considered mandatory.

2.3 Detailed Service Specification

2.3.1 MA_DATA.request

2.3.1.1 Function. This primitive defines the transfer of data from a local LLC sublayer entity to a single peer LLC entity or multiple peer LLC entities in the case of group addresses.

2.3.1.2 Semantics of the Service Primitive. The semantics of the primitive are as follows:

```
MA_DATA.request    (
    destination_address,
    m_sdu,
    service_class
)
```

The `destination_address` parameter may specify either an individual or a group MAC entity address. It must contain sufficient information to create the DA field that is appended to the frame by the local MAC sublayer entity and any physical information. The `m_sdu` parameter specifies the MAC service data unit to be transmitted by the MAC sublayer entity. There is sufficient information associated with `m_sdu` for the MAC sublayer entity to determine the length of the data unit. The `service_class` parameter indicates a quality of service requested by LLC or higher layer (see 2.3.1.5).

2.3.1.3 When Generated. This primitive is generated by the LLC sublayer entity whenever data shall be transferred to a peer LLC entity or entities. This can be in response to a request from higher protocol layers or from data generated internally to the LLC sublayer, such as required by Type 2 service.

2.3.1.4 Effect of Receipt. The receipt of this primitive will cause the MAC entity to append all MAC specific fields, including DA, SA, and any fields that are unique to the particular media access method, and pass the properly formed frame to the lower protocol layers for transfer to the peer MAC sublayer entity or entities.

2.3.1.5 Additional Comments. The CSMA/CD MAC protocol provides a single quality of service regardless of the `service_class` requested.

2.3.2 MA_DATA.indication

2.3.2.1 Function. This primitive defines the transfer of data from the MAC sublayer entity to the LLC sublayer entity or entities in the case of group addresses.

2.3.2.2 Semantics of the Service Primitive. The semantics of the primitive are as follows:

```
MA_DATA.indication (
    destination_address,
    source_address,
    m_sdu,
    reception_status
)
```

The `destination_address` parameter may be either an individual or a group address as specified by the DA field of the incoming frame. The `source_address` parameter is an individual address as specified by the SA field of the incoming frame. The `m_sdu` parameter specifies the MAC service data unit as received by the local MAC entity. The `reception_status` parameter is used to pass status information to the peer LLC sublayer entity.

2.3.2.3 When Generated. The `MA_DATA.indication` is passed from the MAC sublayer entity to the LLC sublayer entity or entities to indicate the arrival of a frame to the local MAC sublayer entity. Such

frames are reported only if they are validly formed, received without error, and their destination address designates the local MAC entity.

2.3.2.4 Effect of Receipt. The effect of receipt of this primitive by the LLC sublayer is unspecified.

2.3.2.5 Additional Comments. If the local MAC sublayer entity is designated by the destination_address parameter of an MA_DATA.request, the indication primitive will also be invoked by the MAC entity to the local LLC entity. This full duplex characteristic of the MAC sublayer may be due to unique functionality within the MAC sublayer or full duplex characteristics of the lower layers (for example, all frames transmitted to the broadcast address will invoke MA_DATA.indication at all stations in the network including the station that generated the request).

3. Media Access Control Frame Structure

3.1 Overview. This section defines in detail the frame structure for data communication systems using local area network MAC procedures. It defines the relative positions of the various components of the MAC frame. It defines the method for representing station addresses. It defines a partition of the address space into individual (single station) and group (multicast or multistation) addresses, and into user administered and globally administered addresses.

3.1.1 MAC Frame Format. Figure 3-1 shows the eight fields of a frame: the preamble, Start Frame Delimiter (SFD), the addresses of the frame's source and destination, a length field to indicate the length of the following field containing the LLC data to be transmitted, a field that contains padding if required, and the frame check sequence field containing a cyclic redundancy check value to detect errors in received frames. Of these eight fields, all are of fixed size except the LLC data and PAD fields, which may contain any integer number of octets between the minimum and maximum values determined by the specific implementation of the CSMA/CD Media Access mechanism. See 4.4 for particular implementations.




Fig 3-1
MAC Frame Format

The minimum and maximum frame size limits in 4.4 refer to that portion of the frame from the destination address field through the frame check sequence field, inclusive.

Relative to Fig 3-1, the octets of a frame are transmitted from top to bottom, and the bits of each octet are transmitted from left to right.

3.2 Elements of the MAC Frame


3.2.1 Preamble Field. The preamble field is a 7-octet field that is used to allow the PLS circuitry to reach its steady-state synchronization with the received frame timing (see 4.2.5).

3.2.2 Start Frame Delimiter (SFD) Field. The SFD field is the sequence 10101011. It immediately follows the preamble pattern and indicates the start of a frame.


3.2.3 Address Fields. Each MAC frame shall contain two address fields: the Destination Address field and the Source Address field, in that order. The Destination Address field shall specify the destination addressee(s) for which the frame is intended. The Source Address field shall identify the station from which the frame was initiated. The representation of each address field shall be as follows (see Fig 3-2):

- (1) Each address field shall contain either 16 bits or 48 bits. However, at any given time, the Source and Destination Address size shall be the same for all stations on a particular local area network.
- (2) The support of 16 or 48 bit address length for Source and Destination Address shall be left to the manufacturer as an implementation decision. There is no requirement that manufacturers support both sizes.
- (3) The first bit (LSB) shall be used in the Destination Address field as an address type designation bit to identify the Destination Address either as an individual or as a group address. In the Source Address field, the first bit is reserved and set to 0. If this bit is 0, it shall indicate that the address field contains an individual address. If this bit is 1, it shall indicate that the address field contains a group address that identifies none, one or more, or all of the stations connected to the local area network.
- (4) For 48 bit addresses, the second bit shall be used to distinguish between locally or globally administered addresses. For globally administered (or U, universal) addresses, the bit is set to 0. If an address is to be assigned locally, this bit shall be set to 1. Note that for the broadcast address, this bit is also a 1.
- (5) Each octet of each address field shall be transmitted least significant bit first.

48 BIT ADDRESS FORMAT



16 BIT ADDRESS FORMAT



I/G = 0 INDIVIDUAL ADDRESS
 I/G = 1 GROUP ADDRESS
 U/L = 0 GLOBALLY ADMINISTERED ADDRESS
 U/L = 1 LOCALLY ADMINISTERED ADDRESS

Fig 3-2
Address Field Format

3.2.3.1 Address Designation. A MAC sublayer address is of one of two types:

- (1) *Individual Address.* The address associated with a particular station on the network.
- (2) *Group Address.* A multdestination address, associated with one or more stations on a given network. There are two kinds of multicast address:
 - (a) *Multicast-Group Address.* An address associated by higher-level convention with a group of logically related stations.
 - (b) *Broadcast Address.* A distinguished, predefined multicast address that always denotes the set of all stations on a given local area network.

All 1's in the Destination Address field (for 16 or 48 bit address size LANs) shall be predefined to be the Broadcast address. This group shall be predefined for each communication medium to consist of all stations

actively connected to that medium; it shall be used to broadcast to all the active stations on that medium. All stations shall be able to recognize the Broadcast address. It is not necessary that a station be capable of generating the Broadcast address.

The address space shall also be partitioned into locally administered and globally administered addresses. The nature of a body and the procedures by which it administers these global (U) addresses is beyond the scope of this standard.⁶

3.2.4 Destination Address Field. The Destination Address field specifies the station(s) for which the frame is intended. It may be an individual or multicast (including broadcast) address.

3.2.5 Source Address Field. The Source Address field specifies the station sending the frame. The Source Address field is not interpreted by the CSMA/CD MAC sublayer.

3.2.6 Length Field. The length field is a 2-octet field whose value⁷ indicates the number of LLC data octets in the data field. If the value is less than the minimum required for proper operation of the protocol, a PAD field (a sequence of octets) will be added at the end of the data field but prior to the FCS field, specified below. The procedure that determines the size of the pad field is specified in 4.2.8. The length field is transmitted and received with the high order octet first.

3.2.7 Data and PAD Fields. The data field contains a sequence of n octets. Full data transparency is provided in the sense that any arbitrary sequence of octet values may appear in the data field up to a maximum number specified by the implementation of this standard that is used. A minimum frame size is required for correct CSMA/CD protocol operation and is specified by the particular implementation of the standard. If necessary, the data field is extended by appending extra bits (that is, a pad) in units of octets after the LLC data field but prior to calculating and appending the FCS. The size of the pad, if any, is determined by the size of the data field supplied by LLC and the minimum frame size and address size parameters of the particular implementation. The maximum size of the data field is determined by the maximum frame size and address size parameters of the particular implementation.

The length of PAD field required for LLC data that is n octets long is $\max(0, \text{minFrameSize} - (8 \times n + 2 \times \text{addressSize} + 48))$ bits. The maximum possible size of the LLC data field is $\text{maxFrameSize} - (2 \times \text{addressSize} + 48)/8$ octets. See 4.4 for a discussion of implementation parameters; see 4.2.3.3 for a discussion of the minFrameSize.

3.2.8 Frame Check Sequence Field. A cyclic redundancy check (CRC) is used by the transmit and receive algorithms to generate a CRC value for the FCS field. The frame check sequence (FCS) field contains a 4-octet (32-bit) cyclic redundancy check (CRC) value. This value is computed as a function of the contents of the source address, destination address, length, LLC data and pad (that is, all fields except the preamble, SFD, and FCS). The encoding is defined by the following generating polynomial.

$$G(x) = x^{32} + x^{26} + x^{23} + x^{22} + x^{16} + x^{12} + x^{11} + x^{10} + x^8 + x^7 + x^5 + x^4 + x^2 + x + 1$$

Mathematically, the CRC value corresponding to a given frame is defined by the following procedure:

- (1) The first 32 bits of the frame are complemented.
- (2) The n bits of the frame are then considered to be the coefficients of a polynomial $M(x)$ of degree $n-1$. (The first bit of the Destination Address field corresponds to the $x^{(n-1)}$ term and the last bit of the data field corresponds to the x^0 term.)
- (3) $M(x)$ is multiplied by x^{32} and divided by $G(x)$, producing a remainder $R(x)$ of degree <31 .
- (4) The coefficients of $R(x)$ are considered to be a 32-bit sequence.
- (5) The bit sequence is complemented and the result is the CRC.

⁶For information on how to use MAC addresses, see IEEE Std 802-1990, Overview and Architecture. To apply for an Organizationally Unique Identifier for building a MAC address, contact the Registration Authority, IEEE Standards Department, P.O. Box 1331, 445 Hoes Lane, Piscataway, NJ 08855-1331, USA; (908) 562-3813; fax (908) 562-1571.

⁷Packets with a length field value greater than those specified in 4.4.2 may be ignored, discarded, or used in a private manner. The use of such packets is beyond the scope of this standard.

The 32 bits of the CRC value are placed in the frame check sequence field so that the x^{31} term is the left-most bit of the first octet, and the x^0 term is the right most bit of the last octet. (The bits of the CRC are thus transmitted in the order $x^{31}, x^{30}, \dots, x^1, x^0$.) See reference [A18].

3.3 Order of Bit Transmission. Each octet of the MAC frame, with the exception of the FCS, is transmitted low-order bit first.

3.4 Invalid MAC Frame. An invalid MAC frame shall be defined as one that meets at least one of the following conditions:

- (1) The frame length is inconsistent with the length field.
- (2) It is not an integral number of octets in length.
- (3) The bits of the incoming frame (exclusive of the FCS field itself) do not generate a CRC value identical to the one received.

The contents of invalid MAC frames shall not be passed to LLC. The occurrence of invalid MAC frames may be communicated to network management.

4. Media Access Control

4.1 Functional Model of the Media Access Control Method

4.1.1 Overview. The architectural model described in Section 1 is used in this section to provide a functional description of the Local Area Network CSMA/CD MAC sublayer.

The MAC sublayer defines a medium-independent facility, built on the medium-dependent physical facility provided by the Physical Layer, and under the access-layer-independent local area network LLC sublayer. It is applicable to a general class of local area broadcast media suitable for use with the media access discipline known as Carrier Sense Multiple Access with Collision Detection (CSMA/CD).

The LLC sublayer and the MAC sublayer together are intended to have the same function as that described in the OSI model for the Data Link Layer alone. In a broadcast network, the notion of a data link between two network entities does not correspond directly to a distinct physical connection. Nevertheless, the partitioning of functions presented in this standard requires two main functions generally associated with a data link control procedure to be performed in the MAC sublayer. They are as follows:

- (1) Data encapsulation (transmit and receive)
 - (a) Framing (frame boundary delimitation, frame synchronization)
 - (b) Addressing (handling of source and destination addresses)
 - (c) Error detection (detection of physical medium transmission errors)
- (2) Media Access Management
 - (a) Medium allocation (collision avoidance)
 - (b) Contention resolution (collision handling)

The remainder of this section provides a functional model of the CSMA/CD MAC method.

4.1.2 CSMA/CD Operation. This section provides an overview of frame transmission and reception in terms of the functional model of the architecture. This overview is descriptive, rather than definitional; the formal specifications of the operations described here are given in 4.2 and 4.3. Specific implementations for CSMA/CD mechanisms that meet this standard are given in 4.4. Figure 4-1 provides the architectural model described functionally in the sections that follow.

The Physical Layer Signaling (PLS) component of the Physical Layer provides an interface to the MAC sublayer for the serial transmission of bits onto the physical media. For completeness, in the operational description that follows some of these functions are included as descriptive material. The concise specification of these functions is given in 4.2 for the MAC functions and in Section 7 for PLS.

Transmit frame operations are independent from the receive frame operations. A transmitted frame addressed to the originating station will be received and passed to the LLC sublayer at that station. This characteristic of the MAC sublayer may be implemented by functionality within the MAC sublayer or full duplex characteristics of portions of the lower layers.

4.1.2.1 Normal Operation

4.1.2.1.1 Transmission Without Contention. When a LLC sublayer requests the transmission of a frame, the Transmit Data Encapsulation component of the CSMA/CD MAC sublayer constructs the frame from the LLC-supplied data. It appends a preamble and a start of frame delimiter to the beginning of the frame. Using information passed by the LLC sublayer, the CSMA/CD MAC sublayer also appends a PAD at the end of the MAC information field of sufficient length to ensure that the transmitted frame length satisfies a minimum frame size requirement (see 4.2.3.3). It also appends destination and source addresses, a length count field, and a frame check sequence to provide for error detection. The frame is then handed to the Transmit Media Access Management component in the MAC sublayer for transmission.

Transmit Media Access Management then attempts to avoid contention with other traffic on the medium by monitoring the carrier sense signal provided by the Physical Layer Signaling (PLS) component and deferring to passing traffic. When the medium is clear, frame transmission is initiated (after a brief inter-




Fig 4-1

MAC Sublayer Partitioning, Relationship to the ISO Open Systems Interconnection (OSI) Reference Model

frame delay to provide recovery time for other CSMA/CD MAC sublayers and for the physical medium). The MAC sublayer then provides a serial stream of bits to the PLS interface for transmission.

The PLS performs the task of actually generating the electrical signals on the medium that represent the bits of the frame. Simultaneously, it monitors the medium and generates the collision detect signal, which, in the contention-free case under discussion, remains off for the duration of the frame. A functional description of the Physical Layer is given in Sections 7 and beyond.

When transmission has completed without contention, the CSMA/CD MAC sublayer so informs the LLC sublayer using the LLC to MAC interface and awaits the next request for frame transmission.

4.1.2.1.2 Reception Without Contention. At each receiving station, the arrival of a frame is first detected by the PLS, which responds by synchronizing with the incoming preamble, and by turning on the carrier sense signal. As the encoded bits arrive from the medium, they are decoded and translated back into binary data. The PLS passes subsequent bits up to the MAC sublayer, where the leading bits are discarded, up to and including the end of the preamble and Start Frame Delimiter.

Meanwhile, the Receive Media Access Management component of the MAC sublayer, having observed carrier sense, has been waiting for the incoming bits to be delivered. Receive Media Access Management collects bits from the PLS as long as the carrier sense signal remains on. When the carrier sense signal is removed, the frame is truncated to an octet boundary, if necessary, and passed to Receive Data Decapsulation for processing.

Receive Data Decapsulation checks the frame's Destination Address field to decide whether the frame should be received by this station. If so, it passes the Destination Address (DA), the Source Address (SA), and the LLC data unit (LLCDU) to the LLC sublayer along with an appropriate status code indicating reception_complete or reception_too_long. It also checks for invalid MAC frames by inspecting the frame check sequence to detect any damage to the frame enroute, and by checking for proper octet-boundary alignment of the end of the frame. Frames with a valid FCS may also be checked for proper octet boundary alignment.

4.1.2.2 Access Interference and Recovery. If multiple stations attempt to transmit at the same time, it is possible for them to interfere with each other's transmissions, in spite of their attempts to avoid