

Implementation of
ISO/IEC 8824:1990

Information technology — Open Systems Interconnection — Specification of Abstract Syntax Notation One (ASN.1)

UDC 681.3:621.39

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW



Document Sharing Hub

Committees responsible for this British Standard

The preparation of this British Standard was entrusted by the Information Systems Technology Standards Policy Committee (IST/-) to Technical Committee IST/21, upon which the following bodies were represented:

- Association for Payment Clearing Services
- British Computer Society
- British Gas plc
- British Railways Board
- British Telecommunications plc
- Computing Services Association
- Department of Trade and Industry (Alvey — Advanced Network Systems Architecture)
- Department of Trade and Industry (Information Technology Division)
- Department of Trade and Industry (National Physical Laboratory)
- EEA (the Association of Electronics, Telecommunications and Business Equipment Industries)
- HM Treasury (Central Computer and Telecommunications Agency)
- Institute of Chartered Secretaries and Administrators
- Institution of Electrical Engineers
- Inter-universities Computing Committee
- Joint Network Team
- Ministry of Defence
- National Health Services
- United Kingdom Atomic Energy Authority
- University of London Computer Centre

This British Standard, having been prepared under the direction of the Information Systems Technology Standards Policy Committee, was published under the authority of the Standards Board and comes into effect on 30 April 1991

© BSI 10-1999

The following BSI references relate to the work on this standard:
Committee reference IST/21
Draft for comment 88/62755 DC

ISBN 0 580 19553 8

Amendments issued since publication

Amd. No.	Date	Comments

Contents

	Page
Committees responsible	Inside front cover
National foreword	ii
Foreword	v
Text of ISO/IEC 8824	1

National foreword

This British Standard reproduces verbatim ISO/IEC 8824:1990 and implements it as the UK national standard. This British Standard supersedes BS 6962:1988 which is withdrawn.

This British Standard is published under the direction of the Information Systems Technology Standards Policy Committee whose Technical Committee IST/21 has the responsibility to:

- aid enquirers to understand the text;
- present to the responsible international committee any enquiries on interpretation, or proposals for change, and keep UK interests informed;
- monitor related international and European developments and promulgate them in the UK.

NOTE International and European Standards, as well as overseas standards, are available from BSI Sales Department, BSI, Linford Wood, Milton Keynes, MK14 6LE.

A British Standard does not purport to include all the necessary provisions of a contract. Users of British Standards are responsible for their correct application.

Compliance with a British Standard does not of itself confer immunity from legal obligations.

Summary of pages

This document comprises a front cover, an inside front cover, pages i and ii, the ISO/IEC title page, pages ii to vi, pages 1 to 67 and a back cover.

This standard has been updated (see copyright date) and may have had amendments incorporated. This will be indicated in the amendment table on the inside front cover.

**Information technology — Open Systems
Interconnection — Specification of Abstract
Syntax Notation One (ASN.1)**

*Technologies de l'information — Interconnexion de systèmes ouverts —
Spécification de la notation de syntaxe abstraite numéro 1 (ASN.1)*



Reference number
ISO/IEC 8824 : 1990 (E)

Contents

	Page
Foreword	v
Introduction	1
1 Scope	3
2 Normative references	3
3 Definitions	3
4 Abbreviations	7
5 Notation used in this International Standard	7
5.1 Productions	8
5.2 The alternative collections	8
5.3 Example of a production	9
5.4 Layout	9
5.5 Recursion	9
5.6 References to a collection of sequences	9
5.7 References to an item	9
5.8 Tags	9
6 Use of the ASN.1 notation	9
7 The ASN.1 character set	10
8 ASN.1 items	10
8.1 General rules	10
8.2 Type references	10
8.3 Identifiers	11
8.4 Value references	11
8.5 Module reference	11
8.6 Comment	11
8.7 Empty item	11
8.8 Number item	12
8.9 Binary string item	12
8.10 Hexadecimal string item	12
8.11 Character string item	12
8.12 Assignment item	12
8.13 Single character items	12
8.14 Keyword items	13
8.15 Range Separator	14
8.16 Ellipsis	14
9 Module definition	14
10 Referencing type and value definitions	16
11 Assigning types and values	17
12 Definition of types and values	17
13 Notation for the boolean type	19
14 Notation for the integer type	19
15 Notation for the enumerated type	20
16 Notation for the real type	20
17 Notation for the bitstring type	21
18 Notation for the octetstring type	22
19 Notation for the null type	23
20 Notation for sequence types	23
21 Notation for sequence-of types	24
22 Notation for set types	24
23 Notation for set-of types	25
24 Notation for choice types	25

		Page
25	Notation for selection types	26
26	Notation for tagged types	26
27	Notation for the any type	27
28	Notation for the object identifier type	28
29	Notation for character string types	29
30	Notation for types defined in clauses 32–35	30
31	Definition of character string types	30
32	Generalized time	31
33	Universal time	32
34	The external type	33
35	The object descriptor type	34
36	Subtype notation	35
37	Subtype Value Sets	36
37.1	Single Value	36
37.2	Contained Subtype	36
37.3	Value Range	36
37.4	Size Constraint	37
37.5	Permitted Alphabet	37
37.6	Inner Subtyping	37
Annex A (normative) The macro notation		40
A.1	Introduction	40
A.2	Extensions to the ASN.1 character set and items	40
A.2.1	Macroreference	40
A.2.2	Productionreference	40
A.2.3	Localtypereference	40
A.2.4	Localvaluereference	41
A.2.5	Alternation item	41
A.2.6	Definition terminator item	41
A.2.7	Syntactic terminal item	41
A.2.8	Syntactic category keyword items	41
A.2.9	Additional keyword items	42
A.3	Macro definition notation	42
A.4	Use of the new notation	45
Annex B (normative) ISO assignment of OBJECT IDENTIFIER component values		45
Annex C (normative) CCITT assignment of OBJECT IDENTIFIER component values		46
Annex D (normative) Joint assignment of OBJECT IDENTIFIER component values		47
Annex E (informative) Examples and hints		47
E.1	Example of a personnel record	47
E.1.1	Informal Description of Personnel Record	47
E.1.2	ASN.1 description of the record structure	48
E.1.3	ASN.1 description of a record value	48
E.2	Guidelines for use of the notation	49
E.2.1	Boolean	49
E.2.2	Integer	49
E.2.3	Enumerated	49
E.2.4	Real	50

	Page
E.2.5 Bit string	50
E.2.6 Octet string	50
E.2.7 Null	51
E.2.8 Sequence and sequence-of	51
E.2.9 Set	52
E.2.10 Tagged	53
E.2.11 Choice	54
E.2.12 Selection type	55
E.2.13 Any	56
E.2.14 External	56
E.3 An example of the use of the macro notation	56
E.4 Use in identifying abstract syntaxes	57
E.5 Subtypes	58
Annex F (informative) Summary of the ASN.1 notation	61
Table 1 — Universal class tag assignments	8
Table 2 — ASN.1 characters	10
Table 3 — Reserved character sequences	11
Table 4 — NumericString	30
Table 5 — PrintableString	31
Table 6 — List of character string types	31
Table 7 — Applicability of subtype value sets	36
Table A.1 — Sequence specified by items	41

Descriptors: Data processing, information interchange, network interconnection, open systems interconnection, coded character sets, specifications.

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

International Standard ISO/IEC 8824 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*.

This second edition cancels and replaces the first edition (ISO 8824:1987), which has been technically revised.

Annex A, Annex B, Annex C and Annex D form an integral part of this International Standard. Annex E and Annex F are for information only.

Introduction

In the lower layers of the Basic Reference Model (see ISO 7498), each user data parameter of a service primitive is specified as the binary value of a sequence of octets.

In the presentation layer, the nature of user data parameters changes. Application layer standards require the presentation service user data (see ISO 8822) to carry the value of quite complex types, possibly including strings of characters from a variety of character sets. In order to specify the value which is carried, they require a defined notation which does not determine the representation of the value. This is supplemented by the specification of one or more algorithms called **encoding rules** which determine the value of the session layer octets carrying such application layer values (called the **transfer syntax**). The presentation layer protocol (see ISO 8823) can negotiate which transfer syntaxes are to be used.

The purpose of specifying a value is to distinguish it from other possible values. The collection of the value together with the values from which it is distinguished is called a **type**, and one specific instance is a **value** of that type. More generally, a value or type can often be considered as composed of several simpler values or types, together with the relationships between them. The term **datatype** is often used as a synonym for type.

In order to correctly interpret the representation of a value (whether by marks on paper or bits on a communication line), it is necessary to know (usually from the context), the type of the value being represented. Thus the identification of a type is an important part of this International Standard.

A very general technique for defining a complicated type is to define a small number of **simple types** by defining all possible values of the simple types, then combining these simple types in various ways. Some of the ways of defining new types are as follows:

- a) given an (ordered) list of existing types, a value can be formed as an (ordered) sequence of values, one from each of the existing types; the collection of all possible values obtained in this way is a new type; (if the existing types in the list are all distinct, this mechanism can be extended to allow omission of some values from the list);
- b) given a list of (distinct) existing types, a value can be formed as an (unordered) set of values, one from each of the existing types; the collection of all possible values obtained in this way is a new type; (the mechanism can again be extended to allow omission of some values);
- c) given a single existing type, a value can be formed as an (ordered) sequence or (unordered) set of zero, one or more values of the existing type; the (infinite) collection of all possible values obtained in this way is a new type;
- d) given a list of (distinct) types, a value can be chosen from any one of them; the set of all possible values obtained in this way is a new type;
- e) given a type, a new type can be formed as a subset of it by using some structure or order relationship among the values.

Types which are defined in this way are called **structured types**.

Every type defined using the notation specified in this International Standard is assigned a **tag**. The tag is defined either by this International Standard or by the user of the notation.

It is common for the same tag to be assigned to many different types, the particular type being identified by the context in which the tag is used.

The user of the notation may choose to assign distinct tags to two occurrences of a single type, thereby creating two distinct types. This can be necessary when it is required to distinguish which choice has been made in situations such as d) above.

Four classes of tag are specified in the notation.

The first is the **universal** class. Universal class tags are only used as specified within this International Standard, and each tag is either

- a) assigned to a single type; or
- b) assigned to a construction mechanism.

The second class of tag is the **application** class. Application class tags are assigned to types by other standards. Within a particular standard, an application class tag is assigned to only one type.

The third class is the **private** class. Private class tags are never assigned by International Standards. Their use is enterprise specific.

The final class of tag is the **context-specific** class. This is freely assigned within any use of this notation, and is interpreted according to the context in which it is used.

Tags are mainly intended for machine use, and are not essential for the human notation defined in this International Standard. Where, however, it is necessary to require that certain types be distinct, this is expressed by requiring that they have distinct tags. The allocation of tags is therefore an important part of the use of this notation.

NOTE 1 All types which can be defined in the notation of this International Standard have a tag. Given any type, the user of the notation can define a new type with a different tag.

NOTE 2 Encoding rules always carry the tag of a type, explicitly or implicitly, with any representation of a value of the type. The restrictions placed on the use of the notation are designed to ensure that the tag is sufficient to unambiguously determine the actual type, provided the applicable type definitions are available.

This International Standard specifies a notation which both enables complicated types to be defined and also enables values of these types to be specified. This is done without determining the way an instance of this type is to be represented (by a sequence of octets) during transfer. A notation which provides this facility is called a **notation for abstract syntax definition**.

The purpose of this International Standard is to specify a notation for abstract syntax definition called **Abstract Syntax Notation One**, or ASN.1. Abstract Syntax Notation One is used as a semi-formal tool to define protocols. The use of the notation does not necessarily preclude ambiguous specifications. It is the responsibility of the users of the notation to ensure that their specifications are not ambiguous.

This International Standard is supported by other standards which specify **encoding rules**. The application of encoding rules to the value of a type defined by ASN.1 results in a complete specification of the representation of values of that type during transfer (a transfer syntax).

This International Standard is technically aligned with CCITT Recommendation X.208 (1988).

Clauses 7 to 30 (inclusive) of this International Standard define the simple types supported by ASN.1, and specify the notation to be used for referencing simple types and defining structured types. Clauses 7 to 30 also specify the notation to be used for specifying values of types defined using ASN.1.

Clause 31 of this International Standard defines additional types (character string types) which, by the application of encoding rules for character sets, can be equated with the octetstring type.

Clauses 32 to 35 (inclusive) of this International Standard define certain structured types which are considered to be of general utility, but which require no additional encoding rules.

NOTE It is expected that these clauses will be added to, to encompass other common datatypes such as diagnostics, authentication information, accounting information, security parameters and so on.

The value notation and semantic definition for types defined in these clauses are derived from a definition of the type using the ASN.1 notation. This type definition can be referenced by standards defining encoding rules in order to specify encodings for these types.

Clauses 36 and 37 of this International Standard define a notation which enables subtypes to be defined from the values of a parent type.

Annex A is part of this International Standard, and specifies a notation for extending the basic ASN.1 notation. This is called the macro facility.

Annex B is part of this International Standard, and defines the object identifier tree for authorities supported by ISO.

Annex C is part of this International Standard and defines the object identifier tree for authorities supported by CCITT.

Annex D is part of this International Standard and defines the object identifier tree for joint use by ISO and CCITT.

Annex E is not part of this International Standard, and provides examples and hints on the use of the ASN.1 notation.

Annex F is not part of this International Standard, and provides a summary of ASN.1 using the notation of clause 5.

The text of this International Standard, and in particular the Annex B to Annex D, are the subject of joint ISO-CCITT agreement.

1 Scope

This International Standard specifies a notation for abstract syntax definition called Abstract Syntax Notation One (ASN.1).

This International Standard defines a number of simple types, with their tags, and specifies a notation for referencing these types and for specifying values of these types.

This International Standard defines mechanisms for constructing new types from more basic types, and specifies a notation for defining such structured types and assigning them tags, and for specifying values of these types.

This International Standard defines character sets (by reference to other International Standards) for use within ASN.1.

This International Standard defines a number of useful types (using ASN.1), which can be referenced by users of ASN.1.

The ASN.1 notation can be applied whenever it is necessary to define the abstract syntax of information. It is particularly, but not exclusively, applicable to application protocols.

The ASN.1 notation is also referenced by other presentation layer standards which define encoding rules for the simple types, the structured types, the character string types and the useful types defined in ASN.1.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 2375:1985, *Data processing — Procedure for registration of escape sequences*.

ISO 3166:1988, *Codes for the representation of names of countries*.

ISO 6523:1984, *Data interchange — Structure for identification of organizations*.

ISO 7498:1984, *Information processing systems — Open Systems Interconnection — Basic Reference Model (see also CCITT Recommendation X.200)*.

ISO 8601:1988, *Data elements and interchange formats — Information Interchange — Representation of dates and times*.

ISO 8822:1988, *Information processing systems — Open Systems Interconnection — Connection-oriented presentation service definition*.

ISO 8823:1988, *Information processing systems — Open Systems Interconnection — Connection-oriented presentation protocol specification*.

ISO/IEC 8825:1990, *Information technology — Open Systems Interconnection — Specification of Basic Encoding Rules for Abstract Syntax Notation One (ASN.1)*.

CCITT X.208 (1988), *Specification of Abstract Syntax Notation One (ASN.1)*.

CCITT X.121 (1988), *International numbering plan for public data networks*.

3 Definitions

For the purposes of this International Standard the definitions given in ISO 7498 and the following definitions apply.

3.1

value

a distinguished member of a set of values

3.2

type

a named set of values

3.3

simple type

a type defined by directly specifying the set of its values

3.4

structured type

a type defined by reference to one or more other types

3.5

component type

one of the types referenced when defining a structured type

3.6

tag

a type denotation which is associated with every ASN.1 type

3.7

tagging

replacing the existing (possibly the default) tag of a type by a specified tag

3.8

ASN.1 character set

the set of characters, specified in clause 7, used in the ASN.1 notation

3.9

items

named sequences of characters from the ASN.1 character set, specified in clause 8, which are used to form the ASN.1 notation

3.10

type (or value) reference name

a name associated uniquely with a type (or value) within some context

NOTE Reference names are assigned to the types defined in this International Standard; these are universally available within ASN.1. Other reference names are defined in other standards, and are applicable only in the context of that standard.

3.11

ASN.1 encoding rules

rules which specify the representation during transfer of the value of any ASN.1 type; ASN.1 encoding rules enable information being transferred to be identified by the recipient as a specific value of a specific ASN.1 type

3.12

character string type

a type whose values are strings of characters from some defined character set

3.13

boolean type

a simple type with two distinguished values

3.14

true

one of the distinguished values of the boolean type

3.15

false

the other distinguished value of the boolean type

3.16

integer type

a simple type with distinguished values which are the positive and negative whole numbers, including zero (as a single value)

NOTE Particular encoding rules limit the range of an integer, but such limitations are chosen so as not to affect any user of ASN.1.

3.17

enumerated type

a simple type whose values are given distinct identifiers as part of the type notation

3.18

real type

a simple type whose distinguished values (specified in **16.2**) are members of the set of real numbers

3.19

bitstring type

a simple type whose distinguished values are an ordered sequence of zero, one or more bits

NOTE Encoding rules do not limit the number of bits in a bit-string.

3.20

octetstring type

a simple type whose distinguished values are an ordered sequence of zero, one or more octets, each octet being an ordered sequence of eight bits

NOTE Encoding rules do not limit the number of octets in an octet string.

3.21

null type

a simple type consisting of a single value, also called null

NOTE The null value is commonly used where several alternatives are possible, but none of them apply.

3.22

sequence type

a structured type, defined by referencing a fixed, ordered, list of types (some of which may be declared to be optional); each value of the new type is an ordered list of values, one from each component type

NOTE Where a component type is declared to be optional, a value of the new type need not contain a value of that component type.

3.23

sequence-of type

a structured type, defined by referencing a single existing type; each value in the new type is an ordered list of zero, one or more values of the existing type

NOTE Encoding rules do not limit the number of values in a sequence-of value.

3.24

set type

a structured type, defined by referencing a fixed, unordered, list of distinct types (some of which may be declared to be optional); each value in the new type is an unordered list of values, one from each of the component types

NOTE Where a component type is declared to be optional, the new type need not contain a value of that component type.

3.25

set-of type

a structured type, defined by referencing a single existing type; each value in the new type is an unordered list of zero, one or more values of the existing type

NOTE Encoding rules do not limit the number of values in a set-of value.

3.26

tagged type

a type defined by referencing a single existing type and a tag; the new type is isomorphic to the existing type, but is distinct from it

3.27

choice type

a structured type, defined by referencing a fixed, unordered, list of distinct types; each value of the new type is a value of one of the component types

3.28

selection type

a structured type, defined by reference to a component type of a choice type

3.29

any type

a choice type whose component types are unspecified, but are restricted to the set of types which can be defined using ASN.1

3.30

external type

a type whose distinguished values cannot be deduced from their characterisation as external, but which can be deduced from the encoding of such a value; the values may, but need not, be describable using ASN.1, and thus their encodings may, but need not, conform to ASN.1 encoding rules

3.31

information object

a well-defined piece of information, definition, or specification which requires a name in order to identify its use in an instance of communication

3.32

object identifier

a value (distinguishable from all other such values) which is associated with an information object

3.33

object identifier type

a type whose distinguished values are the set of all object identifiers allocated in accordance with the rules of this International Standard

NOTE The rules of this International Standard permit a wide range of authorities to independently associate object identifiers with information objects.

3.34

object descriptor type

a type whose distinguished values are human-readable text providing a brief description of an information object

NOTE An object descriptor value is usually, but not always associated with a single information object. Only an object identifier value unambiguously identifies an information object.

3.35

recursive definitions

a set of ASN.1 definitions which cannot be reordered so that all types used in a construction are defined before the definition of the construction

NOTE Recursive definitions are allowed in ASN.1: the user of the notation has the responsibility for ensuring that those values (of the resulting types) which are used have a finite representation.

3.36

module

one or more instances of the use of the ASN.1 notation for type and value definition, encapsulated using the ASN.1 module notation (see clause 9)

3.37

production

a part of the formal notation used to specify ASN.1, in which allowed sequences of items are associated with a name which can be used to reference those sequences in the definition of new sets of allowed sequences

3.38

Coordinated Universal Time (UTC)

the time scale maintained by the Bureau Internationale de l'Heure (International Time Bureau) that forms the basis of a coordinated dissemination of standard frequencies and time signals

NOTE 1 The source of this definition is Recommendation 460-2 of the Consultative Committee on International Radio (CCIR). CCIR has also defined the acronym for Coordinated Universal Time as UTC.

NOTE 2 UTC is also referred to as Greenwich Mean Time and appropriate time signals are regularly broadcast.

3.39

user (of ASN.1)

the individual or organisation that defines the abstract syntax of a particular piece of information using ASN.1

3.40

subtype (of a parent type)

a type whose values are specified as a subset of the values of some other type (the parent type)

3.41

parent type (of a subtype)

type used to define a subtype

NOTE The parent type may itself be a subtype of some other type.

3.42

subtype specification

a notation which can be used in association with the notation for a type, to define a subtype of that type

3.43

subtype value set

a notation forming part of a subtype specification, specifying a set of values of the parent type which are to be included in the subtype

3.5 this International Standard uses the following terms defined in ISO 8822:

- a) presentation data value; and
- b) (an) abstract syntax; and
- c) abstract syntax name; and
- d) transfer syntax name.

3.6 this International Standard also uses the following term defined in ISO 8823:

- a) presentation context identifier.

3.7 this International Standard also uses the following terms defined in ISO 6523:

- a) issuing organization; and
- b) organization code; and
- c) International Code Designator.

4 Abbreviations

ASN.1	Abstract Syntax Notation One.
UTC	Coordinated Universal Time.
ICD	International Code Designator.
DCC	Data Country Code.
DNIC	Data Network Identification Code.
RPOA	Recognised Private Operating Agency.

5 Notation used in this International Standard

The ASN.1 notation consists of a sequence of characters from the ASN.1 character set specified in clause 7. Each use of the ASN.1 notation contains characters from the ASN.1 character set grouped into items. Clause 8 specifies all the sequences of characters forming ASN.1 items, and names each item.

The ASN.1 notation is specified in clause 9 (and following clauses) by specifying the collection of sequences of items which form valid instances of the ASN.1 notation, and by specifying the semantics of each sequence.

In order to specify these collections, this International Standard uses a formal notation defined in the following sub-clauses.

5.1 Productions

A new (more complex) collection of ASN.1 sequences is defined by means of a production. This uses the names of collections of sequences defined in this International Standard and forms a new collection of sequences by specifying either

- a) that the new collection of sequences is to consist of any sequence contained in any of the original collections; or
- b) that the new collection is to consist of any sequence which can be generated by taking exactly one sequence from each collection, and juxtaposing them in a specified order.

Each production consists of the following parts, on one or several lines, in order:

- a) a name for the new collection of sequences;
- b) the characters
::=
- c) one or more alternative collections of sequences, defined as in 5.2, separated by the character
|

A sequence is present in the new collection if it is present in one or more of the alternative collections. The new collection is referenced in this International Standard by the name in a) above.

Table 1 — Universal class tag assignments

UNIVERSAL 1	Boolean type
UNIVERSAL 2	Integer type
UNIVERSAL 3	Bitstring type
UNIVERSAL 4	Octetstring type
UNIVERSAL 5	Null type
UNIVERSAL 6	Object identifier type
UNIVERSAL 7	Object descriptor type
UNIVERSAL 8	External type
UNIVERSAL 9	Real type
UNIVERSAL 10	Enumerated type
UNIVERSAL 11–15	Reserved for future editions of this International Standard
UNIVERSAL 16	Sequence and Sequence-of types
UNIVERSAL 17	Set and Set-of types
UNIVERSAL 18–22, 25–27	Character string types
UNIVERSAL 23–24	Time types
UNIVERSAL 28–...	Reserved for addenda to this International Standard

NOTE If the same sequence appears in more than one alternative, any semantic ambiguity in the resulting notation is resolved by other parts of the complete ASN.1 sequence.

5.2 The alternative collections

Each of the alternative collections of sequences in “one or more alternative collections of” is specified by a list of names. Each name is either the name of an item, or is the name of a collection of sequences defined by a production in this International Standard.

The collection of sequences defined by the alternative consists of all sequences obtained by taking any one of the sequences (or the item) associated with the first name, in combination with (and followed by) any one of the sequences (or item) associated with the second name, in combination with (and followed by) any one of the sequences (or item) associated with the third name, and so on up to and including the last name (or item) in the alternative.

5.3 Example of a production

```
BitStringValue ::=
    bstring      |
    hstring      |
    {IdentifierList}
```

is a production which associates with the name **BitStringValue** the following sequences:

- a) any bstring (an item); and
- b) any hstring (an item); and
- c) any sequence associated with **IdentifierList**, preceded by a { and followed by a }

NOTE { and } are the names of items containing the single characters { and } (see clause 8).

In this example, **IdentifierList** would be defined by a further production, either before or after the production defining **BitStringValue**.

5.4 Layout

Each production used in this International Standard is preceded and followed by an empty line. Empty lines do not appear within productions. The production may be on a single line, or may be spread over several lines. Layout is not significant.

5.5 Recursion

The productions in this International Standard are frequently recursive. In this case the productions are to be continuously reapplied until no new sequences are generated.

NOTE In many cases, such reapplication results in an unbounded collection of allowed sequences, some or all of which may themselves be unbounded. This is not an error.

5.6 References to a collection of sequences

This International Standard references a collection of sequences (part of the ASN.1 notation) by referencing the first name (before the ::=) in a production; the name is surrounded by " to distinguish it from natural language text, unless it appears as part of a production.

5.7 References to an item

This International Standard references an item by referencing the name of the item; the name is surrounded by " to distinguish it from natural language text, unless it appears as part of a production.

5.8 Tags

A tag is specified by giving its class and the number within the class. The class is one of

- universal
- application
- private
- context-specific.

The number is a non-negative integer, specified in decimal notation.

Restrictions on tags assigned by the user of ASN.1 are specified in clause 26.

Tags in the universal class are assigned in such a way that, for structured types, the top-level structure can be deduced from the tag, and for simple types, the type can be deduced from the tag. Table 1 summarises the assignment of tags in the universal class which are specified in this International Standard.

NOTE Additional tags in the universal class are reserved for assignment by future editions of this International Standard.

6 Use of the ASN.1 notation

6.1 The ASN.1 notation for a type definition shall be "Type" (see 12.1).

6.2 The ASN.1 notation for a value of a type shall be "Value" (see 12.7).

NOTE It is not in general possible to interpret the value notation without knowledge of the type.

6.3 The ASN.1 notation for assigning a type to a type reference name shall be "Typeassignment" (see 11.1).

6.4 The ASN.1 notation for assigning a value to a value reference name shall be "Valueassignment" (see 11.2).

6.5 The notation “Typeassignment” and “Valueassignment” shall only be used within the notation “ModuleDefinition” (but see 9.1).

7 The ASN.1 character set

7.1 An ASN.1 item shall consist of a sequence of the characters listed in Table 2, except as specified in 7.2 and 7.3.

Table 2 — ASN.1 characters

A to Z
a to z
0 to 9
: ; = , { } < .
() [] - ' "

NOTE 1 The additional characters > and | are used in the macro-notation (see Annex A).
NOTE 2 Where equivalent derivative standards are developed by national standards bodies, additional characters may appear in the following items (the last five of which are defined in Annex A):

typereference	(8.2.1)
identifier	(8.3)
valuereference	(8.4)
modulereference	(8.5)
macrolreference	(A.2.1)
productionreference	(A.2.2)
localtypereference	(A.2.3)
localvaluereference	(A.2.4)
astring	(A.2.7)

When additional characters are introduced to accommodate a language in which the distinction between upper-case and lower-case letters is without meaning, the syntactic distinction achieved by dictating the case of the first character of certain of the above ASN.1 items has to be achieved in some other way.

7.2 Where the notation is used to specify the value of a character string type, all characters of the defined character set can appear in the ASN.1 notation, surrounded by the characters " (see 8.11).

7.3 Additional characters may appear in the “comment” item (see 8.6).

7.4 There shall be no significance placed on the typographical style, size, colour, intensity, or other display characteristics.

7.5 The upper and lower case letters shall be regarded as distinct.

8 ASN.1 items

8.1 General rules

8.1.1 The following subclauses specify the characters in ASN.1 items. In each case the name of the item is given, together with the definition of the character sequences which form the item.

NOTE Annex A specifies additional items used in the macro notation.

8.1.2 Each item specified in the following subclauses shall appear on a single line, and (except for the “comment” item) shall not contain spaces.

8.1.3 The length of a line is not restricted.

8.1.4 The items in the sequences specified by this International Standard (the ASN.1 notation) may appear on one line or may appear on several lines, and may be separated by one or more spaces or empty lines.

8.1.5 An item shall be separated from a following item by a space, or by being placed on a separate line, if the initial character (or characters) of the following item is a permitted character (or characters) for inclusion at the end of the characters in the earlier item.

8.2 Type references

Name of item — typereference

8.2.1 A “typereference” shall consist of an arbitrary number (one or more) of letters, digits, and hyphens. The initial character shall be an upper-case letter. A hyphen shall not be the last character. A hyphen shall not be immediately followed by another hyphen.

NOTE The rules concerning hyphen are designed to avoid ambiguity with (possibly following) comment.

8.2.2 A “typereference” shall not be one of the reserved character sequences listed in Table 3.

NOTE Subclause A.2.9 specifies additional reserved character sequences when within a macro definition.

8.3 Identifiers

Name of item — identifier

An “identifier” shall consist of an arbitrary number (one or more) of letters, digits, and hyphens. The initial character shall be a lower-case letter. A hyphen shall not be the last character. A hyphen shall not be immediately followed by another hyphen.

NOTE The rules concerning hyphen are designed to avoid ambiguity with (possibly following) comment.

8.4 Value references

Name of item — valuereference

A “valuereference” shall consist of the sequence of characters specified for an “identifier” in 8.3. In analysing an instance of use of this notation, a “valuereference” is distinguished from an “identifier” by the context in which it appears.

8.5 Module reference

Name of item — modulereference

A “modulereference” shall consist of the sequence of characters specified for a “typereference” in 8.2. In analysing an instance of use of this notation, a “modulereference” is distinguished from a “typereference” by the context in which it appears.

Table 3 — Reserved character sequences

BOOLEAN
INTEGER
BIT
STRING
OCTET
NULL
SEQUENCE
OF
SET
IMPLICIT
CHOICE
ANY
EXTERNAL
OBJECT
IDENTIFIER
OPTIONAL
DEFAULT
COMPONENTS
TRUE
FALSE
BEGIN
END

8.6 Comment

Name of item — comment

8.6.1 A “comment” is not referenced in the definition of the ASN.1 notation. It may, however, appear at anytime between other ASN.1 items, and has no significance.

8.6.2 A “comment” shall commence with a pair of adjacent hyphens and shall end with the next pair of adjacent hyphens or at the end of the line, whichever occurs first. A comment shall not contain a pair of adjacent hyphens other than the pair which opens it and the pair, if any, which ends it. It may include characters which are not in the character set specified in 7.1 (see 7.3).

8.7 Empty item

Name of item — empty

The “empty” item contains no characters. It is used in the notation of clause 5 when alternative sets of sequences are specified, to indicate that absence of all alternatives is possible.

8.8 Number item

Name of item — number

A “number” shall consist of one or more digits. The first digit shall not be zero unless the “number” is a single digit.

8.9 Binary string item

Name of item — bstring

A “bstring” shall consist of an arbitrary number (possibly zero) of zeros and ones, preceded by a single ‘ and followed by the pair of characters:

’B

EXAMPLE — ’01101100’B

8.10 Hexadecimal string item

Name of item — hstring

8.10.1 An “hstring” shall consist of an arbitrary number (possibly zero) of the characters

A B C D E F 0 1 2 3 4 5 6 7 8 9

preceded by a single ‘ and followed by the pair of characters

’H

EXAMPLE — ’AB0196’H

8.10.2 Each character is used to denote the value of a semiocet using a hexadecimal representation.

8.11 Character string item

Name of item — cstring

A “cstring” shall consist of an arbitrary number (possibly zero) of characters from the character set referenced by a character string type, preceded and followed by ". If the character set includes the character ", this character shall be represented in the “cstring” by a pair of ". The character set involved is not limited to the character set listed in Table 2, but is determined by the type for which the “cstring” is a value (see 7.2).

EXAMPLE — "宛姐虻怡絢"

8.12 Assignment item

Name of item — “:=”

This item shall consist of the sequence of characters

:=

NOTE This sequence does not contain any space characters (see 8.1.2).

8.13 Single character items

Names of items —

{
}
<
,
.
(
)
[
]

- (hyphen)

;

An item with any of the names listed above shall consist of the single character forming the name.

NOTE 1 The item “|” is defined in A.2.5.

NOTE 2 The item > is defined in A.2.6.

8.14 Keyword items

Names of items —

BOOLEAN
INTEGER
BIT
STRING
OCTET
NULL
SEQUENCE
OF
SET
IMPLICIT
CHOICE
ANY
EXTERNAL
OBJECT
IDENTIFIER
OPTIONAL
DEFAULT
COMPONENTS
UNIVERSAL
APPLICATION
PRIVATE
TRUE
FALSE
BEGIN
END
DEFINITIONS
EXPLICIT
ENUMERATED
EXPORTS
IMPORTS
REAL
INCLUDES
MIN
MAX
SIZE
FROM
WITH
COMPONENT
PRESENT

ABSENT
DEFINED
BY
PLUS-INFINITY
MINUS-INFINITY
TAGS

Items with the above names shall consist of the sequence of characters in the name.

NOTE 1 Spaces do not occur in these sequences.

NOTE 2 Where these sequences are not listed as reserved sequences in 8.2.2, they are distinguished from other items containing the same characters by the context in which they appear.

8.15 Range separator

Name of item — ..

This item shall consist of the sequence of characters

..

NOTE This sequence does not contain any space characters (see 8.1.2).

8.16 Ellipsis

Name of item — ...

This item shall consist of the sequence of characters

...

NOTE This sequence does not contain any space characters (see 8.1.2).

9 Module definition

9.1 A “ModuleDefinition” is specified by the following productions:

ModuleDefinition ::=

ModuleIdentifier
DEFINITIONS
TagDefault
“::=”
BEGIN
ModuleBody
END

ModuleIdentifier ::=

modulereference
AssignedIdentifier

AssignedIdentifier ::=

ObjectIdentifierValue |
empty

TagDefault ::=

EXPLICIT TAGS |
IMPLICIT TAGS |
empty

ModuleBody ::=

Exports Imports AssignmentList |
empty

Exports ::=

EXPORTS SymbolsExported ; |