



BSI Standards Publication

Information technology — Telecommunications and information exchange between systems — Local and metropolitan area networks — Specific requirements

Part 15-4: Wireless medium access control (MAC) and physical layer (PHY) specifications for low-rate wireless personal area networks (WPANs)

National foreword

This British Standard is the UK implementation of ISO/IEC/IEEE 8802-15-4:2024.

The UK participation in its preparation was entrusted to Technical Committee IST/6, Data communications.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2024
Published by BSI Standards Limited 2024

ISBN 978 0 539 30495 4
ICS 35.110

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 September 2024.

Amendments/corrigenda issued since publication

Date	Text affected
<hr/>	



International
Standard

**ISO/IEC/IEEE
8802-15-4**

**Information technology —
Telecommunications and
information exchange between
systems — Local and metropolitan
area networks — Specific
requirements —**

**Part 15-4:
Wireless medium access control
(MAC) and physical layer (PHY)
specifications for low-rate wireless
personal area networks (WPANs)**

*Technologies de l'information — Télécommunications et échange
d'information entre systèmes — Réseaux locaux et métropolitains
— Exigences spécifiques —*

*Partie 15-4: Spécifications du contrôle d'accès du milieu sans fil
(MAC) et de la couche physique (PHY) pour les réseaux personnels
sans fil de faible débit (WPAN)*

**Third edition
2024-07**

Reference number
ISO/IEC/IEEE 8802-15-4:2024(en)

Full document details: BS ISO/IEC/IEEE 8802-15-4:2024

 **Documents**
Document Sharing Hub
© IEEE 2020



COPYRIGHT PROTECTED DOCUMENT

© IEEE 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from IEEE at the address below.

Institute of Electrical and Electronics Engineers, Inc
3 Park Avenue, New York
NY 10016-5997, USA

Email: stds.ipr@ieee.org
Website: www.ieee.org

Published in Switzerland

IEEE Std 802.15.4™-2020
(Revision of IEEE Std 802.15.4-2015)

IEEE Standard for Low-Rate Wireless Networks

Developed by the
LAN/MAN Standards Committee
of the
IEEE Computer Society

Approved on 6 May 2020

IEEE SA Standards Board

Abstract: The physical layer (PHY) and medium access control (MAC) sublayer specifications for low-data-rate wireless connectivity with fixed, portable, and moving devices with no battery or very limited battery consumption requirements are defined in this standard. In addition, the standard provides modes that allow for precision ranging. PHYs are defined for devices operating in a variety of geographic regions.

Keywords: ad hoc network, IEEE 802.15.4™, low data rate, low power, LR-WPAN, mobility, PAN, personal area network, radio frequency, RF, short range, wireless, wireless network, wireless personal area network, WPAN

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2020 by the Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 23 July 2020. Printed in the United States of America.

IEEE and 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by the Institute of Electrical and Electronics Engineers, Incorporated.

PDF: ISBN 978-1-5044-6689-9 STD24181
Print: ISBN 978-1-5044-6690-5 STDPD24181

IEEE Prohibits discrimination, harassment, and bullying.
For more information, visit <http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html>.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page, appear in all standards and may be found under the heading “Important Notices and Disclaimers Concerning IEEE Standards Documents.” They can also be obtained on request from IEEE or viewed at <https://standards.ieee.org/ipr/disclaimers.html>.

Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents (standards, recommended practices, and guides), both full-use and trial-use, are developed within IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (“IEEE SA”) Standards Board. IEEE (“the Institute”) develops its standards through a consensus development process, approved by the American National Standards Institute (“ANSI”), which brings together volunteers representing varied viewpoints and interests to achieve the final product. IEEE Standards are documents developed through scientific, academic, and industry-based technical working groups. Volunteers in IEEE working groups are not necessarily members of the Institute and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE Standards do not guarantee or ensure safety, security, health, or environmental protection, or ensure against interference with or from other devices or networks. Implementers and users of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

IEEE does not warrant or represent the accuracy or content of the material contained in its standards, and expressly disclaims all warranties (express, implied and statutory) not included in this or any other document relating to the standard, including, but not limited to, the warranties of: merchantability; fitness for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness of material. In addition, IEEE disclaims any and all conditions relating to: results; and workmanlike effort. IEEE standards documents are supplied “AS IS” and “WITH ALL FAULTS.”

Use of an IEEE standard is wholly voluntary. The existence of an IEEE standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE should be considered the approved IEEE standard.

Official statements

A statement, written or oral, that is not processed in accordance with the IEEE SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, or be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position of IEEE.

Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE. However, IEEE does not provide consulting information or advice pertaining to IEEE Standards documents. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to comments or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in revisions to an IEEE standard is welcome to join the relevant IEEE working group.

Comments on standards should be submitted to the following address:

Secretary, IEEE SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854 USA

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

IEEE draft and approved standards are copyrighted by IEEE under U.S. and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

Photocopies

Subject to payment of the appropriate fee, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. A current IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every ten years. When a document is more than ten years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE SA Website at <https://ieeexplore.ieee.org> or contact IEEE at the address listed previously. For more information about the IEEE SA or IEEE's standards development process, visit the IEEE SA Website at <https://standards.ieee.org>.

Errata

Errata, if any, for IEEE standards can be accessed via <https://standards.ieee.org/standard/index.html>. Search for standard number and year of approval to access the web page of the published standard. Errata links are located under the Additional Resources Details section. Errata are also available in IEEE Xplore: <https://ieeexplore.ieee.org/browse/standards/collection/ieee/>. Users are encouraged to periodically check for errata.

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE SA Website at <https://standards.ieee.org/about/sasb/patcom/patents.html>. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

Participants

At the time this standard was sent to ballot, the IEEE P802.15 Working Group had the following voting members:

Robert F. Heile, Chair
Rick Alfvén, Co-Vice Chair
Patrick W. Kinney, Co-Vice Chair
James P. K. Gilb, Working Group Technical Editor
Patrick W. Kinney, Secretary

Gary Stuebing, 802.15.4md Task Group Chair
Don Sturek, 802.15.4md Task Group Vice Chair
Kunal P. Shah, 802.15.4md Technical Editor

Hendrik Ahlendorf	Christopher Hett	Michael McInnis
Koorosh Akhavan	Jay Holcomb	Apurva Mody
Bernd Baer	Oliver Holland	Ayman Naguib
David Barras	Iwao Hosako	Jaroslav Niewczas
Tuncer Baykas	Brima Ibrahim	Paul Nikolich
Philip Beecher	Tetsushi Ikegami	Philip Orlik
Friedbert Berens	Yeong Min Jang	Aditya Padaki
Lennert Bober	Seongah Jeong	Glenn Parsons
Monique Brown	Seong-Soon Joo	Charles Perkins
Chris Calvert	Volker Jungnickel	Albert Petrick
Radhakrishna Canchi	Paul Kettle	Joe Pollard
Jaesang Cha	Shoichi Kitazawa	Clinton Powell
Matthew Chang	Tero Kivinen	Demir Rakanovic
Soo-Young Chang	Daniel Knobloch	Ivan Reede
Clint Chaplin	Ryuji Kohno	Joerg Robert
Sangsung Choi	Fumihide Kojima	Benjamin Rolfe
Boris Danev	Ann Krieger	Ren Sakata
Luc Darmon	Thomas Kuerner	Ruben E. Salazar Cardozo
Hendricus De Ruijter	Jack Lee	Ioannis Sarri
Brandon Dewberry	Mingyu Lee	Peter Sauer
Anthony Fagan	Frank Leong	Nikola Serafimovski
Matthew Gillmore	Huan-Bang Li	Tushar Shah
Tim Godfrey	Zheda Li	Stephen Shellhammer
Jianlin Guo	Sang-Kyu Lim	Karthik Srinivasagopalan
Joachim Hammerschmidt	Thomas Lorbach	Billy Verso
Shinsuke Hara	Masood Maqbool	Johannes Wechsler
Hiroshi Harada	Vinayagam Mariappan	Brian Weis
Timothy Harrington	Alejandro Marquez	Peter Yee
Chris Hartman		Shaun Yu

Major contributions in the revision process were received from the following individuals:

Harry Bims	Tero Kivinen	Kunal P. Shah
Hendricus De Ruijter	Clint Powell	Gary Stuebing
Chris Hett	R. K. Rannow	Don Sturek
Roger Hislop	George Robert	Billy Verso
Klaus Hueske	Benjamin Rolfe	Lisa Ward
Shoichi Kitazawa	Ruben E. Salazar Cardozo	Hidetoshi Yokota

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Thomas Alexander	Werner Hoelzl	Benjamin Rolfe
David Barras	Brima Ibrahim	Ruben E Salazar Cardozo
Philip E. Beecher	Raj Jain	Shigenobu Sasaki
Harry Bims	SangKwon Jeong	Naotaka Sato
Nancy Bravin	Srinivas Kandala	Peter Sauer
Vern Brethour	S. G. Karthik	James Schuessler
Demetrio Bucaneg, Jr	Stuart Kerry	Kunal Shah
William Byrd	Yongbum Kim	Tushar Shah
Paul Cardinal	Patrick Kinney	Robert Stacey
Juan Carreon	Tero Kivinen	Dorothy Stanley
Pin Chang	Jarkko Kneckt	Thomas Starai
Clint Chaplin	Daniel Knobloch	Gary Stuebing
Charles Cook	Jan Kruys	Don Sturek
Boris Danev	Yasushi Kudoh	Mark Sturza
Hendricus De Ruijter	Hyeong Ho Lee	Bo Sun
Brandon Dewberry	Mingyu Lee	Mark-Rene Uchida
Igor Dotlic	Wookbong Lee	Aditya V. Padaki
Edward Eckert	Frank Leong	Dmitri Varsanofiev
Anthony Fagan	Zheda Li	Billy Verso
Michael Fischer	Yong Liu	George Vlantis
Avraham Freedman	Thomas Lorbach	Lisa Ward
James Gilb	Michael McLaughlin	Karl Weber
Matthew Gillmore	Michael McInnis	Scott Willy
Robert Golshan	Ayman Naguib	Andreas Wolf
Randall Groves	Nick S.A. Nikjoo	Chi Xu
Rainer Hach	Tetsu Nishimura	Shang-Te Yang
Joachim Hammerschmidt	Bansi Patel	Kangjin Yoon
Timothy Harrington	Dev Paul	Yu Yuan
Robert Heile	Arumugam Paventhan	Oren Yuen
Jerome Henry	Clinton Powell	Sven Zeisberg
Marco Hernandez	Maximilian Riegel	
	Robert Robinson	

When the IEEE SA Standards Board approved this standard on 6 May 2020, it had the following membership:

Gary Hoffman, *Chair*
Jon Walter Rosdahl, *Vice Chair*
Jean-Philippe Faure, *Past Chair*
Konstantinos Karachalios, *Secretary*

Ted Burse	David J. Law	Mehmet Ulema
J. Travis Griffith	Howard Li	Lei Wang
Grace Gu	Dong Liu	Sha Wei
Guido R. Hiertz	Kevin Lu	Philip B. Winston
Joseph L. Koepfinger*	Paul Nikolich	Daidi Zhong
John D. Kulick	Damir Novosel	Jingyi Zhou
	Dorothy Stanley	

*Member Emeritus

Historical participants

Many individuals have participated in the IEEE P802.15 Working Group during various stages of the standard's development. Since the initial publication, many amendments have added functionality or updated material in this standard, and now three revisions have been published. Here is a historical list of the working group participants who dedicated their valuable time, energy, and knowledge to the advancement of this standard at the time of its original publication and for its revisions. Many of these members also worked on amendments.

The following members of the IEEE P802.15 Working Group participated in the development of the original standard, IEEE Std 802.15.4-2003:

Robert F. Heile, *Chair*
James D. Allen, *Vice Chair*
Patrick W. Kinney, *Secretary*
Michael D. McInnis, *Assistant Secretary and Editor*

Ian C. Gifford, *Task Group 1 Chair*
Stephen J. Shellhammer, *Task Group 2 Chair*
John R. Barr, *Task Group 3 Chair*

Patrick W. Kinney, *Task Group 4 Chair*
Phil Jamieson, *Task Group 4 Vice Chair*
José A. Gutierrez, *Task Group 4 Editor-in-Chief*
Marco Naeve, *Task Group 4 Secretary*

Monique Bourgeois, *MAC Technical Editor*
Said Moridi, *PHY Technical Editor*
Phil Jamieson, *Layer Management Technical Editor*
Greg Breen, *Low-Band PHY Technical Editing*
Ed Callaway, *Networking Technical Editing*
Paul Gorday, *High-Band PHY Technical Editing*
Marco Naeve, *General Description Technical Editing*
David Cypher, *PICs/SDLs Technical Editing*
Robert D. Poor, *Coexistence Technical Editing*
Farron Dacus, *Regulatory Technical Editing*

Roberto Aiello
Masaaki Akahane
Richard Alfvén
Arun Arunachalam
Naiel Askar
Venkat I. Bahl
Daniel Bailey
Jay Bain
James Baker
Jaiganesh Balakrishnan
Anuj Batra
Timothy Blaney
Kenneth Boehike
Stan Bottoms
Mark V. Bowles
Chuck Brabenac
Soo-Young Chang
Francois Po-Shin Chin
Aik Chindapol

Craig Conkling
Anand Dabak
Kai Dombrowski
Mary DuVal
Michael Dydyk
Jason L. Ellis
Mark W. Fidler
Jeff R. Foerster
David S. Furuno
Pierre Gandolfo
Atul Garg
James Gilb
Nada Golmie
Yasuo Harada
Allen Heberling
Barry Herold
Robert Y. Huang
Eran Igler
Katsumi Ishii

Jeyhan Karaoguz
Masami Katagiri
Joy H. Kelly
Stuart J. Kerry
Yongsuk Kim
Young Hwan Kim
Günter Kleindl
Bruce P. Kraemer
DoHoon Kwon
Jim Lansford
David Leeper
Liang Li
Yeong-Chang Maa
Steven March
Ralph Mason
Jim Meyer
Leonard E. Miller
Akira Miura
Andreas Molisch

Antonio Mondragon
Tony Morelli
Chiu Ngo
Kei Obara
Knut Odman
John B. Pardee
Jongun Park
Dave Patton
Marcus Pendergrass
Gregg Rasor
Ivan Reede
Jim Richards
Glyn Roberts
Richard Roberts
William Roberts
Chris Rogers
Philippe Rouzet

Chandos Rypinski
John H. Santhoff
Mark Schrader
Tom Schuster
Erik Schylander
Michael Seals
Nick Shepherd
Gadi Shor
William Shvodian
Thomas Siep
Kazimierz Siwiak
Carl Stevenson
Rene Struik
Shigeru Sugaya
Kazuhisa Takamura
Katsumi Takaoka

Teik-Kheong Tan
Larry Taylor
Stephen E. Taylor
Hans vanLeeuwen
Ritesh Vishwakarma
Thierry Walrant
Jing Wang
Fijio Watanabe
Mathew Welborn
Richard Wilson
Stephen Wood
Edward G. Woodrow
Hirohisa Yamaguchi
Amos Young
Song-Lin Young
Nakache Yves-paul
Jim Zyren

Major contributions were received from the following individuals:

Tony Adamson
David Archer
David Avery
Venkat Bahl
Daniel Bailey
Edul Batliwala
Pratik Bose
Boaz Carmeli
Farron Dacus
Martin Digon
Ian C. Gifford

Ed Hogervorst
Stephen Korfhage
Charles Luebke
Masahiro Maeda
Ian Marsden
Chris Marshall
Paul Marshall
Fred Martin
Ralph Mason
Rod Miller
Phil Rudland

Niels Schutten
Nick Shepherd
Ari Singer
Ralph D'Souza
Carl Stevenson
Mark Tilinghast
Hans Van Leeuwen
Jacco van Muiswinkel
Luis Pereira
Richard Wilson
Wim Zwart

The following members of the IEEE P802.15 Working Group participated in the development of the first revision, IEEE Std 802.15.4-2006:

Robert F. Heile, *Chair*
James D. Allen, *Vice Chair*
Patrick W. Kinney, *Assistant Vice Chair*
James P. K. Gilb, *Editor-in-Chief*
Patrick W. Kinney, *Secretary*
Michael D. McInnis, *Assistant Secretary and Editor*

John R. Barr, *Task Group 3b Chair*
Reed Fisher, *Task Group 3c Chair*
Patrick W. Kinney, *Task Group 4a Chair*
Myung Lee, *Task Group 5 Chair*

Robert D. Poor, *Task Group 4b Chair*
Marco Naeve, *Task Group 4b Vice Chair*
Monique B. Brown, *Task Group 4b Editor-in-Chief*
Eric T. Gnoske, *Task Group 4b Secretary*

Philip E. Beecher, *MAC Contributing Editor*
Monique B. Brown, *MAC Technical Editor*
Edgar H. Callaway, Jr., *MAC Contributing Editor*
Francois Chin, *PHY Contributing Editor*
Robert C. Cragie, *MAC/Security Contributing Editor*
Paul Gorday, *PHY Contributing Editor*

James P. K. Gilb, *Draft D3 Editor-in-Chief*
Øyvind Janbu, *MAC/PHY/Security Contributing Editor*
Marco Naeve, *General Description/PICS Editor, MAC Contributing Editor*
Clinton C. Powell, *PHY Technical Editor*
Joseph Reddy, *Security Contributing Editor*
Zachary Smith, *MAC Contributing Editor*
René Struik, *Security Contributing Editor*
Andreas C. Wolf, *PHY Contributing Editor*

Roberto Aiello	Tian-Wei Huang	Philip Orlik
Richard Alfvin	Hideto Ikeda	Laurent Ouvry
Mikio Aoki	Tetsushi Ikegami	John Pardee
Takashi Arita	Adrian Jennings	Nirmalendu Patra
Larry Arnett	Ho-In Jeon	Dave Patton
Arthur Astrin	Tzyy Hong Jiang	Xiaoming Peng
Yasaman Bahreini	David Julian	Tony Pollock
Jay Bain	Jeyhan Karaoguz	Vidyasagar Premkumar
Alan Berkema	Michael Kelly	Yihong Qi
Bruce Bosco	Stuart Kerry	Raad Raad
Mark Bowles	Jae-Hyon Kim	Pekka Ranta
Charles Brabenac	Jaeyoung Kim	Dani Raphaeli
David Brenner	Jinkyong Kim	Gregg Rasor
Vern Brethour	Yongsuk Kim	Charles Razzell
Ronald Brown	Kursat Kimyacioglu	Ivan Reede
Bill Carney	Matthias Kindler	Yuko Rikuta
Kuor-Hsin Chang	Gunter Kleindl	Terry Robar
Jonathon Cheah	Ryuji Kohno	Glyn Roberts
Kwan-Wu Chin	Mike Krell	Richard Roberts
Sarm-Goo Cho	Yasushi Kudo	Benjamin A. Rolfe
Sungsoo Choi	Akiomi Kunisa	Philippe Rouzet
Yun Choi	Yuzo Kuramochi	Chandos Rypinski
Chun-Ting Chou	Jiun-You Lai	Ali Sadri
Manoj Choudhary	Ismail Lakkis	Saeid Safavi
Celestino Corral	John Lampe	Zafer Sahinoglu
Joe Decuir	Kyung Kuk Lee	Tomoki Saito
Javier Del Prado Pavon	Wooyong Lee	Syed Saleem
Kai Dombrowski	David Leeper	Kamran Sayrafian
Stefan Drude	Huan-Bang Li	Jean Schwoerer
Amal Ekbal	Haixiang Liang	Erik Schylander
Jason Ellis	Ian Macnamara	Alireza Seyedi
Shahriar Emami	Akira Maeki	Sanjeev Sharma
Paul Everest	Patricia Martigne	Siddharth Shetty
Mark W. Fidler	Abbie Mathew	John Shi
Kris Fleming	Taisuke Matsumoto	Shusaku Shimada
Amir Freund	Gustaf Max	Yuichi Shiraki
Camillo Gentile	Michael McLaughlin	Gadi Shor
Ian Gifford	Charlie Mellone	William Shvodian
Sung-Wook Goh	Klaus Meyer	Thomas Siep
Sorin Goldenberg	Samuel Mo	Michael Sim
Vivek Gupta	Andreas Molisch	Kazimierz Siwiak
Rainer Hach	Mark Moore	V. Somayazulu
Robert Hall	Ken Naganuma	Amjad Soomro
Shinsuke Hara	Yves-Paul Nakache	Carl Stevenson
Jeff Harris	Hiroyuki Nakase	Kazuaki Takahashi
Allen Heberling	Saishankar Nandagopalan	Kenichi Takizawa
Eric Heinze	Chiu Ngo	Teik-Kheong Tan
Barry Herold	Erwin Noble	Mike Tanahashi
Keisuke Higuchi	John O'Connor	Yasushi Tanaka
Jin-Meng Ho	Knut Odman	James Taylor
Patrick Houghton	Hiroyo Ogawa	Arnaud Tonnerre
Robert Huang	Yasuyuki Okuma	Ichihiko Toyoda

Jerry Upton
Bart Van Poucke
Chris Weber
Matthew Welborn
Magnus Wiklund

Gerald Wineinger
Patrick Worfolk
Tracy Wright
Hirohisa Yamaguchi
Kamya Yekeh Yazdandoost

Su-Khiong Yong
Zhan Yu
Serdar Yurdakul
Mahmoud Zadeh
Bin Zhen

Major contributions in the revision process were received from the following individuals:

Jon Adams
Helmut P. Adamski
Jonathan Avey
Jon Beniston
Bernd Grohmann
José A. Gutierrez
Jesper Holm
ZhiJian Hu
Phil A. Jamieson
Yuen-Sam Kwok

Colin Lanzl
Myung Lee
Zhongding Lei
Liang Li
Yong Liu
Frederick Martin
Frank Poegel
Matthias Scheide
D. C. Seward

Huai-Rong Shao
Mark Shea
Stephen J. Shellhammer
Mark A. Tillinghast
Johannes Van Leeuwen
Richard Wilson
Ping Xiong
Bing Xu
ChenYang Yang
Chunhui Zhu

The following members of the IEEE P802.15 Working Group participated in the development of the second revision, IEEE Std 802.15.4-2011:

Robert F. Heile, Chair
Rick Alfvin, Co-Vice Chair
Patrick W. Kinney, Co-Vice Chair
James P. K. Gilb, Working Group Technical Editor
Patrick W. Kinney, Secretary

James P. K. Gilb, Task Group 4i Chair and Technical Editor

Emad Afifi
Gahng-Seop Ahn
Roberto Aiello
Arthur Astrin
Taehan Bae
Michael Bahr
John Barr
Anuj Batra
Tuncer Baykas
Philip E. Beecher
Ashutosh Bhatia
Ghulam Bhatti
Gary Birk
Mathew Boytim
Peter David Bradley
Nancy Bravin
David Britz
Monique B. Brown
Sverre Brubk
Brian Buchanan
John Buffington
Kiran Bynam
Brent Cain
Edgar H. Callaway
Chris Calvert

Ruben E. Salazar Cardozo
Douglas Castor
Jaesang Cha
Russell Chandler
Kuo-Hsin Chang
Soo-Young Chang
Clint Chaplin
Hind Chebbo
Chang-Soon Choi
Sangsung Choi
Ciaran Connell
David Cypher
Matthew Dahl
David Davenport
Mark Dawkins
Hendricus de Ruijter
Upkar Dhaliwal
Gang Ding
Paul Dixon
Guido Dolmans
Igor Dotlic
Michael Dow
Dietmar Eggert
David Evans
Charles Farlow

John Farserotu
Jeffrey Fischbeck
Mike Fischer
George Flammer
Ryosuke Fujiwara
Noriyasu Fukatsu
Kiyoshi Fukui
John Geiger
Gregory Gillooly
Tim Godfrey
Paul Gorday
Elad Gottlieb
Robert Hall
Shinsuke Hara
Hiroshi Harada
Timothy Harrington
Rodney Hemminger
Marco Hernandez
Garth Hillman
Jin-Meng Ho
Wei Hong
Srinath Hosur
David Howard
Jung-Hwan Hwang
Taeho Hwang

Ichirou Ida	Robert Moskowitz	Steve Shearer
Tetsushi Ikegami	Hamilton Moy	Stephen Shellhammer
Akio Iso	Peter Murray	Shusaku Shimada
Yeong Min Jang	Theodore Myers	Chang Sub Shin
Adrian Jennings	Chiu Ngo	Cheol Ho Shin
Wuncheol Jeong	Paul Nikolich	Michael Sim
Steven Jillings	Hirohito Nishiyama	Jonathan Simon
Noh-Gyoung Kang	David Olson	Jaeseung Son
Tae-Gyu Kang	Okundu Omeni	Paul Stadnik
Shuzo Kato	Ryoji Ono	René Struik
Tatsuya Kato	Laurent Ouvry	Chin-Sean Sum
Jeritt Kent	James Pace	Hui-Hsia Sung
Prithpal Khakuria	Hyung-Il Park	Gu Sungi
Dae Ho Kim	Jahng Park	Kenichi Takizawa
Dong-Sun Kim	Seung-Hoon Park	Hirokazu Tanaka
Dukhyun Kim	Taejoon Park	Larry Taylor
Jaehwan Kim	Ranjeet Patro	Mark Thompson
Jeffrey King	Al Petrick	James Tomcik
Ryuji Kohno	Dalibor Pokrajac	Ichihiko Toyoda
Fumihide Kojima	Daniel Popa	David Tracey
Bruce Kraemer	Stephen Pope	Khanh Tran
Raymond Krasinski	Clinton C. Powell	Jerry Upton
Masahiro Kuroda	Richard Powell	Jana van Greunen
John Lampe	Chang-Woo Pyo	Hartman van Wyk
Zhou Lan	Mohammad Rahman	Michel Veillette
Khanh Le	Sridhar Rajagopal	Billy Verso
Cheolhyo Lee	Jayaram Ramasastry	Bhupender Virk
Hyungsoo Lee	Marc Reed	Joachim Walewski
Myung Lee	Ivan Reede	Junyi Wang
Daniel Lewis	Richard Roberts	Quan Wang
Huan-Bang Li	Craig Rodine	Xiang Wang
Liang Li	June Chul Roh	Andy Ward
Sang-Kyu Lim	Benjamin A. Rolfe	Scott Weikel
Jeremy Link	Seung-Moon Ryu	Nicholas West
Mike Lynch	Didier Sagan	Mark Wilbur
Robert Mason	Kentaro Sakamoto	Ludwig Winkel
Tomokuni Matsumura	Will San Filippo	Eun Tae Won
Jeff McCullough	H. Sanderford	Alan Chi Wai Wong
Michael McGillan	Kamran Sayrafian	Tao Xing
Michael D. McInnis	Timothy Schmidl	Wen-Bin Yang
Michael McLaughlin	Michael Schmidt	Yang Yang
Charles Millet	Jean Schwoerer	Kazuyuki Yasukawa
Siamak Mirnezami	Cristina Seibert	Kamya Yazdandoost
Rishi Mohindra	Neal Seidl	Kaoru Yokoo
Emmanuel Monnerie	Kunal Shah	Mu Zhao
Rajendra Moorti		Bin Zhen

Major contributions in the revision process were received from the following individuals:

Philip E. Beecher	Clint Chaplin	Clinton C. Powell
Vern Brethour	James P. K. Gilb	Benjamin A. Rolfe
Monique B. Brown	Patrick W. Kinney	Timothy Schmidl
Edgar H. Callaway	Michael D. McInnis	René Struik
Kuor-Hsin Chang		Billy Verso

The following members of the IEEE P802.15 Working Group participated in the development of the second revision, IEEE Std 802.15.4-2015:

Robert F. Heile, Chair
Rick Alfvén, Co-Vice Chair
Patrick W. Kinney, Co-Vice Chair
James P. K. Gilb, Working Group Technical Editor
Patrick W. Kinney, Secretary

Patrick W. Kinney, 802.15 Maintenance Committee Chair
Benjamin A. Rolfe, 802.15 Maintenance Committee Vice Chair
James P. K. Gilb, Technical Editor

Mounir Achir	Shinsuke Hara	Robert Moskowitz
Keiji Akiyama	Timothy Harrington	Jinesh P. Nair
Arthur Astrin	James Hartman	Chiu Ngo
Philip Beecher	Marco Hernandez	Paul Nikolich
Frederik Beer	Ken Hiraga	John Notor
Chandrashekhara P. S. Bhat	Iwao Hosako	Hiroyo Ogawa
Kiran Bynam	Yeong Min Jang	Taejoon Park
Edgar Callaway	Seong-Soon Joo	Glenn Parsons
Chris Calvert	Akifumi Kasamatsu	Charles Perkins
Radhakrishna Canchi	Shuzo Kato	Albert Petrick
Kapseok Chang	Toyoyuki Kato	Clinton C. Powell
Soo-Young Chang	Jeritt Kent	Verotiana Rabarijaona
Clint Chaplin	Jaehwan Kim	Ivan Reede
Stephen Chasko	Youngsoo Kim	Richard Roberts
Paul Chilton	Shoichi Kitazawa	Ruben E. Salazar Cardozo
Sangsung Choi	Tero Kivinen	
Hendricus de Ruijter	Ryuji Kohno	Noriyuki Sato
Guido Dolmans	Fumihide Kojima	Norihiko Sekine
Igor Dotlic	Thomas Kuerner	Kunal Shah
Stefan Drude	Byung-Jae Kwak	Stephen Shellhammer
Dietmar Eggert	Jae Seung Lee	Shusaku Shimada
Shahriar Emami	Myung Lee	Gary Stuebing
Andrew Estrada	Sangjae Lee	Don Sturek
David Evans	Huan-Bang Li	Mineo Takai
George Flammer	Liang Li	Kou Togashi
Kiyoshi Fukui	Qing Li	Billy Verso
Matthew Gillmore	Michael Lynch	Gabriel Villardi
Tim Godfrey	Itaru Maekawa	Brian Weis
Elad Gottlieb	Hirofumi Matsumura	Makoto Yaita
Jussi Haapola	Michael McLaughlin	Peter Yee
Rainer Hach	Michael McInnis	Yu Zeng
	Kenichi Mori	Chunhui (Allan) Zhu

Major contributions in the revision process were received from the following individuals:

Philip Beecher	Jeritt Kent	Benjamin A. Rolfe
Monique Brown	Patrick W. Kinney	Ruben E. Salazar Cardozo
Edgar Callaway	Tero Kivinen	Cristina Seibert
Soo-Young Chang	Amarjeet Kumar	Kunal Shal
James P. K. Gilb	Michael McInnis	Shusaku Shimada
Tim Godfrey	Robert Moskowitz	Chin-Sean Sum
Jussi Haapola	Clinton C. Powell	Larry Taylor
Timothy Harrington	Verotiana Rabarijaona	Billy Verso

Introduction

This introduction is not part of IEEE Std 802.15.4-2020, IEEE Standard for Low-Rate Wireless Networks.

This is the fourth revision of IEEE Std 802.15.4. From the beginning, the goal of the IEEE P802.15 Working Group was to produce a standard that enabled very low-cost, low-power communications. The initial standard, IEEE Std 802.15.4-2003, defined two optional physical layers (PHYs), operating in different frequency bands with a simple and effective medium access control (MAC).

In 2006, the standard was revised and added two more PHY options. The MAC remained backward compatible, but the revision added MAC frames with an increased version number and a variety of MAC enhancements, including the following:

- Support for a shared time base with a data timestamping mechanism
- Support for beacon scheduling
- Synchronization of broadcast messages in beacon-enabled personal area networks (PANs)
- Improved MAC layer security

In 2011, the standard was revised to include the three amendments approved subsequent to the 2006 revision. This effort added four more PHY options along with the MAC capability to support ranging. Additionally, the organization of the standard was changed so that each PHY would have a separate clause, and the MAC clause was split into functional description, interface specification, and security specification.

The 2015 revision of the standard was created to roll in the amendments approved subsequent to the 2011 revision: six PHY amendments and one MAC amendment, with corrigenda and clarifications. The features added by the amendments include the following:

- Enhanced frame formats maintaining backward compatibility
- Information Elements (IEs)
- Channel agility
- Extended superframe options
- Low-energy mechanisms
- An enhanced acknowledgment frame that can carry data and can be secured
- Prioritized channel access
- A variety of new PHY modulation, coding, and band options to support a wide variety of application needs including radio frequency identification (RFID), smart utility networks (SUNs), television white space (TVWS) operation, low-energy critical infrastructure monitoring (LECIM), and rail communications and control (RCC)

Much of the corrigenda and clarifications were collected from requests from individuals after the revision in 2011. Major corrigenda items included changes to the security text to correct errors and clarify the text, removal of the encrypt only mode, addition of security policy checks for the IEs, corrections regarding personal area network identifier (PAN ID) compression behavior to eliminate ambiguous specification, and changes to the IEs subclauses to include more information necessary for users of this standard.

The Project Authorization Request (PAR) for IEEE Std 802.15.4-2015 was first proposed in July 2013 and was approved in October 2013 by IEEE's New Standards Committee (NesCom). After three working group ballots and two IEEE SA Committee ballots, the final standard was approved in December 2015, just over two years from start to finish.

The current revision of the standard was revised to include six approved amendments subsequent to the 2015 revision. This effort added two more PHY amendments and one MAC amendment, with corrigenda and clarifications. The features added by the amendments include the following:

- A variety of new PHY modulation, coding, and band options to support a wide variety of application needs including smart utility networks (SUNs), china medical band (CMB), ternary amplitude shift keying (TASK) and rate switch Gaussian frequency shift keying (RS-GFSK)

Much of the corrigenda and clarifications were collected from requests from individuals after the revision in 2015. Major corrigenda items included changes to the transmission order of the address field.

Contents

1.	Overview.....	33
1.1	Scope.....	33
1.2	Purpose.....	33
2.	Normative references.....	34
3.	Definitions, acronyms, and abbreviations.....	35
3.1	Definitions	35
3.2	Acronyms and abbreviations	36
4.	Format conventions.....	40
4.1	General.....	40
4.2	Fields.....	40
4.3	Numbers.....	41
4.4	Strings	41
4.5	Transmission order	41
4.5.1	General.....	41
4.5.2	Vendor OUI transmission order.....	42
4.6	Reserved fields and values.....	42
5.	General description.....	43
5.1	Introduction.....	43
5.2	Special application spaces	43
5.2.1	General.....	43
5.2.2	Smart utility network (SUN).....	43
5.2.3	Rail communications and control (RCC).....	43
5.2.4	Television white space (TVWS).....	44
5.2.5	Radio frequency identification (RFID).....	44
5.2.6	Low-energy, critical infrastructure monitoring (LECIM)	44
5.2.7	Medical body area network (MBAN) services.....	44
5.2.8	China medical band (CMB).....	44
5.3	Components of the IEEE 802.15.4 WPAN.....	45
5.4	Multi-PHY management (MPM) of the SUN WPAN.....	45
5.5	Network topologies.....	45
5.5.1	General.....	45
5.5.2	Star network formation	46
5.5.3	Peer-to-peer network formation.....	46
5.6	Architecture	47
5.6.1	General.....	47
5.6.2	PHY	48
5.6.3	MAC sublayer.....	49
5.7	Functional overview	49
5.7.1	Superframe structure.....	49
5.7.2	Data transfer model.....	51
5.7.3	Frame structure	52
5.7.4	Information element (IEs).....	52
5.7.5	Access methods.....	52
5.7.6	Power consumption considerations	53

5.7.7	Security	54
5.7.8	Enabling spectrum resource measurement capability	55
5.8	Concept of primitives	56
6.	MAC functional description	57
6.1	Device types and conventions	57
6.2	Channel access	57
6.2.1	Superframe structure	57
6.2.2	Incoming and outgoing superframe timing	59
6.2.3	Enhanced Beacon frame timing for MPM procedure	60
6.2.4	IFS	61
6.2.5	Random access methods	62
6.2.6	TSCH slotframe structure	69
6.2.7	LE functional description	71
6.2.8	Superframe use for TMCTP operation	71
6.2.9	Rail communications and control network (RCCN) superframe structure	72
6.2.10	Channel hopping	73
6.3	Starting and maintaining PANs	75
6.3.1	Scanning through channels	75
6.3.2	PAN ID conflict resolution	81
6.3.3	Starting and realigning a PAN	82
6.3.4	Beacon generation	84
6.3.5	Device discovery	86
6.3.6	TSCH PAN formation	86
6.4	Association and disassociation	88
6.4.1	Association	88
6.4.2	Disassociation	91
6.4.3	Fast association	92
6.5	Synchronization	93
6.5.1	General	93
6.5.2	Synchronization with beacons	93
6.5.3	Synchronization without beacons	95
6.5.4	Synchronization in TSCH PAN	95
6.5.5	Orphaned device realignment	98
6.6	Transaction handling	98
6.7	Transmission, reception, and acknowledgment	100
6.7.1	Transmission	100
6.7.2	Reception and rejection	101
6.7.3	Extracting pending data from a coordinator	103
6.7.4	Use of acknowledgments and retransmissions	104
6.7.5	Transmission timing restrictions	107
6.7.6	Guard time	108
6.7.7	Promiscuous mode	109
6.7.8	Transmission scenarios	109
6.7.9	Device announcement	111
6.8	GTS allocation and management	111
6.8.1	GTS general requirements	111
6.8.2	CAP maintenance	112
6.8.3	GTS allocation	112
6.8.4	GTS usage	113
6.8.5	GTS deallocation	114
6.8.6	GTS reallocation	115
6.8.7	GTS expiration	117

6.9	Ranging.....	117
6.9.1	Ranging requirements	117
6.9.2	Set-up activities before a ranging exchange	118
6.9.3	Finish-up activities after a ranging exchange	118
6.9.4	Managing DPS	118
6.9.5	The ranging exchange	120
6.10	PHY parameter change notification procedure.....	120
6.10.1	Signaling using Beacon frames.....	120
6.10.2	Signaling using multipurpose frames	121
6.11	Deterministic and synchronous multichannel extension (DSME).....	122
6.11.1	DSME command requirements.....	122
6.11.2	DSME multi-superframe structure.....	122
6.11.3	Channel diversity	124
6.11.4	CAP reduction.....	126
6.11.5	DSME GTS allocation and management	127
6.11.6	Beacon scheduling	133
6.11.7	Time synchronization	134
6.11.8	Deferred beacon.....	135
6.11.9	Passive channel scan.....	135
6.12	LE transmission, reception, and acknowledgment	136
6.12.1	LE transmission, reception, and acknowledgment with positive handshakes	136
6.12.2	Coordinated sampled listening (CSL).....	136
6.12.3	RIT	140
6.12.4	Implicit RIT (I-RIT).....	143
6.13	Starting and maintaining TMCTPs.....	143
6.14	MPM procedure for inter-PHY coexistence	147
6.15	TVWS access procedures	149
6.15.1	General.....	149
6.15.2	Channel timing management (CTM).....	150
6.16	Spectrum Resource Measurement (SRM)	151
6.16.1	General.....	151
6.16.2	SRM Performance Metrics	151
6.16.3	SRM functionality.....	157
6.17	Using Link Margin IE.....	160
7.	MAC frame formats.....	161
7.1	Device extended address.....	161
7.2	General MAC frame format.....	161
7.2.1	General.....	161
7.2.2	Frame Control field.....	162
7.2.3	Sequence Number field.....	165
7.2.4	Destination PAN ID field	166
7.2.5	Destination Address field.....	166
7.2.6	Source PAN ID field.....	166
7.2.7	Source Address field.....	166
7.2.8	Auxiliary Security Header field.....	166
7.2.9	IE field	166
7.2.10	Frame Payload field.....	167
7.2.11	FCS field.....	167
7.3	Format of individual frame types.....	169
7.3.1	Beacon frame format	169
7.3.2	Data frame format.....	173
7.3.3	Ack frame format.....	174

7.3.4	MAC command frame format.....	175
7.3.5	Multipurpose frame format.....	176
7.3.6	Extended frame format	179
7.4	IEs	179
7.4.1	IE list termination	179
7.4.2	Header IEs.....	180
7.4.3	Payload IEs	197
7.4.4	Nested IE.....	198
7.5	MAC commands	237
7.5.1	Command ID field	237
7.5.2	Association Request command.....	239
7.5.3	Association Response command	240
7.5.4	Disassociation Notification command.....	241
7.5.5	Data Request command	242
7.5.6	PAN ID Conflict Notification command.....	243
7.5.7	Orphan Notification command	243
7.5.8	Beacon Request command.....	243
7.5.9	Enhanced Beacon Request command.....	243
7.5.10	Coordinator Realignment command.....	244
7.5.11	GTS request command.....	245
7.5.12	DSME Association Request command.....	246
7.5.13	DSME Association Response command	247
7.5.14	DSME GTS Request command	249
7.5.15	DSME GTS Response command.....	251
7.5.16	DSME GTS Notify command.....	253
7.5.17	DSME Information Request command.....	254
7.5.18	DSME Information Response command	254
7.5.19	DSME Beacon Allocation Notification command	255
7.5.20	DSME Beacon Collision Notification command.....	256
7.5.21	DSME Link Report command	256
7.5.22	RIT Data Request command.....	257
7.5.23	DBS Request command.....	258
7.5.24	DBS Response command.....	259
7.5.25	RIT Data Response command	260
7.5.26	SRM Request command	260
7.5.27	SRM Response command.....	262
7.5.28	SRM Report command	262
7.5.29	SRM Information command	263
7.5.30	Vendor Specific command.....	264
8.	MAC services	265
8.1	Overview.....	265
8.2	MAC management service.....	265
8.2.1	Primitives supported by the MLME-SAP interface.....	265
8.2.2	Common requirements for MLME primitives.....	267
8.2.3	Association primitives	268
8.2.4	Disassociation primitives.....	275
8.2.5	Communications notification primitives	278
8.2.6	Primitives for reading and writing PIB attributes.....	285
8.2.7	GTS management primitives	288
8.2.8	Primitives for orphan notification.....	291
8.2.9	Primitives for resetting the MAC sublayer	293
8.2.10	Primitives for specifying the receiver enable time	294

8.2.11	Primitives for channel scanning.....	296
8.2.12	Primitives for updating the superframe configuration.....	301
8.2.13	Primitives for synchronizing with a coordinator.....	305
8.2.14	Primitives for requesting data from a coordinator.....	308
8.2.15	Primitives for specifying dynamic preamble.....	310
8.2.16	Primitives for channel sounding.....	311
8.2.17	Primitives for ranging calibration.....	313
8.2.18	Primitives for Beacon Generation.....	314
8.2.19	Primitives for TSCH.....	318
8.2.20	Primitives for DSME GTS management.....	325
8.2.21	Primitives for reporting the link status.....	332
8.2.22	Operating parameter change primitives.....	334
8.2.23	TMCTP DBS allocation primitives.....	338
8.2.24	Primitives for device announcement.....	342
8.2.25	RIT data commands.....	344
8.2.26	Primitives for SRM.....	350
8.3	MAC data service.....	365
8.3.1	General.....	365
8.3.2	MCPS-DATA.request.....	365
8.3.3	MCPS-DATA.confirm.....	370
8.3.4	MCPS-DATA.indication.....	373
8.3.5	MCPS-PURGE.request.....	376
8.3.6	MCPS-PURGE.confirm.....	376
8.4	MAC constants and PIB attributes.....	377
8.4.1	General.....	377
8.4.2	MAC constants.....	377
8.4.3	MAC PIB attributes.....	378
9.	Security.....	400
9.1	Overview.....	400
9.2	Functional description.....	400
9.2.1	General.....	400
9.2.2	Outgoing frame security procedure.....	400
9.2.3	KeyDescriptor lookup procedure.....	402
9.2.4	Incoming frame security procedure, Security Enabled field is set to one.....	402
9.2.5	Incoming frame security procedure, Security Enabled field is set to zero.....	404
9.2.6	DeviceDescriptor lookup procedure.....	405
9.2.7	SecurityLevelDescriptor lookup procedure.....	406
9.2.8	Incoming IE security level checking procedure.....	406
9.2.9	Incoming IE key usage policy checking procedure.....	407
9.2.10	Incoming security level checking procedure.....	407
9.2.11	Incoming key usage policy checking procedure.....	407
9.3	Security operations.....	408
9.3.1	General.....	408
9.3.2	Integer and octet representation.....	408
9.3.3	AEAD nonce.....	408
9.3.4	AEAD prerequisites.....	410
9.3.5	AEAD transformation data representation.....	410
9.3.6	AEAD inverse transformation data representation.....	411
9.4	Auxiliary security header.....	412
9.4.1	General.....	412
9.4.2	Security Control field.....	412
9.4.3	Frame Counter field.....	414

9.4.4	Key Identifier field.....	415
9.5	Security-related MAC PIB attributes.....	415
10.	General PHY requirements.....	421
10.1	General.....	421
10.1.1	Requirements and definitions	421
10.1.2	Operating frequency range.....	422
10.1.3	Channel assignments.....	429
10.1.4	Minimum LIFS and SIFS periods.....	454
10.1.5	RF power measurement	454
10.1.6	Transmit power	454
10.1.7	Out-of-band spurious emission	454
10.1.8	Receiver sensitivity definitions.....	454
10.1.9	Common signaling mode (CSM) for SUN PHY	454
10.2	General radio specifications.....	455
10.2.1	General.....	455
10.2.2	TX-to-RX turnaround time	455
10.2.3	RX-to-TX turnaround time	455
10.2.4	Error-vector magnitude (EVM) definition.....	456
10.2.5	Receiver maximum input level of desired signal.....	456
10.2.6	Receiver ED	457
10.2.7	Link quality indicator (LQI)	457
10.2.8	Clear channel assessment (CCA).....	457
11.	PHY services	459
11.1	Overview.....	459
11.2	PHY constants.....	459
11.3	PHY PIB attributes	459
12.	O-QPSK PHY	467
12.1	PPDU format.....	467
12.1.1	General.....	467
12.1.2	SHR field format.....	467
12.1.3	PHR field format.....	467
12.2	Modulation and spreading	468
12.2.1	General.....	468
12.2.2	Data rate.....	468
12.2.3	Reference modulator diagram.....	468
12.2.4	Bit-to-symbol mapping	468
12.2.5	Symbol-to-chip mapping	469
12.2.6	O-QPSK modulation.....	470
12.2.7	Pulse shape.....	470
12.2.8	Chip transmission order.....	471
12.3	O-QPSK PHY RF requirements	471
12.3.1	Operating frequency range.....	471
12.3.2	Transmit power spectral density (PSD) mask.....	472
12.3.3	Symbol rate.....	472
12.3.4	Receiver sensitivity.....	472
12.3.5	Receiver interference rejection	472
12.3.6	TX-to-RX turnaround time	473
12.3.7	RX-to-TX turnaround time	473

12.3.8	EVM.....	473
12.3.9	Transmit center frequency tolerance.....	473
12.3.10	Transmit power	473
12.3.11	Receiver maximum input level of desired signal.....	473
12.3.12	Receiver ED	473
12.3.13	LQI.....	473
13.	Binary phase-shift keying (BPSK) PHY	474
13.1	PPDU format.....	474
13.2	Modulation and spreading	474
13.2.1	General.....	474
13.2.2	BPSK PHY data rates	474
13.2.3	Reference modulator.....	474
13.2.4	Differential encoding	474
13.2.5	Bit-to-chip mapping.....	475
13.2.6	BPSK modulation	475
13.3	BPSK PHY RF requirements.....	475
13.3.1	Operating frequency range.....	475
13.3.2	915 MHz band transmit PSD mask.....	475
13.3.3	Symbol rate.....	476
13.3.4	Receiver sensitivity.....	476
13.3.5	Receiver interference rejection	476
13.3.6	TX-to-RX turnaround time	476
13.3.7	RX-to-TX turnaround time	477
13.3.8	EVM.....	477
13.3.9	Transmit center frequency tolerance.....	477
13.3.10	Transmit power	477
13.3.11	Receiver maximum input level of desired signal.....	477
13.3.12	Receiver ED	477
13.3.13	LQI.....	477
14.	Chirp spread spectrum (CSS) PHY	478
14.1	CSS PPDU format	478
14.1.1	General.....	478
14.1.2	Preamble field	478
14.1.3	SFD field.....	478
14.1.4	PHR field	479
14.1.5	PHY Payload field	479
14.2	Modulation and spreading	479
14.2.1	General.....	479
14.2.2	Data rates	479
14.2.3	Reference modulator.....	479
14.2.4	De-multiplexer (DEMUX).....	479
14.2.5	Serial-to-parallel mapping	479
14.2.6	Data-symbol-to-bi-orthogonal-codeword mapping	480
14.2.7	Parallel-to-serial converter and QPSK symbol mapping.....	484
14.2.8	DQPSK coding	484
14.2.9	DQPSK-to-DQCSK modulation.....	485
14.2.10	CSK generator.....	485
14.2.11	Bit interleaver	485
14.3	Waveform and subchirp sequences.....	486
14.3.1	General.....	486

14.3.2	Graphical presentation of chirp symbols (subchirp sequences).....	486
14.3.3	Active usage of time gaps.....	486
14.3.4	Mathematical representation of the continuous time CSS base-band signal	487
14.3.5	Raised cosine window for chirp pulse shaping.....	489
14.3.6	Subchirp transmission order	489
14.3.7	Example of CSK signal generation.....	490
14.4	CSS RF requirements.....	491
14.4.1	General.....	491
14.4.2	Transmit power spectral density (PSD) mask and signal tolerance.....	491
14.4.3	Symbol rate.....	491
14.4.4	Receiver sensitivity.....	491
14.4.5	Receiver interference rejection	491
14.4.6	TX-to-RX turnaround time	492
14.4.7	RX-to-TX turnaround time	492
14.4.8	Transmit center frequency tolerance.....	493
14.4.9	Transmit power	493
14.4.10	Receiver maximum input level of desired signal.....	493
14.4.11	Receiver ED	493
14.4.12	LQI.....	493
15.	HRP UWB PHY	494
15.1	General.....	494
15.2	HRP UWB PPDU format	495
15.2.1	General.....	495
15.2.2	PPDU encoding process.....	495
15.2.3	Symbol structure	496
15.2.4	PSDU timing parameters	498
15.2.5	Preamble timing parameters	500
15.2.6	SHR field	502
15.2.7	PHR field	505
15.2.8	PHY Payload field	506
15.3	Modulation.....	507
15.3.1	Modulation mathematical framework.....	507
15.3.2	Spreading	507
15.3.3	FEC	509
15.4	RF requirements.....	511
15.4.1	Operating frequency bands	511
15.4.2	Channel assignments.....	513
15.4.3	Regulatory compliance	513
15.4.4	Baseband impulse response	513
15.4.5	Transmit PSD mask	514
15.4.6	Chip rate clock and chip carrier alignment	514
15.4.7	TX-to-RX turnaround time	515
15.4.8	RX-to-TX turnaround time	515
15.4.9	Transmit center frequency tolerance.....	515
15.4.10	Receiver maximum input level of desired signal.....	515
15.4.11	Receiver ED	515
15.4.12	LQI.....	515
15.4.13	CCA	516
15.5	HRP UWB PHY optional pulse shapes	516
15.5.1	Overview.....	516
15.5.2	HRP UWB PHY optional chirp on UWB (CoU) pulses	516
15.5.3	HRP UWB PHY optional continuous spectrum (CS) pulses	517

15.5.4	HRP UWB PHY linear combination of pulses (LCP)	519
15.6	Extended preamble for optional CCA mode 6	519
15.7	Ranging	520
15.7.1	Overview	520
15.7.2	Ranging counter	520
15.7.3	Crystal characterization	520
15.7.4	Ranging FoM	521
16.	GFSK PHY	523
16.1	PPDU formats	523
16.2	Modulation	523
16.2.1	GFSK PHY data rates	523
16.2.2	Reference modulator diagram	523
16.2.3	Data whitening	523
16.2.4	GFSK modulation	524
16.3	GFSK PHY RF requirements	524
16.3.1	Operating frequency range	524
16.3.2	Transmit PSD mask	524
16.3.3	Symbol rate	525
16.3.4	Receiver sensitivity	525
16.3.5	Receiver interference rejection	525
16.3.6	TX-to-RX turnaround time	525
16.3.7	RX-to-TX turnaround time	525
16.3.8	Transmit center frequency tolerance	525
16.3.9	Transmit power	525
16.3.10	Receiver maximum input level of desired signal	525
16.3.11	Receiver ED	526
16.3.12	LQI	526
17.	MSK PHY	527
17.1	PPDU formats	527
17.1.1	Overview	527
17.1.2	Frame Length LSB field	527
17.1.3	Extended PHR field	527
17.1.4	Frame Length MSB field	527
17.2	Data rate	528
17.3	Multi-PHY functionality	528
17.4	SFD for the MSK PHY	528
17.5	MSK modulation	529
17.5.1	Reference modulator diagram	529
17.5.2	Data whitening	529
17.5.3	Bit-to-symbol mapping	529
17.5.4	Signal modulation	529
17.6	MSK PHY requirements	530
17.6.1	Operating frequency range	530
17.6.2	Transmit PSD mask	530
17.6.3	Symbol rate	530
17.6.4	Transmit center frequency tolerance	531
17.6.5	Transmit power	531
17.6.6	Receiver maximum input level of desired signal	531
17.6.7	Modulation frequency deviation tolerance	531
17.6.8	Zero crossing tolerance	531

18.	LRP UWB PHY specification	532
18.1	Overview.....	532
18.2	LRP UWB PHY symbol structure	532
18.2.1	Overview.....	532
18.2.2	Base mode LRP UWB PHY symbol structure	533
18.2.3	Extended mode LRP UWB PHY symbol structure	533
18.2.4	Long-range mode LRP UWB PHY symbol structure	535
18.3	LRP UWB SHR	535
18.3.1	General.....	535
18.3.2	LRP UWB SHR preamble	536
18.3.3	LRP UWB SHR SFD.....	536
18.4	LRP UWB PHR	536
18.4.1	General.....	536
18.4.2	Encoding Type field.....	537
18.4.3	Header Extension field.....	537
18.4.4	SECEDED field.....	538
18.4.5	Frame Length field.....	538
18.4.6	LEIP Length field	538
18.4.7	LEIP Position field.....	538
18.5	LRP UWB PSDU.....	539
18.6	LRP UWB location enhancing information postamble	539
18.7	LRP UWB transmitter specification	539
18.7.1	Pulse shape.....	539
18.7.2	Pulse timing	539
18.7.3	Transmit PSD mask	540
18.8	LRP UWB receiver specification	540
19.	SUN FSK PHY	541
19.1	Introduction.....	541
19.2	PPDU format for SUN FSK.....	542
19.2.1	General.....	542
19.2.2	SHR field format.....	542
19.2.3	General.....	542
19.2.4	PHR field format.....	543
19.2.5	Mode Switch PHR	543
19.2.6	PHY Payload field	545
19.3	Modulation and coding for SUN FSK	546
19.3.1	General.....	546
19.3.2	Reference modulator.....	549
19.3.3	Bit-to-symbol mapping	550
19.3.4	Modulation quality.....	551
19.3.5	FEC	552
19.3.6	Code-symbol interleaving.....	555
19.4	Data whitening for SUN FSK	556
19.5	Mode switch mechanism for SUN FSK	556
19.6	SUN FSK PHY RF requirements	559
19.6.1	Operating frequency range.....	559
19.6.2	Regulatory compliance	559
19.6.3	Radio frequency tolerance	559
19.6.4	Channel switch time.....	560
19.6.5	Transmitter symbol rate.....	560
19.6.6	Transmit spectral mask	560

19.6.7	Receiver sensitivity.....	561
19.6.8	Receiver interference rejection	561
19.6.9	TX-to-RX turnaround time	561
19.6.10	RX-to-TX turnaround time	561
19.6.11	Transmit power	562
19.6.12	Receiver maximum input level of desired signal.....	562
19.6.13	Receiver ED	562
19.6.14	LQI.....	562
20.	SUN OFDM PHY	563
20.1	Introduction.....	563
20.2	PPDU format for SUN OFDM	563
20.2.1	General.....	563
20.2.2	Short Training field (STF)	563
20.2.3	Long Training field (LTF)	567
20.2.4	PHR.....	570
20.2.5	PSDU field.....	572
20.3	Data rates for SUN OFDM	572
20.4	Modulation and coding for SUN OFDM.....	573
20.4.1	Reference modulator diagram.....	573
20.4.2	Bit-to-symbol mapping	573
20.4.3	PIB attribute values for phySymbolsPerOctet	574
20.4.4	FEC	574
20.4.5	Interleaver	575
20.4.6	Frequency spreading	577
20.4.7	Pilot tones/null tones.....	578
20.4.8	Cyclic prefix (CP).....	581
20.4.9	PPDU Tail field	581
20.4.10	Pad field	581
20.4.11	Scrambler and scrambler seeds	582
20.5	SUN OFDM PHY RF requirements	583
20.5.1	Operating frequency range.....	583
20.5.2	Transmit power spectral density (PSD) mask.....	583
20.5.3	Receiver sensitivity.....	583
20.5.4	Adjacent channel rejection.....	584
20.5.5	Alternate channel rejection	584
20.5.6	TX-to-RX turnaround time	585
20.5.7	RX-to-TX turnaround time	585
20.5.8	EVM definition	585
20.5.9	Transmit center frequency and symbol tolerance	586
20.5.10	Transmit power	586
20.5.11	Receiver maximum input level of desired signal.....	586
20.5.12	Receiver ED	586
20.5.13	LQI.....	586
21.	SUN O-QPSK PHY	587
21.1	Introduction.....	587
21.2	PPDU format for SUN O-QPSK	587
21.2.1	General.....	587
21.2.2	SHR field format.....	587
21.2.3	PHR field format.....	588
21.2.4	PHY Payload field	589

21.3	Modulation and coding for SUN O-QPSK	589
21.3.1	Reference modulator	589
21.3.2	SHR coding and spreading	590
21.3.3	PHR coding and spreading	591
21.3.4	PSDU coding and spreading for DSSS	592
21.3.5	PSDU coding and spreading for MDSSS	596
21.3.6	FEC	598
21.3.7	Code-bit interleaving	600
21.3.8	Bit differential encoding (BDE)	601
21.3.9	DSSS bit-to-chip mapping	602
21.3.10	MDSSS bit-to-chip mapping	606
21.3.11	Chip whitening	609
21.3.12	Pilot insertion	611
21.3.13	Modulation parameters for O-QPSK	613
21.4	Support of legacy devices of the 780 MHz, 915 MHz, and 2450 MHz O-QPSK PHYs	614
21.5	SUN O-QPSK PHY RF requirements	614
21.5.1	Operating frequency range	614
21.5.2	Transmit power spectral density (PSD) mask	615
21.5.3	Receiver sensitivity	615
21.5.4	Adjacent channel rejection	617
21.5.5	TX-to-RX turnaround time	619
21.5.6	RX-to-TX turnaround time	619
21.5.7	EVM definition	619
21.5.8	Transmit center frequency and symbol tolerance	619
21.5.9	Transmit power	619
21.5.10	Receiver maximum input level of desired signal	619
21.5.11	Receiver ED	619
21.5.12	LQI	619
21.5.13	CCA	619
22.	LECIM DSSS PHYs	621
22.1	PPDU format for DSSS	621
22.2	Modulation and spreading	621
22.2.1	General	621
22.2.2	Data rate	621
22.2.3	Reference modulator diagram	622
22.2.4	Convolutional FEC encoding	622
22.2.5	Interleaver	623
22.2.6	Differential encoding	624
22.2.7	Bit-to-symbol and symbol-to-chip encoding	625
22.2.8	BPSK/O-QPSK modulation	627
22.3	PSDU fragmentation	629
22.3.1	General	629
22.3.2	Configuration	630
22.3.3	Fragmentation	630
22.3.4	Fragment packet	630
22.3.5	Calculating FICS field using MIC	631
22.3.6	Fragment acknowledgment and retransmission	631
22.3.7	Frak	632
22.3.8	Reassembly	634
22.4	DSSS PHY RF requirements	634
22.4.1	Radio frequency tolerance	634
22.4.2	Channel switch time	634

22.4.3	Transmit spectral mask	634
22.4.4	Receiver sensitivity	634
22.4.5	Receiver interference rejection	634
22.4.6	TX-to-RX turnaround time	635
22.4.7	RX-to-TX turnaround time	635
22.4.8	Transmit power	635
23.	LECIM FSK PHY specification	636
23.1	General	636
23.2	PPDU format for LECIM FSK PHY	636
23.2.1	General	636
23.2.2	SHR field format	636
23.2.3	PHR field format	637
23.2.4	PHY Payload field	637
23.3	Modulation and coding for LECIM FSK PHY	637
23.3.1	General	637
23.3.2	Reference modulator	638
23.3.3	Bit-to-symbol mapping	638
23.3.4	Modulation quality	638
23.3.5	FEC	639
23.3.6	Code-bit interleaving	640
23.3.7	Spreading	641
23.4	Data whitening for LECIM FSK PHY	642
23.5	LECIM FSK PHY RF requirements	643
23.5.1	Operating frequency range	643
23.5.2	Radio frequency tolerance	643
23.5.3	Channel switch time	643
23.5.4	Transmit spectral mask	643
23.5.5	Receiver sensitivity	643
23.5.6	TX-to-RX turnaround time	644
23.5.7	RX-to-TX turnaround time	644
23.5.8	Transmit power	644
24.	TVWS-FSK PHY	645
24.1	PPDU format for TVWS-FSK	645
24.1.1	General	645
24.1.2	SHR field format	645
24.1.3	PHR field format	646
24.1.4	PHY Payload field	646
24.2	Modulation and coding for TVWS-FSK	646
24.2.1	General	646
24.2.2	Reference modulator	646
24.2.3	FEC and interleaving	647
24.2.4	Data whitening	648
24.2.5	Spreading	648
24.2.6	Bit-to-symbol mapping	648
24.2.7	Modulation quality	648
24.2.8	Values for phySymbolsPerOctet	648
24.3	TVWS-FSK RF requirements	649
24.3.1	Operating frequency range	649
24.3.2	Clock frequency and timing accuracy	649
24.3.3	Channel switch time	649

24.3.4	Receiver sensitivity.....	649
24.3.5	TX-to-RX turnaround time.....	649
24.3.6	RX-to-TX turnaround time.....	649
24.3.7	Receiver maximum input level of desired signal.....	649
24.3.8	Receiver ED.....	649
24.3.9	LQI.....	649
25.	TVWS-OFDM PHY	650
25.1	General.....	650
25.2	PPDU format for TVWS-OFDM.....	650
25.2.1	General.....	650
25.2.2	STF.....	650
25.2.3	LTF	652
25.2.4	PHR field format.....	654
25.2.5	PSDU field.....	654
25.3	System parameters for TVWS-OFDM	654
25.4	Modulation and coding for TVWS-OFDM	655
25.4.1	Reference modulator.....	655
25.4.2	Bit-to-symbol mapping	655
25.4.3	FEC	656
25.4.4	Interleaver	657
25.4.5	Pilot tones/null tones.....	659
25.4.6	CP.....	660
25.4.7	PPDU Tail field	660
25.4.8	Pad field	660
25.4.9	Scrambler and scrambler seeds.....	660
25.5	TVWS-OFDM RF requirements	660
25.5.1	Operating frequency range.....	660
25.5.2	Pulse shaping	661
25.5.3	Transmit power spectral density (PSD) mask.....	661
25.5.4	Receiver sensitivity.....	661
25.5.5	TX-to-RX turnaround time	661
25.5.6	RX-to-TX turnaround time	661
25.5.7	EVM definition	661
25.5.8	Transmit center frequency and symbol tolerance	662
26.	TVWS-NB-OFDM PHY	663
26.1	PPDU format for TVWS-NB-OFDM.....	663
26.1.1	General.....	663
26.1.2	Short Training field (STF)	663
26.1.3	Long training field (LTF)	667
26.1.4	PHR.....	671
26.1.5	PHY Payload field	672
26.2	System parameters for TVWS-NB-OFDM	672
26.3	Modulation and coding parameters for TVWS-NB-OFDM.....	673
26.3.1	General.....	673
26.3.2	Reference modulator.....	673
26.3.3	Scrambler and scrambler seed	673
26.3.4	Outer encoding.....	673
26.3.5	Inner encoding	674
26.3.6	Pad bit insertion	677
26.3.7	Spreader	677

26.3.8	Bit interleaving	678
26.3.9	Subcarrier mapping.....	678
26.3.10	Frequency interleaving	680
26.3.11	Pilot tones	681
26.3.12	Cyclic prefix	681
26.3.13	Pulse shaping	681
26.3.14	PIB attribute values for phySymbolsPerOctet	682
26.4	Channel aggregation for TVWS-NB-OFDM	682
26.5	TVWS-NB-OFDM RF requirements.....	682
26.5.1	Operating frequency range.....	682
26.5.2	Receiver sensitivity.....	682
26.5.3	TX-to-RX turnaround time	683
26.5.4	RX-to-TX turnaround time	683
26.5.5	EVM definition	683
26.5.6	Transmit center frequency and symbol tolerance	684
27.	RCC LMR PHY	685
27.1	RCC PHY overview.....	685
27.2	PPDU format.....	685
27.2.1	General.....	685
27.2.2	SHR.....	685
27.2.3	PHR.....	686
27.2.4	PHY payload.....	686
27.2.5	Tail bits	686
27.3	FEC	686
27.4	Interleaver	687
27.5	Data whitening.....	687
27.6	Modulation.....	688
27.6.1	GMSK.....	688
27.6.2	4-FSK.....	688
27.6.3	QPSK	689
27.6.4	p/4 DQPSK	689
27.6.5	DSSS DPSK.....	690
27.7	Reference modulator.....	692
27.8	LMR PHY RF requirements	692
27.8.1	Transmitter symbol rate tolerance	692
27.8.2	Channel switching time	692
27.8.3	Error vector magnitude	692
27.8.4	Receiver sensitivity.....	692
27.8.5	Receiver interference rejection	692
27.8.6	Receiver maximum input level of desired signal.....	693
27.8.7	TX-to-RX turnaround time	693
27.8.8	RX-to-TX turnaround time	693
27.8.9	Receiver ED	693
27.8.10	LQI.....	693
28.	RCC DSSS BPSK PHY	694
28.1	Overview.....	694
28.2	RCC DSSS BPSK PHY specification	694
29.	CMB PHY.....	695

29.1	CMB O-QPSK PHY specification.....	695
29.1.1	PPDU format for the CMB O-QPSK PHY	695
29.1.2	Modulation and coding for CMB O-QPSK PHY	696
29.1.3	CMB O-QPSK PHY RF requirements	697
29.2	CMB GFSK PHY specification.....	699
29.2.1	PPDU format for CMB GFSK PHY	699
29.2.2	Modulation and coding for CMB GFSK PHY	700
29.2.3	Data whitening for CBM GFSK PHY	702
29.2.4	CMB GFSK PHY RF requirements.....	702
30.	TASK PHY	705
30.1	General.....	705
30.2	PPDU	705
30.2.1	General.....	705
30.2.2	PPDU format.....	705
30.2.3	Generation of PPDU signal.....	708
30.3	MCS mode, MCS, data rates, and related parameters	709
30.3.1	MCS mode	709
30.3.2	Data rates in the 2450 MHz band	709
30.3.3	Data rates in the 780 MHz, 863 MHz, and 915 MHz bands.....	710
30.3.4	Data rates in the 433 MHz and 470 MHz bands.....	710
30.4	FEC, ternary sequence spreading, and pseudo-random chip inversion	711
30.4.1	General.....	711
30.4.2	FEC codes	712
30.4.3	Ternary sequence spreading: Data-symbol-to-chip conversion.....	717
30.4.4	Pseudo-random chip inversion.....	719
30.5	Modulation.....	721
30.6	Pulse shaping	722
30.7	Representation of the modulated waveforms.....	722
30.8	RF requirements.....	722
30.8.1	Transmit PSD mask	722
30.8.2	Receiver sensitivity.....	723
30.8.3	Interference rejection capability	723
30.8.4	TX-to-RX turnaround time	724
30.8.5	RX-to-TX turnaround time	724
30.8.6	EVM.....	724
30.8.7	Transmit power	724
30.8.8	Transmit center frequency tolerance.....	724
30.8.9	Receiver maximum input level of desired signal.....	724
30.8.10	Receiver ED	724
30.8.11	SNR measurement	724
30.8.12	CCA	724
31.	RS-GFSK PHY	725
31.1	PPDU format.....	725
31.1.1	General.....	725
31.1.2	Preamble field	725
31.1.3	SFD	725
31.1.4	Long PHR	725
31.1.5	Short PHR.....	726
31.2	Modulation and coding	727
31.2.1	General.....	727

31.2.2	Reference modulator diagram.....	728
31.2.3	Differential encoding	728
31.2.4	Bit-to-symbol mapping	729
31.2.5	Modulation quality.....	729
31.2.6	Frequency deviation tolerance.....	729
31.2.7	Zero crossing tolerance	730
31.2.8	FEC	730
31.2.9	Code-symbol interleaving.....	730
31.2.10	Data whitening for RS-GFSK.....	730
31.3	Rate switch RS-GFSK	731
31.4	RF requirements.....	731
31.4.1	RF tolerance	731
31.4.2	Channel switch time.....	731
31.4.3	Receiver sensitivity.....	731
31.4.4	Receiver interference rejection	732
31.4.5	TX-to-RX turnaround time	732
31.4.6	RX-to-TX turnaround time	732
31.4.7	Receiver maximum input level of desired signal.....	732
31.4.8	Receiver ED	732
31.4.9	LQI.....	732
31.4.10	CCA	732
Annex A (informative) Bibliography		733
Annex B (normative) CCM* mode of operation		735
Annex C (informative) Test vectors for cryptographic building blocks.....		741
Annex D (informative) Protocol implementation conformance statement (PICS) proforma.....		753
Annex E (normative) Time-slot relaying based link extension (TRLE)		772
Annex F (informative) Geographic regional frequency band details		797

IEEE Standard for Low-Rate Wireless Networks

1. Overview

1.1 Scope

This standard defines the physical layer (PHY) and medium access control (MAC) sublayer specifications for low-data-rate wireless connectivity with fixed, portable, and moving devices with no battery or very limited battery consumption requirements. In addition, the standard provides modes that allow for precision ranging. PHYs are defined for devices operating in a variety of geographic regions.

1.2 Purpose

The standard provides for ultra low complexity, ultra low cost, ultra low power consumption, and low data rate wireless connectivity among inexpensive devices, especially targeting the communications requirements of what is now commonly referred to as the Internet of Things. In addition, some of the alternate PHYs provide precision ranging capability that is accurate to one meter. Multiple PHYs are defined to support a variety of frequency bands.

2. Normative references

The following referenced documents are indispensable for the application of this document (i.e., they must be understood and used, so each referenced document is cited in text and its relationship to this document is explained). For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments or corrigenda) applies.

ANSI X3.66-1979, Advanced Data Communication Control Procedures.¹

Code of Federal Regulations, Title 47: Telecommunication, Part 90—Private Land Mobile Radio Services, Subpart S—Regulations Governing Licensing and Use of Frequencies in the 806–824, 851–869, 896–901, and 935–940 MHz Bands (47 CFR, Part 90, Subpart S).²

Code of Federal Regulations, Title 47: Telecommunication, Part 90—Private Land Mobile Radio Services, Subpart Y—Regulations Governing Licensing and Use of Frequencies in the 4940–4990 MHz Band (47 CFR, Part 90, Subpart Y).

FIPS Pub 197, Advanced Encryption Standard (AES).³

IEEE Std 802[®]-2014, IEEE Standards for Local and Metropolitan Area Networks: Overview and Architecture.^{4, 5}

IETF RFC 6225, Dynamic Host Configuration Protocol Options for Coordinate-Based Location Configuration Information, Internet Engineering Task Force.⁶

¹ANSI publications are available from the American National Standards Institute (<http://www.ansi.org/>)

²CFR publications are available from the U.S. Government Printing Office (<http://www.gpo.gov/>).

³FIPS publications are available from the National Technical Information Service (NTIS) (<http://www.ntis.org/>).

⁴IEEE publications are available from The Institute of Electrical and Electronics Engineers (<http://standards.ieee.org/>).

⁵The IEEE standards or products referred to in this clause are trademarks of The Institute of Electrical and Electronics Engineers, Inc.

⁶IETF RFCs are available from the Internet Engineering Task Force (<http://www.ietf.org/>).

3. Definitions, acronyms, and abbreviations

3.1 Definitions

For the purposes of this document, the following terms and definitions apply. The *IEEE Standards Dictionary* should be consulted for terms not defined in this clause.⁷

association: The service used to establish membership for a device in a network.

authentication tag: Information that allows the verification of authenticity of a message.

channel hopping: Periodically switching the channel using a sequence known to both sending and receiving devices where the entire frame is sent on a single channel.

channel offset: A number used in the channel calculation of a slotted channel hopping system to allow for different channels to be used in the same slot.

chirp: Linear frequency sweep.

dependent device: A device that operates without direct Internet access to the television white space (TVWS) database and depends on another device for channel availability information.

encryption: The transformation of a message into a new representation so that privileged information is required to recover the original representation.

fragment: An individual contiguous subset of a MAC protocol data unit.

frame: The format of aggregated bits from a medium access control sublayer entity that are transmitted together in time.

group key: A key that is known only to the devices in the group.

independent device: A device that has direct access to the television white space (TVWS) database via the Internet.

key: Privileged information that is used, for example, to protect information from disclosure to, and/or undetectable modification by, parties that do not have access to this privileged information.

keying material: The combination of a key and associated security information (e.g., a nonce value).

link key: A key that is shared between precisely two devices.

mobile device: A device whose location in the network can change.

nonce: A nonrepeating value, such as an increasing counter, a sufficiently long random string, or a timestamp.

packet: The formatted, aggregated bits that are transmitted together in time across the physical medium.

payload: The contents of a data message that is being transmitted.

⁷*IEEE Standards Dictionary Online* is available at: <http://dictionary.ieee.org>. An IEEE Account is required for access to the dictionary, and one can be created at no charge on the dictionary sign-in page.

radio frequency identification (RFID): The use of electromagnetic or inductive coupling in the radio frequency (RF) portion of the spectrum to communicate to or from a tag through a variety of modulation and encoding schemes to uniquely read the identity of an RF tag.

slotframe: A collection of timeslots repeating in time, analogous to a superframe in that it defines periods of communication opportunities.

smart utility network (SUN): A principally outdoor, low data rate wireless network that supports two-way communications among sensing, measurement, and control devices in the smart grid.

transaction: The exchange of related, consecutive frames between two peer medium access control (MAC) entities, required for a successful transmission of a MAC command frame or Data frame.

3.2 Acronyms and abbreviations

Ack	acknowledgment
AEAD	authenticated encryption with associated data
AES	advanced encryption standard
AIFS	acknowledgment interframe spacing
ANPI	average noise power indicator
AR	acknowledgment request
ASK	amplitude shift keying
ASN	absolute slot number
ATI	allowed transmission interval
BCH	Bose Chaudhuri Hocquenghem
BDE	bit differential encoding
BLE	battery life extension
BOP	beacon only period
BPM	burst position modulation
BPSK	binary phase-shift keying
BSN	beacon sequence number
CAP	contention access period
CBC-MAC	cipher block chaining message authentication code
CCA	clear channel assessment
CCM	counter mode encryption and cipher block chaining message authentication code
CCM*	extension of counter mode encryption and cipher block chaining message authentication code
CFP	contention-free period
CID	company identifier
CMB	China medical band
CP	cyclic prefix
CoU	chirp on ultra-wide band
CRC	cyclic redundancy check
CS	continuous spectrum
CSK	chirp-shift keying
CSL	coordinated sampled listing
CSM	common signaling mode
CSMA-CA	carrier sense multiple access with collision avoidance

CSS	chirp spread spectrum
DA	device announcement
DAA	detect and avoid
DBS	dedicated beacon slot
DEMUX	de-multiplexer
DFT	discrete Fourier transform
DPS	dynamic preamble selection
DPSK	differential phase-shift keying
DQCSK	differential quadrature chirp-shift keying
DQPSK	differential quadrature phase-shift keying
DSME	deterministic and synchronous multichannel extension
DSN	data sequence number
DSSS	direct sequence spread spectrum
EBSN	enhanced beacon sequence number
ED	energy detection (also in 6.2.8, extended duration)
EIRP	effective isotropic radiated power
Enh-Ack	enhanced acknowledgment
ESDU	encapsulated service data unit
EUI-64	64-bit extended unique identifier
EVM	error-vector magnitude
FCS	frame check sequence
FEC	forward error correction
FFD	full-function device
FICS	fragment integrity check sequence
FoM	figure of merit
Frak	fragment acknowledgment
FSCD	fragment sequence context description
FSK	frequency shift keying
GDB	geolocation database
GFSK	Gaussian frequency-shift keying
GMSK	Gaussian-filtered minimum shift keying
GTS	guaranteed timeslot
HCS	header check sequence
HRP	high rate pulse repetition frequency
ID	identifier
IDFT	inverse discrete Fourier transform
IE	information element
IFS	interframe space or spacing
Imm-Ack	immediate acknowledgment
IPI	idle power indicator
ISR	interference-to-signal ratio
I-RIT	implicit receiver initiated transmission
LBT	listen before talk
LCP	linear combination of pulses
LE	low energy
LECIM	low-energy, critical infrastructure monitoring

LEIP	location enhancing information postamble
LFSR	linear feedback shift register
LIFS	long interframe spacing
LMR	land mobile radio
LRP	low rate pulse repetition frequency
LQI	link quality indication
LR-WPAN	low-rate wireless personal area network
LSB	least significant bit
LTF	long training field
MAC	medium access control
MBAN	medical body area network
MCPS	MAC common part sublayer
MCPS-SAP	MAC common part sublayer service access point
MCS	modulation and coding scheme
MD	multi-superframe duration
MDSSS	multiplexed direct sequence spread spectrum
MFR	MAC footer
MHR	MAC header
MIC	message integrity code
MLME	MAC sublayer management entity
MLME-SAP	MAC sublayer management entity service access point
MPM	multi-PHY management
MSB	most significant bit
MSK	minimum shift keying
MPDU	MAC protocol data unit
MSDU	MAC service data unit
NRNSC	nonrecursive and nonsystematic code
OFDM	orthogonal frequency division multiplexing
OOK	on-off keying
O-QPSK	offset quadrature phase-shift keying
OUI	organizationally unique identifier
OVSF	orthogonal variable spreading factor
PAN	personal area network
PCA	priority channel access
PD-SAP	physical layer data service access point
PER	packet error rate
P-FSK	position-based frequency shift keying
PHR	PHY header
PHY	physical layer
PIB	personal area network information base
PICS	protocol implementation conformance statement
PLME	physical layer management entity
PLME-SAP	physical layer management entity service access point
PN	pseudo-random noise
PPDU	PHY protocol data unit
PPM	pulse position modulation

PRBS	pseudo-random binary sequence
PRF	pulse repetition frequency
PSD	power spectral density
PSDU	PHY service data unit
QAM	quadrature amplitude modulation
QPSK	quadrature phase-shift keying
RCC	rail communications and control
RCCN	rail communications and control network
RCPI	received channel power indicator
RDEV	ranging-capable device
RF	radio frequency
RFD	reduced-function device
RFD-RX	reduced function device—receive only
RFD-TX	reduced function device—transmit only
RFID	radio frequency identification
RFRAME	ranging frame
RIT	receiver initiated transmission
RMARKER	ranging marker
RSC	recursive and systematic code
RS-GFSK	rate switch Gaussian frequency shift keying
RSNI	received signal noise indicator
RSSI	receive signal strength indicator
RX	receive or receiver
SAB	slot allocation bitmap
SD	superframe duration
SF	spreading factor
SFD	start-of-frame delimiter
SHR	synchronization header
SIFS	short interframe spacing
SiPC	single parity check
SNR	signal-to-noise ratio
SPC	super PAN coordinator
SRM	spectrum resource measurement
STF	short training field
SUN	smart utility network
TASK	ternary amplitude shift keying
TBPC	turbo product code
TID	transaction identifier
TMCTP	TVWS multichannel cluster tree PAN
TPC	transmission power control
TRLE	timeslot relaying based link extension
TSCH	timeslotted channel hopping
TVWS	television white space
TX	transmit or transmitter
UWB	ultra-wide band
WPAN	wireless personal area network

4. Format conventions

4.1 General

Throughout this standard, unless otherwise stated, data structures exposed in interfaces are represented using the conventions and formats defined in this clause.

NOTE—It is important to note that interfaces are depicted in this standard as bit serial by convention but can be implemented in other forms, e.g., 4- or 8-bit parallel.⁸

Within the PHY, data structures are passed to the reference modulator input in bit-serial convention. PHY specific coding may change the bit-order and encode multiple information bits into symbols. Hence the over-the-air interface may express the data structure content in a manner different than the conventions defined here.

After all applicable expansion, the size of a MAC frame shall be less than the maximum PHY service data unit (PSDU) size supported by the PHY in use.

4.2 Fields

The general format of a data structure is shown in Figure 4-1. Each field is represented by a column in the figure giving the size of the field and the name and/or type of the datum encoded in the field. The convention of a data structure is recursive in that a field may contain a data structure which is in turn composed of fields.

Octets: 2	Bits: 0–5	6–7	...
Field Name/Type (Number datum)	Field Name/Type (Bit string datum)	Field Name/Type (Bit string datum)	...

Figure 4-1—General data structure format

The form <Octets: n > means the field is n octets long. The form <Bits: n > or <Bits: m – n > means bit number n or bits m to n of the data structure. In a figure, if a field length appears without either Octets or Bits, then the preceding units apply.

The form <Octets: $n/m/l$ > means the field can be n , m or l octets long.

Fields are concatenated into larger data structures, e.g., Figure 4-1 represents a data structure with 3 fields of length 2 octets, 6 bits and 2 bits for a total size of 3 octets.

Order of representation is strict with the leftmost field as shown in any figure occurring before the next field to its right. The second field from the left occurs before the third field and so on.

Significance, as expressed in the terms least significant bit (LSB) and most significant bit (MSB), only applies to numbers as defined in 4.3. All other fields are treated as strings.

The convention of “processing a data structure” or “transmitting a data structure” mean treatment of the content of the data structure in the order defined in the following subclauses.

⁸Notes in text, tables, and figures are given for information only and do not contain requirements needed to implement the standard.

4.3 Numbers

Numbers are represented in decimal (nnn), binary (0bnnn), or hexadecimal (0xnnn) notation with the number of digits indicated. For example, 0b001 is a 3 digit binary number of value 1 and 0x001 is a 3-digit hexadecimal number of value 1. Numbers encoded in fields are either signed or unsigned integers unless explicitly defined otherwise. Other formats (e.g., a field containing a floating point number) are stated in the field definition where applicable.

When represented in fields, numbers are expressed with LSB leftmost and MSB rightmost as shown in Figure 4-2 for an n -bit unsigned integer. (Note that this is the inverse of the number representations 0bnnn and 0xnnn and of common number representations used in mathematical notations.) For example, the number 0x47 would be represented in an 8-bit field as 1110 0010.

Bit:0	...	7	Bits 8–($n-2$)	$n-1$
LSB	...	—	Subsequent octets	MSB

Figure 4-2—General number field format

Numbers of size greater than 1 octet occur with the octet containing the least significant bits first (leftmost) followed by octets containing bits of increasing significance to the right.

Unless otherwise stated in the definition of a field, a number in a field shall be formatted as an unsigned integer.

4.4 Strings

A string of length k bits is represented as a bit sequence numbered from 0 to $k-1$. Bit 0 occurs first and is represented as the leftmost bit of a string field. Bit 1 occurs to the right of bit 0 and so on until bit $(k-1)$. This is illustrated in Figure 4-3.

Bits:0	...	7	Bits 8–($k-1$)
String bit 0	...	String bit 7	String bits 8 to $k-1$

Figure 4-3—General string field format

A string of length greater than 1 octet is represented by the octet containing the lowest numbered bits first and leftmost, followed by octets containing increasing bit numbers to the right.

4.5 Transmission order

4.5.1 General

For every address field, the bit transmission order shall be performed from the right most octet (RMO) to the left most octet (LMO) in the field, and inside an octet from the LSB to the MSB.

Figure 4-4 shows the MAC Address field containing a 64-bit MAC address. For this example the MAC address value is assumed to be AC-DE-64-23-45-67-89-01.

Octets: 8
MAC address

Figure 4-4—Field containing a 64-bit MAC address

Figure 4-5 shows the bit transmission order of the MAC Address field of Figure 4-4.

RMO → LMO	Octet 8 RMO	Octet 7	Octet 6	Octet 5	Octet 4	Octet 3	Octet 2	Octet 1 LMO
	01	89	67	45	23	64	DE	AC
LSB → MSB	10000000	10010001	11100110	10100010	11000100	00100110	01111011	00110101

Transmission order

Figure 4-5—Transmission order for the MAC Address field

4.5.2 Vendor OUI transmission order

Vendor organizationally unique identifier (OUI) bit transmission order shall be performed from the right most octet (RMO) to the leftmost octet (LMO) in the field, and inside an octet from the LSB to the MSB.

Figure 4-6 shows the Vendor OUI field. For this example, the vendor OUI field value is assumed to be AC-DE-64.

Octets: 3
Vendor OUI

Figure 4-6—Vendor OUI field

Figure 4-7 shows the bit transmission order of the vendor OUI field of Figure 4-6.

RMO → LMO	Octet 3 RMO	Octet 2	Octet 1 LMO
	64	DE	AC
LSB → MSB	00100110	01111011	00110101

Figure 4-7—Transmission order for the vendor OUI field

4.6 Reserved fields and values

Each bit within any Reserved field shall be set to zero on transmission and shall be ignored on reception.

A decision should never be made based on the contents of any Reserved field or field containing a reserved value.

5. General description

5.1 Introduction

A low-rate wireless personal area network (LR-WPAN) is a simple, low-cost communication network that allows wireless connectivity in applications with limited power and relaxed throughput requirements. The main objectives of an LR-WPAN are ease of installation, reliable data transfer, extremely low cost, and a reasonable battery life, while maintaining a simple and flexible protocol.

This standard defines multiple PHYs operating in a variety of frequency bands, as described in 10.1.

Two different device types can participate in an IEEE 802.15.4 network: a full-function device (FFD) and a reduced-function device (RFD). An FFD is a device that is capable of serving as a personal area network (PAN) coordinator or a coordinator, as defined in 6.1. An RFD is a device that is not capable of serving as either a PAN coordinator or a coordinator. An RFD is intended for applications that are extremely simple, such as a light switch or a passive infrared sensor; it does not have the need to send large amounts of data and only associates with a single FFD at a time. Consequently, the RFD can be implemented using minimal resources and memory capacity.

Supplemental information for various industrial domains is described in “Applications of IEEE Std 802.15.4” [B3].⁹

5.2 Special application spaces

5.2.1 General

Although this standard is intended to address many diverse application spaces, some application spaces have unique requirements which required specific elements to be added to this standard. These application spaces are described in this subclause.

5.2.2 Smart utility network (SUN)

SUNs enable multiple applications to operate over shared network resources, providing monitoring and control of a utility system. SUN devices are designed to operate in very large-scale, low-power wireless applications and often require using the maximum transmit power available under applicable regulations, in order to provide long-range, point-to-point connections. Frequently, SUNs are required to cover geographically widespread areas containing a large number of outdoor devices. In these cases, SUN devices typically employ mesh or peer-to-peer multihop techniques to communicate with an access point.

5.2.3 Rail communications and control (RCC)

RCC refers to a wireless information exchange and sensor or control communications deployed in applications such as the following:

- A wireless link between trains, locomotives, or other mobile rolling stock to fixed trackside or network infrastructure
- A link between connected fixed, remote trackside infrastructure, and fixed network infrastructure
- A link between vehicles in the same train or between two or more trains

⁹The numbers in brackets correspond to the numbers of the bibliography in Annex A.

RCC devices are intended to support mobile rail vehicle communications at high speeds with data rates that enable connections at distances of over 50 km. The RCC PHYs are designed to take advantage of relatively small amounts of spectrum where spectrum is costly or scarce.

5.2.4 Television white space (TVWS)

TVWS operation has the requirement to determine which TVWS frequency allocations are available for use at a given time and geographic location. TVWS devices need to have access to TVWS channel availability information, for example, via a central database that is accessed over the Internet. A TVWS device that has no connection to the Internet must depend upon another TVWS device that has access to the TVWS database via the Internet to acquire channel availability information.

5.2.5 Radio frequency identification (RFID)

Active RFID devices are used to identify and often locate people or objects in industrial or commercial environments. Typical applications include asset management, inventory management, process control and automation, safety, and accountability.

In its simplest form an active RFID system comprises a number of transmit-only tags that periodically transmit a packet containing a unique identifier (ID) and a small amount of data. The packet is received by one or more readers that may simply register the tag as present, may employ further processing to determine the location of the tag, or forward data to an application server. More complex active RFID systems might employ two-way communications with the tag for control, communication, and coordination.

5.2.6 Low-energy, critical infrastructure monitoring (LECIM)

The LECIM portions of this standard are designed to implement a minimal network infrastructure that enables the collection of scheduled and event data from a large number of non-mains powered end points that are widely dispersed, or are in challenging propagation environments. To facilitate low energy operation necessary for multi-year battery life, MAC protocols that minimize network maintenance traffic and device wake durations have been defined.

5.2.7 Medical body area network (MBAN) services

Some countries have allocated spectrum for MBAN services on a secondary basis such that MBAN devices are required to protect all primary users and accept possible interference from those users. MBAN devices operating within this allocated spectrum conform to a set of rules which restrict use of the band to only medical, non-voice use under direction of a healthcare practitioner, among other requirements. When a primary user is making use of a portion of the band, MBAN devices vacate that portion of the band. Use of the band by the primary user is, in general, scheduled well in advance, allowing MBAN users to share the band in an orderly manner.

5.2.8 China medical band (CMB)

The Ministry of Industry and Information Technology (MIIT) of the People's Republic of China has approved the 174–216 MHz, 407–425 MHz, and 608–630 MHz bands for medical information transmission.

CMB devices operating within these bands conform to a set of rules specified in MIIT Doc 423-2005 [B13], which restricts use of the band to only medical, non-voice use under direction of a healthcare practitioner, among other requirements.

This standard defines a PHY for devices operating on Chinese-approved bands for medical signals.

5.3 Components of the IEEE 802.15.4 WPAN

A system conforming to this standard consists of several components. The most basic is the device. A device has a single radio interface that implements an IEEE Std 802.15.4 MAC and PHY. Two or more devices communicating on the same physical channel constitute a wireless personal area network (WPAN). A WPAN includes at least one FFD, operating as the PAN coordinator.

5.4 Multi-PHY management (MPM) of the SUN WPAN

Multiple, different SUN PHYs can operate in the same location and within the same frequency band. In order to mitigate interference, an MPM scheme is specified for SUNs to facilitate inter-PHY coexistence. For this purpose, the MPM scheme facilitates interoperability and negotiation among potential coordinators with different PHYs by permitting a potential coordinator to detect an operating network during its discovery phase using the common signaling mode (CSM) appropriate to the band being used. The MPM procedure can be used in conjunction with the clear channel assessment (CCA) mechanism to provide coexistence.

5.5 Network topologies

5.5.1 General

Depending on the application requirements, an IEEE 802.15.4 LR-WPAN operates in either of two topologies: the star topology or the peer-to-peer topology. Both are shown in Figure 5-1. In the star topology, the communication is established between devices and a single central controller, called the PAN coordinator. A device typically has some associated application and is either the initiation point or the termination point for network communications. The PAN coordinator is the primary controller of the PAN. All devices operating on a network of either topology have unique addresses, referred to as extended addresses. In addition, a device can be assigned a short address during the association process. A device will use either the extended address or the short address for communication within the PAN. The transmission of the extended and short address fields is optional for reduced function device-transmit only (RFD-TX) devices. The PAN coordinator will often be mains powered, while the devices will likely be battery powered. Applications that benefit from a star topology include home automation, personal computer peripherals, games, and personal health care.




Figure 5-1—Star and peer-to-peer topology examples

The peer-to-peer topology also has a PAN coordinator; however, it differs from the star topology in that any device is able to communicate with any other device as long as they are in range of one another. Peer-to-peer topology allows more complex network formations to be implemented, such as mesh networking topology.

Applications such as industrial control and monitoring, wireless sensor networks, asset and inventory tracking, intelligent agriculture, and security would benefit from such a network topology. A peer-to-peer network allows multiple hops to route messages from any device to any other device on the network. Such functions can be added at the higher layer, but they are not part of this standard.

Each independent PAN selects a unique ID. This PAN ID allows communication between devices within a network using short addresses and enables transmissions between devices across independent networks. The mechanism by which identifiers are chosen is outside the scope of this standard.

The network formation is performed by the higher layer, which is not part of this standard.

5.5.2 Star network formation

The basic structure of a star network is illustrated in Figure 5-1. After an FFD is activated, it can establish its own network and become the PAN coordinator. All star networks operate independently from all other star networks currently in operation. This is achieved by choosing a PAN ID that is not currently used by any other network within the radio communications range. Once the PAN ID is chosen, the PAN coordinator allows other devices, potentially both FFDs and RFDs, to join its network. The higher layer can use the procedures described in 6.3 and 6.4 to form a star network. An reduced function device with receive-only capability (RFD-RX) can serve as a PAN coordinator termination point for RFD-TXs.

Timeslotted channel hopping (TSCH) PANs are topology independent and can be used in star topologies as well as partial or full mesh topologies.

LECIM networks primarily operate in a star topology. LECIM networks are typically asymmetric in energy supply and capability, having a PAN coordinator that is mains powered (or otherwise provided a substantial power source) and energy and/or cost constrained devices. The PAN coordinator typically monitors the channel more often than a device. A device may sleep unless it has a Data frame to send.

5.5.3 Peer-to-peer network formation

In a peer-to-peer topology, each device is capable of communicating with any other device within its radio communications range. One device is nominated as the PAN coordinator, for instance, by virtue of being the first device to communicate on the channel. Further network structures are constructed out of the peer-to-peer topology, and it is possible to impose topological restrictions on the formation of the network.

An example of the use of the peer-to-peer communications topology is the cluster tree. The cluster tree network is a special case of a peer-to-peer network in which most devices are FFDs. An RFD connects to a cluster tree network as a leaf device at the end of a branch because RFDs do not allow other devices to associate. Any FFD is able to act as a coordinator and provide synchronization services to other devices or other coordinators. Only one of these coordinators is the overall PAN coordinator, potentially because it has greater computational resources than any other device in the PAN. The PAN coordinator forms the first cluster by choosing an unused PAN ID and broadcasting beacon frames to neighboring devices. A contention resolution mechanism is required if two or more FFDs simultaneously attempt to establish themselves as PAN coordinators; however, such a mechanism is outside the scope of this standard. A candidate device receiving a beacon frame is able to request to join the network at the PAN coordinator. If the PAN coordinator permits the device to join, it adds the new device as a child device in its neighbor list. Then the newly joined device adds the PAN coordinator as its parent in its neighbor list and begins transmitting periodic beacons; other candidate devices are able to then join the network at that device. If the original candidate device is not able to join the network at the PAN coordinator, it will search for another parent device. The detailed procedures describing how a PAN is started and how devices join a PAN are found in 6.3 and 6.4.