

Diese Bauartspezifikation ist vom CECC-Generalsekretariat unter der Nummer registriert.

CECC 16 207-001
1.Ausgabe

Harmonized system of quality assessment for electronic components; detail specification:
Hermetically sealed relays for severe airborne environmental conditions;
Relay TO5CU, grid pattern 2,54 mm, coil 5 to 28 V d.c., 2 make and break contacts, 1 A (CECC 16 207-001)

Diese Anwenderspezifikation des Bundesamtes für Wehrtechnik und Beschaffung (BWB) ist ausgerichtet nach dem Vordruck für Bauartspezifikationen CECC 16 207 des CENELEC-Komitees für Bauelemente der Elektronik (CECC) im "Europäischen Komitee für elektrotechnische Normung (CENELEC)".

Die grundlegenden Bestimmungen und die Verfahrensregeln für dieses harmonisierte Gütebestätigungssystem sind in CECC 00 101 bis 00 106, 00 108, 00 109, 00 111 bis 00 114 festgelegt.

Das zuständige Arbeitsgremium für diese Spezifikation ist der NEA 671.1 "Relais" der Normenstelle Elektrotechnik im DIN.

Zitierte Normen

- | | |
|-------------|--|
| CECC 00 101 | Harmonisiertes Gütebestätigungssystem für Bauelemente der Elektronik;
Das CENELEC-Komitee für Bauelemente der Elektronik (CECC) |
| CECC 00 102 | -; Organisation und Verwaltung |
| CECC 00 103 | -; Komitee für Gütesicherung von Bauelementen der Elektronik (ECQAC) |
| CECC 00 104 | -; CECC-Arbeitsgruppen |
| CECC 00 105 | -; CECC-Mitgliederverzeichnis |
| CECC 00 106 | -; Methoden zur Änderung der Verfahrensregeln des Systems |
| CECC 00 108 | -; Konformitäts-Bestätigung |
| CECC 00 109 | -; Bestätigte Prüfberichte |
| CECC 00 111 | -; Spezifikation |
| CECC 00 112 | -; Abstimmverfahren |
| CECC 00 113 | -; Nationale Erklärung über die Überwachungsmaßnahmen |

Übrige Normen siehe Abschnitt 1

Fortsetzung 23 Seiten CECC-Spezifikation

Normenstelle Elektrotechnik (NE) im DIN Deutsches Institut für Normung e.V.

Deutsche Elektrotechnische Kommission im DIN und VDE (DKE), Stresemannallee 15, 6000 Frankfurt/Main 70

CECC 16 207-001
Issue: 1 February 1993
Pages 1 to 23



ELECTRONIC COMPONENTS OF ASSESSED QUALITY
- IN ACCORDANCE WITH:
CECC 16 000, issue 2 with amendment 1
CECC 16 200, issue 1 with amendment 1
CECC 16 207, issue 1

User specification of Bundesamt für Wehrtechnik und Beschaffung (BWB)
Holder of Specification:
Normenstelle Elektrotechnik (NE) im DIN
Deutsches Institut für Normung e.V.

Detail specification for All-or-nothing Relays

Type: monostable not polarized, 2 make and break contacts, 1 A


Construction: hermetically sealed, terminals 2,54 mm, grid pattern, solderable straight terminals

Application category of contacts: CA 0 10 mA max.


CA 1 0,1 A max. resistive

CA 2 1 A max. resistive


Outline drawing and wiring diagram
Dimensions in mm, tolerances $\pm 0,25$ mm
if not otherwise specified
Wiring diagram marked on top;
figures show terminal view.



Without transient suppression



With transient suppression



Application:

Relays according to this standard are provided for the operation in military and/or commercial equipment and/or installations with increased mechanical and environmental requirements. The applicable load range is from low level to 1 Ampere.

Test schedule 7 of CECC 16 200

The relays have a quality assessment level Y.

Coil data: 5 V, 6 V, 9 V, 12 V, 18 V, or 28 V d.c.

Contact data: 2 make and break contacts

Low level: 10 mA max., 10 mV to 50 mV

High current: rated contact voltage 28 V d.c.

contact current 1 A resistive load

0,2 A inductive load for inductance of $(0,32 \text{ H} \pm 10 \%)$

Temperature range: Storage temperature: - 65 to + 150 °C

Ambient temperature: - 65 to + 125 °C

Information about manufacturers who have components qualified to this detail specification is available in the current CECC 00 200: Qualified Products List, the MUAHAG-PPL Volume 5 and VG 95 212 Part 10 (LZB).

1 Related documents

CECC 00 114 (Issue 1) Quality assessment procedures

CECC 00 200 (Issue 1) Harmonized System of Quality Assessment for Electronic Components; Qualified Products List

CECC 16 000 (Issue 2) -; generic specification; electromechanical all or nothing relays

CECC 16 200 (Issue 1) -; sectional specification; electromechanical all or nothing relays

CECC 16 207 (Issue 1) -; blank detail specification; hermetically sealed relays for severe airborne environmental conditions

IEC 62 Marking codes for resistors and capacitors

IEC 68 - 1 Environmental testing, Part 1: General and guidance

IEC 68 - 2 - 17 Basic environmental testing procedures; Part 2: Tests - Test Q: Sealing

IEC 68 - 2 - 20 -; Part 2: Tests - Test T: Soldering

IEC 68 - 2 - 47 -; Part 2: Tests - Mounting of components, equipment and other articles for dynamic tests including shock (Ea), bump (Eb), vibration (Fc and Fd) and steady-state acceleration (Ga) and guidance

IEC 410 Sampling plans and procedures for inspection by attributes

MUAHAG-PPL Volume 5 Cenelec Electronics Components Committee; Military Usage and Harmonisation Advisory Group; Preferred Products List; Relays

VG 95 212 part 10 Listen zugelassener Bauelemente (LZB); Hermetisch dichte Relais

2 Characteristic values of the relay

2.1 General data

- Thermal resistance : n.a.
- Application category of contact: 0, 1 and 2
- Contact arrangement : 2 make and break contacts
- Mass (Weight) : 2,55 g max.
- Finish of the relay housing : anti-corrosion
- Finish of the terminals : tin-plated or gold-plated
- Insulation resistance : 10 000 MΩ min at 500 V d.c.
- Dielectric withstand voltage : according to table 1
- Nominal free internal volume : 0,2 cm³ max.

Table 1 Dielectric test voltages

	at sea level V a.c. min.	at 2 kPa (26 600 m) V a.c. min.
Open contacts:	500	250
Between adjacent contacts:	500	250
Contacts to case:	500	250
Coil to contacts:	500	250
Coil to case:	500	250

2.2 Construction of designation (ordering information):

	Relay	CECC 16 207	001	A	1	B	1	Y
Denomination: _____	_____	_____	_____	_____	_____	_____	_____	_____
CECC-Number _____	_____	_____	_____	_____	_____	_____	_____	_____
Type code (CECC registration number) _____	_____	_____	_____	_____	_____	_____	_____	_____
Coil voltage (according to 2.3) _____	_____	_____	_____	_____	_____	_____	_____	_____
Terminals (according to 2.5) _____	_____	_____	_____	_____	_____	_____	_____	_____
Mounting (according to 2.6) _____	_____	_____	_____	_____	_____	_____	_____	_____
Special attributes (according to 2.3) _____	_____	_____	_____	_____	_____	_____	_____	_____
Assessment level _____	_____	_____	_____	_____	_____	_____	_____	_____

For electronic data processing the ordering data shall be written without blanks.

2.4.3 Static contact resistance:

max. 100 m Ω initial resistance (measured at 3 mm distance from the relay header)
max. 200 m Ω after electrical life

2.4.4 Dynamic contact voltage drop (for low level load)

Voltage drop 5 % max. of voltage across closed contacts

2.4.5 Mechanical life:

900 000 switching cycles after low level electrical endurance

2.4.6 Timing (Over the whole temperature range):

- Operate time max. 2 ms
- Release time max. 1,5 ms
4 ms (with coil transient suppression)
- Bounce time max. 1,5 ms
- Stabilisation time max. 2,5 ms

Note: Stabilisation time is the sum of bounce time and the time to stabilize to 90 % of static contact resistance.

2.5 Terminals, variants and codes

Table 4.1

Code number	Terminals	Finish
2	Pins	tinned
3	Pins	gold plated
4	Long leads	tinned
5	Long leads	gold plated

For further informations see annex 1.

2.6 Mounting

Table 4.2

Code letter	Mounting variant
J	Ground pin
K	Ground pin with mounting pad round 0,36 mm
L	Ground pin with pad grid 2,54 mm, H = 0,8 mm
O	Without mounting hardware accessories
P	Mounting pad round, H = 0,36 mm
T	Padgrid 2,54 mm, H = 0,8 mm

For further informations see annex 1.

2.7 Environmental data

The relays shall withstand at least the following environmental stresses:

- shock: 981 m/s² (100 g) peak acceleration, 6 ms duration.
- bump: 392 m/s² (40 g) peak acceleration, 6 ms duration.
- vibration (sinusoidal): 10 Hz to 60 Hz peak amplitude 2,0 mm
60 Hz to 3000 Hz 294 m/s² (30 g) peak acceleration
- vibration (random): 0,2 g²/Hz, 20 Hz to 2000 Hz
- acceleration (constant): 98 m/s², duration 5 minutes
- mechanical robustness of terminals:
 - Test Ua1 tensile 5 N
 - Test Ua2 shear stress under consideration
 - Test Ub bending 2,5 N
 - Test Uc torsion n.a.

3 Qualification approval

- as stated in CECC 00 114/II section 1.4 (1) "fixed sampling"
- sampling and test schedule are specified in Table 6
- the tests specified and their order are mandatory.

4 Quality conformance inspection

Quality conformance inspection contains the tests stated in Table 5

- group A and B tests for inspection lots acceptance
- group C and D periodic tests.

Unless otherwise stated in this detail specification, all tests of Table 5 are mandatory.

Where a sub-group contains cumulative tests, the order of the tests is mandatory.

Specimens subjected to tests denoted as destructive (D) shall not be released for delivery.

4.1 Formation of inspection lots

According to CECC 00 114/II section 3.1

4.2 Intervals between group C and group D tests

The tests of group C and D shall be performed in the intervals specified in Table 5.

5 Marking and documentation

Relays and their package supplied according to this detail specification shall be marked as follows:

5.1 Marking of the relay:

The marking shall be durable and easily legible, the following items shall be present:

- a) Manufacturer's name or trade mark
- b) CECC-mark of conformity
- c) Date of manufacture, year/week coded according to IEC 62
- d) Wiring diagram
- e) CECC ordering information according to clause 2.2

5.2 Marking of packaging

- a) Manufacturer's name or trade mark
- b) Indication of place and/or country of manufacturing
- c) CECC ordering information according to clause 2.2
- d) Date of manufacture, year/week coded according to IEC 62
- e) Quantity

5.3 Documentation

For each delivery shall be added a certificate of conformance according to CECC 00 114.

6 Annexes

Annex 1 shows terminals and mounting (Variants and codes according to table 4.1 respectively table 4.2)

Annex 2 shows insulation pad information.

7 Tests

7.1 Standard conditions for testing:

If not otherwise stated all tests shall be performed according to section 5.5 of CECC 16 000.

7.2 Mounting of test items during the test

The following indications shall apply for mechanical tests e.g. shock, vibration, acceleration, bump.

The relay shall be mounted by its normal mounting methods and additional fixtures to the test plate where inherent resonances have been minimized so as not to invalidate the test results; IEC 68-2-47 refers.

7.3 General conditions for testing

Unless otherwise stated, the tests shall be carried out under general test conditions according to IEC 68 part 1.

Unless otherwise stated, the rated coil voltage specified in table 2 shall be used for all tests.

8 Ordering information

See clause 2.2

Notes on Table 5

Note 1: Unless otherwise stated the sectional numbers of tests and performance requirements refer to CECC 16 000, Issue 2.

Note 2: Section number refers to this specification.

Note 3: Inspection Levels (IL) and Acceptable Quality Levels (AQL) are selected from IEC 410.

Note 4: P = periodicity (in months)
n = sample size
c = acceptance criterion (permitted number of defectives)

Note 5: More severe than CECC 16 207