

Förderverein für Elektrotechnische Normung (FEN) e. V.
Cenelec Electronic Components Committee

CECC

Système Harmonisé d'Assurance de la Qualité
des Composants Electroniques

SPECIFICATION PARTICULIERE
CADRE:

CONNECTEURS COAXIAUX
POUR FREQUENCE
RADIOELECTRIQUE
Série 1,6/5,6

Harmonized System of Quality Assessment for
Electronic Components

BLANK DETAIL SPECIFICATION:

RADIO FREQUENCY
COAXIAL CONNECTORS
Series 1,6/5,6

Harmonisiertes Gütebestätigungssystem für
Bauelemente der Elektronik

VORDRUCK
FÜR BAUARTSPEZIFIKATION:

HOCHFREQUENZ-
KOAXIAL-STECKVERBINDER
Serie 1,6/5,6



1

Edition
Issue
Ausgabe

CECC 22 241

1989



Documents

Document Sharing Hub

Information about the System may be obtained from:



FEN Secretariat
and
CECC General Secretariat
Stresemannallee 15
D-6000 Frankfurt/Main 70
Telefon: Int.+ (49) 69 6 30 82 83
Telex 4-12871 vdetz d
Telefax Int.+ (49) 69 6 30 82 83 (Gr. 2/3)
or from the National Authorized Institutions
of the participating countries listed
who can supply copies of:

- 1 The Internal Regulations of the FEN e.V.
- 2 CECC Specifications of the FEN and National Specifications for the System
- 3 CECC 00 200: Qualified Products List (QPL)
- 4 CECC 00 300: CECC Publications and their related national documents

Austria
Österreichischer Verband
für Elektrotechnik
Eschenbachgasse 9
A-1010 Vienna

Belgium
Comité Electrotechnique Belge
Galerie Ravenstein 3
Boîte 11
B-1000 Brussels

Denmark
Dansk Elektroteknisk Komite
Strandgade 36
DK-1401 Copenhagen K

Finland
Finnish Electrotechnical
Standards Association
P.O. Box 134
SF-00211 Helsinki 21

France
Union Technique de l'Electricité
Participation française au CECC
12, Place des Etats-Unis
F-75783 Paris Cedex 16

Germany
Deutsche Elektrotechnische
Kommission im DIN und VDE
Stresemannallee 15
D-6000 Frankfurt/Main 70

Ireland
EOLAS- The Irish Science and
Technology Agency
Glasnevin
IRL-Dublin 9

Italy
Comitato Elettrotecnico Italiano
Viale Monza, 259
I-20126 Milan

Netherlands
Nederlands Elektrotechnisch Comité
Postbus 5059
NL-2600 GB Delft

Norway
Norsk Elektroteknisk Komite
P.O. Box 280
Skøyen
N-0212 Oslo 2

Portugal
Instituto Português da Qualidade
Rua José Estêvão, 83A
P-1199 Lisbon Codex

Spain
Asociación Electrotécnica y Electrónica Española
Comité Español del CECC
Avda. de Brasil, 7
E-28020 Madrid 20

Sweden
Svenska Elektriska Kommissionen
Box 1284
S-16428 Kistå-Stockholm

Switzerland
Schweizerischer Elektrotechnischer
Verein
Postfach
CH- 8008 Zürich

United Kingdom
British Electrotechnical Committee
British Standards Institution
2, Park Street
GB-London W1A 2BS

FOREWORD

The CENELEC Electronic Components Committee (CECC) is composed of those member countries of the European Committee for Electrotechnical Standardization (CENELEC) who wish to take part in a harmonized system for electronic components of assessed quality.

The object of the System is to facilitate international trade by the harmonization of the specifications and quality assessment procedures for electronic components and by the grant of an internationally recognized Mark, or Certificate of Conformity. The components produced under the System are thereby accepted by all member countries without further testing.

This specification has been formally approved by the CECC, and has been prepared for those countries taking part in the System who wish to issue national harmonized specifications for RADIO FREQUENCY COAXIAL CONNECTORS AND ACCESSORIES SERIES 1,6/5,6. It should be read in conjunction with the current regulations for the CECC System.

At the date of printing of this specification the member countries of the CECC are Austria, Belgium, Denmark, Finland, France, Germany, Ireland, Italy, the Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and the United Kingdom, and copies of it can be obtained from the addresses shown on the blue flysheet.

PREFACE

This blank detail specification (BDS) was prepared by CECC Working Group 22: R.F. Connectors.

It is based, wherever possible, on the Publications of the International Electrotechnical Commission and in particular on IEC 169-13: Radio-frequency connectors, Part 13: R.F. coaxial connectors with inner diameter of outer conductor 5,6 mm (0,220 in) - Characteristic impedance 75 Ω (Type 1,6/5,6).

This BDS and its associated sectional specification (SS) are specific to Series 1,6/5,6 radio frequency connectors and their related accessories; they should be read in conjunction with document CECC 22 000, Generic Specification: Radio Frequency Coaxial Connectors.

The text of this BDS was circulated to the CECC for voting in the document listed below and was ratified by the President of the CECC for printing as a CECC specification:

<u>Document</u>	<u>Voting Date</u>	<u>Report on the Voting</u>
CECC(Secretariat)1934	September 1986	CECC(Secretariat)2059

CECC SPECIFICATION SYSTEM FOR RADIO FREQUENCY CONNECTORS

<u>GENERIC SPECIFICATION (GS)</u> -Scope -General -Quality assessment procedures -Test and measurement procedures	CECC 22 000
<u>SECTIONAL SPECIFICATION (SS)</u> -Drawings Mating face drawings for standard test connectors, general-purpose connectors & applicable gauges -Standard conditions for testing -Qualification approval tests -Lot-by-lot tests -Periodic tests	CECC 22 110 Series SMA CECC 22 120 Series BNC CECC 22 130 Series SMB etc etc
<u>BLANK DETAIL SPECIFICATION (BDS)</u> -Pro-forma for preparation of DS	CECC 22 111 CECC 22 121 CECC 22 131 etc etc
<u>DETAIL SPECIFICATION (DS)</u> -Description of style -Details of any variants, appropriate cables, etc. -Outline drawing(s) -Assessment level -Ratings (including limiting conditions of use) and characteristics -Test requirements	CECC 22 111-001 CECC 22 111-002 CECC 22 111-003 etc CECC 22 111-801 CECC 22 111-802 CECC 22 111-803 etc
NOTES: 1. - A detail specification (DS) is a 'completed' blank detail specification (BDS). 2. - Document numbering for r.f. connector specifications follows 2.2(1) of CECC 00 400 Part III, in order to permit the issue of more than nine SS. The approved numbering system is shown above.	PRODUCED BY AN ONH PRODUCED BY CECC/WG22

INSTRUCTIONS FOR PREPARATION OF DETAIL SPECIFICATIONS

The numbers between square brackets on pages 1 and 2 correspond to the following indications which shall be given:

Identification of the detail specification (DS)

- [1] The name of the National Standards Institution under whose authority the DS is published and, if applicable, the organization from whom the DS is available.
- [2] The CECC symbol and the number allotted to the DS by the CECC General Secretariat.
- [3] The number and issue number of the CECC generic or sectional specification as relevant; also national reference if different.
- [4] If different from the CECC number, the national number of the DS, date of issue and any further information required by the national system, together with any amendment numbers.

Identification of the component

- [5] Enter the following details:

Style: The style designation or model number of the connector.

The method of cable/wire attachment to the centre and outer conductor:
By deletion of inapplicable options given.

Special features and markings: Example: 'Fitted with both panel and barrier seals'.

Mass: The maximum mass in grams, rounded upwards to the nearest whole number. If several variants (having differing mass) are included, list the maximum mass of each variant separately.

- [6] Enter details of assessment level, characteristic impedance and climatic category.
- [7] A reproduction of the outline drawing and panel piercing details shall be provided. It shall provide maximum envelope dimensions of the relevant body style and in the case of a fixed connector the position of the mounting plane(s) relative to the front face of the connector. Conformance of the interface and/or outline dimensions with other specifications such as CECC 22 240 and IEC 169-13, shall be stated.

Any maximum panel thickness limitations for fixed connectors shall be stated.

- [8] Particulars of all variants covered by the DS. Where appropriate, the information shall include:
- cable types (or sizes) applicable to each variant
 - alternative plated or protective finishes
 - details of alternative mounting flanges having either tapped or plain mounting holes
 - details of alternative solder spills or solder buckets for microwave component-mounting styles.
- [9] Performance data listing the most important characteristics of the connector in accordance with the requirements of 3.1 of CECC 22 240. Deviations from the minimum requirements listed shall be clearly indicated. Non-applicable parameters shall be marked 'na'.

For [5] and [6] the text to be given in the DS should be suitable for an entry in CECC 00 200 (QPL) or CECC 00 300.

[1]	page 1 of ...	[2] CECC 22 241 -	
ELECTRONIC COMPONENT OF ASSESSED [3] QUALITY IN ACCORDANCE WITH GENERIC SPECIFICATION SECTIONAL SPECIFICATION	[4]	Issue	
[5] DETAIL SPECIFICATION for RADIO FREQUENCY COAXIAL CONNECTOR OF ASSESSED QUALITY:		SERIES 1.6/5.6	
Locking devices:			
Style:		Special Features & Markings:	
Method of cable/wire* attachment: centre conductor - solder/crimp* : outer conductor - solder/clamp/crimp*			
Mass:(Max.) *Delete as appropriate			
[6] Assessment level Characteristic impedance 75 Ω Climatic category/...../.....			
[7] Outline and maximum dimensions		Panel piercing and mounting details	

For mating interface dimensions and position of reference plane see CECC 22 240

Maximum panel thickness: for front mounting mm, for rear mounting mm

The outline dimensions meet the requirements of

[8] Variants

Variant No.	Description of Variant	Relevant Cables		
		IEC 96	RG	National Cables
.....-01				
.....				
.....				
.....				
.....				
.....				
.....				
.....				

Information about manufacturers who have components qualified to this detail specification is available in the current CECC 00 200: Qualified Products List.

RATINGS AND CHARACTERISTICS		CECC 22 240 CLAUSE	VALUE	REMARKS
ELECTRICAL				
+ Working voltage at sea level	Variant No./ Designation -01			
			 V	86 to 106 kPa
				
				
				
				
				
				
				
				
+ Working voltage at 20 km altitude	Variant No./ Designation -01			
			 V	4,4 kPa
				
				
				
				
				
				
				
				
RF high potential withstanding voltage		4.4.7	na	
Screening effectiveness	Variant No./ Designation -01			
		4.4.8	$Z_t < \dots \Omega$	Providing > dB
				
				
				
				
				
				
				
				
ADDITIONAL ELECTRICAL CHARACTERISTICS				

+ Voltage values are r.m.s. values of a.c. at 50 to 60 Hz unless otherwise stated.

RATINGS AND CHARACTERISTICS	CEOC 22 240 CLAUSE	VALUE	REMARKS
MECHANICAL			
Contact captivation: - axial force - torque	4.5.2	 N na	
Static load (for fixed connectors only)	4.5.3	na	
Engagement and separation - torque	4.5.4	..na.. Nm max.	(to overcome friction of coupling nut)
- axial force		 N max. N max.	Engagement Screw and Slide-in Snap-on
Coupling torque - normal - proof		 N min. N min. na	Separation Screw and Slide-in Snap-on
Effectiveness of clamping device against cable pulling	Variant No./ Designation -01	4.5.5 (1)	
Effectiveness of clamping device against cable torsion	-01	4.5.5 (2) Nm	

RATINGS AND CHARACTERISTICS	CECC 22 240 CLAUSE	VALUE	REMARKS
MECHANICAL			
Tensile strength of coupling mechanism	4.5.6	 N	(screw coupling connectors only)
Bending moment	4.5.9	 Nm	Relative to reference plane (screw + snap coupling connectors only)
ADDITIONAL MECHANICAL CHARACTERISTICS			
ENVIRONMENTAL			
Bump	4.6.2	na	
Vibration	4.6.3	 m/s ² to..... Hz	(..g _n acceleration)
Shock	4.6.4	na	
Climatic category	4.6.5	/..../....	
Damp heat, steady state	4.6.6		
Sealing (panel and barrier sealed connectors)	4.6.8		100 to 110 kPa pressure differential
Sealing (hermetically sealed connectors)	4.6.9		100 to 110 kPa pressure differential
Salt mist	4.6.10		
ADDITIONAL ENVIRONMENTAL CHARACTERISTICS			

RATINGS AND CHARACTERISTICS	CECC 22 240 CLAUSE	VALUE	REMARKS
ENDURANCE			
Mechanical	4.7.1	operations	
High temperature	4.7.2	 h at..... °C	
ADDITIONAL ENDURANCE CHARACTERISTICS			

[10] SUPPLEMENTARY INFORMATION

- marking of the component: in accordance with 2.4 of CECC 22 000, in the following order of precedence:

- | | | |
|---|------------------------------------|----------------|
| (1) Component identification | Variant No./
Designation
-01 | Identification |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| (2) Identification of manufacturer: | | |
| (3) Manufacturing date, code, year/week | | |

- marking and contents of package: in accordance with 2.5 and 2.5.1 of CECC 22 000 as follows:

- (1) Information prescribed in 2.4 of CECC 22 000 detailed above
- (2) Nominal characteristics impedance 75.Ω.....
- (3) Assessment level code letter
- (4) Any additional marking required

- ordering information: in accordance with 2.6 of CECC 22 000 as follows:

- (1) Number of the detail specification CECC 22 241-.../Variant code
- (2) Assessment level code letter
- (3) Body finish (if more than one listed)
- (4) Any additional information or special requirements

- related documents (if not included in CECC 22 000 or CECC 22 240):
.....
.....
- certified test records (RCE): in accordance with 3.7 of CECC 22 000
(when applicable) (requirements to be included later)
- structural similarity: in accordance with 3.2 and 3.4 of CECC 22 000.

NOTE: Relevant information on a basic style should be entered as Variant 01.

[11]TEST SCHEDULES AND INSPECTION REQUIREMENTS - SERIES 1,6/5,6

ACCEPTANCE TESTS

GROUP A1

Visual examination

CECC 22 240 Clause	Level			
	Test Required	IL	AQL	Period
4.2				
4.3.1				
4.5.7				
4.5.4				Lot
4.5.1				by
4.6.8				Lot
4.6.9				
4.4.5				

GROUP B1

Outline dimensions

Compatibility mechanical

Engagement and
separationGauge retention force
(resilient contacts)

Sealing (panel and barrier)

Sealing (hermetic)

Voltage proof

PERIODIC TESTS

GROUP C1(d)

Soldering

Insulation resistance

CECC 22 240 Clause	Test Required	IL	AQL	Period
4.6.1				
4.4.4				

For notes relating to symbols: See page 10.

	CECC 22 240 Clause	Test Required	Specimens (may be from C1)	Permitted Failures per group†	Period
GROUP D1(d)					
Mechanical tests on cable clamping device	4.5.5				
Bending moment	4.5.9				
GROUP D2(d)					
Contact resistance	4.4.2				
Outer conductor continuity	4.4.3				
Vibration	4.6.3				
Damp heat, steady state	4.6.6				
Salt mist	4.6.10				
GROUP D3					
Dimensions and materials (piece parts)*	4.3.2				
Mass	4.3.1				
GROUP D4(d)					
Mechanical endurance	4.7.1				
High temperature endurance	4.7.2				
GROUP D6(d)					
Reflection factor	4.4.1				
Screening effectiveness	4.4.8				

For notes relating to symbols: See page 10.