



BRITISH STANDARDS INSTITUTION 389 CHISWICK HIGH ROAD LONDON W4 4AL	BS CECC 30 501-033  ISSUE 1 FEBRUARY 1995
Specification available from: AS SHOWN IN PD 9002, CECC 00 200 and mfd capacitors (1991) Ltd.  Penley Wrexham Clwyd LL13 0LY Telephone: 01978 710 551 Fax: 01978 710 501	MANUFACTURER'S TYPE NUMBER PCCA/MKC21 SEE PD 9002 AND CECC 00 200 For ordering information see clause 1.6
ELECTRONIC COMPONENTS OF ASSESSED QUALITY DETAIL SPECIFICATION IN ACCORDANCE WITH BS CECC 30 000: 1984 BS CECC 30 500: 1989 Outline and dimensions First angle projection   Minimum lead length 30 All dimensions in mm Marking information: see clause 1.5	FIXED METALLIZED POLYCARBONATE FILM DIELECTRIC D.C. CAPACITOR TYPICAL CONSTRUCTION: CYLINDRICAL NON METALLIC CASE AXIAL TERMINATIONS ASSESSMENT LEVEL E

QUICK REFERENCE DATA

Capacitance range	10 nF to 10 μ F
Capacitance tolerance	$\pm 1\%$, $\pm 2\%$, $\pm 5\%$, $\pm 10\%$, $\pm 20\%$
Rated voltage ranges	63 V d.c. to 400 V d.c.
Climatic category	55/100/56
Performance grade	1

Refer to Qualified Products List PD 9002 and/or CECC 00 200 for details of manufacturers approved to this specification

BS CECC 30 501-033
ISSUE 1 FEBRUARY 1995

1 General data

1.1 Method of mounting for vibration and shock tests

Each capacitor shall be mounted on a printed circuit board, the body being pressed firmly against the mounting surface and fixed by soldering the leads, which shall be bent through 90° at a point 6 mm to 6.5 mm from the point of emergence of the termination. Units of mass of 3g or greater shall also have their bodies clamped.

1.2 Dimensions

Table 1

Case size reference	D max	L max	d min	d nom	d max
Dimensions (in mm)					
A	8.0	15.3	0.55	0.6	0.65
B	9.6	19.8	0.55	0.6	0.65
C	12.5	22.0	0.75	0.8	0.88
D	12.5	29.0	0.75	0.8	0.88
E	14.0	32.0	0.75	0.8	0.88
F	17.5	32.0	0.75	0.8	0.88

1.3 Ratings and characteristics

Capacitance range	10 nF to 10 μ F The preferred values of rated capacitance conform to the E6 values of IEC 63 (See Table 2). Where the use of other values is essential they shall be chosen from that document		
Tolerance on rated capacitance	$\pm 1\%$, $\pm 2\%$, $\pm 5\%$, $\pm 10\%$, $\pm 20\%$		
Rated voltage	63 Vd.c., 100 Vd.c., 160 Vd.c., 250 Vd.c., 400 Vd.c. (See Table 2)		
Category voltage	50 Vd.c., 80 Vd.c., 128 Vd.c., 200 Vd.c., 320 Vd.c. (See Table 2)		
Climatic category	55/100/56		
Rated temperature	85 °C		
Tangent of the loss angle (@ 1 kHz)	$C_R \leq 1 \mu F$	$\leq 30 \times 10^{-4}$	
	$C_R > 1 \mu F$	$\leq 50 \times 10^{-4}$	
Insulation resistance:			
Measuring point 1a (between terminations)	$U_R \leq 100 V$	$C_R \leq 330 nF$	$\geq 15 G\Omega$
		$C_R > 330 nF$	$\geq 5 ks$
	$U_R > 100 V$	$C_R \leq 330 nF$	$\geq 30 G\Omega$
		$C_R > 330 nF$	$\geq 10 ks$
Measuring point 1c (between terminations connected together and foil or V-block)	$\geq 30 G\Omega$		

Table 2
Values of capacitance related to voltages and case sizes

Rated voltage (V @ 85 °C)	63	100	160	250	400
Category voltage (V @ 100 °C)	50	80	128	200	320
Rated capacitance	Case size reference				
10 nF					A
15 nF					A
22 nF					A
33 nF					A
47 nF				A	B
68 nF		A	A	B	B
100 nF		A	A	B	B
150 nF		A	A	B	B
220 nF	A	B	B	B	C
330 nF	B	B	B	C	C
470 nF	B	C	C	C	D
680 nF	B	C	C	D	E
1.0 µF	B	C	C	E	F
1.5 µF	C	D	D	E	
2.2 µF	C	E	E	F	
3.3 µF	D	F	F		
4.7 µF	E				
6.8 µF	E				
10 µF	F				

1.4 Related documents

IEC 63 (BS 2488)	Schedule of preferred numbers for the resistance of resistors and the capacitance of capacitors for telecommunication equipment
IEC 68 (BS 2011)	Basic environmental testing procedures
IEC 410 (BS 6001)	Sampling procedures and tables for inspection by attributes
BS CECC 30 000	Generic specification for fixed capacitors
BS CECC 30 500	Sectional specification: Fixed metallized polyethylene-terephthalate film dielectric capacitors for direct current
PD 9002	BS 9000 component selection guide
CECC 00 200	Qualified products list

1.5 Marking

The following information will be marked on the capacitor:

- 1) Rated capacitance
- 2) Rated voltage
- 3) Tolerance on rated capacitance (%)
- 4) Week and year of manufacture
- 5) Type number

The package containing the capacitor(s) shall be clearly marked with all the information listed in 1) to 5) above, together with the following:

- 6) Manufacturer's name
- 7) Climatic category
- 8) Category voltage
- 9) Reference to this detail specification

1.6 Ordering information

Orders for components to this specification shall contain the following minimum information:

- 1) Quantity
- 2) Manufacturer's type number
- 3) Rated capacitance
- 4) Tolerance on rated capacitance
- 5) Rated d.c. voltage
- 6) This specification number, issue and date
- 7) Case size reference, if not the preferred size, see Table 2

Example: 100 off PCCA 680 nF $\pm$ 10 % 250 V d.c. to BS CECC 30 501-033. Issue 1
February 1995

1.7 Certified test records

Not required

1.8 Additional information (not for inspection purposes)**1.8.1 Case size and mass**

Case size reference	A	B	C	D	E	F
Mass (g)	1.0	1.7	3.4	4.3	5.7	11.0

1.8.2 Mounting for normal use

The full vibration and shock performance may not be available if mounting methods other than those specified in sub-clause 1.1 of this specification are used.

1.8.3 This specification is intended to replace:

BS 9076 F0019, BS 9076 F0039, BS CECC 30 501-011 BS CECC 30 501-022