


BRITISH STANDARDS INSTITUTION 2 PARK STREET, LONDON. W1A 2BS Specification available from:- AS SHOWN IN PD 9002 AND CECC 00 200 AND	BS CECC 90103 - 013 ISSUE 1 NOVEMBER 1981 Page 1 of 16 pages
ELECTRONIC COMPONENTS OF ASSESSED QUALITY DETAIL SPECIFICATION IN ACCORDANCE WITH: BS CECC 90 000 : 1976 BS CECC 90 100 : 1977	MANUFACTURERS TYPE NUMBER 54LS14 64LS14 74LS14 84LS14
Outline not to scale: Isometric projection Marking information see clause 1  Refer to IEC 191-1-50a (type A50B) Dual-in-Line (plastic or ceramic) refer to Appendix A1.3 Flatpack (metal or ceramic)	SEE PD 9002 AND CECC 00 200 For ordering information see clause 1 HEX SCHMITT TRIGGER INVERTERS TYPICAL CONSTRUCTION SILICON MONOLITHIC BIPOLAR TTL-LOW-POWER SCHOTTKY ASSESSMENT LEVELS R, S, T AND V

1. Type description

1.1 Truth table (each inverter)

IN	OUT
H	L
L	H

H = High level
 L = Low level


1.1.1 Boolean equation

$$Y = \overline{A.B}$$

Refer to Qualified Products List PD 9002 and/or CECC 00 200
 for details of manufacturers approved to this specification

1.2 Terminal identification, type designation and marking

1.2.1 Terminal identification



Six independent Hex Schmitt trigger inverters

1.2.2 Type designation

TEMPERATURE RANGE	PACKAGE		
	Ceramic Dual-in-Line	Plastic Dual-in-Line	Ceramic Flatpack
0 + 70	74LS14J	N	W
-25 + 85	84LS14J		
-40 + 85	64LS14J		
-55 +125	54LS14J		

1.2.3 Marking

Each integrated circuit shall bear the following markings:

- (1) Terminal identification
- (2) Type designation
- (3) Date code
- (4) Factory identification code (unless derived from trademark)
- (5) Manufacturers trade name or mark
- (6) Mark of conformity (unless a certificate of conformity is used)

1.3 Ordering information

Orders for these integrated circuits shall contain the following minimum information:

Manufacturers integrated circuit type designation, screening procedures and assessment level as detailed to this CECC specification number.

(For details of screening procedures see Appendix A1.1).

2. Limiting conditions of use (not for inspection purposes)

2.1	Maximum continuous supply voltage	V_{CC}		-0,5V	+7,0V		
2.2	Maximum input voltages						
2.2.1	Maximum input voltage	V_I		-0,5V	+7,0V		
2.2.2	Maximum input voltage between multiple emitter transistor inputs	V_{II}		+5,5V			
				54LS	64LS	74LS	84LS
2.3	Maximum and minimum operating ambient temperatures	$T_{amb}(^{\circ}C)$	min.	-55	-40	0	-25
			max.	+125	+85	+70	+85
2.4	Maximum and minimum storage temperatures	$T_{stg}(^{\circ}C)$	min.	-65	(All types)		
			max.	+150			

3. Recommended operating conditions and associated characteristics (not for inspection purposes)

3.1 Recommended operating conditions

These apply over the operating ambient temperature range unless otherwise stated.

Description	Symbol	Type	Value	Unit
Positive supply voltage	V_{CC}	54LS 64/74/84LS	4,5 - 5,5 4,75 - 5,25	V V
Minimum value of input voltage	V_{INB}	All types	-0,3	V
Maximum value of input voltage	V_{INA}	All types	5,5	V
Maximum value of Low level output current for each output	I_{OLA}	54LS 64/74/84LS	4,0 8,0	mA mA
Maximum value of High level output current for each output at V_{OH}	I_{OHA}	All types	-0,4	mA

3.2 Associated characteristics

3.2.1 Minimum and maximum values are given for the worst case operation over the ambient temperature range, except for those conditions marked with an asterisk (*)

	54LS	64LS	74LS	84LS	
T _{amb} min.	-55	-40	0	-25	°C
T _{amb} max.	+125	+85	+70	+85	
V _{CC} min.	4,5	4,75			V
V _{CC} max.	5,5	5,25			

3.2.2

Characteristics	Conditions	$V_{CC}(V)$	Symbol	Min.	Max.	Unit
Total supply current with High level output	$V_{IN} = 0V$ (1)	$V_{CC} \text{ max.}$	I_{CCH}	-	16,0	mA
Total supply current with Low level output	$V_{IN} = 4,5V$	$V_{CC} \text{ max.}$	I_{CCL}	-	21,0	mA
High level input current	$V_{IN} = 7,0V$	$V_{CC} \text{ max.}$	$I_{IH(1)}$	-	100,0	μA
	$V_{IN} = 2,7V$	$V_{CC} \text{ max.}$	$I_{IH(2)}$	-	20,0	μA
Low level input current	$V_{IN} = 0,4V$	$V_{CC} \text{ max.}$	$-I_{IL}$	-	0,4	mA
Input clamping voltage	$-I_{IC} = 18,0mA$	$V_{CC} \text{ min.}$	$-V_{ICA}$	-	1,5	V
Output voltage	54LS $I_{OH} = -0,4mA$	$V_{CC} \text{ min.}$	V_{OH}	2,5	-	V
	64/74/84LS $I_{OH} = -0,4mA$		V_{OH}	2,7	-	V
	All types $I_{OL(1)} = 4,0mA$ (2)	$V_{CC} \text{ min.}$	$V_{OL(1)}$	-	0,4	V
	64/74/84LS $I_{OL(2)} = 8,0mA$ (3)		$V_{OL(2)}$	-	0,5	V
Output loading circuit current	$V_O = 0V$ (4) $V_{IN} = 0V$	$V_{CC} \text{ max.}$	$-I_{OS}$	15,0	130,0	mA
Positive going threshold voltage	$V_{CC} = 5,0V$		V_{T+}	1,4	1,9	V
Negative going threshold voltage	$V_{CC} = 5,0V$		V_{T-}	0,5	1,0	V

- (1) To all inputs, (2) Fan out = 10, (3) Fan out = 20,
(4) Only one output at a time, duration $t \leq 1 \text{ sec}$


3.2.2 (contd)

Characteristics	Conditions	$V_{CC}(V)$	Symbol	Min.	Max.	Unit
Hysteresis ($V_{T+} - V_{T-}$)	$V_{CC} = 5,0V$		V_{HSTB}	0,4	-	V
Propagation time All types	$T_{amb} = 25^{\circ}C$ test conditions as in Sub-group A5	5,0V	t_{PLH} t_{PHL}	- -	22,0 22,0	ns ns

* See 3.2.1 of this specification



3.3 Supplementary information

3.3.1 Change of typical propagation time with output loading



Propagation times Vs. load capacitance

3.3.2 Variation of propagation time with temperature



3.3.3 DC noise margin

Low level $V_{ILA} - V_{OLA} = V_{NL}$

High level $V_{OHB} - V_{IHB} = V_{NH}$