

BRITISH STANDARDS INSTITUTION

2 PARK STREET, LONDON. W1A 2BS

BS CECC 90103 - 017

ISSUE 1

NOVEMBER 1981



Page 1 of 15 pages


ELECTRONIC COMPONENTS OF ASSESSED QUALITY
DETAIL SPECIFICATION IN ACCORDANCE WITH:

BS CECC 90 000 : 1976
BS CECC 90 100 : 1977

MANUFACTURERS TYPE NUMBER

54LS22
64LS22
74LS22
84LS22

Outline not to scale: Isometric projection
Marking information see clause 1



Refer to IEC 191-1-50a (type A50B)
Dual-in-Line (plastic or ceramic)
refer to Appendix A1.3
Flatpack (metal or ceramic)

SEE PD 9002 AND CECC 00 200
For ordering information see
clause 1

DUAL 4-INPUT NAND GATES WITH
OPEN COLLECTOR OUTPUTS

TYPICAL CONSTRUCTION
SILICON MONOLITHIC
BIPOLAR TTL-LOW-POWER
SCHOTTKY

ASSESSMENT LEVELS
R, S, T AND V

1. Type description

1.1 Truth table

INPUTS				OUTPUTS
A	B	C	D	Y
H	H	H	H	L
L	X	X	X	H
X	L	X	X	H
X	X	L	X	H
X	X	X	L	H

H = High level
L = Low level
X = Logic level irrelevant


Refer to Qualified Products List PD 9002 and/or CECC 00 200
for details of manufacturers approved to this specification

1.1.1 Boolean equation

$$Y = \overline{A.B.C.D}$$

1.2 Terminal identification, type designation and marking.

1.2.1 Terminal identification



Dual 4-input Nand gates
with open collector outputs

Terminals marked with 'NC' are not connected internally and may be used as electrical support points. The applied voltage shall not exceed 7,0V.

1.2.2 Type designation

TEMPERATURE RANGE	PACKAGE		
	Ceramic Dual-in-Line	Plastic Dual-in-Line	Ceramic Flat pack
0 +70	74LS22J	N	W
-25 +85	84LS22J		
-40 +85	64LS22J		
-55 +125	54LS22J		

1.2.3 Marking

Each integrated circuit shall bear the following markings:

- (1) Terminal identification
- (2) Type designation
- (3) Date code
- (4) Factory identification code (unless derived from trademark)
- (5) Manufacturers trade name or mark
- (6) Mark of conformity (unless a certificate of conformity is used,

1.3 Ordering information

Orders for these integrated circuits shall contain the following minimum information:

Manufacturers integrated circuit type designation, screening procedures and assessment levels as detailed to this CECC specification number.

(For details of screening procedures see Appendix A1.1)

2. Limiting conditions of use (not for inspection purposes)

2.1	Maximum continuous supply voltage	V_{CC}						-0,5V +7,0V
2.2	Maximum input voltage	V_I						-0,5V +7,0V
2.3	Minimum and maximum operating ambient temperatures	$T_{amb}(^{\circ}C)$	min. max.	54LS -55 +125	64LS -40 +85	74LS 0 +70	84LS -25 +85	
2.4	Minimum and maximum storage temperatures	$T_{stg}(^{\circ}C)$	min. max.	-65 +150	(All types)			

3. Recommended operating conditions and associated characteristics (not for inspection purposes)

3.1 Recommended operating conditions

These apply over the operating ambient temperature range unless otherwise stated.

Description	Symbol	Type	Value	Unit
Positive supply voltage range	V_{CC}	54LS 64/74/84LS	4,5 - 5,5 4,75 - 5,25	V V
Minimum value of High level input voltage	V_{IHB}	All types	2,0	V
Maximum value of High level input voltage	V_{IHA}	All types	5,5	V
Minimum value of Low level input voltage	V_{ILB}	All types	-0,3	V
Maximum value of Low level input voltage	V_{ILA}	54LS 64/74/84LS	0,7 0,8	V V
Maximum value of Low level output current for each output	I_{OLA}	54LS 64/74/84LS	4,0 8,0	V V
High level output for each output at $V_{OH} = 5,5V$	$-I_{OHX}$		100,0	μA
Maximum value of applied off state output voltage	V_{OZA}	All types	5,5	V

3.2 Associated characteristics

3.2.1 Minimum and maximum values are given for the worst case operation over the ambient temperature range, except for those conditions marked with an asterisk (*)

	54LS	64LS	74LS	84LS	
T _{amb} min.	-55	-40	0	-25	°C
T _{amb} max.	+125	+85	+70	+85	
V _{CC} min.	4,5	4,75			V
V _{CC} max.	5,5	5,25			

3.2.2


Characteristics	Conditions	$V_{CC}(V)$	Symbol	Min.	Max.	Unit
Total supply current with High level outputs	$V_{IL} = 0V^{(1)}$	$V_{CC} \text{ max.}$	I_{CCH}	-	0,8	mA
Total supply current with Low level outputs	$V_{IH} = 4,5V$	$V_{CC} \text{ max.}$	I_{CCL}	-	2,2	mA
High level input current	$V_{IH(1)} = 7,0V$	$V_{CC} \text{ max.}$	$I_{IH(1)}$	-	100,0	μA
	$V_{IH(2)} = 2,7V$	$V_{CC} \text{ max.}$	$I_{IH(2)}$	-	20,0	μA
Low level input current	$V_{IL} = 0,4V$	$V_{CC} \text{ max.}$	$-I_{IL}$	-	0,4	mA
Input clamping voltage	$-I_{IC} = 18,0mA$	$V_{CC} \text{ min.}$	$-V_{ICA}$	-	0,5	V
Output voltage All types 64/74/84LS	$I_{OL(1)} = 4,0mA^{(2)}$	$V_{CC} \text{ min.}$	$V_{OL(1)}$	-	0,4	V
	$I_{OL(2)} = 8,0mA^{(3)}$		$V_{OL(2)}$	-	0,5	V
Propagation times All types	$T_{amb} = 25^{\circ}C^*$ test conditions as in Sub-group A5	5,0V	t_{PLH}	-	32,0	ns
			t_{PHL}	-	28,0	ns

(1) To all inputs, (2) Fan out = 10, (3) Fan out = 20,

*See 3.2.1 of this specification



3.3 Supplementary information

3.3.1 Change of typical propagation time with output loading



Propagation time Vs. load capacitance

3.3.2 Variation of propagation time with temperature



3.3.3 D.C. noise margin

Low level $V_{ILA} - V_{OLA} = V_{NL}$