




BRITISH STANDARDS INSTITUTION 2 PARK STREET, LONDON. W1A 2BS		BS CECC 90103 - 021	
Specification available from:- AS SHOWN IN PD 9002 AND CECC 00 200 AND		ISSUE 1 NOVEMBER 1981	
ELECTRONIC COMPONENTS OF ASSESSED QUALITY DETAIL SPECIFICATION IN ACCORDANCE WITH: BS CECC 90 000 : 1976 BS CECC 90 100 : 1977		Page 1 of 17 pages	
Outline not to scale: Isometric projection Marking information see clause 1		MANUFACTURERS TYPE NUMBER 54LS30 64LS30 74LS30 84LS30	
		SEE PD 9002 AND CECC 00 200 For ordering information see clause 1	
Refer to IEC 191-1-50a (type A50B) Dual-in-Line (plastic or ceramic) refer to Appendix A1.3 Flatpack (metal or ceramic)		8-INPUT NAND GATES	
		TYPICAL CONSTRUCTION SILICON MONOLITHIC BIPOLAR TTL-LOW-POWER SCHOTTKY	
		ASSESSMENT LEVELS R, S, T AND V	

1. Type description

1.1 Truth table (see page 2)

Refer to Qualified Products List PD 9002 and/or CECC 00 200
for details of manufacturers approved to this specification

1.1 Truth table

INPUTS								OUTPUTS
A	B	C	D	E	F	G	H	Y
H	H	H	H	H	H	H	H	L
L	X	X	X	X	X	X	X	H
X	L	X	X	X	X	X	X	H
X	X	L	X	X	X	X	X	H
X	X	X	L	X	X	X	X	H
X	X	X	X	L	X	X	X	H
X	X	X	X	X	L	X	X	H
X	X	X	X	X	X	L	X	H
X	X	X	X	X	X	X	L	H


H = High level
L = Low level
X = Logic level irrelevant

1.1.1 Boolean equation

$$Y = \overline{A.B.C.D.E.F.G.H}$$

1.2 Terminal identification, type designation and marking.

1.2.1 Terminal identification



8-input Nand gates

Terminals marked with 'NC' are not connected internally and may be used as electrical support points. The applied voltage shall not exceed 7,0V.

1.2.2 Type designation

TEMPERATURE RANGE	PACKAGE		
	Ceramic Dual-in-Line	Plastic Dual-in-Line	Ceramic Flat pack
0 +70	74LS30J	N	W
-25 +85	84LS30J		
-40 +85	64LS30J		
-55 +125	54LS30J		

1.2.3 Marking

Each integrated circuit shall bear the following markings:

- (1) Terminal identification
- (2) Type designation
- (3) Date code
- (4) Factory identification code (unless derived from trademark)
- (5) Manufacturers trade name or mark
- (6) Mark of conformity (unless a certificate of conformity is used)

1.3 Ordering information

Orders for these integrated circuits shall contain the following minimum information:

Manufacturers integrated circuits type designation, screening procedures and assessment level as detailed to this CECC specification number.

(For details of screening procedures see Appendix A1.1)

2. Limiting conditions of use (not for inspection purposes)

2.1	Maximum continuous supply voltage	V_{CC}					-0,5V +7,0V
2.2	Maximum input voltages						
2.2.1	Maximum input voltage	V_I					-0,5V +7,0V
2.2.2	Maximum input voltage between multiple emitter transistor inputs	V_{II}					+5,5V
2.3	Minimum and maximum operating ambient temperatures	$T_{amb}(^{\circ}C)$	min. max.	54LS -55 +125	64LS -40 +85	74LS 0 +70	84LS -25 +85
2.4	Minimum and maximum storage temperatures	$T_{stg}(^{\circ}C)$	min. max.	-65 +150	(All types)		

3. Recommended operating conditions and associated characteristics (not for inspection purposes)

3.1 Recommended operating conditions

These apply over the operating ambient temperature range unless otherwise stated.

Description	Symbol	Type	Value	Unit
Positive supply voltage range	V_{CC}	54LS 64/74/84LS	4,5 - 5,5 4,75 - 5,25	V V
Minimum value of High level input voltage	V_{IHB}	All types	2,0	V
Maximum value of High level input voltage	V_{IHA}	All types	5,5	V
Minimum value of Low level input voltage	V_{ILB}	All types	-0,3	V
Maximum value of Low level input voltage	V_{ILA}	54LS 64/74/84LS	0,7 0,8	V V
Maximum value of Low level output current for each output	I_{OLA}	54LS 64/74/84LS	4,0 8,0	mA mA
Maximum value of output current for each output at V_{OH}	I_{OHA}	All types	-400,0	μA

3.2 Associated characteristics

3.2.1 Minimum and maximum values are given for the worst case operation over the ambient temperature range, except for those conditions marked with an asterisk (*)

	54LS	64LS	74LS	84LS	
T _{amb} min.	-55	-40	0	-25	°C
T _{amb} max.	+125	+85	+70	+85	
V _{CC} min.	4,5	4,75			V
V _{CC} max.	5,5	5,25			

3.2.2

Characteristics	Conditions	$V_{CC}(V)$	Symbol	Min.	Max.	Unit
Total supply current with High level output	$V_{IL} = 0V^{(1)}$	$V_{CC} \text{ max.}$	I_{CCH}	-	0,5	mA
Total supply current with Low level output	$V_{IH} = 4,5V$	$V_{CC} \text{ max.}$	I_{CCL}	-	1,1	mA
High level input current	$V_{IH(1)} = 7,0V$	$V_{CC} \text{ max.}$	$I_{IH(1)}$	-	100,0	μA
	$V_{IH(2)} = 2,7V$	$V_{CC} \text{ max.}$	$I_{IH(2)}$	-	20,0	μA
Low level input current	$V_{IL} = 0,4V$	$V_{CC} \text{ max.}$	$-I_{IL}$	-	0,4	mA
Input clamping voltage	$-I_{IC} = 18,0mA$	$V_{CC} \text{ min.}$	$-V_{ICA}$	-	1,5	V
Output voltage 54LS 64/74/84LS All types 64/74/84LS	$I_{OH} = -400,0\mu A$	$V_{CC} \text{ min.}$	V_{OH}	2,5	-	V
	$I_{OH} = -400,0\mu A$		V_{OH}	2,7	-	V
	$I_{OL(1)} = 4,0mA^{(2)}$		$V_{OL(1)}$	-	0,4	V
	$I_{OL(2)} = 8,0mA^{(3)}$		$V_{OL(2)}$	-	0,5	V
Output short circuit current	$V_O = 0V^{(4)}$ $V_{IL} = 0V$	$V_{CC} \text{ max.}$	$-I_{OS}$	15,0	130,0	mA
Propagation times All types	$T_{amb} = 25^\circ C^*$ test conditions as in Sub-group A5	5,0V	t_{PLH}	-	15,0	ns
			t_{PHL}	-	20,0	ns


(1) To all inputs, (2) Fan out = 10, (3) Fan out = 20,

(4) Only one output at a time, duration $t \leq 1 \text{ sec}$

* See 3.2.1 of this specification

3.3 Supplementary information

3.3.1 Change of typical propagation time with output loading



Propagation time Vs. load capacitance

3.3.2 Variation of propagation time with temperature

