



CGA P-49—2014

REAFFIRMED 2020

PREVENTION OF TOW-AWAY INCIDENTS

FIRST EDITION

This document licensed for the sole use of the purchaser. It may not be shared with any other person or used after the expiration date without the express written permission of the CGA. Any unauthorized use, reproduction, distribution, or modification of this printed page will result in a \$5,000 liquidated damages fee plus loss of access to CGA publications for one year for your company.

Full document details: [CGA P-49-2014 \(2020\)](#)



Documents

Document Sharing Hub

PREFACE

As part of a program of harmonization of industry standards, the Compressed Gas Association (CGA) has issued CGA P-49, *Prevention of Tow-Away Incidents* jointly produced by members of the International Harmonization Council and originally published by the European Industrial Gases Association (EIGA) as EIGA Doc 63, *Prevention of Tow-Away Incidents*.

This publication is intended as an international harmonized standard for the worldwide use and application of all members of the Asia Industrial Gases Association (AIGA), Compressed Gas Association (CGA), European Industrial Gases Association (EIGA), and Japan Industrial and Medical Gases Association (JIMGA). Each association's technical content is identical, except for regional regulatory requirements and minor changes in formatting and spelling.

PLEASE NOTE:

The information contained in this document was obtained from sources believed to be reliable and is based on technical information and experience currently available from members of the Compressed Gas Association, Inc. and others. However, the Association or its members, jointly or severally, make no guarantee of the results and assume no liability or responsibility in connection with the information or suggestions herein contained. Moreover, it should not be assumed that every acceptable commodity grade, test or safety procedure or method, precaution, equipment or device is contained within, or that abnormal or unusual circumstances may not warrant or suggest further requirements or additional procedure.

This document is subject to periodic review, and users are cautioned to obtain the latest edition. The Association invites comments and suggestions for consideration. In connection with such review, any such comments or suggestions will be fully reviewed by the Association after giving the party, upon request, a reasonable opportunity to be heard. Proposed changes may be submitted via the Internet at our web site, www.cganet.com.

This document should not be confused with federal, state, provincial, or municipal specifications or regulations; insurance requirements; or national safety codes. While the Association recommends reference to or use of this document by government agencies and others, this document is purely voluntary and not binding unless adopted by reference in regulations.

A listing of all publications, audiovisual programs, safety and technical bulletins, and safety posters is available via the Internet at our website at www.cganet.com. For more information contact CGA at Phone: 703-788-2700, ext. 799. E-mail: customerservice@cganet.com.

Work Item 18-038

Bulk Distribution Equipment and Standards Committee

NOTE—No technical information has been changed from the 2014 edition. This reaffirmed edition may include minor editorial changes.

REAFFIRMED: 2020
FIRST EDITION: 2014

© – Reproduced with permission from, the European Industrial Gases Association. All rights reserved.

Contents	Page
1 Introduction.....	1
2 Scope and purpose	1
3 Definitions.....	1
4 Systems to prevent tow-aways.....	2
4.1 Procedures	2
4.2 Training.....	2
4.3 Technical solutions	3
5 Description of the technical solutions	3
5.1 Interlock with the braking system	3
5.2 Interlock with a barrier	4
5.3 System consisting of visible and/or audible alarms	4
6 System to minimize the consequences of tow-aways	4
6.1 Liquid product	4
6.2 Gaseous product	5

Figures

Figure 1—Typical breakaway coupling for liquid filling	5
Figure 2—Typical breakaway coupling for gaseous filling	5

Appendices

Appendix A—Example of an interlocking device.....	6
Appendix B—Typical tow-away incident prevention devices	7
Appendix C—Layout of interlock with a barrier	8

Appendices Figures

Figure A-1—Typical diagram of interlock with braking system (deactivation above 8 km/h)	6
Figure B-1—Tow-away incident prevention device blocking the coupling when activated	7
Figure B-2—Interlock with braking system active when cabinet door is opened	7
Figure B-3—Visual and acoustic warning signs	7

1 Introduction

Before moving a bulk delivery vehicle, the failure to disconnect the product delivery hose(s) that connect the vehicle to a storage tank or utilization point can lead to a serious incident.

A tow-away incident occurs when flexible hose(s) used to transfer product between a delivery vehicle and stationary equipment is not disconnected prior to moving the vehicle. When this occurs, flexible hoses and the interconnecting piping can be damaged or fail.

Moving the vehicle while delivery hose(s) is still connected to fixed equipment creates the potential for equipment damage and a hazardous atmosphere. Personal injury can be caused due to:

- a large quantity of gas or liquid under pressure being released by the ruptured hose(s) and the production of a potentially hazardous atmosphere (oxygen-enriched or -deficient) that can lead to cold burns, asphyxiation, fire or explosion; and
- if the hose(s) resists the pulling effort and does not break, the vehicle can, in certain cases, pull away part or the whole of the fixed equipment or damage the delivery vehicle pipework.

Such incidents can lead to disruption of service.

2 Scope and purpose

The primary objective of this publication is to recommend practical methods for preventing road vehicles being moved away while still connected to fixed equipment. It supports compliance with the relevant requirements of existing regulations and standards.

This publication is also applicable to vehicles carrying cryogenic receptacles that are filled or emptied into a fixed installation while on board the vehicle.

Prevention of tow-away incidents of rail transportation is *not* discussed in this publication. However, the principles discussed may be appropriate in some cases.

This publication also covers breakaway couplings, which minimize the consequences of tow-aways, should they occur. These devices may be considered for use for transfilling from both road vehicles and rail wagons.

3 Definitions

For the purpose of this publication, the following definitions apply.

3.1 Publication Terminology

3.1.1 Shall

Indicates that the procedure is mandatory. It is used wherever the criterion for conformance to specific recommendations allows no deviation.

3.1.2 Should

Indicates that a procedure is recommended.

3.1.3 May

Indicates that the procedure is optional.

3.1.4 Will

Used only to indicate the future, not a degree of requirement.

3.1.5 Can

Indicates a possibility or ability.