



CAVI COASSIALI PER RADIOFREQUENZA
TIPO RG.. /U
RADIO-FREQUENCY COAXIAL CABLE
RG.. /U TYPE

STANDARD N° 1.240.003

REV. 01

FOGLIO
SHEET

1

DO

2

SOSTITUISCE
REPLACES

INDICE:

Cavi Tipo RG../U Pag. 2

INDEX:

RG../U Type Cables Pag. 2

[illegible]




CAVI COASSIALI PER RADIOFREQUENZA
TIPO RG.. /U
RADIO-FREQUENCY COAXIAL CABLE
RG.. /U TYPE

STANDARD N° 1.240.003

REV. 01	FOGLIO 2	DI OF 2
SOSTITUISCE REPLACES		

CLASSIFICAZIONE: 01811149



Es. di design.:
 0.111504.S Cavo per Radiofrequenza
 Coassiale RG8/U
 Diam. 10,3 - 52 Ohm

Es. di design.:
 0.111504.S Radio-Frequency Cable
 Coaxial RG8/U
 Diam. 10,3 - 52 Ohm

Sigla Tag	Conduttore / Conductor		Schermo Screen	Dielettrico / Dielectric		Guaina / Sheath		Impedenza nominale Rated Impedence Ohm	Codice Code
	Diametro Diam. mm	Materiale Material		Diametro Diam. mm	Tipo Type	Diametro Diam. mm	Tipo Type		
RG8/U	7 x 0,72	C	C	7,2	PE	10,3	RI	52	0.111504.S
RG11/U	7 x 0,4	CS	C	7,2	PE	10,3	RII	75	0.111505.T
RG58/U	0,81	CS	CS	2,95	PE	5	RI	53,5	0.111506.R
RG59/U	0,64	CW	C	3,7	PE	6,2	RI	73	0.111507.V

Tensione Nominale d' esercizio: RG8/U e RG11/U 5KV -
 RG58/U 1,9KV - RG59/U 2,3KV.

Temperatura Nominale Esercizio: 60°C

Conduttore: C = Rame non stagnato
 CS = Rame stagnato
 CW = Acciaio ramato (copperweld).

Schermo: C = Rame non stagnato
 CS = Rame stagnato

Isolante (dielettrico): Polietilene (PE).

Guaina: RI = Resina termoplastica colore Nero
 RII = Resina termoplastica non contaminante
 color Cenere.

Pezzature Normali: Secondo standard costruttore.

Rated Working Voltage: RG8/U e RG11/U 5KV -
 RG58/U 1,9KV - RG59/U 2,3KV.

Rated Working Temperature: 60°C

Conductor: C = Untinned copper
 CS = Tinned copper
 CW = Copper-plate steel.

Screen: C = Untinned copper
 CS = Tinned copper

Insulation (dielectric): Polyethylene (PE).

Sheath: RI = Black thermoplastic resin
 RII = Non-polluting grey thermoplastic resin.

Nominal Pieces: Manufacturer std.

Aggiornata (tolto sigla Ceda)
 Descrizione - Description

12/95
 Date
 01
 Rev.