




ROSETTE ELASTICHE SPACCASTE DIN 127 - UNI 1751 - Forma B
SPRING LOCK WASHERS DIN 127 - UNI 1751 - Form B



Materiale: Acciaio per molle HRC 44-49
Acc. inoss. A2-70
Estremità diritte forma B
Stato fornit.: fosfatate (FAR)
zincate Fe/Zn8c1A DIN 267/9
A2-70 grezze
Impiego: bulloneria cl. di resist. ≤ 5.8

Material: Spring steel HRC 44-49
Stainless steel A2-70
Square ends form B
Supply: phosphatized (FAR)
zinc coated Fe/Zn8c1A DIN 267/9
A2-70 rough
Fittings strength cl. ≤ 5.8

Es. di design.:
0.001298.P Rosetta el. spacc. DIN 127 UNI 1751
B 20 Acc. per molle
Fosfatata nera

Ex. of design.:
0.001298.P Spring washer DIN 127 UNI 1751
B 20 Spring steel
Phosphatized

 Sconsigliato
Not recommended

d nom filett. thrd.	d ₁ min	d ₂ max	s	h min	Mass Kg	CODICE - CODE			
						Viti Destre Right screws Acc. fosfatato C steel phosp.	Viti Sinistre Left screws Acc. fosfatato C steel phosp.	Viti Destre Right screws Acc. zincato C steel galv.	Viti Destre Right screws A2 - 70
4	4,1	7,6	0,9	1,8	0,001	0.001291.G	0.088714.F	0.113031.L	0.113289.B
5	5,1	9,2	1,2	2,4	0,001	0.001292.A	0.088715.G	0.113032.M	0.113290.G
6	6,1	11,8	1,6	3,2	0,001	0.001293.B	0.088716.A	0.113033.N	0.113291.V
8	8,2	14,8	2	4	0,001	0.001294.C	0.088718.K	0.113034.P	0.113292.W
10	10,2	18,1	2,2	4,4	0,002	0.001295.D	0.088719.L	0.113035.Q	0.113293.X
12	12,2	21,1	2,5	5	0,004	0.001296.E	0.088720.H	0.113036.H	0.113294.Z
14	14,2	24,1	3	6	0,006	0.050639.S	0.088721.E	0.113037.K	0.113295.S
16	16,2	27,4	3,5	7	0,009	0.001297.F	0.088722.F	0.113038.T	0.113296.T
18	18,2	29,4	3,5	7	0,01	0.088700.W	0.088723.G	0.157459.H	0.083364.C
20	20,2	33,6	4	8	0,015	0.001298.P	0.088724.A	0.165554.A	0.152053.G
22	22,5	35,9	4	8	0,016	0.088701.K	0.088725.B	0.314484.Z	0.314485.S
24	24,5	40	5	10	0,026	0.001299.Q	0.088726.C	0.165553.G	0.063557.A
27	27,5	43	5	10	0,029	0.088702.L	0.088727.D	-	-
30	30,5	48,2	6	12	0,044	0.001300.W	0.088728.M	-	-
33	33,5	55,2	6	12	0,063	0.088703.M	0.088729.N	-	-
36	36,5	58,2	6	12	0,067	0.001301.K	0.088730.L	-	-
39	39,5	61,2	6	12	0,072	0.088704.N	0.088731.G	-	-
42	42,5	68,2	7	14	0,111	0.001302.L	0.088732.A	-	-
48	49	75	7	14	0,123	0.001303.M	0.088734.C	-	-
52	53	83	8	16	0,182	0.001304.N	0.088735.D	-	-
56	57	87	8	16	0,193	0.088706.Q	0.088736.E	-	-
60	61	91	8	16	0,203	0.088707.H	0.088737.F	-	-
64	65	95	8	16	0,218	0.088708.S	0.088738.P	-	-
68	69	99	8	16	0,228	0.088709.T	0.088739.Q	-	-
72	73	103	8	16	0,24	0.088710.P	0.088740.V	-	-
80	81	111	8	16	0,262	0.088711.C	0.088741.H	-	-
90	91	121	8	16	0,29	0.088712.D	0.088742.K	-	-
100	101	131	8	16	0,318	0.088713.E	0.088743.L	-	-