

Radio-frequency connectors —

Part 40: Sectional specification for 2.4 series R.F connectors

ICS 33.120.30

National foreword

This Draft for Development is the UK implementation of IEC/PAS 61169-40:2008.

This publication is not to be regarded as a British Standard.

It is being issued in the Draft for Development series of publications and is of a provisional nature. It should be applied on this provisional basis, so that information and experience of its practical application can be obtained.

A PAS is a Technical Specification not fulfilling the requirements for a standard, but made available to the public and established in an organization operating under a given procedure.

A review of this Draft for Development will be carried out not later than three years after its publication.

Notification of the start of the review period, with a request for the submission of comments from users of this Draft for Development, will be made in an announcement in the appropriate issue of *Update Standards*. According to the replies received, the responsible BSI Committee will judge whether the validity of the PAS should be extended for a further three years or what other action should be taken and pass their comments on to the relevant international committee.

Observations which it is felt should receive attention before the official call for comments will be welcomed. These should be sent to the Secretary of the responsible BSI Technical Committee at British Standards House, 389 Chiswick High Road, London W4 4AL.

The UK participation in its preparation was entrusted by Technical Committee EPL/46, Cables, wires and waveguides, radio frequency connectors and accessories for communication and signalling, to Subcommittee EPL/46/2, Radio frequency connectors and waveguides.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

This Draft for Development was published under the authority of the Standards Policy and Strategy Committee on 30 September 2008

© BSI 2008

ISBN 978 0 580 62179 6

Amendments/corrigenda issued since publication

Date	Comments



PUBLICLY AVAILABLE SPECIFICATION PRE-STANDARD

**Radio-frequency connectors –
Part 40: Sectional specification for 2.4 series R.F connectors**

blank

CONTENTS

1	Scope.....	5
2	Normative reference	5
3	Mating face and gauge information	5
3.1	Dimensions-High performance connectors – Grade1	6
3.1.1	Connector with pin-centre contact.....	6
3.1.2	Connector with socket-centre contact	7
3.2	Gauges	8
3.2.1	Gauge pins for socket-centre contact.....	8
3.2.2	Test procedure.	8
3.3	Dimensions- standard test connectors - grade 0.....	9
3.3.1	Connector with pin-centre contact.....	9
3.3.2	Connector with socket-centre contact	10
4	Quality assessment procedure.....	11
4.1	General.....	11
4.2	Rating and Characteristics (see clause 6 of IEC 61169/QC 220000).....	11
4.3	Test Schedule and Inspection requirements	13
4.3.1	Acceptance tests	13
4.3.2	Periodic tests	14
4.4	Procedures.....	15
4.4.1	Quality conformance inspection	15
4.4.2	Qualification approval and its maintenance.....	15
5	Instructions for preparation of detail specifications	15
5.1	General.....	15
5.2	Identification of the Detail specification	16
5.3	Identification of the component.....	16
5.4	Performance.....	16
5.5	Marking, ordering information and related matters	16
5.6	Selection of tests, test conditions and severities.....	16
6	Blank detail specification pro-forma for type 2.4 connector	18
	Figure 1 – Connector with pin- centre contact (for dimensions, see Table 1).....	6
	Figure 2 – Connector with socket-centre contact (for dimensions see Table 2)	7
	Figure 3 – Gauge pins for socket-centre contact (for dimensions see Table 3).....	8
	Figure 4 – Connector with pin-centre contact (for dimensions, see Table 4).....	9
	Figure 5 – Connector with socket-centre contact (for dimensions see Table 5)	10
	Table 1 – Dimensions of connector with pin-centre contact.....	6
	Table 2 – Dimensions of connector with socket-centre contact.....	7
	Table 3 – Dimensions of gauge pins for socket-centre contact	8
	Table 4 – Dimensions of connector with pin-centre contact	9
	Table 5 – Dimensions of connector with socket-centre contact.....	10
	Table 6 – Ratings and characteristics	11

Table 7 – Acceptance tests	13
Table 8 – Periodic tests	14

RADIO-FREQUENCY CONNECTORS –

Part 40: Sectional specification for 2.4 series R.F connectors

1 Scope

This PAS is a sectional specification providing information and rules for preparation of detail specification of 2.4 series R.F connectors together with the pro-forma blank detail specification.

2.4 series connectors with characteristic impedance $50\ \Omega$ are used for millimeter wave applications, connecting with RF cables or microstrips. The operating frequency limit is up to 50 GHz.

It also prescribes mating face dimensions for high performance connectors grade 1, dimensional detail of standard test connectors grade 0, gauging information and tests selected from QC 22000 (IEC 61169-1) applicable to all detail specifications relating to 2.4 series RF connectors.

This specification indicates recommended performance characteristics to be considered when writing a detail specification and it covers test schedules and inspection requirements for assessment levels M and H.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61169-1:1992, *Radio-frequency connectors – Part 1: Generic specification – General requirements and measuring methods*¹⁾

Amendment 1 (1996)

Amendment 2 (1997)

3 Mating face and gauge information

Metric dimension are original dimensions.

All undimensioned pictorial configurations are for reference purpose only.

¹⁾ A consolidated edition 1.2 (1998) exists, that comprises IEC 61169-1 (1992), Amendment 1 and Amendment 2.

3.1 Dimensions-High performance connectors – Grade1

3.1.1 Connector with pin-centre contact




Figure 1 – Connector with pin- centre contact (for dimensions, see Table 1)

Table 1 – Dimensions of connector with pin-centre contact

Ref.	mm		Note
	Min.	Max.	
<i>a</i>	1,850	2,450	
<i>b</i>	4,340	4,660	
<i>c</i>	0,000	0,076	
<i>d</i>	3,380	3,480	
<i>e</i>	0,200	0,400	
<i>f</i>	—	0,050	Radius
<i>g</i>	56°	64°	Angle
<i>h</i>	1,029	1,054	Diameter
<i>j</i>	1,270	1,524	
<i>k</i>	0,000	0,250	Diameter
<i>l</i>	7,010	7,110	Diameter
<i>m</i>	4,725	4,750	Diameter
<i>n</i>	2,3875	2,4125	Diameter
<i>p</i>	0,498	0,523	Diameter
<i>q</i>	0,508	0,762	
<i>r</i>	M7×0,75-6H		
NOTE 1 Mechanical and electrical reference plane.			
NOTE 2 Gasket required on Grade 1 connectors.			