

Screened balanced cables — Coupling attenuation measurement, triaxial method

ICS 17.220.20; 29.060.10

National foreword

This Draft for Development reproduces verbatim IEC/PAS 62338:2002.

This publication is not to be regarded as a British Standard.

It is being issued in the Draft for Development series of publications and is of a provisional nature because it is considered that further experience is required in its application before it is converted in to a British Standard. It should be applied on this provisional basis, so that information and experience of its practical application may be obtained.

A PAS is a Technical Specification not fulfilling the requirements for a standard, but made available to the public and established in an organization operating under a given procedure.

Comments arising from the use of this Draft for Development are requested so that UK experience can be reported to the international organization responsible for the Technical Specification. A review of this publication will be initiated not later than 3 years after its publication by the international organization so that a decision can be taken on its status at the end of its 3-year life. Notification of the start of the review period will be made in an announcement in the appropriate issue of *Update Standards*.

According to the replies received by the end of the review period, the responsible BSI Committee will decide whether to support the conversion into an international standard, to extend the life of the Technical Specification for another 3 years or to withdraw it. Comments should be sent in writing to the Secretary of BSI Subcommittee EPL/46/1, Communication cables, at British Standards House, 389 Chiswick High Road, London W4 4AL, giving the document reference and clause number and proposing, where possible, an appropriate revision of the text.

A list of organizations represented on this committee can be obtained on request to its secretary.

Cross-references

The British Standards which implement international publications referred to in this document may be found in the *BSI Catalogue* under the section entitled “International Standards Correspondence Index”, or by using the “Search” facility of the *BSI Electronic Catalogue* or of British Standards Online.

This Draft for Development was published under the authority of the Standards Policy and Strategy Committee on 28 April 2003

Summary of pages

This document comprises a front cover, an inside front cover, the IEC/PAS title page, pages 2 to 14, an inside back cover and a back cover.

The BSI copyright date displayed in this document indicates when the document was last issued.

Amendments issued since publication

Amd. No.	Date	Comments

© BSI 28 April 2003

ISBN 0 580 41643 7

IEC/PAS 62338

Edition 1.0
2002-10

Screened balanced cables – Coupling attenuation measurement, triaxial method

PUBLICLY AVAILABLE SPECIFICATION



INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

Reference number
IEC/PAS 62338

CONTENTS

FOREWORD	3
1 General.....	4
2 Principle of the measuring method	4
3 Definitions and the theoretical background.....	5
3.1 Electrical symbols.....	5
3.2 Theoretical background.....	6
3.2.1 Unbalance attenuation a_u	6
3.2.2 Screening attenuation a_s of the screen	7
3.2.3 Coupling attenuation a_c	8
4 Measurement	9
4.1 Equipment	9
4.2 Balun requirements	10
4.3 Sample preparing	10
4.4 Procedure	11
4.6 Measurement Precautions	11
5 Expression of results	12
6 Requirement.....	12
7 Typical measuring curves of coupling attenuation.....	13

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SCREENED BALANCED CABLES – COUPLING ATTENUATION MEASUREMENT, TRIAxIAL METHOD

FOREWORD

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical specifications, technical reports or guides and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this PAS may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

A PAS is a technical specification not fulfilling the requirements for a standard, but made available to the public.

IEC/PAS 62338 has been prepared by IEC technical committee 46: Cables, wires, waveguides, r.f. connectors, r.f. and microwave passive components and accessories.

The text of this PAS is based on the following document:

This PAS was approved for publication by the P-members of the committee concerned as indicated in the following document:

Draft PAS	Report on voting
46/107/PAS	46/110/RVD

Following publication of this PAS, the technical committee or subcommittee concerned will investigate the possibility of transforming the PAS into an International Standard.

This PAS shall remain valid for no longer than 3 years starting from 2002-10. The validity may be extended for a single 3-year period, following which it shall be revised to become another type of normative document, or shall be withdrawn."

SCREENED BALANCED CABLES – COUPLING ATTENUATION MEASUREMENT, TRIAxIAL METHOD

1 General

This test method determines the coupling attenuation a_c of screened balanced cables. Due to the concentric outer tube, measurements are independent of irregularities on the circumference and outer electromagnetic field.

A wide dynamic and frequency range can be applied to test even super screened cables with normal instrumentation from low frequencies up to the limit of defined transversal waves in the outer circuit at approximately 4 GHz.

For balanced cables the upper frequency is limited by the properties of the baluns.

The procedure to measure the coupling attenuation a_c is based on the procedure to measure the screening attenuation a_s according to IEC 61196-1, Amendment 1.

2 Principle of the measuring method

The test set up is a triaxial system consisting of the cable under test and a solid metallic tube.

The matched cable under test which is fed by a generator forms the disturbing respectively the inner or primary circuit. The disturbed respectively the outer or the second circuit is formed by the outer conductor (or the outer most layer in the case of multiscreen cables) of the cable under test and a solid metallic tube having the cable under test in its axis.

The voltage peaks at the far end of the secondary circuit have to be measured. The near end of the secondary circuit is short-circuited. For this measurement a matched receiver is not necessary. The likely voltage peaks at the far end are not dependant on the input impedance of the receiver, provided that it is lower than the characteristic impedance of the secondary circuit. However, it is an advantage to have a low mismatch, for example by selecting a range of tube diameters for several sizes of coaxial cables.