

DIN EN ISO 13143-1

ICS 03.220.20; 35.240.60

Ersatz für
DIN EN ISO 13143-1:2017-03

**Elektronische Gebührenerhebung –
Bewertung der Konformität fahrzeuginterner und straßenseitiger
Ausrüstung nach ISO 12813 –
Teil 1: Struktur und Zweck des Prüfprogrammes (ISO 13143-1:2020);
Englische Fassung EN ISO 13143-1:2020**

Electronic fee collection –

Evaluation of on-board and roadside equipment for conformity to ISO 12813 –

Part 1: Test suite structure and test purposes (ISO 13143-1:2020);

English version EN ISO 13143-1:2020

Perception du télépéage –

Évaluation des équipements embarqués et en bord de route quant à la conformité avec
l'ISO 12813 –

Partie 1: Structure de suite d'essais et buts des essais (ISO 13143-1:2020);

Version anglaise EN ISO 13143-1:2020

Gesamtumfang 82 Seiten

DIN-Normenausschuss Automobiltechnik (NAAutomobil)

Nationales Vorwort

Dieses Dokument (EN ISO 13143-1:2020) wurde vom Technischen Komitee ISO/TC 204 „Intelligent Transport Systems“ in Zusammenarbeit mit dem Technischen Komitee CEN/TC 278 „Intelligente Verkehrssysteme“, dessen Sekretariat von NEN (Niederlande) gehalten wird, erarbeitet.

Das zuständige deutsche Normungsgremium ist der Gemeinschaftsarbeitsausschuss NA 052-00-71 GA „Gemeinschaftsarbeitsausschuss NAAutomobil/DKE: Intelligente Verkehrssysteme“ des DIN-Normenausschusses Automobiltechnik (NAAutomobil).

Dieses Dokument enthält unter Berücksichtigung des DIN-Präsidialbeschlusses 1/2004 nur die Englische Fassung von EN ISO 13680:2020.

Dieses Dokument legt den Prozess und Prüfungen für die Evaluierung der Konformität von fahrzeuginternen sowie straßenseitigen Systemen nach den Anforderungen in ISO 12813:2019 fest.

Die Norm dient deshalb EFC-Systemherstellern zur Qualitätsprüfung ihrer Systeme und somit der Sicherstellung interoperabler Mautsysteme.

DIN EN ISO 13143 besteht unter dem allgemeinen Titel *Elektronische Gebührenerhebung — Bewertung der Konformität fahrzeuginterner und straßenseitiger Ausrüstung nach ISO 12813* aus den folgenden Teilen:

- Teil 1: Struktur und Zweck des Prüfprogrammes
- Teil 2: Zusammengefasstes Prüfprogramm

Änderungen

Gegenüber DIN EN ISO 13143-1:2017-03 wurden folgende Änderungen vorgenommen:

- a) Inhalte wurden basierend auf Änderungen der zugrunde liegenden Normen DIN EN ISO 12813 und DIN EN ISO 14906 vorgenommen;
- b) Ergänzungen von Begriffen, um die Harmonisierung von Begriffen innerhalb aller EFC-Normen zu berücksichtigen.

Frühere Ausgaben

DIN CEN ISO/TS 13143-1 (DIN SPEC 91231): 2011-09

DIN EN ISO 13143-1: 2017-03

Nationaler Anhang NA (informativ)

Begriffe

Die Benummerung der folgenden Begriffe ist identisch mit der Benummerung in der englischen Fassung.

Für die Anwendung dieses Dokuments gelten die folgenden Begriffe.

ISO und IEC stellen terminologische Datenbanken für die Verwendung in der Normung unter den folgenden Adressen bereit:

- ISO Online Browsing Platform: verfügbar unter <http://www.iso.org/obp>
- IEC Electropedia: verfügbar unter <http://www.electropedia.org/>

3.1

Zugriffsbeglaubigung

AC-CR

(en: access credentials)

vertrauenswürdiger Nachweis oder Sicherheitsmodul, das die beanspruchte Identität eines Objekts oder einer Anwendung nachweist

[QUELLE: ISO/TS 17573-2:2020, 3.4]

3.2

Attribut

(en: attribute)

adressierbares Datenpaket, welches aus einem einzelnen Datenelement oder einer strukturierten Sequenz von Datenelementen besteht

[QUELLE: ISO/TS 17573-2:2020, 3.13]

3.3

Authentifizierung

(en: authentication)

Sicherheitsmechanismus, der die Überprüfung der bereitgestellten Identität erlaubt

[QUELLE: ISO/TS 17573-2:2020, 3.15]

3.4

Authentifikator

(en: authenticator)

Daten, wenn möglich verschlüsselt, die zur *Authentifizierung* (3.3) verwendet werden

[QUELLE: ISO/TS 17573-2:2020, 3.16]

3.5

Datengruppe

(en: data group)

Klasse von eng verwandten *Attributen* (3.2)

[QUELLE: ISO/TS 17573-2:2020, 3.55]

3.6

Element

(en: element)

dediziertes Nahbereichskommunikations-Verzeichnis (DRSC), welches Anwendungsinformation in Form von *Attributen* (3.2) beinhaltet

3.7

Erklärung zur Konformität der Implementierung

ICS

(en: implementation conformance statement)

Erklärung bezogen auf die implementierte Leistungsfähigkeit und Optionen, die festlegt, in welchem Ausmaß die Implementierung zu einer gegebenen Spezifikation konform ist

[QUELLE: ISO/TS 17573-2:2020, 3.90]

3.8

Erklärung zur Konformität der Protokollimplementierung

PICS

(en: protocol implementation conformance statement)

ICS (3.7) für eine Implementierung oder ein System, deren (dessen) Konformität mit einer gegebenen Protokollspezifikation erklärt wird

[QUELLE: ISO/IEC 9646-1:1994, 3.3.80]

3.9

fahrzeuginterne Einrichtung

OBE

(en: on-board equipment)

alle erforderlichen Einrichtungen im Fahrzeug zur Durchführung notwendiger Funktionen der elektronischen Gebührenerhebung (en: electronic fee collection, EFC) und von Kommunikationsdiensten

[QUELLE: ISO/TS 17573-2:2020, 3.126]

3.10

fahrzeuginterne Einheit

OBU

(en: on-board unit)

einzelne elektronische fahrzeuginterne Einheit zur Durchführung spezifischer Funktionen zur elektronischen Gebührenerhebung (EFC) und zur Kommunikation mit externen Systemen

[QUELLE: ISO/TS 17573-2:2020, 3.127]

3.11

Straßenrand-Einrichtung

RSE

(en: roadside equipment)

feste oder bewegliche Einrichtung zur elektronischen Gebührenerhebung (EFC) entlang oder an einer Straße

[QUELLE: ISO/TS 17573-2:2020, 3.161, modifiziert – Anmerkung 1 zum Begriff wurde gelöscht.]

3.12

Tester

(en: tester)

Kombination von Einrichtung, Personen und Prozessen, die spezifische Konformitätsprüfungen durchführen kann

[QUELLE: ISO/TS 17573-2:2020, 3.188]

3.13

Transaktion

(en: transaction)

gesamter Austausch von Informationen zwischen zwei, physisch getrennten Kommunikationseinrichtungen

[QUELLE: ISO/TS 17573-2:2020, 3.211]

— Leerseite —

English Version

Electronic fee collection -
Evaluation of on-board and roadside equipment
for conformity to ISO 12813 -
Part 1: Test suite structure and test purposes
(ISO 13143-1:2020)

Perception de télépéage -
Évaluation des équipements embarqués et en bord
de route quant à la conformité avec l'ISO 12813 -
Partie 1: Structure de suite d'essais et buts des essais
(ISO 13143-1:2020)

Elektronische Gebührenerhebung -
Bewertung der Konformität fahrzeuginterner und
straßenseitiger Ausrüstung nach ISO 12813 -
Teil 1: Struktur und Zweck des Prüfprogrammes
(ISO 13143-1:2020)

This European Standard was approved by CEN on 24 October 2020.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

European foreword

This document (EN ISO 13143-1:2020) has been prepared by Technical Committee ISO/TC 204 "Intelligent transport systems" in collaboration with Technical Committee CEN/TC 278 "Intelligent transport systems" the secretariat of which is held by NEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by May 2021, and conflicting national standards shall be withdrawn at the latest by May 2021.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN ISO 13143-1:2016.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Endorsement notice

The text of ISO 13143-1:2020 has been approved by CEN as EN ISO 13143-1:2020 without any modification.

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Abbreviated terms	3
5 Test suite structure (TSS)	4
5.1 Structure	4
5.2 Reference to conformance test specifications	4
5.3 Test purposes (TPs)	5
5.3.1 TP definition conventions	5
5.3.2 TP naming conventions	5
5.4 Conformance test report	6
Annex A (normative) Test purposes for on-board equipment	7
Annex B (normative) Test purposes for roadside equipment	46
Annex C (normative) Protocol conformance test report proforma for on-board equipment	58
Annex D (normative) Protocol conformance test report proforma for roadside equipment	65
Bibliography	70

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 204, *Intelligent transport systems*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 278, *Intelligent transport systems*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This second edition cancels and replaces the first edition (ISO 13143-1:2016), which has been technically revised.

The main changes compared to the previous edition are as follows:

- amendments to reflect changes to the underlying requirements standards, in particular ISO 12813 and ISO 14906;
- amendment of terms to reflect the harmonization of terms across electronic fee collection (EFC) standards.

A list of all parts in the ISO 13143 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

On-board equipment (OBE) that uses satellite-based positioning technology to collect data required for charging for the use of roads operates in an autonomous way (i.e. without relying on dedicated roadside infrastructure). The OBE records the amount of road usage in all toll charging systems it passes through.

This document defines the process and tests for evaluation of OBE and roadside equipment (RSE) for conformity to ISO 12813.

ISO 12813 defines requirements for dedicated short-range communication (DSRC) between OBE and an interrogator for the purpose of checking conformance of road use with a local toll regime. It assumes an electronic fee collection (EFC) services architecture according to ISO 17573-1.

This document is intended to:

- assess OBE and RSE capabilities,
- assess OBE and RSE behaviour,
- serve as a guide for OBE and RSE conformance evaluation and type approval,
- achieve comparability between the results of the corresponding tests applied in different places at different times, and
- facilitate communication between parties.

This document is based on:

- ISO 12813,
- the set of DSRC standards defining the communication stack, and
- ISO/IEC 9646.

Electronic fee collection — Evaluation of on-board and roadside equipment for conformity to ISO 12813 —

Part 1: Test suite structure and test purposes

1 Scope

This document specifies the test suite structure (TSS) and test purposes (TPs) for evaluating the conformity of on-board equipment (OBE) and roadside equipment (RSE) to ISO 12813.

It provides a basis for conformance tests for dedicated short-range communication (DSRC) OBE and RSE to support interoperability between different equipment supplied by different manufacturers.

ISO 12813 defines requirements on the compliance check communication (CCC) interface level, but not for the RSE or OBE internal functional behaviour. Consequently, tests regarding OBE and/or RSE functional behaviour remain outside the scope of this document.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3166-1, *Codes for the representation of names of countries and their subdivisions — Part 1: Country codes*

ISO 12813:2019, *Electronic fee collection — Compliance check communication for autonomous systems*

ISO 14816, *Road transport and traffic telematics — Automatic vehicle and equipment identification — Numbering and data structure*

ISO 14906:2018, *Electronic fee collection — Application interface definition for dedicated short-range communication*

ISO/TS 14907-2:2016, *Electronic fee collection — Test procedures for user and fixed equipment — Part 2: Conformance test for the on-board unit application interface*

EN 12834:2003, *Road transport and traffic telematics — Dedicated Short Range Communication (DSRC) — DSRC application layer*

EN 13372:2004, *Road Transport and Traffic Telematics (RTTT) — Dedicated short-range communication — Profiles for RTTT applications*

EN 15509:2014, *Electronic fee collection — Interoperability application profile for DSRC*

EN 15876-1, *Electronic fee collection — Evaluation of on-board and roadside equipment for conformity to EN 15509 — Part 1: Test suite structure and test purposes*

ETSI/TS 102 486-2-2 V1.2.1(2008-10), *Intelligent Transport Systems (ITS); Road Transport and Traffic Telematics (RTTT); Test specifications for Dedicated Short Range Communication (DSRC) transmission equipment; Part 2: DSRC application layer; Sub-Part 2: Test Suite Structure and Test Purposes (TSS & TP)*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1 access credentials

AC-CR

trusted attestation or secure module that establishes the claimed identity of an object or application

[SOURCE: ISO/TS 17573-2:2020, 3.4]

3.2 attribute

addressable package of data consisting of a single data element or structured sequences of data elements

[SOURCE: ISO/TS 17573-2:2020, 3.13]

3.3 authentication

security mechanism allowing verification of the provided identity

[SOURCE: ISO/TS 17573-2:2020, 3.15]

3.4 authenticator

data, possibly encrypted, that is used for *authentication* (3.3)

[SOURCE: ISO/TS 17573-2:2020, 3.16]

3.5 data group

class of closely related *attributes* (3.2)

[SOURCE: ISO/TS 17573-2:2020, 3.55]

3.6 Element

dedicated short-range communication (DSRC) directory containing application information in the form of *attributes* (3.2)

3.7 implementation conformance statement

ICS

statement of capabilities and options that have been implemented that defines to what extent the implementation is compliant with a given specification

[SOURCE: ISO/TS 17573-2:2020, 3.90]

3.8 protocol implementation conformance statement

PICS

ICS (3.7) for an implementation or system claimed to conform to a given protocol specification

[SOURCE: ISO/IEC 9646-1:1994, 3.3.80]

3.9

on-board equipment

OBE

all required equipment on-board a vehicle for performing required electronic fee collection (EFC) functions and communication services

[SOURCE: ISO/TS 17573-2:2020, 3.126]

3.10

on-board unit

OBU

electronic unit on-board a vehicle for performing specific electronic fee collection (EFC) functions and for communication with external systems

[SOURCE: ISO/TS 17573-2:2020, 3.127]

3.11

roadside equipment

RSE

fixed or moveable electronic fee collection (EFC) equipment located along or on the road

[SOURCE: ISO/TS 17573-2:2020, 3.161, modified — Note 1 to entry deleted.]

3.12

tester

combination of equipment, humans and processes able to perform specified conformance tests

[SOURCE: ISO/TS 17573-2:2020, 3.188]

3.13

transaction

whole of the exchange of information between two physically separated communication facilities

[SOURCE: ISO/TS 17573-2:2020, 3.211]

4 Abbreviated terms

APDU	application protocol data unit
AP	application process
ATS	abstract test suite
BI	behaviour invalid (i.e. invalid behaviour tests)
BST	beacon service table
BV	behaviour valid (i.e. valid behaviour tests)
CCC	compliance check communication
DLC	data link control
DSRC	dedicated short-range communication
DUT	device under test
EFC	electronic fee collection
EID	Element identifier

LLC	logical link control
MAC	medium access control
PCTR	protocol conformance test report
PDU	protocol data unit
PIXIT	protocol implementation extra information for testing
SCTR	system conformance test report
T-APDU	transfer-application protocol data unit
TP	test purpose
TSS	test suite structure
VST	vehicle service table

5 Test suite structure (TSS)

5.1 Structure

Table 1 shows the test suite structure (TSS) including its subgroups that are inherited from other specifications.

Table 1 — Test suite structure

Group	Type of DUT	Behaviour
Physical layer	OBE	BV
		BI
	RSE	BV
		BI
Data link Control (DLC) Medium Access Control (MAC) sublayer	OBE	BV
		BI
	RSE	BV
		BI
DLC Logical Link Control (LLC) sublayer	OBE	BV
		BI
	RSE	BV
		BI
Application layer	OBE	BV
		BI
	RSE	BV
		BI

Physical layer tests are to be performed in a radio wave laboratory. They will not form part of the abstract test suite (ATS).

5.2 Reference to conformance test specifications

Conformance to a profile standard implies conformance to the related base standards. Hence, a number of test cases for the CCC application are identical to the conformance test cases for the related base

standards. Other test cases are derived from the base standards conformance test cases, by applying some restrictions or choices in, for example, the parameters values, according to what is stated in the profile standard. Finally, specific conformance test cases for the CCC application are identified for statements contained in the CCC application, which have no equivalence in the base standards. These latter cases cover for example, the application layer data test purposes. This document takes into account already defined test purposes for conformance to the base standards by referencing them, so that:

- a) For test purposes that are identical to those defined in the base standards conformance test cases (see e.g. ETSI/TS 102 486-2-2 or EN 15876-1), a direct reference is reported. For the reader's convenience, the title or a verbal description of the referenced test purpose is given, together with the reference.
- b) For test purposes that are derived from those defined in the base standards conformance test cases, a direct reference is reported, plus an indication on how the referred test purpose has been modified for the profile conformance testing.
- c) For test purposes that are specific to the standard profile, a complete description is given.

An indication on whether a test purpose is identical, derived, or specific is given in each test purpose.

5.3 Test purposes (TPs)

5.3.1 TP definition conventions

The TPs are defined following the rules shown in Table 2. All TPs are defined in Annex A and Annex B.

Table 2 — TP definition rules

TP ID according to the TP naming conventions	Title
	Reference
	TP origin
	Initial condition
	Stimulus and expected behaviour
TP ID	The TP ID is a unique identifier. It is specified according to the TP naming conventions defined in 5.3.2.
Title	Short description of TP objective.
Reference	Contains the reference (document, clause, paragraph) to the subject to be validated by the actual TP.
TP origin	Indicates if the TP is identical to a TP defined in another test standard, derived from a TP defined in another test standard, or specific for this standard profile.
Initial condition	The condition defines the required initial state of the DUT at the time of launching of the actual TP.
Stimulus and expected behaviour	Definition of the events the tester performs and the events that are expected from the DUT to conform to the base specification.

5.3.2 TP naming conventions

Each TP is given a unique identification. This unique identification is built up to contain the following string of information:

TP/ <group>/<dut>/<x>-<nn>

- TP : to indicate that it is a test purpose;
- <group> : to which group among those defined in Table 1 the TP applies;
- <dut> : type of DUT (i.e. OBE or RSE);
- <x> : type of testing (i.e. Valid behaviour tests, BV, or Invalid behaviour tests, BI);
- <nn> : sequential TP number (01 to 99).

The naming conventions are as described in Table 3.

Table 3 — TP naming conventions

<group>	<dut>	<x>
<i>applicable for OBU/RSE</i>	PHY	Physical layer
<i>applicable for OBU/RSE</i>	MAC/LLC	MAC/LLC sublayer
<i>applicable for OBU/RSE</i>	AP-BAS	Application layer – I Kernel support
<i>applicable for OBU</i>	AP-FUN	Application layer – T Kernel support
<i>applicable for OBU</i>	AP-DAT	Application layer – Data attributes support
<i>applicable for OBU</i>	AP-SEC	Application layer – Security Level 1 support
<i>applicable for RSE</i>	AP-GET	Application layer - GET-rq protocol data unit (PDU) test purposes,
<i>applicable for RSE</i>	AP-STA	Application layer - GET-STAMPED-rq PDU test purposes
<i>applicable for RSE</i>	AP-MMI	Application layer - SET-MMI-rq PDU test purposes
<i>applicable for RSE</i>	AP-ECH	Application layer - ECHO-rq PDU test purposes
<i>applicable for RSE</i>	AP-REL	Application layer - EVENT-REPORT-rq PDU test purposes

5.4 Conformance test report

The manufacturer of the OBE and the RSE, respectively, is responsible for providing a conformance test report.

The manufacturer of the OBE shall complete the protocol conformance test report (PCTR) for OBE as defined in Annex C.

The manufacturer of the RSE shall complete the PCTR for roadside equipment as defined in Annex D.

Annex A (normative)

Test purposes for on-board equipment

A.1 Introduction

A.1.1 General

This annex contains the test purposes (TPs) for the conformity evaluation of OBE to ISO 12813.

A.1.2 Symbols in TP descriptions

For the application layer test purposes, a special notation and symbol convention is used, as defined in this subclause.

Symbols are used in the description of the TPs, with meanings according to Table A.1.

Table A.1 — Description of TP symbols

Symbol	Description
XXX.rq $\Rightarrow$	The Tester sends the XXX.rq protocol data unit (PDU) to the device under test (DUT).
$\Leftarrow$ YYY.rs	The DUT sends the YYY.rs PDU to the Tester.
$A \equiv B$	Test purpose A "is congruent to" Test purpose B. The notation "Test purpose A $\equiv$ Test purpose B" means that the Test purpose A is the same as Test purpose B. If differences in parameters or parameter values have to be applied, these differences are indicated in the text immediately below.
$A \rightarrow B$	Object A "is transformed" into Object B. So, a notation like "Table X $\rightarrow$ Table Y" means that, for the scope of the TP, any reference of Table X should be changed into a reference to Table Y.
=	Means "assignment". That is, a notation like "accessCredentials = a value" means that the field accessCredentials is given a value.
$\emptyset$	Means "empty" or "not set". So, a notation like "accessCredentials = $\emptyset \rightarrow$ accessCredentials = calculated value", for a given TP, means "change all occurrences in which the field accessCredentials has not been assigned to a calculation of the value accessCredentials to a given value".

A.2 Physical layer

As per ISO 12813:2019, 5.5.2, all test purposes TP/PHY/OBU/Bx/yy defined in EN 15876-1 are applicable for the conformity evaluation of OBE to CEN-DSRC based CCC as defined in ISO 12813:2019, Table B.8, Item 1.

A.3 MAC and LLC

As per ISO 12813:2019, 5.5.2, all test purposes TP/MAC/OBU/Bx/yy (except TP/MAC/OBU/BV/09, see NOTE) and TP/LLC/OBU/Bx/yy defined in EN 15876-1 are applicable for the conformity evaluation of OBE to CEN-DSRC based CCC as defined in ISO 12813:2019, Table B.8, Item 1.

NOTE Test purpose TP/MAC/OBU/BV/09 has been excluded from this document as this TP does not apply for profiles 0/1 of EN 13372.

A.4 Application Layer

A.4.1 Structure of BST and VST

A.4.1.1 BST

The BST general structure, as is transmitted to the OBE, is described in Table A.2.

Table A.2 — BST general structure

			Length	Allowed values
T-APDUs			4 bits	'1000' indicating initialisation-request (BST)
Option indicator			1 bit (nonmandApplications opt.)	0/1
RSE	manufacturerid		16 bits	As per ISO 14816
	individualid		27 bits	As specified by manufacturer
Time			32 bits	UNIX real time
Profile			1 bit (Profile ext.)	0 (= no extension)
			7 bits	As per Profile in EN 13372:2004, 6.3.2
MandAp- plications			1 bit (mandApplications ext.)	0 (= no extension)
			7 bits (number of applications)	M
	CCC application		1 bit (eid opt.)	0 (= eid not present)
			1 bit (parameter opt.)	0 (= parameter not present)
		Aid	1 bit (aid ext.)	0 (= no extension)
			5 bits	20 (= CCC application)
	Applica- tion 2 (not CCC)		1 bit (eid opt.)	0/1
			1 bit (parameter opt.)	0/1
		Aid	1 bit (aid ext.)	0 (= no extension)
			5 bits	≠ 20 (= no CCC application)
		Eid	1 bit (eid ext.)	0 (= no extension)
			7 bits	Any
		parameter		Refer to ApplicationContextMark as per EN 12834:2003, Annex A
		...		...
		Application M (not CCC)		1 bit (eid opt.)
			1 bit (parameter opt.)	0/1
	Aid		1 bit (aid ext.)	0 (= no extension)
			5 bits	≠ 20 (= no CCC application)
	Eid		1 bit (eid ext.)	0 (= no extension)
			7 bits	Any
	parameter			Refer to ApplicationContextMark as per EN 12834:2003, Annex A
	Nonmand Applica- tions			
		7 bits (number of applications)	N	
Application 1 (not CCC)		See “Application 2 (not CCC)” of mandApplications		
...		...		
Application N (not CCC)		See “Application 2 (not CCC)” of mandApplications		
profileList			1 bit (profileList ext.)	0 (= no extension)

Table A.2 (continued)

		Length	Allowed values
		7 bits (number of profiles)	K
	Profile 1	1 bit (Profile ext.)	0 (= no extension)
		7 bits	Refer to Profile as per EN 12834:2003, Annex A and EN 13372:2004, 6.3.2
	...	...	...
	Profile K	1 bit (Profile ext.)	0 (= no extension)
		7 bits	Refer to Profile as per EN 12834:2003, Annex A and EN 13372:2004, 6.3.2

A.4.1.2 VST

The general structure for a VST indicating one CCC-application as is transmitted by the OBE is described in Table A.3.

Table A.3 — VST1 (security level 1): valid VST indicating one CCC application

					Length	Allowed value			
Fill					4 bits	Any			
Profile					1 bit (Profile ext.)	0 (= no extension)			
					7 bits	Refer to Profile as per EN 12834:2003, Annex A			
					1 bit (applications ext.)	0 (= no extension)			
					7 bits (number of applic.)	M			
					1 bit (eid opt.)	1 (= eid present)			
					1 bit (parameter opt.)	1 (= parameter present)			
					aid			1 bit (aid ext.)	0 (= no extension)
		5 bits	20 (= CCC application)						
		eid			1 bit (eid ext.)	0 (= no extension)			
					7 bits	Any (≠ other eid used in this VST)			
						1 bit (Container ext.)	0 (= no extension)		
						7 bits (Container CHOICE)	2 (= OCTET STRING)		
						1 bit (octet string ext.)	0 (= no extension)		
						7 bits (octet string length)	16		
				CCC-ContextMark		Contract Provider	10 bits (CountryCode)	As per ISO 3166-1	
							14 bits (IssuerIdentifier)	As per ISO 14816	
				Applications	CCC application	para meter	CCC-ContextMark	typeOf Contract	16 bits
		context Version	1 bit (contextVersion ext.)					0 (= no extension)	
							7 bits	Any	
							1 bit (Container ext.)	0 (= no extension)	
							7 bits (Container CHOICE)	2 (= OCTET STRING)	
							1 bit (octet string ext.)	0 (= no extension)	
							7 bits (octet string length)	2	
							AC_CR-Reference	AC_Master KeyRef	8 bits
							AC_CR-Diversifier	8 bits	Any

Table A.3 (continued)

				Length	Allowed value		
				7 bits (Container CHOICE)	2 (= OCTET STRING)		
				1 bit (octet string ext.)	0 (= no extension)		
				7 bits (octet string length)	4		
		RndOBE	32 bits	Any			
	Application 2			1 bit (eid opt.)	0/1		
				1 bit (parameter opt.)	0/1		
			aid	1 bit (aid ext.)	0 (= no extension)		
				5 bits	Refer to DSRCApplicationEntit- yID, as per EN 12834:2003, Annex A		
			eid	1 bit (eid ext.)	0 (= no extension)		
				7 bits	Any (≠ other eid used in this VST)		
		parameter		Refer to ApplicationContextMark, as per EN 12834:2003, Annex A			
			...				
		Application M		aid	1 bit (eid opt.)	0/1	
1 bit (parameter opt.)					0/1		
1 bit (aid ext.)	0 (= no extension)						
5 bits	Refer to DSRCApplicationEntit- yID, as per EN 12834:2003, Annex A						
eid	1 bit (eid ext.)				0 (= no extension)		
	7 bits				Any (≠ other eid used in this VST)		
parameter				Refer to ApplicationContextMark, as per EN 12834:2003, Annex A			
					1 bit (obeStatus opt.)	0/1	
OBE Configuration	equipmentClass			15 bits	Any		
	manufacturerId			16 bits	Any		
	obeStatus			16 bits	Any		

The general structure for a VST indicating two CCC applications as is optionally transmitted by the OBE is described in Table A.4.

VST2 shall indicate the presence of two CCC applications with the following definitions (refer to ISO 12813:2019, 8.2.3):

- one CCC application shall conform to ISO 12813:2019; and
- the other CCC application shall conform to ISO 12813:2015.

NOTE Evaluation of conformance with ISO 12813:2015 is outside the scope of this document.

Table A.4 — VST2 (security level 1) — Valid VST indicating two CCC applications

				Length	Allowed value
Fill				4 bits	Any
Profile				1 bit (Profile ext.)	0 (= no extension)
				7 bits	Refer to Profile as per EN 12834:2003, Annex A
				1 bit (applications ext.)	0 (= no extension)
				7 bits (number of applic.)	M (≥2)
				1 bit (eid opt.)	1 (= eid present)
				1 bit (parameter opt.)	1 (= parameter present)

Table A.4 (continued)

				Length	Allowed value
Applications	CCC application1	aid		1 bit (aid ext.)	0 (= no extension)
				5 bits	20 (= CCC application)
		eid		1 bit (eid ext.)	0 (= no extension)
				7 bits	Any
		parameter		1 bit (Container ext.)	0 (= no extension)
				7 bits (Container CHOICE)	2 (= OCTET STRING)
				1 bit (octet string ext.)	0 (= no extension)
				7 bits (octet string length)	16
			CCC-ContextMark1	Contract Provider	10 bits (CountryCode) As per ISO 3166-1
				14 bits (IssuerIdentifier)	As per ISO 14816
				TypeOf Contract	16 bits Any
			context Version	1 bit (contextVersion ext.)	0 (= no extension)
				7 bits	Any
				1 bit (Container ext.)	0 (= no extension)
				7 bits (Container CHOICE)	2 (= OCTET STRING)
				1 bit (octet string ext.)	0 (= no extension)
				7 bits (octet string length)	2
			AC_CR-Reference	AC_Master KeyRef	8 bits Any
				AC_CR-Diversifier	8 bits Any
				1 bit (Container ext.)	0 (= no extension)
				7 bits (Container CHOICE)	2 (= OCTET STRING)
				1 bit (octet string ext.)	0 (= no extension)
				7 bits (octet string length)	4
			RndOBE	32 bits	Any
	CCC application2			1 bit (eid opt.)	1 (= eid present)
				1 bit (parameter opt.)	1 (= parameter present)
			aid	1 bit (aid ext.)	0 (= no extension)
				5 bits	20 (= CCC application)
			eid	1 bit (eid ext.)	0 (= no extension)
				7 bits	≠ eid of CCC application1
				1 bit (Container ext.)	0 (= no extension)
				7 bits (Container CHOICE)	2 (= OCTET STRING)
				1 bit (octet string ext.)	0 (= no extension)
				7 bits (octet string length)	16
		parameter	CCC-ContextMark2	Contract Provider	10 bits (CountryCode) As per ISO 3166-1
				14 bits (IssuerIdentifier)	As per ISO 14816
				TypeOf Contract	16 bits Any
				context Version	1 bit (contextVersion ext.) 0 (= no extension)
				7 bits	Any
				1 bit (Container ext.)	0 (= no extension)
				7 bits (Container CHOICE)	2 (= OCTET STRING)
				1 bit (octet string ext.)	0 (= no extension)
				7 bits (octet string length)	2

Table A.4 (continued)

					Length	Allowed value	
			AC_CR-Reference	AC_MasterKeyRef	8 bits	Any	
				AC_CR-Diversifier	8 bits	Any	
						1 bit (Container ext.)	0 (= no extension)
						7 bits (Container CHOICE)	2 (= OCTET STRING)
						1 bit (octet string ext.)	0 (= no extension)
						7 bits (octet string length)	4
			RndOBE			32 bits	Any
	⋮						
	Optional application M (non CCC-application)	aid		1 bit (eid opt.)	1 (= eid present)		
				1 bit (parameter opt.)	0 (= parameter not present)		
			1 bit (aid ext.)	0 (= no extension)			
			5 bits	≠ 20			
		eid	1 bit (eid ext.)	0 (= no extension)			
			7 bits	Any (≠ other eid used in this VST)			
	obe Configuration					1 bit (obeStatus opt.)	1 (= obeStatus present)
		equipmentClass				15 bits	Any
manufacturerId				16 bits	Any		
obeStatus				16 bits	Any		

A.4.2 PDUs parameters

A.4.2.1 Parameters of request PDUs

The following tables describe the valid format of the request APDUs:

- Table A.5;
- Table A.6;
- Table A.7;
- Table A.8;
- Table A.9.

No other request commands are used by CCC application.

Fill bits shall always be set to zero.

Table A.5 — GET-Rq parameters (security level 1)

	EN 12834:2003, Annex A	ISO 14906:2018, Annex A	EN 15509:2014, Table C.16
GET-Rq	Fill	=	=
	Eid		=
	accessCredentials optional		mandatory
	lid optional		prohibited
	attributeIdList optional		mandatory

Table A.6 — Action-Rq parameters for GET_STAMPED action (security level 1)

	EN 12834:2003, Annex A	ISO 14906:2018, Annex A	EN 15509:2014, Table C.16 and ISO 12813
ACTION-Rq	Mode	=	TRUE
	Eid		=
	actionType		0 (GET_STAMPED)
	accessCredentials optional		mandatory
	actionParameters optional		GetStampedRq
	lid optional		prohibited

Table A.7 — Action-Rq parameters for SET_MMI action

	EN 12834:2003, Annex A	ISO 14906:2018, Annex A	EN 15509:2014, Table C.16 and ISO 12813
ACTION-Rq	Mode	=	=
	Eid		0
	actionType		10 (SET_MMI)
	accessCredentials optional		prohibited
	actionParameters optional		SetMMIRq
	lid optional		prohibited

Table A.8 — Action-Rq parameters for ECHO action

	EN 12834:2003, Annex A	ISO 14906:2018, Annex A	EN 15509:2014, Table C.16 and ISO 12813
ACTION-Rq	Mode	=	=
	Eid		0
	actionType		15 (ECHO)
	accessCredentials optional		prohibited
	actionParameters optional		mandatory
	lid optional		prohibited

Table A.9 — EVENT-REPORT-Rq parameters

	EN 12834:2003, Annex A	ISO 14906:2018, Annex A	EN 15509:2014, Table C.16 and ISO 12813
EVENT-REPORT-Rq	Mode	=	=
	Eid		0
	eventType		0 (release)
	accessCredentials optional		prohibited
	eventParameters optional		prohibited
	lid optional		prohibited

A.4.2.2 Parameters of response PDUs

The following tables describe the valid format of the response APDUs:

- Table A.10;
- Table A.11;
- Table A.12;