

DIN EN ISO 17677-1

ICS 01.040.25; 25.160.10

Ersatz für
DIN EN ISO 17677-1:2019-06**Widerstandsschweißen –****Begriffe –****Teil 1: Punkt-, Buckel- und Rollennahtschweißen (ISO 17677-1:2021);
Dreisprachige Fassung EN ISO 17677-1:2021**

Resistance welding –

Vocabulary –

Part 1: Spot, projection and seam welding (ISO 17677-1:2021);

Trilingual version EN ISO 17677-1:2021

Soudage par résistance –

Vocabulaire –

Partie 1: Soudage par points, par bossages et à la molette (ISO 17677-1:2021);

Version trilingue EN ISO 17677-1:2021

Gesamtumfang 93 Seiten

DIN-Normenausschuss Schweißen und verwandte Verfahren (NAS)

Nationales Vorwort

Dieses Dokument (EN ISO 17677-1:2021) wurde vom Technischen Komitee ISO/TC 44 „Welding and allied processes“ in Zusammenarbeit mit dem Technischen Komitee CEN/TC 121 „Schweißen und verwandte Verfahren“ erarbeitet, dessen Sekretariat von DIN (Deutschland) gehalten wird.

Das zuständige nationale Normungsgremium ist der Arbeitsausschuss NA 092-00-12 AA „Widerstandsschweißen (DVS AG V 3)“ im DIN-Normenausschuss Schweißen und verwandte Verfahren (NAS).

Hinweis: In der deutschen Übersetzung fehlt der Literaturhinweis [3], ISO/TR 25901-1:2016, *Welding and allied processes — Vocabulary — Part 1: General terms*. Dadurch hat sich die Benummerung der nachfolgenden Literaturhinweise entsprechend verschoben.

Für die in diesem Dokument zitierten Dokumente wird im Folgenden auf die entsprechenden deutschen Dokumente hingewiesen:

ISO 4063	siehe	DIN EN ISO 4063
ISO 17659:2002	siehe	DIN EN ISO 17659:2005-09

Aktuelle Informationen zu diesem Dokument können über die Internetseiten von DIN (www.din.de) durch eine Suche nach der Dokumentennummer aufgerufen werden.

Änderungen

Gegenüber DIN EN ISO 17677-1:2019-06 wurden folgende Änderungen vorgenommen:

- a) die Begriffe aus ISO 14329 wurden überführt;
- b) redaktionelle Anpassungen.

Frühere Ausgaben

DIN EN ISO 17677-1: 2010-01, 2019-06

Nationaler Anhang NA (informativ)

Literaturhinweise

DIN EN ISO 4063, *Schweißen und verwandte Prozesse — Liste der Prozesse und Ordnungsnummern*

DIN EN ISO 17659:2005-09, *Schweißen — Mehrsprachige Benennungen für Schweißverbindungen mit bildlichen Darstellungen (ISO 17659:2002); Dreisprachige Fassung EN ISO 17659:2004*

Dreisprachige Fassung / Trilingual version / Version trilingue

Widerstandsschweißen —
Begriffe —
Teil 1: Punkt-, Buckel- und Rollennahtschweißen
(ISO 17677-1:2021)

Resistance welding —
Vocabulary —
Part 1: Spot, projection and seam welding
(ISO 17677-1:2021)

Soudage par résistance —
Vocabulaire —
Partie 1: Soudage par points, par bossages et à la molette
(ISO 17677-1:2021)

Diese Europäische Norm wurde vom CEN am 28. Februar 2021 angenommen.

Die CEN-Mitglieder sind gehalten, die CEN/CENELEC-Geschäftsordnung zu erfüllen, in der die Bedingungen festgelegt sind, unter denen dieser Europäischen Norm ohne jede Änderung der Status einer nationalen Norm zu geben ist. Auf dem letzten Stand befindliche Listen dieser nationalen Normen mit ihren bibliographischen Angaben sind beim Management-Zentrum des CEN-CENELEC oder bei jedem CEN-Mitglied auf Anfrage erhältlich.

Diese Europäische Norm besteht in drei offiziellen Fassungen (Deutsch, Englisch, Französisch). Eine Fassung in einer anderen Sprache, die von einem CEN-Mitglied in eigener Verantwortung durch Übersetzung in seine Landessprache gemacht und dem Management-Zentrum mitgeteilt worden ist, hat den gleichen Status wie die offiziellen Fassungen.

CEN-Mitglieder sind die nationalen Normungsinstitute von Belgien, Bulgarien, Dänemark, Deutschland, Estland, Finnland, Frankreich, Griechenland, Irland, Island, Italien, Kroatien, Lettland, Litauen, Luxemburg, Malta, den Niederlanden, Norwegen, Österreich, Polen, Portugal, der Republik Nordmazedonien, Rumänien, Schweden, der Schweiz, Serbien, der Slowakei, Slowenien, Spanien, der Tschechischen Republik, der Türkei, Ungarn, dem Vereinigten Königreich und Zypern.

This European Standard was approved by CEN on 28 February 2021.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.

La présente Norme européenne a été adoptée par le CEN le 28 février 2021.

Les membres du CEN sont tenus de se soumettre au Règlement Intérieur du CEN/CENELEC, qui définit les conditions dans lesquelles doit être attribué, sans modification, le statut de norme nationale à la Norme européenne. Les listes mises à jour et les références bibliographiques relatives à ces normes nationales peuvent être obtenues auprès du Centre de Gestion du CEN-CENELEC ou auprès des membres du CEN.

La présente Norme européenne existe en trois versions officielles (allemand, anglais, français). Une version dans une autre langue faite par traduction sous la responsabilité d'un membre du CEN dans sa langue nationale et notifiée au Centre de Gestion du CEN-CENELEC, a le même statut que les versions officielles.

Les membres du CEN sont les organismes nationaux de normalisation des pays suivants: Allemagne, Autriche, Belgique, Bulgarie, Chypre, Croatie, Danemark, Espagne, Estonie, Finlande, France, Grèce, Hongrie, Irlande, Islande, Italie, Lettonie, Lituanie, Luxembourg, Malte, Norvège, Pays-Bas, Pologne, Portugal, République de Macédoine du Nord, République de Serbie, République Tchèque, Roumanie, Royaume-Uni, Slovaquie, Slovénie, Suède, Suisse et Turquie.



EUROPÄISCHES KOMITEE FÜR NORMUNG
EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION

CEN-CENELEC Management-Zentrum: Rue de la Science 23, B-1040 Brüssel
CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels
CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Bruxelles

European foreword

This document (EN ISO 17677-1:2021) has been prepared by Technical Committee ISO/TC 44 "Welding and allied processes" in collaboration with Technical Committee CEN/TC 121 "Welding and allied processes" the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 2021, and conflicting national standards shall be withdrawn at the latest by September 2021.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN ISO 17677-1:2019.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Endorsement notice

The text of ISO 17677-1:2021 has been approved by CEN as EN ISO 17677-1:2021 without any modification.

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
3.1 Welding and testing procedures	1
3.2 Hardware and tools	3
3.3 Welding process and parameters	4
3.4 Measurements and values	9
Bibliography	27

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 44, *Welding and allied processes*, Subcommittee SC 6, *Resistance welding and allied mechanical joining*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 121, *Welding and allied processes*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This third edition cancels and replaces the second edition (ISO 17677-1:2019), of which it constitutes a minor revision. The main changes compared to the previous edition are as follows:

- the terms and definitions of ISO 14329 have been implemented;
- editorial changes have been made.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Official interpretations of ISO/TC 44 documents, where they exist, are available from this page: <https://committee.iso.org/sites/tc44/home/interpretation.html>.

Resistance welding — Vocabulary —

Part 1:

Spot, projection and seam welding

1 Scope

This document establishes a vocabulary of terms and definitions for resistance spot welding, projection welding and seam welding.

NOTE In addition to terms used in English and French, two of the three official ISO languages, this document gives the equivalent terms in German; these are published under the responsibility of the member body for Germany (DIN). However, only the terms and definitions given in the official languages can be considered as ISO terms and definitions.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1 Welding and testing procedures

3.1.1

chisel test

test in which a chisel is driven between the sheets near to adjacent welds until either fracture occurs or until the metal near the weld yields or bends

3.1.2

cross tension test

tensile test of a resistance welded specimen to determine the mechanical properties and failure mode of the weld

3.1.3

cross-wire welding

projection welding (3.1.11) of crossed wires or rods

3.1.4

direct welding

resistance welding secondary circuit variant in which welding current and *electrode force* (3.3.5) are applied to the workpieces by directly opposed *electrodes* (3.2.1) and only one weld is made by one welding operation

Note 1 to entry: See Figure 12 for typical arrangements.

3.1.5

indirect welding

resistance welding secondary circuit variant in which the welding current flows through the workpieces in locations away from, as well as at, the welds

Note 1 to entry: See Figure 13 for typical arrangements.

3.1.6

multiple impulse welding

welding with more than one impulse

Note 1 to entry: See Figures 4 to 7 for related time and *electrode force* (3.3.5) diagrams.

3.1.7

multiple spot welding

spot welding in which two or more welds are made simultaneously in one welding operation

Note 1 to entry: Examples are *parallel spot welding* (3.1.8) and *series spot welding* (3.1.14).

3.1.8

parallel spot welding

resistance welding secondary circuit variant in which the secondary current is divided in parallel electrical paths to make two or more welds simultaneously

Note 1 to entry: See Figure 11 a).

3.1.9

peel test

destructive test in which a resistance-welded lap joint is tested by applying a peel force which results in stresses mainly in the thickness direction of the weld

3.1.10

pillow test

destructive test in which internal pressure is applied in order to test for leaks and the strength of a seam weld

3.1.11

projection welding

resistance welding in which the resulting welds are localized at predetermined points by projections, embossments or intersections, concentrating force and current by their geometry

Note 1 to entry: The projections are raised on, or formed from, one or more of the *faying surfaces* (3.3.16) and collapse during welding.

3.1.12

resistance spot welding

resistance welding process producing a weld at the *faying surfaces* (3.3.16) between overlapping parts by the heat obtained from resistance to the flow of welding current through the workpieces from the *electrodes* (3.2.1) serving to concentrate the welding current and pressure at the weld area

3.1.13

seam welding

resistance welding in which force is applied continuously and current is applied continuously or intermittently to produce a linear weld, the workpieces being between two *electrode wheels* (3.2.5) or an electrode wheel and an electrode bar

3.1.14

series spot welding

resistance welding secondary circuit variant in which the secondary current is conducted through the workpieces and *electrodes* (3.2.1) in a series electrical path to simultaneously form multiple resistance spot, seam or projection welds

Note 1 to entry: See Figures 1 and 11 b).

3.1.15

roll spot welding

resistance welding process variant that produces intermittent spot welds using one or more rotating circular electrodes

Note 1 to entry: The rotation of the *electrodes* (3.2.1) may or may not be stopped during the making of a weld.

3.1.16

shunt weld

first weld on a series of spot welds, which acts as a shunt

3.1.17

tensile shear test

test in which a lap-welded specimen is subjected to a tensile force with the aim of determining the mechanical properties of the specimen

3.1.18

stitch welding

spot welding in which successive welds overlap

3.2 Hardware and tools

3.2.1

electrode

resistance welding electrode

component of the electrical circuit that supplies electrical power and applies *electrode force* (3.3.5) to the workpiece

EXAMPLE Rotating wheel, rotating roll, bar, cylinder, plate, clamp, chuck, variations thereof.

3.2.1.1

angled electrode

bent electrode

electrode for spot or *stitch welding* (3.1.18) whose *electrode working face* (3.2.6) is not normal to the mounting axis

3.2.1.2

contact electrode

resistance welding electrode (3.2.1) designed to conduct secondary current through a workpiece without making a weld

3.2.1.3

offset electrode

eccentric electrode

electrode for spot or *stitch welding* (3.1.18) whose *electrode working face* (3.2.6) is not concentric with the axis of the *electrode adaptor* (3.2.2)

3.2.2

electrode adaptor

shank

device used to attach an *electrode* (3.2.1) to an *electrode holder* (3.2.4)

3.2.3

electrode cap

replaceable *electrode* (3.2.1) tip used in *resistance spot welding* (3.1.12)

3.2.4

electrode holder

device holding a welding *electrode* (3.2.1)

3.2.5

electrode wheel

seam welding wheel

rotating *resistance welding electrode* (3.2.1) of ring or disc shape

3.2.6

electrode working face

<resistance spot welding and projection welding> end of a *resistance welding electrode* (3.2.1) in contact with the workpiece

3.2.7

welding head

device comprising the force generation and guiding system, carrying an *electrode holder* (3.2.4), platen or *electrode wheel* (3.2.5)

3.3 Welding process and parameters

3.3.1

chill time

quench time

period of time between the end of the weld current and the start of post-heat current during which no current flows and the weld is cooled by the *electrodes* (3.2.1)

Note 1 to entry: See Figure 5.

3.3.2

cool time

pause time

time interval between successive heat times in *multiple impulse welding* (3.1.6) or *seam welding* (3.1.13)

Note 1 to entry: See Figures 4 and 7.

3.3.3

current delay time

time interval between reaching set force and initiation of current flow

Note 1 to entry: See Figure 3.

3.3.4

current-off time

period of time between the cessation of current in one *welding cycle* (3.3.43) and the beginning of current in the next one

3.3.5

electrode force

force applied by the electrodes to the workpieces

Note 1 to entry: See *welding force* (3.3.44).

3.3.6

welding electrode force

electrode force applied during *weld time* (3.3.40)

3.3.7

forging electrode force forge force

electrode force applied in the forge force time

3.3.8

dynamic electrode force

electrode force applied during the actual *welding cycle* (3.3.43)

3.3.9

static electrode force

electrode force with no current flowing and no movement in the welding machine

3.3.10

theoretical electrode force

force, neglecting friction and inertia, available at the electrodes of a resistance welding machine by virtue of the initial force and the theoretical mechanical properties of the system

3.3.11

electrode force programme

predetermined sequence of changes of force during welding

3.3.12

electrode force and current programme

predetermined sequence of changes of force and current during the *welding cycle* (3.3.43)

3.3.13

electrode movement during welding

physical displacement of *electrodes* (3.2.1) due to thermal expansion, shrinkage and indentation during welding

3.3.14

electrode skidding

lateral movement of the *electrodes* (3.2.1) relative to the surface of the workpieces during the welding process

3.3.15

electrode stroke

physical movement of *electrodes* (3.2.1) in the electrode axis during the *welding cycle* (3.3.43)

3.3.16

faying surface

mating surface of a workpiece in contact with another workpiece to which it is to be joined

3.3.17

force application time

total time of the application of force by the *electrodes* (3.2.1) to the workpiece in a *welding cycle* (3.3.43)

Note 1 to entry: See Figures 3 to 7.

3.3.18

force fall time

time between the start of force decrease to zero force

Note 1 to entry: See Figures 3 to 7.

3.3.19

force maintenance time

time in the *welding cycle* (3.3.43) during which a force is maintained at a predetermined level, excluding the *force rise time* (3.3.20) and *force fall time* (3.3.18)

Note 1 to entry: See Figures 3 to 7.

3.3.20

force rise time

time between the start of a force increase and the application of the predetermined force

Note 1 to entry: See Figures 3 to 7.

3.3.21

electrode force time

force time

time during which the force is built up and applied

Note 1 to entry: See Figures 3 to 7.

3.3.22

forge time

<welding force programme> time of increased force applied during or after the passage of the welding current

Note 1 to entry: See Figure 6.

3.3.23

head approach time

time of movement of the *electrode* (3.2.1) from the rest position to contact with the workpiece

Note 1 to entry: See Figures 3 to 7.

3.3.24

head return time

time of electrode return from contact with the workpiece to the rest position

3.3.25

heat-affected zone

HAZ

portion of non-melted parent metal whose microstructure has been affected by the heat of welding

Note 1 to entry: See Figure 2.

[SOURCE: ISO/TR 25901-1:2016, 2.1.2.2, modified — “by the heat of welding” has been added to the definition and Note 1 to entry has been added.]

3.3.26

heat time

duration of any one impulse in *multiple impulse welding* (3.1.6) or resistance *seam welding* (3.1.13)

Note 1 to entry: See Figures 4 to 7.

3.3.27

hold time

duration of *electrode force* (3.3.5) after cessation of current flow

Note 1 to entry: See Figures 3 to 7.

3.3.28

off-time

force set off-time

time after hold time until next start of working cycle

Note 1 to entry: See *actual force off-time* (3.3.29).

3.3.29

actual force off-time

actual off-time

measured period of time between two successive *welding cycles* (3.3.43) when no *electrode force* (3.3.5) is being applied to the workpiece

Note 1 to entry: See *off-time* (3.3.28).

Note 2 to entry: See Figures 3 to 7.

3.3.30

opposing forces

forces tending to separate the electrodes, such as from a mismatch of workpieces, spring back, sealants, etc.

Note 1 to entry: See *welding force* (3.3.44).

3.3.31

post-heat time

temper time

time following the *chill time* (3.3.1) during which a current is passed through the weld for heat treatment or improvement of weld microstructure

Note 1 to entry: See Figures 5 and 6.

3.3.32

preheat time

duration of preheating current flow applied before the welding current

Note 1 to entry: See Figures 5 and 6.

3.3.33

expulsion

splash

spatter

flash

metal particles expelled between the *faying surfaces* (3.3.16) of the components or between the components and electrodes during *resistance spot welding* (3.1.12), *projection welding* (3.1.11) or *seam welding* (3.1.13)

3.3.34

squeeze time

set time between the initiation of the *welding cycle* (3.3.43) and first application of current

Note 1 to entry: See *actual squeeze time* (3.3.35).

Note 2 to entry: See Figures 3 to 7.

3.3.35

actual squeeze time

actual time between the initiation of the *welding cycle* (3.3.43) and first application of current

Note 1 to entry: See *squeeze time* (3.3.34).

Note 2 to entry: The time and *electrode force* (3.3.5) diagrams of Figures 3 to 8 show squeeze time.

3.3.36

time base

time expressed in cycles of the power supply frequency or in milliseconds

3.3.37

upslope

controlled continuous increase of the current from a predetermined value or zero during a set time period

Note 1 to entry: See *down slope* (3.3.38).

3.3.38

down slope

controlled continuous decrease of the current until a predetermined value or zero is reached during a set time period

Note 1 to entry: See *upslope* (3.3.37).

3.3.39

weld contact area

area in the *faying surface* (3.3.16) through which welding current passes from one component to another during resistance welding

3.3.40

weld time

duration of continuous flow of welding current

Note 1 to entry: See Figures 3 to 7.

3.3.41

welding current programme

predetermined sequence of changes of current

3.3.42

welding cycle time

time required to complete a *welding cycle* (3.3.43), excluding the time for positioning the *electrodes* (3.2.1)

Note 1 to entry: See Figures 3 to 7.

3.3.43

welding cycle

<resistance welding> sequence of operations carried out by the machine to make a weld and return the *electrodes* (3.2.1) to their initial position

3.3.44

welding force

force acting on the *faying surfaces* (3.3.16), resulting from the *electrode force* (3.3.5) and any *opposing forces* (3.3.30), e.g. spring back of the workpieces, and the geometry of the parts

3.3.45

welding force programme

predetermined sequence of changes of force

3.3.46

work clearance stroke

physical displacement of *electrodes* (3.2.1), which allows them to move from one welding position to the next

Note 1 to entry: See Figure 8.

3.3.47

working cycle time

duration of a succession of operations carried out by a machine or gun for the making of a weld, including the return to the initial position

Note 1 to entry: See Figures 3 to 7.

3.3.48

working stroke

minimum movement of the *electrodes* (3.2.1) during the *welding cycle* (3.3.43)

Note 1 to entry: See Figure 8.

3.3.49

maximum stroke

high lift stroke

retract stroke

maximum *electrode* (3.2.1) stroke

3.4 Measurements and values

3.4.1

corona bond area

area surrounding the *nugget* (3.4.11) at the *faying surfaces* (3.3.16) in which only solid phase bonding has occurred

3.4.2

corona bond diameter

d_c

mean diameter of the *corona bond area* (3.4.1)

Note 1 to entry: See Figures 2 and 9.

3.4.3

current pass area

area through which current passes from an *electrode* (3.2.1) to the workpiece, smaller than the *electrode working face* (3.2.6) and which varies during the welding operation

3.4.4

duty cycle

X_c

percentage of time during a specified period when a power source or its accessories can be operated at rated output without overheating

Note 1 to entry: $X_c = \frac{\sum(t_{on})}{t_{sp}} \times 100\%$

where t_{on} is the heat time, and t_{sp} is the specific period.

3.4.5

electrode indentation

spot or seam weld depression formed on the surface of workpieces by *electrodes* (3.2.1)

3.4.6

electrode indentation depth

e_w, e_l

maximum depth of the *electrode indentation* (3.4.5) measured in the direction of the *electrode force* (3.3.5)

Note 1 to entry: See Figure 2.

3.4.7

electrode indentation diameter

d_{ew}, d_{el}

diameter of the *electrode indentation* (3.4.5)

Note 1 to entry: See Figure 2.

Note 2 to entry: If possible the mean value should be used.

3.4.8

electrode life

number of acceptable spot welds or length of weld seam that can be made with an electrode without any redressing or replacement of the electrode

3.4.9

electrode service life

electrode production life

number of acceptable spot welds or length of weld seam that can be made with an *electrode* (3.2.1) before the electrode is no longer useable

3.4.10

electrode misalignment

unintentional offset between the axes of the *electrodes* (3.2.1)

3.4.11

nugget

zone in spot, projection or seam weld where the metal has been melted

Note 1 to entry: See Figure 2.

3.4.12

nugget penetration

p_l, p_u

maximum penetration of the *nugget* (3.4.11) into the upper or lower workpiece, measured perpendicular to the *faying surface(s)* (3.3.16) of the workpieces

Note 1 to entry: See Figure 2.

3.4.13

nugget thickness

p

<spot, projection or seam weld> maximum thickness of the *nugget* (3.4.11) in two or more sheets measured perpendicular to the *faying surface(s)* (3.3.16) of the workpieces

Note 1 to entry: For two sheets, $p = p_l + p_u$; see Figure 2.

3.4.14

nugget overlap

o

<seam weld> length of common area between two adjacent overlapping seam weld *nuggets* (3.4.11)

Note 1 to entry: See Figure 14.

Note 2 to entry: The area contains the portion of the preceding weld nugget remolten by the succeeding weld.

3.4.15

seam weld width

width of the weld metal in the plane of the *faying surfaces* (3.3.16) in a direction normal to the longitudinal axis of the linear seam weld

3.4.16

seam weld nugget length

d_l

length of individual weld *nugget* (3.4.11) in the *seam welding* (3.1.13) direction

3.4.17
sheet separation

x

gap between the *faying surfaces* (3.3.16) measured at a distance of $0,5 d_n$ from the edge of the *nugget* (3.4.11)

Note 1 to entry: See Figure 2.

3.4.18
throat area

region bounded by the physical components of the secondary circuit of the welding machine

3.4.19
width of seam weld electrode indentation

width of the *electrode indentation* (3.4.5) measured in a direction normal to the longitudinal axis of the linear seam weld

3.4.20
weld diameter

d_w

mean diameter of fused zone at *faying surface* (3.3.16) after destructive testing without metallurgical examination

Note 1 to entry: See Figure 10.

3.4.21
nugget diameter

d_n

diameter of *nugget* (3.4.11) measured at the *faying surface* (3.3.16) by metallurgical examination

Note 1 to entry: See Figure 2.

3.4.22
plug diameter

d_p

mean diameter of the plug measured after destructive testing

Note 1 to entry: See Figure 10.

3.4.23
plug
button

part of a spot weld, which tears out during destructive testing

Note 1 to entry: It may include all or part of the nugget, the heat-affected zone and base metal.

Note 2 to entry: A hole is left in the mating sheet(s).

3.4.24
interface failure

fracture through the weld nugget along the *faying surface* (3.3.16)

Note 1 to entry: See Figures 9 and 15.

Note 2 to entry: If less than approximately 20 % of the mating sheet thickness is removed, the fracture is still interfacial.

3.4.25

plug failure button pull

failure mode of a weld, where separation occurs through base metal or the *heat-affected zone* (3.3.25) of the weld, resulting in a *plug* (3.4.23) on one sheet and a hole in the other sheet

Note 1 to entry: See Figures 10 and 15.

3.4.26

partial thickness failure

failure mode of a weld where parts of the nugget and/or parent metal are pulled out of the mating sheets without leaving a through hole

Note 1 to entry: See Figures 15 and 16.

Note 2 to entry: The portion removed must be more than 20 % of the mating sheet thickness, otherwise the fracture is interfacial. In all cases of partial thickness failures a cavity is left in the mating sheet wherever there is no through thickness hole from a button plug pull.

Note 3 to entry: In case of having a fracture along the boundary between the weld *nugget* (3.4.11) and the heat-affect zone the fracture is called a dome failure.

3.4.27

mixed failure mode

failure mode of a spot weld where two or three different failure modes are combined

Note 1 to entry: See Figure 17.

Note 2 to entry: The three different failure modes are the *interface failure* (3.4.24), the *plug failure* (3.4.25) and the *partial thickness failure* (3.4.26).

3.4.28

fused area

area of the weld at the *faying surface* (3.3.16) after destructive testing in case of interface failure

Note 1 to entry: See Figure 9.

3.4.29

solid phase joint

forged joint formed without melting

3.4.30

asymmetrical weld

elongated or oval welds in spot or *projection welding* (3.1.11)

Note 1 to entry: See Figure 10.

3.4.31

minimum seam weld width

$w_{\min}$

minimum width of the *seam weld width* (3.4.15) along the longitudinal direction

Note 1 to entry: See Figure 18.

3.4.32

brazed area

<welding of metallic coated sheets> area over which the bond is formed between the coatings only

Note 1 to entry: See Figure 19.

3.4.33

brazed zone diameter

d_{sb}

<welding of metallic coated sheets> diameter of the *brazed area* (3.4.32) measured in the plane of the weld at the *faying surface* (3.3.16)

Note 1 to entry: The mean value should be used (see Figure 19).

3.4.34

distance between nugget centres

a

<seam weld> distance between the centres of two adjacent *nuggets* (3.4.11)

Note 1 to entry: See Figure 16.

Note 2 to entry: The position of the nugget centre normally corresponds with the position of maximum nugget penetration.

3.4.35

heat-affected zone diameter

d_{HAZ}

diameter of the *heat-affected zone* (3.3.25) measured on a macro- or microsection

Note 1 to entry: See Figure 2.

3.4.36

heat-affected zone penetration

$P_{HAZ,u}, P_{HAZ,l}$

maximum size of the *heat-affected zone* (3.3.25) in the thickness direction of each sheet

Note 1 to entry: See Figure 2.

3.4.37

maximum thickness of seam weld

p_{max}

<seam weld> maximum thickness of the *nugget* (3.4.11) in the thickness direction

Note 1 to entry: See Figure 14.

3.4.38

minimum thickness of seam weld

p_{min}

<seam weld> minimum thickness of the *nugget* (3.4.11) in the thickness direction

Note 1 to entry: See Figure 14.

Note 2 to entry: It is usually achieved in the overlap area.

Note 3 to entry: The minimum nugget thickness can be measured in discontinuous seam and roll spot welds but the ability to do so in continuous seam and roll spot welds depends on the weld condition and metal.


3.4.39

plug failure in parent metal

button pull in parent metal

special case of *plug failure* (3.4.25) where the failure occurs through the base metal, resulting in a greater plug diameter than the nugget diameter which would be measured in a cross section


Note 1 to entry: See Figure 20.



Key

- 1 electrode
- 2 workpiece
- 3 current flow
- 4 copper packing piece


Figure 1 — Examples of series spot welding



Key

- 1 workpieces
- 2 nugget
- 3 heat-affected zone (HAZ)
- 4 electrode indentation
- d_{HAZ} diameter of heat-affected zone
- $p_{HAZ,l}$ lower penetration of heat-affected zone
- $p_{HAZ,u}$ upper penetration of heat-affected zone
- t_l thickness of the lower workpiece
- t_u thickness of the upper workpiece
- d_{eu} electrode indentation diameter
- d_{el} electrode indentation diameter
- d_c corona bond diameter
- d_n nugget diameter
- p_u nugget penetration
- p_l nugget penetration
- x sheet separation
- e_u electrode indentation depth
- e_l electrode indentation depth
- a Location for the measurement of sheet separation (x).


Figure 2 — Measurements taken at weld cross-section



Key

1	working cycle time	11	head approach time
2	welding cycle time	12	squeeze time
3	force application time	13	weld time
4	electrode force time	14	hold time
5	force rise time	15	force fall time
6	force maintenance time	16	actual force off-time
7	current delay time	17	head return time
8	electrode force	18	off-time
9	current	19	upslope
10	head lift off position	20	down slope
		<i>t</i>	time


Figure 3 — Time and electrode force diagram for simple spot, stitch or projection welding



Key

- | | |
|---------------------------|-----------------------------------|
| 1 working cycle time | 12 squeeze time |
| 2 welding cycle time | 13 weld time |
| 3 force application time | 14 hold time |
| 4 electrode force time | 15 force fall time |
| 5 force rise time | 16 actual force off-time |
| 6 force maintenance time | 17 head return time |
| 7 current delay time | 18 off-time |
| 8 electrode force | 19 cool time |
| 9 current | 20 heat time/individual weld time |
| 10 head lift off position | t time |
| 11 head approach time | |


Figure 4 — Time and electrode force diagram for pulsation spot or projection welding



Key

1	working cycle time	12	squeeze time
2	welding cycle time	13	weld time
3	force application time	14	hold time
4	electrode force time	15	force fall time
5	force rise time	16	actual force off-time
6	force maintenance time	17	head return time
7	current delay time	18	off-time
8	electrode force	19	chill time
9	current	20	heat time/individual weld time
10	head lift off position	21	preheat time
11	head approach time	22	post-heat time
		<i>t</i>	time


**Figure 5 — Time and electrode force diagram for spot or projection welding —
Current programme control**



Key

- | | |
|---------------------------|-----------------------------------|
| 1 working cycle time | 13 weld time |
| 2 welding cycle time | 14 hold time |
| 3 force application time | 15 force fall time |
| 4 electrode force time | 16 actual force off-time |
| 5 force rise time | 17 head return time |
| 6 force maintenance time | 18 off-time |
| 7 current delay time | 19 heat time/individual weld time |
| 8 electrode force | 20 preheat time |
| 9 current | 21 post heat time |
| 10 head lift off position | 22 forge delay time |
| 11 head approach time | 23 forge time |
| 12 squeeze time | 24 forge force |
| | t time |


**Figure 6 — Time and electrode force diagram for spot welding —
Current and electrode force programme control**



Key

- | | | | |
|----|------------------------|----|--------------------------------|
| 1 | working cycle time | 11 | head approach time |
| 2 | welding cycle time | 12 | squeeze time |
| 3 | force application time | 13 | hold time |
| 4 | electrode force time | 14 | force fall time |
| 5 | force rise time | 15 | actual force off-time |
| 6 | force maintenance time | 16 | head return time |
| 7 | current delay time | 17 | off-time |
| 8 | electrode force | 18 | cool time |
| 9 | current | 19 | heat time/individual weld time |
| 10 | head lift off position | t | time |

Figure 7 — Time and electrode force diagram for seam welding



Key

- | | |
|---|-----------------------|
| 1 | working stroke |
| 2 | work clearance stroke |
| 3 | high lift stroke |

Figure 8 — Position of upper electrode before spot welding





Figure 9 — Measurement of weld diameter for interface failure



Key

- 1 symmetrical $d_p = d_w = d$
- 2 asymmetrical $d_p = d_w = (d_1 + d_2)/2$
- 3 partial plug with partial interface failure $d_p = (d_1 + d_2)/2$
 $d_w = (d_3 + d_4)/2$

d_p plug diameter
 d_w weld diameter

NOTE d_1 and d_3 are the minimum diameters. d_2 and d_4 are the maximum diameters.

Figure 10 — Measurement of weld and plug diameter for plug failure and partial plug with interface failure