

DIN EN ISO 19125-1

ICS 35.240.70

**Geoinformation –
Simple feature access –
Teil 1: Gemeinsame Architektur (ISO 19125-1:2004);
Englische Fassung EN ISO 19125-1:2006**

Geographic information –
Simple feature access –
Part 1: Common architecture (ISO 19125-1:2004);
English version EN ISO 19125-1:2006

Information géographique –
Accès aux entités simples –
Partie 1: Architecture commune (ISO 19125-1:2004);
Version anglaise EN ISO 19125-1:2006

Gesamtumfang 50 Seiten

Normenausschuss Bauwesen (NABau) im DIN

Nationales Vorwort

Der Text von ISO 19125-1:2004 wurde vom Technischen Komitee ISO/TC 211 „Geoinformation/Geomatik“ erarbeitet und als EN ISO 19125-1:2006 vom Technischen Komitee CEN/TC 287 „Geoinformation“ übernommen, dessen Sekretariat vom NEN gehalten wird.

Der Text von ISO 19125-1:2004 wurde von CEN als EN ISO 19125-1:2006 ohne Änderungen angenommen.

Der für die deutsche Mitarbeit zuständige Arbeitsausschuss im DIN Deutsches Institut für Normung e. V. ist der als Spiegelausschuss zum CEN/TC 287 und ISO/TC 211 eingesetzte Arbeitsausschuss NA 005-03-03 AA „Kartographie und Geoinformation“ des Normenausschusses Bauwesen (NABau).

Das Präsidium des DIN hat mit seinem Beschluss 1/2004 festgelegt, dass von dem in den Regeln der europäischen Normungsarbeit von CEN/CENELEC verankerten Grundsatz, wonach Europäische Normen in den drei offiziellen Sprachen Deutsch, Englisch und Französisch veröffentlicht werden, in begründeten Ausnahmefällen abgewichen und auf die deutsche Sprachfassung verzichtet werden kann.

Die Genehmigung dafür hat die DIN-Geschäftsleitung entsprechend ihren in Anlage 1 zu dem DIN-Rundschreiben A 5/2004 festgelegten Kriterien für die vorliegende Norm auf Antrag des NABau-FB 03 „Vermessungswesen; Geoinformation“ erteilt.

Allgemeines

DIN EN ISO 19125-1 beschreibt die gemeinsame Architektur einfacher geometrischer Merkmale. Das Simple Feature-Geometriemodell ist unabhängig bezüglich einer verteilten Datenhaltung (en: Distributed Computing Platform) und nutzt die UML-Notation. Die Basis-Geometrieklasse beinhaltet Unterklassen für Punkte, Linien, Flächen und eine Menge von Geometrietypen. Jeder Geometrietyp steht in Verbindung mit einem räumlichen Referenzsystem.

Das erweiterte Geometriemodell hat eine Spezialisierung für 0, ein- und zwei-dimensionale Objekte, die zu beliebigen Mengen zusammengefasst werden können. So werden z. B. die Mengen *MultiPoint*, *MultiLineString* und *MultiPolygon* aus den korrespondierenden Geometriebasistypen Punkte, Linien und Polygone gebildet. Die Mengen *MultiCurve* und *MultiSurface* sind als abstrakte Oberklassen eingeführt und aus Linien und Flächen generalisiert.

Die Attribute, Methoden und Erklärungen für alle Geometrieklassen sind in Bild 1 beschrieben.

Der Zugriff auf die Simple Features über die COM-Technologie (en: Component Object Model) nutzt eine andere Notation als Simple Feature Access (SFA) für SQL. Die COM-Notation ist den COM-Programmierern vertrauter. Davon unabhängig nutzt dieses Dokument die UML-Notation. Es kann angenommen werden, dass einige Methoden innerhalb dieses Dokuments genutzt werden, die von denjenigen in DIN EN ISO 19125-2 abweichen. Wo dies der Fall ist, werden die Unterschiede innerhalb des betroffenen Dokuments angezeigt.

DIN EN ISO 19125-1 implementiert das Profil eines raumbezogenen Schemas, wie es in DIN EN ISO 19107 beschrieben wird.

Anhang A erläutert detailliert den Zusammenhang zwischen DIN EN ISO 19125-1 und DIN EN ISO 19107.

Nationaler Anhang NA

(informativ)

Englisch-deutsche Fachwörterliste

common architecture	gemeinsame Architektur
foreign key	Fremdschlüssel
geometric value	geometrischer Bezug mit raumbezogenen Werten (Flächengröße und -eigenschaften)
member bodies	Mitglieder
non-spatial attribute	nichträumliches (flächenhaftes) Attribut
spatial attribute	räumliches Attribut
technical committee	Technisches Komitee
vertices	Punkte, Brechpunkte, Scheitelpunkte
mapped	abgebildet
splines	Kurven (z. B. Höhenlinien)
UML-Notation	UML-Notationen (Beschreibungen, Aufzeichnungen)
SFA	Simple Feature Access
COM	Component Object Model

Nationaler Anhang NB

(informativ)

Literaturhinweise

DIN EN ISO 19107, *Geoinformation – Raumbezugsschema*

— Leerseite —

English Version

**Geographic information - Simple feature access - Part 1:
Common architecture (ISO 19125-1:2004)**

Information géographique - Accès aux entités simples -
Partie 1: Architecture commune (ISO 19125-1:2004)

Geoinformation - Simple feature access - Teil 1 :
Gemeinsame Architektur (ISO 19125-1:2004)

This European Standard was approved by CEN on 16 February 2006.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents

Page

Foreword	3
Introduction	4
1 Scope	5
2 Conformance	5
3 Normative references	5
4 Terms and definitions	5
5 Abbreviated terms	8
6 Architecture	9
6.1 Geometry object model	9
6.2 Well-known Text Representation for Geometry	25
6.3 Well-known Binary Representation for Geometry	26
6.4 Well-known Text Representation of Spatial Reference Systems	29
Annex A (informative) The correspondence of concepts of the common architecture with concepts of the geometry model of ISO 19107	32
Annex B (informative) Supported spatial reference data	40
Bibliography	46

Foreword

The text of ISO 19125-1:2004 has been prepared by Technical Committee ISO/TC 211 "Geographic information/Geomatics" of the International Organization for Standardization (ISO) and has been taken over as EN ISO 19125-1:2006 by Technical Committee CEN/TC 287 "Geographic Information", the secretariat of which is held by NEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 2006, and conflicting national standards shall be withdrawn at the latest by September 2006.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

Endorsement notice

The text of ISO 19125-1:2004 has been approved by CEN as EN ISO 19125-1:2006 without any modifications.

Introduction

This part of ISO 19125 describes the common architecture for simple feature geometry. The simple feature geometry object model is Distributed Computing Platform neutral and uses UML notation. The base Geometry class has subclasses for Point, Curve, Surface and GeometryCollection. Each geometric object is associated with a Spatial Reference System, which describes the coordinate space in which the geometric object is defined.

The extended Geometry model has specialized 0, 1 and 2-dimensional collection classes named MultiPoint, MultiLineString and MultiPolygon for modelling geometries corresponding to collections of Points, LineStrings and Polygons, respectively. MultiCurve and MultiSurface are introduced as abstract superclasses that generalize the collection interfaces to handle Curves and Surfaces.

The attributes, methods and assertions for each Geometry class are described in Figure 1 in 6.1.1. In describing methods, *this* is used to refer to the receiver of the method (the object being messaged).

The SFA COM function “signatures” may use a different notation from SFA SQL. COM notation is more familiar for COM programmers. However, UML notation is used throughout this part of ISO 19125. There may also be methods used in this International Standard that differ from one part to another. Where this is the case, the differences are shown within the part.

This part of ISO 19125 implements a profile of the spatial schema described in ISO 19107:2003, *Geographic information — Spatial schema*. Annex A provides a detailed mapping of the schema in this part of ISO 19125 with the schema described in ISO 19107:2003.

1 Scope

This part of ISO 19125 establishes a common architecture and defines terms to use within the architecture.

This part of ISO 19125 does not attempt to standardize and does not depend upon any part of the mechanism by which Types are added and maintained, including the following:

- a) syntax and functionality provided for defining types;
- b) syntax and functionality provided for defining functions;
- c) physical storage of type instances in the database;
- d) specific terminology used to refer to User Defined Types, for example UDT.

This part of ISO 19125 does standardize names and geometric definitions for Types for Geometry.

This part of ISO 19125 does not place any requirements on how to define the Geometry Types in the internal schema nor does it place any requirements on when or how or who defines the Geometry Types.

2 Conformance

In order to conform to this part of ISO 19125, an implementation shall satisfy the requirements of one or more test suites specified in the other parts of ISO 19125.

3 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 19107:2003, *Geographic information — Spatial schema*

ISO 19111:2003, *Geographic information — Spatial referencing by coordinates*

4 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

4.1

boundary

set that represents the limit of an entity

NOTE Boundary is most commonly used in the context of geometry, where the set is a collection of points or a collection of objects that represent those points. In other arenas, the term is used metaphorically to describe the transition between an entity and the rest of its domain of discourse.

[ISO 19107]

4.2
buffer
geometric object (4.14) that contains all **direct positions** (4.7) whose distance from a specified geometric object is less than or equal to a given distance

[ISO 19107]

4.3
coordinate
one of a sequence of n -numbers designating the position of a **point** (4.17) in n -dimensional space

NOTE In a coordinate reference system, the numbers must be qualified by units.

[adapted from ISO 19111]

4.4
coordinate dimension
number of measurements or axes needed to describe a position in a **coordinate system** (4.6)

[ISO 19107]

4.5
coordinate reference system
coordinate system (4.6) that is related to the real world by a datum

[adapted from ISO 19111]

4.6
coordinate system
set of mathematical rules for specifying how **coordinates** (4.3) are to be assigned to **point** (4.17)

[ISO 19111]

4.7
curve
1-dimensional **geometric primitive** (4.15), representing the continuous image of a line

NOTE The boundary of a curve is the set of points at either end of the curve. If the curve is a cycle, the two ends are identical, and the curve (if topologically closed) is considered to not have a boundary. The first point is called the start point, and the last is the end point. Connectivity of the curve is guaranteed by the "continuous image of a line" clause. A topological theorem states that a continuous image of a connected set is connected.

[ISO 19107]

4.7
direct position
position described by a single set of **coordinates** (4.3) within a **coordinate reference system** (4.5)

[ISO 19107]

4.9
end point
last **point** (4.17) of a **curve** (4.7)

[ISO 19107]

4.10**exterior**

difference between the universe and the closure

NOTE The concept of exterior is applicable to both topological and geometric complexes.

[ISO 19107]

4.11**feature**

abstraction of real world phenomena

NOTE A feature may occur as a type or an instance. Feature type or feature instance is used when only one is meant.

[adapted from ISO 19101]

4.12**feature attribute**

characteristic of a **feature** (4.11)

NOTE A feature attribute has a name, a data type, and a value domain associated to it. A feature attribute for a feature instance also has an attribute value taken from the value domain.

[adapted from ISO 19101]

4.13**geometric complex**

set of disjoint **geometric primitives** (4.15) where the **boundary** (4.1) of each geometric primitive can be represented as the union of other geometric primitives of smaller dimension within the same set

NOTE The geometric primitives in the set are disjoint in the sense that no direct position is interior to more than one geometric primitive. The set is closed under boundary operations, meaning that for each element in the geometric complex, there is a collection (also a geometric complex) of geometric primitives that represents the boundary of that element. Recall that the boundary of a point (the only 0D primitive object type in geometry) is empty. Thus, if the largest dimension geometric primitive is a solid (3D), the composition of the boundary operator in this definition terminates after at most 3 steps. It is also the case that the boundary of any object is a cycle.

[ISO 19107]

4.14**geometric object**

spatial object representing a geometric set

NOTE A geometric object consists of a geometric primitive, a collection of geometric primitives, or a geometric complex treated as a single entity. A geometric object may be the spatial representation of an object such as a feature or a significant part of a feature.

[ISO 19107]

4.15**geometric primitive**

geometric object (4.14) representing a single, connected, homogeneous element of space

NOTE Geometric primitives are non-decomposed objects that represent information about geometric configuration. They include points, curves, surfaces, and solids.

[ISO 19107]

4.16
interior

set of all **direct positions** (4.7) that are on a **geometric object** (4.14) but which are not on its **boundary** (4.1)

NOTE The interior of a topological object is the homomorphic image of the interior of any of its geometric realizations. This is not included as a definition because it follows from a theorem of topology.

[ISO 19107]

4.17
point

0-dimensional **geometric primitive** (4.15), representing a position

NOTE The boundary of a point is the empty set.

[ISO 19107]

4.18
simple feature

feature (4.11) restricted to 2D geometry with linear interpolation between vertices, having both spatial and non spatial attributes

4.19
start point

first **point** (4.17) of a **curve** (4.7)

[ISO 19107]

4.20
surface

2-dimensional **geometric primitive** (4.15), locally representing a continuous image of a region of a plane

NOTE The boundary of a surface is the set of oriented, closed curves that delineate the limits of the surface.

[adapted from ISO 19107]

5 Abbreviated terms

API	Application Program Interface
COM	Component Object Model
CORBA	Common Object Request Broker Architecture
DCE	Distributed Computing Environment
DCOM	Distributed Component Object Model
DE-9IM	Dimensionally Extended Nine-Intersection Model
IEEE	Institute of Electrical and Electronics Engineers, Inc.
NDR	Little Endian byte order encoding
OLE	Object Linking and Embedding
RPC	Remote Procedure Call
SQL	Structured Query Language

The attributes, methods and assertions for each Geometry class are described below. In describing methods, *this* is used to refer to the receiver of the method (the object being messaged).

6.1.2 Geometry

6.1.2.1 Description

Geometry is the root class of the hierarchy. Geometry is an abstract (non-instantiable) class.

The instantiable subclasses of Geometry defined in this International Standard are restricted to 0, 1 and 2-dimensional geometric objects that exist in 2-dimensional coordinate space ($\mathbb{R}^2$).

All instantiable Geometry classes described in this part of ISO 19125 are defined so that valid instances of a Geometry class are topologically closed, i.e. all defined geometries include their boundary.

6.1.2.2 Basic methods on geometric objects

- **Dimension** ():Integer — The inherent dimension of *this* geometric object, which must be less than or equal to the coordinate dimension. This specification is restricted to geometries in 2-dimensional coordinate space.
- **GeometryType** ():String — Returns the name of the instantiable subtype of Geometry of which *this* geometric object is a instantiable member. The name of the subtype of Geometry is returned as a string.
- **SRID** ():Integer — Returns the Spatial Reference System ID for *this* geometric object.
- **Envelope** ():Geometry — The minimum bounding box for *this* Geometry, returned as a Geometry. The polygon is defined by the corner points of the bounding box [(MINX, MINY), (MAXX, MINY), (MAXX, MAXY), (MINX, MAXY), (MINX, MINY)].
- **AsText** ():String — Exports *this* geometric object to a specific Well-known Text Representation of Geometry.
- **AsBinary** ():Binary — Exports *this* geometric object to a specific Well-known Binary Representation of Geometry.
- **IsEmpty** ():Integer — Returns 1 (TRUE) if *this* geometric object is the empty Geometry. If true, then this geometric object represents the empty point set, $\emptyset$, for the coordinate space.
- **IsSimple** ():Integer — Returns 1 (TRUE) if *this* geometric object has no anomalous geometric points, such as self intersection or self tangency. The description of each instantiable geometric class will include the specific conditions that cause an instance of that class to be classified as not simple.
- **Boundary** ():Geometry — Returns the closure of the combinatorial boundary of *this* geometric object (Reference [1], section 3.12.2). Because the result of this function is a closure, and hence topologically closed, the resulting boundary can be represented using representational Geometry primitives (Reference [1], section 3.12.2).

6.1.2.3 Methods for testing spatial relations between geometric objects

The methods in this subclause are defined and described in more detail following the description of the subtypes of Geometry.

- **Equals**(anotherGeometry:Geometry):Integer — Returns 1 (TRUE) if *this* geometric object is “spatially equal” to anotherGeometry.
- **Disjoint**(anotherGeometry:Geometry):Integer — Returns 1 (TRUE) if *this* geometric object is “spatially disjoint” from anotherGeometry.

- **Intersects**(anotherGeometry:Geometry):Integer — Returns 1 (TRUE) if *this* geometric object “spatially intersects” anotherGeometry.
- **Touches**(anotherGeometry:Geometry):Integer — Returns 1 (TRUE) if *this* geometric object “spatially touches” anotherGeometry.
- **Crosses**(anotherGeometry:Geometry):Integer — Returns 1 (TRUE) if *this* geometric object “spatially crosses” anotherGeometry.
- **Within**(anotherGeometry:Geometry):Integer — Returns 1 (TRUE) if *this* geometric object is “spatially within” anotherGeometry.
- **Contains**(anotherGeometry:Geometry):Integer — Returns 1 (TRUE) if *this* geometric object “spatially contains” anotherGeometry.
- **Overlaps**(anotherGeometry:Geometry):Integer — Returns 1 (TRUE) if *this* geometric object “spatially overlaps” anotherGeometry.
- **Relate**(anotherGeometry:Geometry, intersectionPatternMatrix:String):Integer — Returns 1 (TRUE) if *this* geometric object is spatially related to anotherGeometry by testing for intersections between the interior, boundary and exterior of the two geometric objects as specified by the values in the intersectionPatternMatrix.

6.1.2.4 Methods that support spatial analysis

- **Distance**(anotherGeometry:Geometry):Double — Returns the shortest distance between any two Points in the two geometric objects as calculated in the spatial reference system of *this* geometric object.
- **Buffer**(distance:Double):Geometry — Returns a geometric object that represents all Points whose distance from *this* geometric object is less than or equal to distance. Calculations are in the spatial reference system of *this* geometric object.
- **ConvexHull**():Geometry — Returns a geometric object that represents the convex hull of *this* geometric object.
- **Intersection**(anotherGeometry:Geometry):Geometry — Returns a geometric object that represents the Point set intersection of *this* geometric object with anotherGeometry.
- **Union**(anotherGeometry:Geometry):Geometry — Returns a geometric object that represents the Point set union of *this* geometric object with anotherGeometry.
- **Difference**(anotherGeometry:Geometry):Geometry — Returns a geometric object that represents the Point set difference of *this* geometric object with anotherGeometry.
- **SymDifference**(anotherGeometry:Geometry):Geometry — Returns a geometric object that represents the Point set symmetric difference of *this* geometric object with anotherGeometry.

6.1.3 GeometryCollection

6.1.3.1 Description

A GeometryCollection is a geometric object that is a collection of 1 or more geometric objects.

All the elements in a GeometryCollection shall be in the same Spatial Reference. This is also the Spatial Reference for the GeometryCollection.