

DIN EN 60870-6-702

ICS 33.200

Einsprüche bis 2013-06-22
Vorgesehen als Ersatz für
DIN EN 60870-6-702:2000-02

Entwurf

**Fernwirkeinrichtungen und -systeme –
Teil 6-702: Fernwirkprotokolle, die mit ISO-Normen und
ITU-T-Empfehlungen kompatibel sind –
Funktionsprofil für den TASE.2-Anwendungsdienst in Endsystemen
(IEC 57/1214/CD:2012), Text in Englisch**

Telecontrol equipment and systems –
Part 6-702: Telecontrol protocols compatible with ISO standards and ITU-T
recommendations –
Functional profile for providing the TASE.2 application service in end systems
(IEC 57/1214/CD:2012), Text in English

Anwendungswarnvermerk

Dieser Norm-Entwurf mit Erscheinungsdatum 2013-04-22 wird der Öffentlichkeit zur Prüfung und
Stellungnahme vorgelegt.

Weil die beabsichtigte Norm von der vorliegenden Fassung abweichen kann, ist die Anwendung dieses
Entwurfes besonders zu vereinbaren.

Stellungnahmen werden erbeten

- vorzugsweise online im Norm-Entwurfs-Portal des DIN unter www.entwuerfe.din.de bzw. für Norm-Entwürfe der DKE auch im Norm-Entwurfs-Portal der DKE unter www.entwuerfe.normenbibliothek.de, sofern dort wiedergegeben;
- oder als Datei per E-Mail an dke@din.de möglichst in Form einer Tabelle. Die Vorlage dieser Tabelle kann im Internet unter www.din.de/stellungnahme oder für Stellungnahmen zu Norm-Entwürfen der DKE unter www.dke.de/stellungnahme abgerufen werden;
- oder in Papierform an die DKE Deutsche Kommission Elektrotechnik Elektronik Informationstechnik im DIN und VDE (Hausanschrift: Stresemannallee 15, 60596 Frankfurt am Main).

Die Empfänger dieses Norm-Entwurfs werden gebeten, mit ihren Kommentaren jegliche relevanten
Patentrechte, die sie kennen, mitzuteilen und unterstützende Dokumentationen zur Verfügung zu stellen.

Gesamtumfang 38 Seiten

DKE Deutsche Kommission Elektrotechnik Elektronik Informationstechnik im DIN und VDE

Nationales Vorwort

Die englische Originalfassung des internationalen Dokuments IEC 57/1214/CD:2012 „Telecontrol equipment and systems – Part 6-702: Telecontrol protocols compatible with ISO standards and ITU-T recommendations – Functional profile for providing the TASE.2 application service in end systems“ (CD, en: Committee Draft) ist unverändert in diesen Norm-Entwurf übernommen worden.

Das internationale Dokument wurde vom TC 57 „Power systems management and associated information exchange“ der Internationalen Elektrotechnischen Kommission (IEC) erarbeitet und den nationalen Komitees zur Stellungnahme vorgelegt.

Die IEC und das Europäische Komitee für Elektrotechnische Normung (CENELEC) haben vereinbart, dass ein auf IEC-Ebene erarbeiteter Entwurf für eine Internationale Norm zeitgleich (parallel) bei IEC und CENELEC zur Umfrage (CDV-Stadium) und Abstimmung als FDIS (en: Final Draft International Standard) bzw. Schluss-Entwurf für eine Europäische Norm gestellt wird, um eine Beschleunigung und Straffung der Normungsarbeit zu erreichen. Dokumente, die bei CENELEC als Europäische Norm angenommen und ratifiziert werden, sind unverändert als Deutsche Normen zu übernehmen.

Da der Abstimmungszeitraum für einen FDIS bzw. Schluss-Entwurf prEN nur 2 Monate beträgt, und dann keine sachlichen Stellungnahmen mehr abgegeben werden können, sondern nur noch eine „JA/NEIN“-Entscheidung möglich ist, wobei eine „NEIN“-Entscheidung fundiert begründet werden muss, wird bereits der CD als DIN-Norm-Entwurf veröffentlicht, um die Stellungnahmen aus der Öffentlichkeit frühzeitig berücksichtigen zu können.

Für dieses Dokument ist das nationale Arbeitsgremium K 952 „Netzleittechnik“ der DKE Deutsche Kommission Elektrotechnik Elektronik Informationstechnik im DIN und VDE (www.dke.de) zuständig.

Für den Fall einer undatierten Verweisung im normativen Text (Verweisung auf eine Norm ohne Angabe des Ausgabedatums und ohne Hinweis auf eine Abschnittsnummer, eine Tabelle, ein Bild usw.) bezieht sich die Verweisung auf die jeweils neueste gültige Ausgabe der in Bezug genommenen Norm.

Für den Fall einer datierten Verweisung im normativen Text bezieht sich die Verweisung immer auf die in Bezug genommene Ausgabe der Norm.

Der Zusammenhang der zitierten Normen mit den entsprechenden Deutschen Normen ergibt sich, soweit ein Zusammenhang besteht, grundsätzlich über die Nummer der entsprechenden IEC-Publikation. Beispiel: IEC 60068 ist als EN 60068 als Europäische Norm durch CENELEC übernommen und als DIN EN 60068 ins Deutsche Normenwerk aufgenommen.

Das Präsidium des DIN hat mit Präsidialbeschluss 1/2004 festgelegt, dass DIN-Normen, deren Inhalt sich auf internationale Arbeitsergebnisse der Informationsverarbeitung gründet, unter bestimmten Bedingungen allein in englischer Sprache veröffentlicht werden dürfen. Diese Bedingungen sind für die vorliegenden Normentwurf erfüllt.

Da sich die Benutzer des vorliegenden Normentwurfs der englischen Sprache als Fachsprache bedienen, wird die Englische Fassung der EN 60870-6-702 veröffentlicht. Für die meisten der verwendeten Begriffe existieren keine gebräuchlichen deutschen Benennungen, da sich die deutschen Anwender in der Regel ebenfalls der englischen Benennungen bedienen. Dieser Normentwurf steht nicht in unmittelbarem Zusammenhang mit Rechtsvorschriften und ist nicht als Sicherheitsnorm anzusehen.

Es ist vorgesehen, auch bei der entsprechenden zukünftigen Deutschen Norm auf die deutsche Sprachfassung zu verzichten und diese in der englischsprachigen Fassung zu veröffentlichen.

Änderungen

Gegenüber DIN EN 60870-6-702:2000-02 wurden folgende Änderungen vorgenommen:

- a) Aufnahme weiterer normativer Verweise in Abschnitt 2,
- b) Anforderungen "Lower Layer" wurden ergänzt in Abschnitt 6,
- c) in Anhang 6 wurden Eintragungen der Tabellen überarbeitet; Verweise auf die IEC 62351-4 ergänzt, MMS Identifier, MMSString und ObjectName ergänzt (A.4.1-3), Tabelle A.31 zur Zugangskontrolle (Access Control) ist neu, PDU spezifischen Anforderungen wurden aufgenommen (A.4.5), Annex B "Future developments" der früheren Ausgabe wurde gelöscht.

Contents

1	Scope	7
2	Normative references	8
3	Definitions	9
4	Abbreviations	9
5	Profile protocol stacks	9
6	Conformance requirements	9
6.1	TASE.2 requirements	9
6.2	MMS requirements	9
6.3	Upper layers requirements	9
6.4	Lower Layer requirements	10
Annex A	(normative) ISPICS requirements lists	11
A.1	General	11
A.2	Classification of requirements	11
A.2.1	Base column	11
A.2.2	F/S column	12
A.2.3	Status column	12
A.2.4	Profile column	13
A.3	TASE.2	13
A.4	MMS	19
A.4.1	MMS Identifier	19
A.4.2	MMSString	19
A.4.3	ObjectName	19
A.4.4	Supported MMS PDUs	19
A.4.5	PDU-specific requirements	25
A.5	ACSE	29
A.5.1	Supported functions	29
A.5.2	Initiator/responder capability	30
A.5.3	Supported APDUs	31
A.5.4	Supported APDU parameters	31
A.5.5	Supported parameter forms	33
Annex B	(informative) Bibliography	36
Table A.1	- Client/Server capability	13
Table A.2	- TASE.2 CBBs	13
Table A.3	- Association management	14
Table A.4	- Data value	14
Table A.5	- Data sets	14
Table A.6	- Accounts	15
Table A.7	- DS transfer sets	15
Table A.8	- Time series transfer set objects	16
Table A.9	- Transfer account transfer set objects	16
Table A.10	- Information message objects	16
Table A.11	- Special transfer set objects	16
Table A.12	- SBO devices	17

Table A.13 - Programs	17
Table A.14 - Event enrollments	17
Table A.15 - Event conditions	18
Table A.16 - Object models	18
Table A.17 - Environment and general management	19
Table A.18 - MMS modifiers	20
Table A.19 - Parameter CBBs	20
Table A.20 - VMD support	21
Table A.21 - Domain management	21
Table A.22 - Program invocation management	21
Table A.23 - Variable access	22
Table A.24 - Semaphore management	22
Table A.25 - Operator communication	22
Table A.26 - Event management	23
Table A.27 - Journal management	23
Table A.28 - File access	23
Table A.29 - File management	24
Table A.30 - Data exchange management	24
Table A.31 - AccessControl	24
Table A.32 - Additional PDUs	24
Table A.33 – GetNameList conformance statement	25
Table A.34 – VariableAccessSpecification conformance statement	25
Table A.35 – VariableSpecification conformance statement	26
Table A.36 – Read conformance statement	26
Table A.37 – Write conformance statement	26
Table A.38 – InformationReport conformance statement	27
Table A.39 – GetVariableAccessAttributes conformance statement	27
Table A.40 – DefineNamedVariableList conformance statement	27
Table A.41 – GetNamedVariableListAttributes conformance statement	28
Table A.42 – DeleteNamedVariableList conformance statement	28
Table A.43 - Protocol versions	29
Table A.44 - Other protocol versions	29
Table A.45 - Technical corrigenda implemented	29
Table A.46 - Global statement of conformance	29
Table A.47 - Protocol mechanisms	29
Table A.48 - Association establishment procedure	30
Table A.49 - Normal release procedure	30
Table A.50 - Abnormal release procedure	30
Table 51 - Functional units	30
Table A.52 - ACSE Supported APDUs	31
Table A.53 - A-associate-request APDU	31
Table A.54 - A-associate-response APDU	31
Table A.55 - A-release-request APDU	32

Table A.56 - A-release-response APDU	32
Table A.57 - Abort APDU.....	32
Table A.58 - AE title syntax name-form	33
Table A.59 - Authentication value form	33

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**TELECONTROL EQUIPMENT AND SYSTEMS –
Part 6-702: Telecontrol protocols compatible with
ISO standards and ITU-T recommendations –
Functional profile
for providing the TASE.2 application service in end systems**

FOREWORD

1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.

2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.

3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical reports or guides and they are accepted by the National Committees in that sense.

4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.

5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.

6) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60870-6-702 has been prepared by IEC technical committee 57: Power system control and associated communications.

The text of this standard is based on the following documents:

FDIS	Report on voting
57/368/FDIS	57/377/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

Annex A forms an integral part of this standard.

Annexes B and C are for information only.

INTRODUCTION

This part of IEC 60870 is one of the IEC 60870-6 series defining functional profiles to be used in telecommunication networks for electric power systems. It is largely based on existing ISO/IEC International Standards and International Standardized Profiles (ISP).

The notion of functional profiles is fundamental in the organization of the IEC 60870-6 series. A description of functional profiles, their classification scheme and the manner of defining them are laid down in IEC 60870-6-1.

This profile for telecontrol application service element (TASE.2, also known as inter-control centre communications protocol, ICCP) is an application-class profile (A-profile) providing communications capabilities to control centre applications. The TASE.2 in the application layer is specified in IEC 60870-6-503. The present standard refines the application layer protocol to meet interoperability requirements and specifies requirements on the presentation and session layers support for TASE.2. TASE.2 operates in a connection mode, so this A-profile needs to interface to a transport-class profile of the T-profile variety.

Since the TASE.2 is an MMS-based protocol, this functional profile (FP) is based on MMS profiles. In the OSI international standardized profile taxonomy there is a category for MMS A-profiles. The present standard makes frequent use of the AMM11 profile.

TELECONTROL EQUIPMENT AND SYSTEMS –
Part 6-702: Telecontrol protocols compatible with
ISO standards and ITU-T recommendations –
Functional profile for providing the TASE.2 application
service in end systems

1 Scope

This part of IEC 60870 is a functional profile (FP) and defines the provision of the TASE.2 communications services between two control centre end systems. It is supported by the transport services implemented in accordance with transport-profiles defined for the type of network that interconnects the control centre end systems. This is demonstrated in figure 1.

This FP also defines the provision of the OSI connection-mode presentation and session services between the end systems.

ISO/ISP 14226 specifies the AMM11 profiles for MMS. The parts of ISO/ISP 14226 that cover the profile that are used as a basis for this FP are ISO/ISP 14226-1 and ISO/ISP 14226-2. This FP is in alignment with ISO/ISP 14226, as far as possible, and maintains this compatibility by reference. There are TASE.2 requirements in addition to ISO/ISP 14226. These requirements are specified in this FP.




Figure 1 – Applicability of functional profile

2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of IEC 60870. At the time of publication, the editions indicated were valid. All normative documents are subject to revision, and parties to agreements based on this part of IEC 60870 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 60870-6-503:2011	Telecontrol equipment and systems – Part 6: Telecontrol protocols compatible with ISO standards and ITU-T recommendations – Section 503: TASE.2 Services and protocol
ISO/IEC 8327-2:1996	Information technologies – Open Systems interconnection – Connection- oriented session protocol – Part 2: Protocol implementation conformance statement (PICS) proforma
ISO/IEC 8650-2:1997	Information technology – Open Systems Interconnection – Protocol specification for the Association Control Service Element – Part 2: Protocol Implementation Conformance Statement (PICS) proforma
ISO/IEC 8823-2:1997	Information technology – Open Systems Interconnection – Connection- oriented presentation protocol – Part 2: Protocol Implementation Conformance Statement (PICS) Proforma
ISO/ISP 14226-1:1996	Industrial automation systems – International Standardized Profile AMM11: MMS General Applications Base Profile – Part 1: Specification of ACSE, Presentation and Session protocols for the use by MMS
ISO/ISP 14226-2:1996	Industrial automation systems – International Standardized Profile AMM11: MMS General Applications Base Profile – Part 2: Common MMS requirements
RFC 2126	ISO Transport Service on top of TCP (ITOT)
RFC 791	<i>Internet Protocol DARPA Internet Program Protocol Specification</i>
RFC 826	<i>An Ethernet Address Resolution Protocol</i>
RFC 894	<i>A Standard for the Transmission of IP Datagrams over Ethernet Networks</i>
RFC 793	<i>Transmission Control Procedure – DARPA Internet Program Protocol Specification</i>
ISO/IEC 9506-1:2003	Industrial automation systems -- Manufacturing Message Specification -- Part 1: Service definition
ISO/IEC 9506-2:2003	Industrial automation systems -- Manufacturing Message Specification -- Part 2: Protocol specification
IEC 62351-4 ed1.0	Power systems management and associated information exchange - Data and communications security - Part 4: Profiles including MMS

3 Definitions

All the terms used in this standard are as defined in the above-referenced standards.

4 Abbreviations

All the abbreviations used in this standard are as defined in the above-referenced standards.

5 Profile protocol stacks

As shown in figure 1, the TASE.2 profile includes the TASE.2, MMS and ACSE elements in the TASE.2 protocol, the connection-mode presentation protocol, and the connection-mode session protocol.

6 Conformance requirements

The TASE.2 application profile can be referred to as a TASE.2 MMS application profile. It shall follow the same rules and regulations governing MMS ISPs. Requirements of the TASE.2 MMS application profile to support TASE.2 are separated into upper layer requirements, MMS requirements, and TASE.2 requirements.

The ISPICS requirements lists for TASE.2, MMS, ACSE, presentation and session are given in annex A. Annex A makes mandatory some features that were optional in ISO/ISP 14226-1 and ISO/ISP 14226-2.

For each implementation claiming conformance to this part of IEC 60870 an appropriate set of PICSS shall be made available stating support or non-support of each option identified in this part.

6.1 TASE.2 requirements

The TASE.2 conformance requirements can be found in A.3.

6.2 MMS requirements

The MMS conformance requirements can be found in A.4. A data structure nesting level parameter value of greater than 1 shall be supported.

6.3 Upper layers requirements

Upper layer requirements for TASE.2 shall be as defined by ISO/ISP 14226-1 for the AMM11 profile. In addition, the presentation protocol shall be able to support the default context negotiation, default context name and simply encoded data options.

The TASE.2 MMS application profile requires that there be a mechanism for the application association performance/quality attributes to be conveyed to the transport (and thus network) service. The mechanism employed is implementation-defined, but the TASE.2 and transport profile implementations must be compatible.

When an association is requested, if there is a priority class agreed for it, the value agreed between the control centres is given to the transport layer. Every data unit that is sent on this association is treated according to the priority class in the transport service. If no priority value is agreed, then none is expressed and a default value is assumed.

6.4 Lower Layer requirements

The lower layers shall be based upon TCP/IP and include RFC-2126.

The implementation of IPv4 is mandatory.