

DIN EN IEC 62832-2

ICS 25.040.40; 35.240.50

Einsprüche bis 2020-12-16

Entwurf

**Industrielle Automatisierungs- und Leittechnik –
Rahmenwerk der Digitalen Fabrik –
Teil 2: Modellelemente
(IEC 65/774/CDV:2019);
Englische Fassung prEN IEC 62832-2:2019**

Industrial-process measurement, control and automation –
Digital Factory framework –
Part 2: Model elements
(IEC 65/774/CDV:2019);
English version prEN IEC 62832-2:2019

Mesure, commande et automation dans les processus industriels –
Cadre de l'usine numérique (digital factory) –
Partie 2: Éléments de modèles
(IEC 65/774/CDV:2019);
Version anglaise prEN IEC 62832-2:2019

Anwendungswarnvermerk

Dieser Norm-Entwurf mit Erscheinungsdatum 2020-10-16 wird der Öffentlichkeit zur Prüfung und Stellungnahme vorgelegt.

Weil die beabsichtigte Norm von der vorliegenden Fassung abweichen kann, ist die Anwendung dieses Entwurfs besonders zu vereinbaren.

Stellungnahmen werden erbeten

- vorzugsweise online im Norm-Entwurfs-Portal von DIN unter www.din.de/go/entwuerfe bzw. für Norm-Entwürfe der DKE auch im Norm-Entwurfs-Portal der DKE unter www.entwuerfe.normenbibliothek.de, sofern dort wiedergegeben;
- oder als Datei per E-Mail an dke@vde.com möglichst in Form einer Tabelle. Die Vorlage dieser Tabelle kann im Internet unter www.din.de/go/stellungnahmen-norm-entwuerfe oder für Stellungnahmen zu Norm-Entwürfen der DKE unter www.dke.de/stellungnahme abgerufen werden;
- oder in Papierform an die DKE Deutsche Kommission Elektrotechnik Elektronik Informationstechnik in DIN und VDE oder Stresemannallee 15, 60596 Frankfurt am Main.

Die Empfänger dieses Norm-Entwurfs werden gebeten, mit ihren Kommentaren jegliche relevanten Patentrechte, die sie kennen, mitzuteilen und unterstützende Dokumentationen zur Verfügung zu stellen.

Gesamtumfang 75 Seiten

DKE Deutsche Kommission Elektrotechnik Elektronik Informationstechnik in DIN und VDE

Nationales Vorwort

Die Englische Fassung des europäischen Dokuments prEN IEC 62832-2:2019 „Industrielle Automatisierungs- und Leittechnik – Rahmenwerk der Digitalen Fabrik – Teil 2: Modellelemente“ (Entwurf in der Umfrage) ist unverändert in diesen Norm-Entwurf übernommen worden.

Die Internationale Elektrotechnische Kommission (IEC) und das Europäische Komitee für Elektrotechnische Normung (CENELEC) haben vereinbart, dass ein auf IEC-Ebene erarbeiteter Entwurf für eine Internationale Norm zeitgleich (parallel) bei IEC und CENELEC zur Umfrage (CDV-Stadium) und Abstimmung als FDIS (en: Final Draft International Standard) bzw. Schluss-Entwurf für eine Europäische Norm gestellt wird, um eine Beschleunigung und Straffung der Normungsarbeit zu erreichen. Dem entsprechend ist das internationale Dokument IEC 65/774/CDV:2019-11 „Industrial-process measurement, control and automation – Digital Factory framework – Part 2: Model elements“ unverändert in den Entwurf prEN IEC 62832-2:2019 übernommen worden.

Das internationale Dokument wurde vom IEC/TC 65 „Industrial-process measurement, control and automation“ der Internationalen Elektrotechnischen Kommission (IEC) erarbeitet und unterliegt dem Copyright der IEC . Das Dokument wurde den nationalen Komitees zur Stellungnahme vorgelegt.

Bei der Abstimmung zu dem Europäischen Schluss-Entwurf bei CENELEC und dem Internationalen Schluss-Entwurf bei IEC [Final Draft International Standard (FDIS)] sind jeweils nur „JA/NEIN“-Entscheidungen möglich, wobei „NEIN“-Entscheidungen fundiert begründet werden müssen. Dokumente, die bei CENELEC als Europäische Norm angenommen und ratifiziert werden, sind unverändert als Deutsche Normen zu übernehmen.

Für dieses Dokument ist das nationale Arbeitsgremium DKE/K 931 „Systemaspekte der Automatisierung“ der DKE Deutsche Kommission Elektrotechnik Elektronik Informationstechnik in DIN und VDE (www.dke.de) zuständig.

Aktuelle Informationen zu diesem Dokument können über die Internetseiten von DKE (www.dke.de) und DIN (www.din.de) durch eine Suche nach der Dokumentennummer aufgerufen werden.

Das Präsidium des DIN hat mit Präsidialbeschluss 1/2004 festgelegt, dass DIN-Normen, deren Inhalt sich auf internationale Arbeitsergebnisse der Informationsverarbeitung gründet, unter bestimmten Bedingungen allein in englischer Sprache veröffentlicht werden dürfen. Diese Bedingungen sind für den vorliegenden Norm-Entwurf erfüllt.

Da sich die Benutzer des vorliegenden Norm-Entwurfs der englischen Sprache als Fachsprache bedienen, wird die Englische Fassung der prEN IEC 62832-2 veröffentlicht. Zu deren Einleitung, Abschnitt 1, der den Anwendungsbereich festlegt, und Abschnitt 3, der die Begriffe festlegt, wurde eine Übersetzung angefertigt und als informativer Nationaler Anhang NA des vorliegenden Norm-Entwurfs hinzugefügt. Für einige der verwendeten Begriffe existieren keine gebräuchlichen deutschen Benennungen, da sich die deutschen Anwender in der Regel ebenfalls der englischen Benennungen bedienen. Dieser Norm-Entwurf steht nicht in unmittelbarem Zusammenhang mit Rechtsvorschriften und ist nicht als Sicherheitsnorm anzusehen.

Es ist vorgesehen, auch bei der entsprechenden zukünftigen Deutschen Norm auf die deutsche Sprachfassung zu verzichten und diese in der englischsprachigen Fassung zu veröffentlichen.

Für den Fall einer undatierten Verweisung im normativen Text (Verweisung auf ein Dokument ohne Angabe des Ausgabedatums und ohne Hinweis auf eine Abschnittsnummer, eine Tabelle, ein Bild usw.) bezieht sich die Verweisung auf die jeweils aktuellste Ausgabe des in Bezug genommenen Dokuments.

Für den Fall einer datierten Verweisung im normativen Text bezieht sich die Verweisung immer auf die in Bezug genommene Ausgabe des Dokuments.

Der Zusammenhang der zitierten Dokumente mit den entsprechenden deutschen Dokumenten ergibt sich, soweit ein Zusammenhang besteht, grundsätzlich über die Nummer der entsprechenden IEC-Publikation. Beispiel: IEC 60068 ist als EN 60068 als Europäische Norm durch CENELEC übernommen und als DIN EN 60068 ins Deutsche Normenwerk aufgenommen.

Es wird auf die Möglichkeit hingewiesen, dass einige Elemente dieses Dokuments Patentrechte berühren können. IEC ist nicht dafür verantwortlich, einige oder alle diesbezüglichen Patentrechte zu identifizieren.

Nationaler Anhang NA (informativ)

Auszugsweise Übersetzung

Reihenfolge und Inhalt der folgenden Abschnitte sind identisch mit denen in den jeweiligen Abschnitten der Englischen Fassung.

Einleitung

IEC 62832 enthält ein Rahmenwerk für die Erstellung und Pflege der digitalen Darstellungen von Produktionssystemen, einschließlich der Darstellung der Elemente des Produktionssystems und der Beziehungen zwischen diesen Elementen. Das Rahmenwerk ist auch dafür vorgesehen, den Austausch von Informationen zu diesen Elementen zu unterstützen.

Mit diesem Rahmenwerk sollen Interoperabilitätshürden beim Informationsaustausch für die verschiedenen Aktivitäten in Bezug auf Produktionssysteme überwunden werden. Die wesentlichen Vorteile dieser Methode sind, dass alle Informationen in Bezug auf ein Produktionssystem in standardisierter Weise beschrieben werden, und dass sie während des gesamten Lebenszyklus verwendet und modifiziert werden können. Die in IEC 62832 festgelegte Methode wird so allgemein wie möglich gehalten, damit sie in verschiedenen Industriesektoren verwendet werden kann.

Während IEC 62832-1 die allgemeinen Grundsätze des DF-Referenzmodells und dessen wichtigste Modellelemente beschreibt, stellt dieser Teil von IEC 62832 eine technologieunabhängige Definition aller Modellelemente des DF-Referenzmodells bereit.

Der Zweck dieses Dokuments besteht darin, unter Verwendung verschiedener Technologien (zum Beispiel verschiedene Wörterbuchtechnologien und verschiedene Formate von Engineering-Daten) eine gemeinsame Grundlage für die Implementierung des DF-Rahmenwerks bereitzustellen.

Die in diesem Dokument bereitgestellte Datentypspezifikation ist dazu vorgesehen, eine Zuordnung des DF-Rahmenwerks zu verschiedenen Wörterbüchern zu ermöglichen.

In 3.3 werden zwei Vorlagetypen für Darstellungen, nämlich für bestimmte Datenelementtypen (DataElementTypes) und für Modellelemente, beschrieben. Auf Grundlage dieser Vorlagen werden in Abschnitt 4 Definitionen bestimmter DataElementTypes und in Abschnitt 5 Definitionen von Modellelementen unter Verwendung der DataElementTypes angegeben.

Die Anforderungen für diese beiden Definitionsgruppen werden so gering wie möglich gehalten, damit das Rahmenwerk in möglichst vielen Bereichen verwendet werden kann.

Falls die Konzepte des DF-Rahmenwerks angewendet werden, um Modellelemente für verschiedene Engineering-Domänen bereitzustellen, werden domänenspezifische Datenspezifikationen verwendet (zum Beispiel basierend auf IEC 62656-1).

1 Anwendungsbereich

Dieser Teil von IEC 62832 legt die Anforderungen für Modellelemente des Rahmenwerks der Digitalen Fabrik fest. Er definiert die Art der von den Modellelementen bereitgestellten Informationen, jedoch nicht das Format dieser Informationen.

ANMERKUNG Allgemeine Anforderungen für die Hauptmodelelemente des DF-Referenzmodells werden in IEC 62832-1 festgelegt.

3 Begriffe, (Symbole,) Abkürzungen und Konventionen

3.1 Begriffe

Für die Anwendung dieses Dokuments gelten die Begriffe nach IEC 62832-1

ISO und IEC stellen terminologische Datenbanken für die Verwendung in der Normung unter den folgenden Adressen bereit:

- IEC Electropedia: verfügbar unter <http://www.electropedia.org/>
- ISO Online Browsing Platform: verfügbar unter <http://www.iso.org/obp>

3.2 Abkürzungen

Für die Anwendung dieses Dokuments gelten die folgenden Abkürzungen.

CDEL	Sammlung von Datenelementen (en: Collection of Data Elements)
DER	Datenelementbeziehung (en: Data Element Relationship)
DET	Datenelementtyp (en: Data Element Type) (siehe IEC 62832-1)
DF	Digitale Fabrik (attributiv)
DLOP	Geräte-Merkmalleiste (en: Device List of Properties) (siehe IEC 61987-10)
IC	Einheitencode (en: Item Code) (siehe IEC 62832-1)
ID	Identifikator
IRDI	Internationaler Registrierungsdaten-Identifikator (siehe ISO TS 29002-5)
LOP	Merkmalleiste (en: List of Properties) (siehe IEC 61987-10)
OLOP	Betriebs-Merkmalleiste (en: Operational List of Properties) (siehe IEC 61987-10)
PS	Produktionssystem (attributiv)
UML	Vereinheitlichte Modellierungssprache (en: Unified Modeling Language) (siehe ISO/IEC 19505-1)
URI	Einheitlicher Bezeichner für Ressourcen (en: Uniform Resource Identifier) (siehe IETF RFC 3986)
VI	Versions-Identifikator (siehe IEC 62832-1)

ANMERKUNG 1 Die Abkürzung DF wird nur attributiv zu Modellelementen verwendet, die in diesem Dokument festgelegt werden. Sie ist nicht als Ersatz für das in IEC 62832-1:—, 3.1.19, verwendete Konzept „Digitale Fabrik“ zu verstehen.

ANMERKUNG 2 Die Abkürzung PS wird nur attributiv zu Modellelementen verwendet, die in diesem Dokument festgelegt werden. Sie ist nicht als Ersatz für das in IEC 62832-1:—, 3.1.24, verwendete Konzept „Produktionssystem“ zu verstehen.

3.3 Konventionen für die Darstellung der Definition eines Modellelements

3.3.1 Konvention für Namen

Während in IEC 62832-1 allgemeine Namen für die Beschreibung von Konzepten verwendet werden, legen IEC 62832-2 und IEC 62832-3 formale Anforderungen fest. Zur eindeutigen Identifizierung der Namen der Modellelemente werden in den Dokumenten IEC 62832-2 und IEC 62832-3 die englischen Namen in „PascalCase“ (mit Binnenversalien) verwendet.

Tabelle B.1 bietet eine Hilfestellung für die Zuordnung der Namen.

3.3.2 Darstellung bestimmter DataElementTypes

Die in diesem Dokument verwendete Vorlage für die Darstellung der Definition bestimmter DataElementTypes (Datenelementtypen) des DF-Referenzmodells ist in Tabelle 1 angegeben.

ANMERKUNG Die Definitionen in diesem Dokument sind unabhängig von tatsächlichen Definitionen von Modellelementen in einem bestimmten Wörterbuch.

Tabelle 1 – Vorlage für die Darstellung der Definition bestimmter DataElementTypes

ItemCode (Einheitencode)	
VersionIdentifier (Versions-Identifikator)	
PreferredName (bevorzugter Name)	
DFMdataType (DFM-Datentyp)	
Description (Beschreibung)	

Tabelle 1 zeigt die verbindlichen Felder zur Definition eines bestimmten DataElementType (Datenelementtyps). Optional dürfen weitere Felder zur Verfügung gestellt werden (zum Beispiel SynonymousName (Synonym), LetterSymbol (Kurzzeichen), PermissibleValues (zulässige Werte), PhysicalUnit (physische Einheit) und DETcategory (DET-Kategorie)).

Jede grau unterlegte Zelle zeigt den Namen eines entsprechenden Felds (der Wert des Felds wird als nicht farbig unterlegte Zelle dargestellt).

Die Vorlage stellt die Definition eines bestimmten DataElementTypes bereit (Identität und Bedeutung). Sie ist als Felder mit entsprechenden Werten formatiert. In den Feldern stehen Namen von in diesem Dokument definierten Modellelementen, da die Vorlage entsprechend verwendet werden soll, wenn die bestimmten DataElementTypes in ein ConceptDictionary (Konzeptwörterbuch) aufgenommen werden.

Ein bestimmter DataElementType wird definiert, indem Daten in die entsprechenden Felder eingetragen werden (d. h. die Tabelle wird ausgefüllt). Ein „-“ in einer nicht farbig unterlegten Zelle weist darauf hin, dass das Feld für die Definition des bestimmten DataElementType nicht anwendbar ist.

3.3.3 Darstellung der Definition von Modellelementen

Die in diesem Dokument verwendete Vorlage für die Darstellung der Definition von Modellelementen des DF-Referenzmodells ist in Tabelle 2 angegeben.

Tabelle 2 – Vorlage für die Darstellung der Definition von Modellelementen

ItemCode (Einheitencode)	
VersionIdentifier (Versions-Identifikator)	
PreferredName (bevorzugter Name)	
LetterSymbol (Kurzzeichen)	
Description (Beschreibung)	
ParentModelElement (übergeordnetes Modellelement)	

Struktur				
Strukturelement	I/R	Kardinalität	Bedingungen	Bemerkungen

Der obere Teil der Vorlage stellt die Definition eines Modellelements bereit (Identität und Bedeutung). Sie ist als Felder mit entsprechenden Werten formatiert. In den Feldern werden Namen von in diesem Dokument definierten Modellelementen verwendet, da diese Felder entsprechend verwendet werden soll, wenn die Modellelemente ein ConceptDictionary (Konzeptwörterbuch) aufgenommen werden. Die Felder ItemCode und VersionIdentifier können zur eindeutigen Identifikation eines Modellelements im DF-Rahmenwerk verwendet werden.

Die Struktur des Modellelements wird im unteren Teil der Vorlage als Liste der Einzelelemente dargestellt. Jedes Einzelelement in der Vorlage darf als Teil des definierten Modellelements instanziiert werden, abhängig von Kardinalität und Bedingungen. Vom ParentModelElement (übergeordneten Modellelement) übernommene Einzelelemente sind nicht aufgeführt.

Das Feld „Strukturelement“ enthält eine Referenz auf die Definition eines Modellelements. Das Einzelelement wird von der referenzierten Definition des Modellelements abgeleitet.

Ein Einzelelement darf als Instanz eines Modellelements oder als Referenz auf eine Instanz eines Modellelements definiert werden.

Das Feld „I/R“ enthält eine Textfolge („I“, „R“ oder „I/R“), die angibt, ob das Einzelelement als Instanz oder Referenz definiert ist:

- der Wert „I“ gibt an, dass die Struktur eine Instanz des bestimmten Einzelelements enthält (oder mehrere Instanzen, je nach Wert der Kardinalität);
- der Wert „R“ gibt an, dass die Struktur eine Referenz auf eine Instanz des bestimmten Einzelelements enthält (oder mehrere Referenzen, je nach Wert der Kardinalität);
- der Wert „I/R“ gibt an, dass die Struktur entweder eine Instanz des bestimmten Einzelelements oder eine Referenz auf eine Instanz des bestimmten Einzelelements enthält (oder mehrere, je nach Wert der Kardinalität).

ANMERKUNG Im Fall von „I/R“ wird die Verwendung einer Instanz oder Referenz durch die tatsächliche Implementierung entschieden.

Das Feld „Kardinalität“ enthält einen Bereich, mit dem die Anzahl der Einzelelemente festgelegt wird. Der Bereich wird entsprechend der folgenden Konvention ausgedrückt:

[a..b]

Dabei ist:

- a die Mindestanzahl an Einzelelementen;
- b die Höchstanzahl an Einzelelementen.

BEISPIEL 1 Die Anzahl der Einzelelemente kann wie folgt ausgedrückt werden:

[0..1] gibt an, dass das Modellelement aus einem Einzelelement bestehen darf;

[0..n] gibt an, dass das Modellelement aus einem oder mehreren Einzelelementen bestehen darf;

[1..1] gibt an, dass das Modellelement genau aus einem Einzelelement bestehen muss;

[1..n] gibt an, dass das Modellelement aus einem oder mehreren Einzelelementen bestehen muss.

E DIN EN IEC 62832-2:2020-11

Das Feld „Bedingungen“ enthält eine Textfolge, mit der mögliche Einschränkungen für die Einzelelemente in Bezug auf Beziehungen zu anderen Einzelelementen beschrieben werden.

Das Feld „Bemerkungen“ enthält eine Textfolge, die zusätzliche Informationen und Erläuterungen bereitstellt, ohne die Bedeutung der Definition des Einzelelements zu verändern.

In den Feldern „ParentModelElement“ und „Strukturelement“ wird eine Referenz auf ein Modellelement bereitgestellt, indem ein PreferredName und ein ItemCode kombiniert werden (formatiert als <PreferredName>,(,<ItemCode>‘‘)).

BEISPIEL 2 VersionIdentifier (DFF033)

3.3.4 Konvention für die UML-Notation

Die Konventionen für die in diesem Dokument verwendete UML-Notation werden in Anhang E definiert.

CONTENTS

FOREWORD	7
INTRODUCTION	9
1 Scope	10
2 Normative references	10
3 Terms, definitions, (symbols,) abbreviated terms and conventions	10
3.1 Terms and definitions	10
3.2 Abbreviated terms	10
3.3 Conventions for representing the definition of a model element	11
3.3.1 Convention for names	11
3.3.2 Representation of specific DataElementTypes	11
3.3.3 Representation of the definition of model elements	12
3.3.4 Convention for UML notation	13
4 Definitions of specific DataElementTypes	14
4.1 General	14
4.2 ConceptIdentifier	14
4.3 DataValue	14
4.4 DateAndTimeOfRelease	14
4.5 Description	14
4.6 DETcategory	15
4.7 DFMdataType	15
4.8 DictionarySupplierID	15
4.9 ElementIdentifier	16
4.10 ItemCode	16
4.11 LetterSymbol	16
4.12 ParentModelElement	17
4.13 PhysicalUnit	17
4.14 PreferredName	17
4.15 PSassetIdentifier	18
4.16 ReferenceToCDEL	18
4.17 ReferenceToCDELdefinition	18
4.18 ReferenceToDataElement	19
4.19 ReferenceToDET	19
4.20 ReferenceToDFasset	19
4.21 ReferenceToDFassetClass	20
4.22 ReferenceToDFassetClassAssociation	20
4.23 ReferenceToDFassetClassDefinition	20
4.24 ReferenceToGenericAssociation	20
4.25 RoleBasedEquipmentIdentifier	21
4.26 RuleOfRelationship	21
4.27 SearchSpace	21
4.28 SupplierName	22
4.29 SynonymousName	22
4.30 TechnicalDiscipline	22
4.31 TimeCreated	24
4.32 TimeStamp	24

4.33	ValueQuality	24
4.34	VersionIdentifier.....	25
4.35	VersionNumber	25
5	Definitions of model elements.....	26
5.1	General.....	26
5.2	Model elements related to dictionaries	26
5.2.1	ConceptDictionary	26
5.2.2	ConceptDictionaryEntry	27
5.2.3	Model elements related to PermissibleValues	29
5.3	Model elements related to DataElement.....	32
5.3.1	CollectionOfDataElements (CDEL)	32
5.3.2	DataElement.....	33
5.4	Model elements related to libraries	34
5.4.1	Library	34
5.4.2	LibraryEntry	35
5.5	Model elements related to DigitalFactory	42
5.5.1	DigitalFactory	42
5.5.2	DFasset.....	43
5.5.3	DFassetLink	44
5.5.4	DFassetLinkEndPoint	45
5.5.5	DFassetAssignment.....	45
Annex A	(informative) Data type specification	46
Annex B	(informative) Naming correspondence between IEC 62832-1 and IEC 62832-2	47
Annex C	(informative) Mapping of DF model elements onto different data standards	49
C.1	Mapping onto IEC 61360 and ISO 13584-42	49
C.1.1	General	49
C.1.2	Detailed mapping for Dictionary.....	49
C.1.3	Detailed mapping for DFassetClassDefinition	50
C.1.4	Detailed mapping for CDELdefinition	50
C.1.5	Detailed mapping for DET.....	50
C.2	Mapping onto ISO 22745	51
C.2.1	General	51
C.2.2	Detailed mapping for Dictionary.....	51
C.2.3	Detailed mapping for DFassetClassDefinition	52
C.2.4	Detailed mapping for CDELdefinition	52
C.2.5	Detailed mapping for DET.....	53
C.2.6	Detailed mapping for Library.....	53
C.2.7	Detailed mapping for DFassetClass	53
C.2.8	Detailed mapping for DataElement	54
Annex D	(informative) UML Model.....	55
D.1	ConceptDictionary	55
D.2	Model elements related to DataElements	56
D.3	Library	57
D.4	Digital Factory	59
Annex E	(informative) UML notation.....	62
E.1	General.....	62
E.2	Class diagram.....	62
E.3	Object diagram	62

Bibliography.....	67
Figure A.1 – Data types overview	46
Figure D.1 – Concept dictionary and related class definitions and type	55
Figure D.2 – Permissible values.....	56
Figure D.3 – Model elements related to DataElements	56
Figure D.4 – Library	57
Figure D.5 – DFassetClass	57
Figure D.6 – DFassetClass showing origin of definitions	58
Figure D.7 – Composite DFassetClass.....	58
Figure D.8 – DigitalFactory structure.....	59
Figure D.9 – Digital Factory example	59
Figure D.10 – Relationship between DFassets	60
Figure D.11 – Example: DigitalFactory with composite DFasset	60
Figure D.12 – Example: DFassetLink and DER	61
Figure D.13 – Example: DFassetAssignment	61
Figure E.1 – Note	62
Figure E.2 – Class	62
Figure E.3 – Association	63
Figure E.4 – Composition.....	63
Figure E.5 – Aggregation	63
Figure E.6 – Containment	63
Figure E.7 – Dependency	63
Figure E.8 – Abstract class, generalization and interface	64
Figure E.9 – Multiplicity	64
Figure E.10 – Association class	65
Figure E.11 – Class	65
Figure E.12 – Link	65
Figure E.13 – Link instantiated from composition	65
Figure E.14 – Link instantiated from aggregation	66
Table 1 – Template for representing the definition of specific DataElementTypes	11
Table 2 – Template for representing the definition of model elements	12
Table 3 – Definition of ConceptIdentifier	14
Table 4 – Definition of DataValue.....	14
Table 5 – Definition of DateAndTimeOfRelease	14
Table 6 – Definition of Description	15
Table 7 – Definition of DETcategory.....	15
Table 8 – Definition of DFMdataType	15
Table 9 – Definition of DictionarySupplierID	16
Table 10 – Definition of ElementIdentifier.....	16
Table 11 – Definition of ItemCode.....	16
Table 12 – Definition of LetterSymbol	17

Table 13 – Definition of ParentModelElement.....	17
Table 14 – Definition of PhysicalUnit.....	17
Table 15 – Definition of PreferredName	18
Table 16 – Definition of PSassetIdentifier	18
Table 17 – Definition of ReferenceToCDEL.....	18
Table 18 – Definition of ReferenceToCDELdefinition.....	19
Table 19 – Definition of ReferenceToDataElement.....	19
Table 20 – Definition of ReferenceToDET	19
Table 21 – Definition of ReferenceToDFasset.....	19
Table 22 – Definition of ReferenceToDFassetClass	20
Table 23 – Definition of ReferenceToDFassetClassAssociation	20
Table 24 – Definition of ReferenceToDFassetClassDefinition.....	20
Table 25 – Definition of ReferenceToGenericAssociation	21
Table 26 – Definition of RoleBasedEquipmentIdentifier	21
Table 27 – Definition of RuleOfRelationship.....	21
Table 28 – Definition of SearchSpace	22
Table 29 – Definition of SupplierName	22
Table 30 – Definition of SynonymousName	22
Table 31 – Definition of TechnicalDiscipline	23
Table 32 – Definition of TimeCreated	24
Table 33 – Definition of TimeStamp	24
Table 34 – Definition of ValueQuality	24
Table 35 – Definition of VersionIdentifier	25
Table 36 – Definition of VersionNumber	25
Table 37 – Definition of ConceptDictionary	26
Table 38 – Definition of DFdictionary	27
Table 39 – Definition of ConceptDictionaryEntry	27
Table 40 – Definition of DFassetClassDefinition.....	28
Table 41 – Definition of CDELdefinition.....	28
Table 42 – Definition of DataElementType	29
Table 43 – Definition of RangeOfPermissibleValues	29
Table 44 – Definition of ListOfPermissibleValues	30
Table 45 – Definition of MaximumPermissibleValue	30
Table 46 – Definition of MinimumPermissibleValue	31
Table 47 – Definition of PermissibleValue	31
Table 48 – Definition of CollectionOfDataElements	32
Table 49 – Definition of DataElement.....	33
Table 50 – Definition of Library	34
Table 51 – Definition of SupplierLibrary	34
Table 52 – Definition of DFlibrary.....	35
Table 53 – Definition of LibraryEntry	35
Table 54 – Definition of LibraryEntryHeader.....	36
Table 55 – Definition of DFassetClass	36

Table 56 – Definition of DFassetClassHeader	37
Table 57 – Definition of DFassetClassBody	37
Table 58 – Definition of DFassetClassAssociation	38
Table 59 – Definition of DFassetClassAssociationEndPoint	38
Table 60 – Definition of GenericAssociation	39
Table 61 – Definition of GenericAssociationEndPoint	39
Table 62 – Definition of DataElementRelationship	40
Table 63 – Definition of DERendPoint	40
Table 64 – Definition of ViewElement	41
Table 65 – Definition of DigitalFactory	42
Table 66 – Definition of DFasset	43
Table 67 – Definition of DFassetHeader	43
Table 68 – Definition of DFassetBody	44
Table 69 – Definition of DFassetLink	44
Table 70 – Definition of DFassetLinkEndPoint	45
Table 71 – Definition of DFassetAssignment	45
Table A.1 – Data types used within the DF framework	46
Table B.1 – Cross reference table	47
Table C.1 — Mapping of DF model elements onto IEC 61360 and ISO 13584-42	49
Table C.2 — Detailed mapping of Dictionary	49
Table C.3 — Detailed mapping of DFassetClassDefinition	50
Table C.4 — Detailed mapping of CDELdefinition	50
Table C.5 — Detailed mapping of DET	50
Table C.6 — Mapping of DF model elements onto ISO 22745	51
Table C.7 — Detailed mapping of Dictionary	52
Table C.8 — Detailed mapping of DFassetClassDefinition	52
Table C.9 — Detailed mapping of CDELdefinition	52
Table C.10 — Detailed mapping of DET	53
Table C.11 — Detailed mapping of Library	53
Table C.12 — Detailed mapping of DFassetClass	53
Table C.13 — Detailed mapping of DFassetClassHeader	54
Table C.14 — Detailed mapping of DFassetClassBody	54
Table C.15 — Detailed mapping of DataElement	54

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**INDUSTRIAL-PROCESS MEASUREMENT, CONTROL AND AUTOMATION –
Digital Factory framework**

Part 2: Model elements

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62832-2 has been prepared by IEC technical committee 65:
Industrial-process measurement, control and automation.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
XX/XX/FDIS	XX/XX/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

49 A list of all parts of the IEC 62832 series, published under the general title, *Industrial-process*
50 *measurement, control and automation – Digital Factory framework*, can be found on the IEC
51 website.

52 The committee has decided that the contents of this publication will remain unchanged until the
53 stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to
54 the specific publication. At this date, the publication will be

- 55 • reconfirmed,
- 56 • withdrawn,
- 57 • replaced by a revised edition, or
- 58 • amended.

59

60 The National Committees are requested to note that for this publication the stability date
61 is 2024

62 THIS TEXT IS INCLUDED FOR THE INFORMATION OF THE NATIONAL COMMITTEES AND WILL BE DELETED
63 AT THE PUBLICATION STAGE.

64

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

65

66

67

INTRODUCTION

68 IEC 62832 provides a framework used for establishing and maintaining the digital
69 representations of production systems, including the representation of the elements of the
70 production systems and of the relationships between these elements. The framework is
71 intended also to support the exchange of information about these elements.

72 The framework aims at reducing the interoperability barriers for exchange of information for the
73 various activities related to production systems. The main advantages of this method are that
74 all information related to a production system is described in a standardized manner, and it can
75 be used and modified through its entire life cycle. The method defined in IEC 62832 is kept as
76 generic as possible in order to enable its use in several industrial sectors.

77 While IEC 62832-1 describes the general principles of the DF reference model together with its
78 most important model elements, this part of IEC 62832 provides a technology-independent
79 definition of all model elements of the DF reference model.

80 The intention of this document is to provide a common base for implementation of the DF
81 framework using different technologies (for example different dictionary technologies and
82 different engineering data formats).

83 The data type specification provided with this document is intended to allow mapping of the DF
84 framework to different dictionaries.

85 Two types of templates for representation, namely for specific DataElementTypes and for model
86 elements, are described in 3.3. Based on these templates, definitions of specific
87 DataElementTypes are given in Clause 4, and definitions of model elements, using the
88 DataElementTypes are given in Clause 5.

89 The requirements for these two sets of definitions are kept to as minimal as possible, in order
90 to allow broad use of the framework.

91 If the concepts of DF framework are applied to provide model elements for different engineering
92 domains, domain-specific data specifications will be used (for example based on IEC 62656-1).

93

INDUSTRIAL-PROCESS MEASUREMENT, CONTROL AND AUTOMATION –

Digital Factory framework Part 2: Model elements

1 Scope

This part of IEC 62832 specifies detailed requirements for model elements of the Digital Factory framework. It defines the nature of the information provided by the model elements, but not the format of this information.

NOTE General requirements for the main model elements of the DF reference model are specified in IEC 62832-1.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62832-1:—¹, *Industrial-process measurement, control and automation – Digital factory framework – Part 1: General principles*

ISO TS 29002-5:2009, *Industrial automation systems and integration – Exchange of characteristic data – Part 5: Identification scheme*

ISO/IEC 6523 (all parts), *Information technology – Structure for the identification of organizations and organization parts*

IETF RFC 3986, *Uniform Resource Identifier (URI): Generic Syntax*, available at <<http://www.ietf.org>>

3 Terms, definitions, (symbols,) abbreviated terms and conventions

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 62832-1 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

3.2 Abbreviated terms

For the purposes of this document, the following abbreviated terms apply.

CDEL	Collection of Data Elements
DER	Data Element Relationship
DET	Data Element Type (see IEC 62832-1)

¹ Under preparation

130	DF	Digital Factory (as qualifier)
131	DLOP	Device List of Properties (see IEC 61987-10)
132	IC	Item Code (see IEC 62832-1)
133	ID	Identifier
134	IRDI	International Registration Data Identifier (see ISO TS 29002-5)
135	LOP	List of Properties (see IEC 61987-10)
136	OLOP	Operational List of Properties (see IEC 61987-10)
137	PS	Production System (as qualifier)
138	UML	Unified Modeling Language (see ISO/IEC 19505-1)
139	URI	Uniform Resource Identifier (see IETF RFC 3986)
140	VI	Version Identifier (see IEC 62832-1)

141 NOTE 1 The abbreviated term DF is only used as a qualifier for model elements specified in this document. It is not
142 to be understood as a replacement for the Digital Factory concept defined in IEC 62832-1:—, 3.1.19.

143 NOTE 2 The abbreviated term PS is only used as a qualifier for model elements specified in this document. It is not
144 to be understood as a replacement for the production system concept defined in IEC 62832-1:—, 3.1.24.

145

146 3.3 Conventions for representing the definition of a model element

147 3.3.1 Convention for names

148 While IEC 62832-1 is using general names for describing the concepts, IEC 62832-2 and
149 IEC 62832-3 define more formal requirements. In order to clearly identify the names of the
150 model elements the documents IEC 62832-2 and IEC 62832-3 use 'PascalCase' for names.

151 A help for matching the names is provided in Table B.1.

152 3.3.2 Representation of specific DataElementTypes

153 The template used in this document for representing the definition of specific
154 DataElementTypes of the DF reference model is specified in Table 1.

155 NOTE Definitions in this document are independent of actual definitions of model elements in any specific
156 dictionary.

157 **Table 1 – Template for representing the definition of specific DataElementTypes**

ItemCode	
VersionIdentifier	
PreferredName	
DFMdataType	
Description	

158

159 Table 1 shows the mandatory fields for defining a specific DataElementType. Optionally,
160 additional fields may be provided (for example SynonymousName, LetterSymbol,
161 PermissibleValues, PhysicalUnit and DETcategory).

162 Each shaded cell indicates the name of a corresponding field (the value of the field is shown
163 as unshaded cell).

164 The template provides the definition of a specific DataElementType (identity and meaning). It
165 is formatted as fields with respective values. The fields have names of model elements defined

in this document, because the template is intended to be used accordingly when the specific DataElementTypes are registered in a ConceptDictionary.

A specific DataElementType is defined by providing data in the relevant fields (i.e. the table is filled). A “-” in an unshaded cell indicates that the field is not applicable to the definition of the specific DataElementType.

3.3.3 Representation of the definition of model elements

The template used in this document for representing the definition of model elements of the DF reference model is specified in Table 2.

Table 2 – Template for representing the definition of model elements

ItemCode				
VersionIdentifier				
PreferredName				
LetterSymbol				
Description				
ParentModelElement				
Structure				
Structure element	I/R	Cardinality	Conditions	Remarks

The upper part of the template provides the definition of a model element (identity and meaning). It is formatted as fields with respective values. The fields use names of model elements defined in this document, because these fields are intended to be used accordingly when the model elements will be registered in a ConceptDictionary. The ItemCode and VersionIdentifier fields can be used to uniquely identify a model element within the DF framework.

The structure of the model element is represented in the lower part of the template as a list of constituent elements. Each constituent element in the template may be instantiated as a constituent of the defined model element, depending on cardinality and conditions. Constituent elements inherited from the ParentModelElement are not listed.

The field “Structure element” contains a reference to a model element definition. The constituent element is derived from the referenced model element definition.

A constituent element may be defined as an instance of a model element or as a reference to an instance of a model element.

The field “I/R” contains a text string (“I”, “R” or “I/R”), which indicates whether the constituent element is defined as an instance or as a reference:

- the value “I” indicates that the structure contains an instance of the particular constituent element (or multiple instances depending on the value of the cardinality);
- the value “R” indicates that the structure contains a reference to an instance of the particular constituent element (or multiple references depending on the value of the cardinality);
- the value “I/R” indicates that the structure contains either an instance of or a reference to an instance of the particular constituent element (or multiple ones depending on the value of the cardinality).

199 NOTE In the case of “I/R” the use of an instance or a reference is decided by the actual implementation.

200 The field “Cardinality” contains a range which defines the number of constituent elements, the
201 range is expressed using the following convention:

202 [a..b]

203 where:

204 a is the minimum number of constituent elements;

205 b is the maximum number of constituent elements.

206 EXAMPLE 1

207 The number of constituent elements can be expressed as follows:

208 [0..1] indicates the model element may have one constituent element;

209 [0..n] indicates the model element may have one or more constituent elements;

210 [1..1] indicates the model element shall have exactly one constituent element;

211 [1..n] indicates the model element shall have one or more constituent elements.

212

213 The field “Conditions” contains a text string which describes potential restrictions applicable to
214 the number of constituent elements in terms of relationships with other constituent elements.

215 The field “Remarks” contains a text string which provides additional information and
216 explanation, without changing the meaning of the definition of the constituent element.

217 Within the fields “ParentModelElement” and “Structure element”, a reference to a model element
218 is provided by combining a PreferredName and an ItemCode (formatted as <PreferredName>
219 ‘(<ItemCode>’)).

220 EXAMPLE 2 VersionIdentifier (DFF033)

221

222 3.3.4 Convention for UML notation

223 The conventions for UML notation used in this document are defined in Annex E.

4 Definitions of specific DataElementTypes

4.1 General

This Clause 4 defines specific DataElementTypes using the template provided in 3.3.1.

4.2 ConceptIdentifier

Table 3 is the definition of ConceptIdentifier.

Table 3 – Definition of ConceptIdentifier

ItemCode	DFF001
VersionIdentifier	001
PreferredName	ConceptIdentifier
DFMdataType	IRDI_STRING
Description	Globally unique identifier according to ISO TS 29002-5

NOTE The ConceptIdentifier is a general concept detailed in IEC 62832-1:—, 5.1.

4.3 DataValue

Table 4 is the definition of DataValue.

Table 4 – Definition of DataValue

ItemCode	DFF002
VersionIdentifier	001
PreferredName	DataValue
DFMdataType	<defined by the corresponding DFMdataType>
Description	Value defined by the DFMdataType (DFF006) and optionally the PermissibleValues (DFF041 and DFF042) of the corresponding DET

The data specification that is base for the DFMdataType shall define whether an infinite value representation is supported.

4.4 DateAndTimeOfRelease

Table 5 is the definition of DateAndTimeOfRelease.

Table 5 – Definition of DateAndTimeOfRelease

ItemCode	DFF003
VersionIdentifier	001
PreferredName	DateAndTimeOfRelease
DFMdataType	DATE_TIME_TYPE
Description	Date and time of release of the corresponding model element

4.5 Description

Table 6 is the definition of Description.

243 **Table 6 – Definition of Description**

ItemCode	DFF004
VersionIdentifier	001
PreferredName	Description
DFMdataType	TRANSLATABLE_STRING_TYPE
Description	Normative text explaining the corresponding item, optionally in a language designated by a language code.

244

245 **4.6 DETcategory**

246 Table 7 is the definition of DETcategory.

247 **Table 7 – Definition of DETcategory**

ItemCode	DFF005						
VersionIdentifier	001						
PreferredName	DETcategory						
DFMdataType	STRING_TYPE						
Description	Information that describes the categorization of a DET in regard to behaviour of the value in the derived DataElement.						
ListOfPermissibleValue	<table border="1"> <thead> <tr> <th>Value</th><th>Meaning</th></tr> </thead> <tbody> <tr> <td>"constant"</td><td>the value of the DataElement derived from the corresponding DET cannot change</td></tr> <tr> <td>"variable"</td><td>the value of the DataElement derived from the corresponding DET can change</td></tr> </tbody> </table>	Value	Meaning	"constant"	the value of the DataElement derived from the corresponding DET cannot change	"variable"	the value of the DataElement derived from the corresponding DET can change
Value	Meaning						
"constant"	the value of the DataElement derived from the corresponding DET cannot change						
"variable"	the value of the DataElement derived from the corresponding DET can change						

248

249 **4.7 DFMdataType**

250 Table 8 is the definition of DFMdataType.

251 **Table 8 – Definition of DFMdataType**

ItemCode	DFF006
VersionIdentifier	001
PreferredName	DFMdataType
DFMdataType	STRING_TYPE
Description	String representation of the data type based on the corresponding type system of the ConceptDictionary (defined in a data specification)

252

253 A DataElement derived from this DET in this document provides a reference to a particular data
 254 type of the type system of DF framework (see Annex A).

255 **4.8 DictionarySupplierID**

256 Table 9 is the definition of DictionarySupplierID.

Table 9 – Definition of DictionarySupplierID

ItemCode	DFF007
VersionIdentifier	001
PreferredName	DictionarySupplierID
DFMdataType	STRING_TYPE
Description	Identifier (according to ISO/IEC 6523) of the organization that is the registration authority of the ConceptDictionary

4.9 ElementIdentifier

Table 10 is the definition of ElementIdentifier.

Table 10 – Definition of ElementIdentifier

ItemCode	DFF008
VersionIdentifier	001
PreferredName	ElementIdentifier
LetterSymbol	URI
DFMdataType	URI_TYPE
Description	Globally unique identifier according to IETF RFC 3986. URI according to IETF RFC 3986 may also provide relative references.

4.10 ItemCode

Table 11 is the definition of ItemCode.

Table 11 – Definition of ItemCode

ItemCode	DFF009
VersionIdentifier	001
PreferredName	ItemCode
LetterSymbol	IC
DFMdataType	STRING_TYPE
Description	part of the ConceptIdentifier, unique within a limited context (code space) (see IEC 62832-1:—, 5.1)

NOTE 1 The values for ItemCode defined in this document as identifiers of the model elements are intended for use only inside IEC 62832 (all parts).

NOTE 2 If model elements are registered in different concept dictionaries, then different values for ItemCode will be assigned according to the rules of the corresponding ConceptDictionary.

4.11 LetterSymbol

Table 12 is the definition of LetterSymbol.