

DIN EN ISO 12813



ICS 03.220.20; 35.240.60

Einsprüche bis 2022-06-29
Vorgesehen als Ersatz für
DIN EN ISO 12813:2020-03

Entwurf

**Elektronische Gebührenerhebung –
Kommunikation zur Übereinstimmungsprüfung für autonome Systeme
(ISO/DIS 12813:2022);
Englische Fassung prEN ISO 12813:2022**

Electronic fee collection –

Compliance check communication for autonomous systems (ISO/DIS 12813:2022);
English version prEN ISO 12813:2022

Perception de télépéage –

Communication de contrôle de conformité pour systèmes autonomes (ISO/DIS 12813:2022);
Version anglaise prEN ISO 12813:2022

Anwendungswarnvermerk

Dieser Norm-Entwurf mit Erscheinungsdatum 2022-04-29 wird der Öffentlichkeit zur Prüfung und Stellungnahme vorgelegt.

Weil die beabsichtigte Norm von der vorliegenden Fassung abweichen kann, ist die Anwendung dieses Entwurfs besonders zu vereinbaren.

Stellungnahmen werden erbeten

- vorzugsweise online im Norm-Entwurfs-Portal von DIN unter www.din.de/go/entwuerfe bzw. für Norm-Entwürfe der DKE auch im Norm-Entwurfs-Portal der DKE unter www.entwuerfe.normenbibliothek.de, sofern dort wiedergegeben;
- oder als Datei per E-Mail an naaautomobil@din.de möglichst in Form einer Tabelle. Die Vorlage dieser Tabelle kann im Internet unter www.din.de/go/stellungnahmen-norm-entwuerfe oder für Stellungnahmen zu Norm-Entwürfen der DKE unter www.dke.de/stellungnahme abgerufen werden;
- oder in Papierform an den DIN-Normenausschuss Automobiltechnik (NAAutomobil), 10004 Berlin, Postfach 8 04 62 oder Behrenstr. 35, 10117 Berlin.

Die Empfänger dieses Norm-Entwurfs werden gebeten, mit ihren Kommentaren jegliche relevanten Patentrechte, die sie kennen, mitzuteilen und unterstützende Dokumentationen zur Verfügung zu stellen.

Gesamtumfang 66 Seiten

DIN-Normenausschuss Automobiltechnik (NAAutomobil)

Nationales Vorwort

Dieses Dokument (prEN ISO 12813:2022) wurde vom Technischen Komitee ISO/TC 204 „Intelligent Transport Systems“ in Zusammenarbeit mit dem Technischen Komitee CEN/TC 278 „Intelligente Verkehrssysteme“, dessen Sekretariat von NEN (Niederlande) gehalten wird, erarbeitet.

Das zuständige deutsche Normungsgremium ist der Gemeinschaftsarbeitsausschuss NA 052-00-71 GA „Gemeinschaftsarbeitsausschuss NAAutomobil/DKE: Intelligente Verkehrssysteme“ des DIN-Normenausschusses Automobiltechnik (NAAutomobil).

Dieses Dokument ist derzeit zur parallelen Abstimmung vorgelegt.

Dieses Dokument enthält unter Berücksichtigung des DIN-Präsidialbeschlusses 1/2004 nur die englische Originalfassung von prEN ISO 12813:2022.

Fahrzeuginterne Einrichtungen (OBE), die auf satellitengestützter Positionierung zur Datensammlung für Gebührenerhebung zur Straßennutzung dienen, werden autonom gegenüber der Straßenrandinfrastruktur betrieben. Die OBE zeichnet dabei die gefahrene Entfernung in einem mautpflichtigen Gebiet auf.

Dieses Dokument definiert Anforderungen an die DSRC (en: dedicated short-range communication) zwischen OBE und einem Fragesteller zur Einhaltungsprüfung der Straßennutzung in einem Mautregime. Es basiert auf einer Gebührenerhebungsarchitektur nach ISO 17573-1.

Aktuelle Informationen zu diesem Dokument können über die Internetseiten von DIN (www.din.de) durch eine Suche nach der Dokumentennummer aufgerufen werden.

Änderungen

Gegenüber DIN EN ISO 12813:2020-03 wurden folgende Änderungen vorgenommen:

- a) Überarbeitung einiger Begriffe basierend auf ISO/TS 17573-2 als primäre Quelle;
- b) einige Datenfestlegungen wurden, basierend auf ISO/TS 17573-3 als primäre Quelle, angepasst.

Nationaler Anhang NA (informativ)

Begriffe

Die Benummerung der folgenden Begriffe und Abkürzungen ist identisch mit der Benummerung in der englischen Fassung.

Für die Anwendung dieses Dokuments gelten die folgenden Begriffe.

ISO und IEC stellen terminologische Datenbanken für die Verwendung in der Normung unter den folgenden Adressen bereit:

- IEC Electropedia: verfügbar unter <http://www.electropedia.org/>
- ISO Online Browsing Platform: verfügbar unter <http://www.iso.org/obp>

3.1

Zugriffsbeglaubigung

AC_CR, en: access credentials

vertrauliche Bescheinigung oder sicheres Modul, welches die geforderte Identität eines Objektes oder einer Anwendung schafft

[QUELLE: CEN ISO/TS 17573-2:2020, 3.4]

3.2

Attribut

en attribute

adressierbares Datenpaket, welches aus einem einzelnen Datenelement oder strukturierten Sequenzen von Datenelementen besteht

[QUELLE: CEN ISO/TS 17573-2:2020, 3.13]

3.3

Authentifizierung

en authentication

Sicherheitsmechanismus, welcher die Überprüfung der bereitgestellten Identität ermöglicht

[QUELLE: EN 301 175 V1.1.1:1998, 3]

3.4

Authentifikator

en authenticator

Daten, wenn möglich verschlüsselt, die zur Authentifizierung verwendet werden

[QUELLE: CEN ISO/TS 17573-2:2020, 3.16]

3.5

Datenintegrität

en data integrity

Eigenschaft, dass Daten nicht in unautorisierter Art und Weise verändert oder vernichtet wurden

[QUELLE: ISO 7498-2:1989, 3.3.21]

- 3.6**
festе strаßenseitige Einrichtung
en fixed roadside equipment
an einer festen Position installierte strаßenseitige Einrichtung
- [QUELLE: CEN ISO/TS 17573-2:2020, 3.81]
- 3.7**
mobile strаßenseitige Einrichtung
en mobile roadside equipment
Einrichtung, die in einer mobilen Einheit oder in einem mobilen Endgerät montiert ist, die entlang der Strаße verwendet wird
- [QUELLE: CEN ISO/TS 17573-2:2020, 3.119]
- 3.8**
fahrzeuginterne Einrichtung
OBE, en: on-board equipment
alle erforderlichen Einrichtungen im Fahrzeug, die zur Durchführung notwendiger EFC-Funktionen (en: electronic fee collection, EFC) und Kommunikationsdienste benötigt werden
- [QUELLE: CEN ISO/TS 17573-2:2020, 3.126]
- 3.9**
Straßenrand-Einrichtung
RSE, en: roadside equipment
feste oder mobile Einrichtung zur mobilen Gebührenerhebung (EFC) entlang oder an einer Strаße
- [QUELLE: CEN ISO/TS 17573-2:2020, 3.161]
- 3.10**
Dienstprimitive
en service primitive
elementarer Kommunikationsdienst, der durch die Anwendungsschicht den Anwendungsprozessen zur Verfügung gestellt wird
- [QUELLE: CEN ISO/TS 17573-2:2020, 3.173]
- 3.11**
Mautkontext
en toll context
logischer Blick auf ein Mautschema, das anhand von Attributen und Funktionen eines Basiselements definiert ist und aus einem einzelnen Basismautprinzip, der räumlichen Verteilung eines Abrechnungsobjektes und dem einzelnen Verhalten des betroffenen Front Ends besteht
- [QUELLE: CEN ISO/TS 17573-2:2020, 3.196]
- 3.12**
Mautregime
en toll regime
Regelwerk, einschließlich Regeln zur Kontrolle, für die Erhebung von Maut in einem Mautgebiet
- [QUELLE: CEN ISO/TS 17573-2:2020, 3.203]

3.13

Mautdienstanbieter

TSP, en: toll service provider

Organisation, die Mautdienste in einem oder mehreren Mautgebieten anbietet

[QUELLE: CEN ISO/TS 17573-2:2020, 3.206]

3.14

Transaktion

en transaction

Gesamtheit eines Informationsaustausches zwischen zwei physisch getrennten Kommunikationseinheiten

[QUELLE: CEN ISO/TS 17573-2:2020, 3.211]

— Leerseite —

Contents	Page
Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	2
3 Terms and definitions	3
4 Abbreviated terms	5
5 Application interface architecture.....	6
5.1 General.....	6
5.2 Services provided.....	6
5.3 Attributes	6
5.4 Toll context.....	7
5.5 Use of lower layers.....	7
5.5.1 Supported DSRC communication stacks	7
5.5.2 Use of the CEN-DSRC stack	8
6 Functions.....	8
6.1 Functions in detail	8
6.1.1 General.....	8
6.1.2 Initialise communication	8
6.1.3 Data retrieval.....	8
6.1.4 Authenticated data retrieval.....	9
6.1.5 Driver notification	9
6.1.6 Terminate communication	9
6.1.7 Test communication.....	9
6.2 Security	9
6.2.1 General.....	9
6.2.2 Authentication/non-repudiation	10
6.2.3 Access credentials.....	10
7 Attributes	10
7.1 General.....	10
7.2 Data regarding identification	12
7.3 Data regarding status	12
7.4 Data regarding vehicle	20
8 Transaction model.....	22
8.1 General.....	22
8.2 Initialisation phase.....	22
8.2.1 Initialisation request	22
8.2.2 CCC application-specific contents of BST.....	23
8.2.3 CCC application-specific contents of VST.....	23
8.3 Transaction phase.....	23
Annex A (normative) CCC data type specifications	24
Annex B (normative) PICS proforma.....	25

Annex C (informative) ETSI ES 200 674-1 communication stack usage for CCC applications 34

Annex D (informative) Using the IR DSRC communication stack (CALM IR) for CCC applications 37

Annex E (informative) Using the ARIB DSRC communication stack for CCC applications.....38

Annex F (informative) Using the WAVE communication stack for CCC applications 40

Annex G (informative) Example CCC transaction 43

Annex H (informative) Security considerations 46

Annex I (informative) Use of this document for the EETS.....51

Bibliography 53

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 204, *Intelligent transport systems*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 278 *Intelligent transport systems*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This third edition cancels and replaces the second edition (ISO 12813:2019)), which has been subject to a minor revision.

The main changes compared to the previous edition are as follows:

- minor updating of terms, including the reference to ISO/TS 17573-2 as the primary source;
- minor updating of data definitions, including the reference to ISO/TS 17573-3 as the primary source.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

On-board equipment (OBE) that uses satellite-based positioning technology to collect data required for charging for the use of roads operates in an autonomous way (i.e. without relying on dedicated roadside infrastructure). The OBE will record the amount of road usage in all toll charging systems it passes through.

This document defines requirements for dedicated short-range communication (DSRC) between OBE and an interrogator for the purpose of checking compliance of road use with a local toll regime. It assumes an electronic fee collection (EFC) services architecture according to ISO 17573-1. See Figure 1.




Figure 1 — Compliance check communication in EFC architecture according to ISO 17573-1

Toll chargers have the need to check whether the road is used in compliance with the rules in the local toll regime. One way of checking compliance is to observe a passing vehicle and to interrogate the OBE. This interrogation happens under control of an entity responsible for toll charging (see Figure 1), accomplished via short-range communication between an interrogator at roadside or in another vehicle (operated by a competent enforcement agency) and the OBE. In an interoperable environment, it is essential that this interrogation communication be standardized such that every operator of compliance checking equipment can check all passing OBE. For that purpose, this document defines attributes required on all OBE for reading by an interrogator.

This document has been prepared to fulfil the following statements:

- Collected evidence can be used as court proof. Data is indisputable and secured such that the operator of the compliance checking interrogator can prove the integrity and authenticity of the data in case of dispute.
- The data required for compliance checking is read only, since the operator of the interrogator does not interfere with the working of the OBE.
- All attributes, standardized at the time of personalisation of the OBE, are present in the OBE such that an operator of an interrogator essentially can read the same data from all OBE independent of type and make. In case an attribute does not make sense in a certain OBE implementation, a value

assignment for “not applicable” or “not defined” is provided in each case. An OBE compliant to the first edition will not answer with such a response for new attributes introduced in the current edition of this document.

- d) The attributes, derived from the individual toll regime, are of general importance for all toll system types (motorway tolling, area tolling, tolls for ferries, bridges, tunnels, cordon pricing, etc.).
- e) The attributes apply to all OBE architectures, and especially to both thin (edge-light) and fat (edge heavy) client architectures. The interrogator is intended to receive essentially the same information irrespective of the type of OBE.

It is assumed that the prime objective of the operator of the compliance checking interrogation is to check whether the user has fulfilled his obligations, especially:

- whether the OBE is mounted in the correct vehicle;
- whether the classification data transmitted by the OBE are correct; and
- whether the OBE is in operational condition, both in a technical and a contractual sense.

Regarding the last point of the above list, on the operational status of OBE, the following model is assumed.

As long as the OBE signals to the user correct operational status (“green”), the service provider takes full responsibility for the correct operation of the OBE and for the payment by the user. Hence, as long as the OBE signals “green” and the user fulfils its other obligations (e.g. entering correct classification data and not tampering with the OBE), the user can expect the OBE to serve as a valid payment means. As soon as the OBE signals an invalid operational status (“red”) — either set by the central system of the service provider (e.g. because the user account is negative), by internal mechanisms of the OBE itself (e.g. because of a detected defect or an outdated data set) or a user manipulation with such result — the user knows that the OBE is no longer a valid payment means. The user then has to use alternative means of toll declaration or payment until the problem is remedied and the OBE is “green” again¹.

Ultimately, the policy of when to signal “green” or “red” is defined by the service provider in accordance with the requirements defined by the toll charger(s).

In the case where the OBE status turns “red”, the user has to take action, declare road usage subject to fees or pay by some alternative means as soon as practicable. Until he does, the user is in a potentially non-compliant situation. In order to allow a judgment to be made as to whether or not a user has taken the appropriate action within an acceptable period of time, information is provided by this document not only on the “green/red” operational status but also on the length of time that the OBE has been in its current status.

Different toll contexts can overlap geographically. A user could be liable in several toll contexts at once, e.g. for a nationwide distance-dependent road tax and a local city access pricing scheme — a fact of which the user might not in all cases be aware. This document builds on the concept that regarding compliance, there is no notion of toll context as far as possible (see especially 5.4). It is within the responsibility of the service provider to resolve issues with overlapping toll contexts and to distil all information into a binary “red/green” message to the user.

A secondary objective of the operator of the compliance checking interrogator might be to collect data on the performance of the OBE, e.g. in order to check for the correct technical functioning. Since

¹ In this case, “red” and “green” are used in the abstract, symbolic sense, and do not imply any physical implementation. The design of the user interface of the OBE is implementation-dependent, and several methods for signalling “red” or “green” are conceivable.

different OBE can work according to quite different principles, the possibilities for doing this in a standardized way are quite limited. This document contains some provisions for this task (e.g. the attributes CommunicationStatus, GnssStatus, DistanceRecordingStatus), but otherwise assumes that toll chargers monitor correct recording by comparing observed traffic (e.g. with cameras) with usage data received from service providers.

This document has been prepared with the intention to be “minimalist” in the sense that it covers what is required by operational systems and systems planned in the foreseeable future.

A test suite for checking an OBE or RSE implementation for compliance with this document is defined in the corresponding edition of ISO 13143-1 and ISO 13143-2.

Electronic fee collection — Compliance check communication for autonomous systems

1 Scope

This document defines requirements for short-range communication for the purposes of compliance checking in autonomous electronic fee collecting systems. Compliance checking communication (CCC) takes place between a road vehicle's on-board equipment (OBE) and an interrogator (roadside mounted equipment, mobile device or hand-held unit), and serves to establish whether the data that are delivered by the OBE correctly reflect the road usage of the corresponding vehicle according to the rules of the pertinent toll regime.

The operator of the compliance checking interrogator is assumed to be part of the toll charging role as defined in ISO 17573-1. The CCC permits identification of the OBE, vehicle and contract, and verification of whether the driver has fulfilled his obligations and the checking status and performance of the OBE. The CCC reads, but does not write, OBE data.

This document is applicable to OBE in an autonomous mode of operation; it is not applicable to compliance checking in dedicated short-range communication (DSRC)-based charging systems.

It defines data syntax and semantics, but not a communication sequence. All the attributes defined herein are required in any OBE claimed to be compliant with this document, even if some values are set to “not defined” in cases where certain functionality is not present in an OBE. The interrogator is free to choose which attributes are read in the data retrieval phase, as well as the sequence in which they are read. In order to achieve compatibility with existing systems, the communication makes use of the attributes defined in ISO 14906 and the ISO 17573 series (all parts) wherever useful.

The CCC is suitable for a range of short-range communication media. Specific definitions are given for the CEN-DSRC as specified in EN 15509, as well as for the use of ISO CALM IR, the Italian DSRC as specified in ETSI ES 200 674-1, ARIB DSRC and WAVE DSRC as alternatives to the CEN-DSRC. The attributes and functions defined are for compliance checking by means of the DSRC communication services provided by DSRC application layer, with the CCC attributes and functions made available to the CCC applications at the roadside equipment (RSE) and OBE. The attributes and functions are defined on the level of application data units (ADUs).

The definition of the CCC includes:

- the application interface between OBE and RSE (as depicted in Figure 2);
- use of the generic DSRC application layer as specified in ISO 15628 and EN 12834;
- CCC data type specifications given in Annex A;
- a protocol implementation conformance statement (PICS) proforma is given in Annex B;
- use of the CEN-DSRC stack as specified in EN 15509, or other equivalent DSRC stacks as described in Annex C, Annex D, Annex E and Annex F;

- security services for mutual authentication of the communication partners and for signing of data (see Annex H);
- an example CCC transaction is presented in Annex G;
- the informative Annex I highlights how to use this document for the European electronic toll service (EETS).

Test specifications are not within the scope of this document.

NOTE A test suite for checking an OBE or RSE implementation for compliance with this document is defined in the corresponding edition of ISO 13143-1 and ISO 13143-2.




Figure 2 — CCC application interface

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 8824-1:2015, *Information technology — Abstract Syntax Notation One (ASN.1): Specification of basic notation — Part 1*

ISO/IEC 8825-2:2015, *Information technology — ASN.1 encoding rules: Specification of Packed Encoding Rules (PER) — Part 2*

ISO 12855:2022, *Electronic fee collection — Information exchange between service provision and toll charging*

ISO/DIS 14906:2022, *Electronic fee collection — Application interface definition for dedicated short-range communication*

ISO 15628:2013, *Intelligent transport systems — Dedicated short range communication (DSRC) — DSRC application layer*

EN 12834:2003, *Road transport and traffic telematics — Dedicated Short Range Communication (DSRC) — DSRC application layer*

FprEN 15509:2022, *Electronic fee collection — Interoperability application profile for DSRC*

ISO/TS 17573-3:2021, *Electronic fee collection — System architecture for vehicle-related tolling — Part 3: Data dictionary*

NIMA Technical Report TR8350.2 version 3 — *Department of Defense World Geodetic System 1984, Its Definition and Relationships With Local Geodetic Systems*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1

access credentials

AC_CR

trusted attestation or secure module that establishes the claimed identity of an object or application

[SOURCE: CEN ISO/TS 17573-2:2020, 3.4]

3.2

attribute

addressable package of data consisting of a single data element or structured sequences of data elements

[SOURCE: CEN ISO/TS 17573-2:2020, 3.13]

3.3

authentication

security mechanism allowing verification of the provided identity

[SOURCE: EN 301 175 V1.1.1:1998, 3]

3.4

authenticator

data, possibly encrypted, that is used for authentication

[SOURCE: CEN ISO/TS 17573-2:2020, 3.16]

3.5

data integrity

property that data has not been altered or destroyed in an unauthorized manner

[SOURCE: ISO 7498-2:1989, 3.3.21]

3.6

fixed roadside equipment

roadside equipment located at a fixed position

[SOURCE: CEN ISO/TS 17573-2:2020, 3.81]

3.7

mobile roadside equipment

equipment mounted on a mobile unit or handheld equipment to be used along the road

[SOURCE: CEN ISO/TS 17573-2:2020, 3.119]

3.8

on-board equipment

OBE

all required equipment on-board a vehicle for performing required electronic fee collection (EFC) functions and communication services

[SOURCE: CEN ISO/TS 17573-2:2020, 3.126]

3.9

roadside equipment

RSE

fixed or movable electronic fee collection (EFC) equipment located along or on the road

[SOURCE: CEN ISO/TS 17573-2:2020, 3.161]

3.10

service primitive

elementary communication service provided by the application layer protocol to the application processes

[SOURCE: CEN ISO/TS 17573-2:2020, 3.173]

3.11

toll context

logical view as defined by attributes and functions of the basic elements of a toll scheme consisting of a single basic tolling principle, a spatial distribution of the charge objects and a single behaviour of the related Front End

[SOURCE: CEN ISO/TS 17573-2:2020, 3.196]

3.12

toll regime

set of rules, including enforcement rules, governing the collection of a toll in a toll domain

[SOURCE: CEN ISO/TS 17573-2:2020, 3.203]

3.13

toll service provider

TSP

entity providing toll services in one or more toll domains

[SOURCE: CEN ISO/TS 17573-2:2020, 3.206]

3.14

transaction

whole of the exchange of information between two physically separated communication facilities

[SOURCE: CEN ISO/TS 17573-2:2020, 3.211]

4 Abbreviated terms

For the purpose of this document, the following abbreviated terms apply.

AC_CR	access credentials
ADU	application data unit (ISO 14906)
ASN.1	abstract syntax notation one (ISO/IEC 8824-2)
BST	beacon service table (ISO 14906)
CCC	compliance check communication
DSRC	dedicated short-range communication (ISO 14906)
EID	Element Identifier (ISO 15628 and EN 12834)
EFC	electronic fee collection
GNSS/CN	global navigation satellite systems/cellular network
MAC	message authentication code (ISO 14906)
OBE	on-board equipment (ISO 14906)
PICS	protocol implementation conformance statement
RSE	roadside equipment (ISO 14906)
TSP	toll service provider
VST	vehicle service table (ISO 14906)
WGS84	World Geodetic System 1984

5 Application interface architecture

5.1 General

This clause gives an insight into the CCC architecture. It identifies the services provided to CCC applications and the functions that implement these services. It also defines principles regarding attributes and the use of DSRC communication service primitives. A detailed description of the functions is given in Clause 6, whilst the detailed list of the attributes is given in Clause 7.

The CCC application interface has been designed to make use of the CEN-DSRC communication stack, via the application layer specified in ISO 15628 and EN 12834. For other identified DSRC communication media, detailed mappings to corresponding services are given in annexes.

From a general addressing viewpoint, it should be noted that only one CCC context is used, as compliance checking attributes are independent of context.

5.2 Services provided

The CCC application interface offers the following services to CCC applications:

- retrieval of compliance significant attributes, in order for RSE to assess OBE compliance,
- mutual authentication of RSE and OBE by means of exchange of credentials and authenticators, and
- a command to the OBE to signal to the user the result of the compliance check.

NOTE 1 The policy on whether or not the result of the compliance check or the fact that a transaction has taken place is signalled to the user is decided by the entity operating the CCC interrogator and is outside the scope of this document.

The above services are realized by means of protocol exchanges performed by means of communication services and transactions as described in Clause 8.

The services are provided by the following functions:

- the “initialise communication” function, which shall be used to establish the CCC communication link between RSE and OBE;
- the “data retrieval” function, which shall be used to retrieve CCC attributes;
- the “authenticated data retrieval” function, which shall be used to retrieve data with an authenticator from the OBE;
- the “driver notification” function, which shall be used to invoke a human-machine-interface (HMI) function (e.g. signal “OK” via a buzzer sound);
- the “terminate communication” function, which shall be used to terminate the CCC communication;
- the “test communication” function, which shall be used for testing and localizing the OBE.

NOTE 2 A “write” service is not provided, since the writing of data into the OBE is not foreseen.

5.3 Attributes

The attributes available on the OBE side for a CCC application at roadside for checking the compliance of a vehicle are given in detail in Clause 7.

All attributes defined in this document shall be available on the OBE side.

The RSE is free to decide to read any combination of attributes from the OBE. The attributes shall be identified and retrieved using the mechanisms defined in ISO 14906. More specifically, the addressing of the CCC application data implemented by the OBE and RSE shall conform to the rules defined in ISO/DIS 14906:2022, 5.3.

Multiple instances of attributes are not supported.

5.4 Toll context

An OBE may be located in several tolling contexts at once.

NOTE This can occur, e.g. in situations where a motorway toll geographically overlaps with an area-based charging system.

In these different tolling contexts, the OBE might run different charging applications or several instances of one charging application in parallel.

This document builds on the concept that for compliance checking, there is basically no need to distinguish between tolling contexts. In certain circumstances and in the cases specified in the semantic definition, the toll service provider shall ensure that the attribute content complies with the specifications of the toll charger (e.g. for local vehicle classes).

The OBE should hold only one CCC context, represented by a single element as specified in ISO 14906. However, for backwards compatibility reasons, one additional CCC context, represented by a second element may be used to support ISO 12813:2015 (see also 8.2.3).

5.5 Use of lower layers

5.5.1 Supported DSRC communication stacks

The CCC application interface makes use of the CEN-DSRC communication stack as described in Table 1. Other communication media can be used as listed in Table 1 if an equivalent mapping to corresponding services is provided. Detailed examples are provided in informative annexes.

Table 1 — Supported short-range communication stacks

Medium	Application layer	Lower layers	Detailed specifications
CEN-DSRC	ISO 15628 EN 12834	EN 12795 EN 12253	Specification in 5.5.2
Italian DSRC	ETSI ES 200 674-1 (Clause 11 and Annex D)	ETSI ES 200 674-1 (Clauses 7 to 10 and Annex D)	Implementation example in Annex C
ISO CALM IR	ISO 15628 EN 12834	ISO 21214	Implementation example in Annex D
ARIB DSRC	ARIB STD-T75 ISO 15628	ARIB STD-T75 ITU-R.M1453-2	Implementation example in Annex E
WAVE DSRC	IEEE 1609.11-2010 ISO 15628	IEEE 1609.3-2010 IEEE 1609.4-2016 IEEE 802.11	Implementation example in Annex F

NOTE EN 12795 and EN 12253 have been adopted in ITU-R.M 1453-2.

If more than one communication medium is implemented in an OBE, then the OBE shall respond to RSE interrogations on the same medium that the RSE has initiated the CCC interrogation.

5.5.2 Use of the CEN-DSRC stack

The following requirements apply to the CCC application when used with the CEN-DSRC communication stack.

The OBE shall comply with FprEN 15509:2022, 6.1.2.

Fixed RSE shall comply with FprEN 15509:2022, 6.2.2.

Mobile RSE shall comply with FprEN 15509:2022, 6.2.2, except for *Downlink Parameter D4a* (not applicable to mobile RSE).

NOTE EN 15509 defines the CEN-DSRC communication stack for fixed RSE only.

6 Functions

6.1 Functions in detail

6.1.1 General

All functions defined in 6.1 shall be available on the OBE side.

For CEN-DSRC, the OBE shall provide the following functions:

- INITIALISATION, GET and RELEASE application layer services according to ISO 15628 and EN 12834;
- GET_STAMPED, SET_MMI and ECHO EFC functions according to ISO 14906.

Clauses 6.1.2 to 6.1.7 define the functions for CEN-DSRC only. For other supported media, according to 5.5.1 equivalent functionality should be provided; see Annex C for ETSI ES 200 674-1 5.8 GHz microwave DSRC, Annex D for CALM Infrared DSRC, Annex E for ARIB microwave DSRC and Annex F for WAVE 5.9 GHz microwave DSRC.

6.1.2 Initialise communication

Initialisation of the communication between the RSE and the OBE shall be initiated by the RSE, by means of the invocation of an initialisation request by the RSE. After successful initialisation, the function “Initialise communication” shall notify the applications on the RSE and OBE sides.

The initialisation notification on the OBE side shall carry at least the identity of the beacon (e.g. beacon serial number) and absolute time.

The initialisation notification on the RSE side shall carry the CCC application identity and shall also carry data required for the security services (e.g. nonce value, key identifier).

The function “Initialise communication” shall be provided by the application layer INITIALISATION services as specified in ISO 15628 and EN 12834. It is defined in Annex A: refer to CCC-InitialiseComm-Request and CCC-InitialiseComm-Response.

6.1.3 Data retrieval

The function “Data retrieval” shall be provided by the application layer GET service as specified in ISO 15628 and EN 12834. It is defined in Annex A: refer to CCC-DataRetrieval-Request and CCC-DataRetrieval-Response.

In the GET service primitives, iid shall not be used.

NOTE The invocation of a service primitive by an application process implicitly calls upon and uses services offered by the lower protocol layers.