

EIA-535ABAD

DETAIL SPECIFICATION

Fixed Tantalum Capacitors With Non-Solid Electrolyte And Porous Anode

EIA-535ABAD

MAY 1987

ELECTRONIC INDUSTRIES ASSOCIATION
ENGINEERING DEPARTMENT



NOTICE

EIA Engineering Standards and Publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for his particular need. Existence of such Standards and Publications shall not in any respect preclude any member or non-member of EIA from manufacturing or selling products not conforming to such Standards and Publications, nor shall the existence of such Standards and Publications preclude their voluntary use by those other than EIA members, whether the standard is to be used either domestically or internationally.

Recommended Standards and Publications are adopted by EIA without regard to whether or not their adoption may involve patents on articles, materials, or processes. By such action, EIA does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the Recommended Standard or Publication.

Published by

ELECTRONIC INDUSTRIES ASSOCIATION
Engineering Department
2001 Eye Street, NW
Washington, D.C. 20006

Copyright 1987
ELECTRONIC INDUSTRIES ASSOCIATION

PRICE: \$9.00

January 1984

INTERNATIONAL ELECTROTECHNICAL COMMISSION

*Quality Assessment System
for Electronic Components*

IECQ

Detail Specification for use in electronic equipment

Fixed Tantalum Capacitors with Non-Solid Electrolyte and
Porous Anode

Originator:

ECCB

**THE ELECTRONIC COMPONENTS
CERTIFICATION BOARD, INC.**

The U.S. National Authorized Institution
for the IEC


QUALITY ASSESSMENT SYSTEM
FOR ELECTRONIC COMPONENTS

2001 Eye Street, N.W.
Washington, D.C. 20006
USA

**FIXED TANTALUM CAPACITORS WITH NON-SOLID
ELECTROLYTE AND POROUS ANODE**

This Standard represents US adoption of International Electrotechnical Commission Quality Assessment Systems (IECQ) Detail Specification QC300202/US0004, January 1984. It is issued as an EIA document to provide a Specification in the National Electronic Components Quality Assessment System (NECQ).

IEC documents referenced in this Detail Specification (e.g. QC 300000) may be obtained from the American National Standards Institute, 1430 Broadway, New York, New York 10018. EIA numbers are assigned to these IEC documents for reference purposes and to facilitate later publication of equivalent EIA documents.

National Standards Organization ELECTRONIC INDUSTRIES ASSOCIATION	Detail Specification Number QC300202/US0004 (EIA-535ABAC)
Generic Specification Number Electronic components of assessed quality in accordance with QC300000 (EIA-5350000)	Blank Detail Specification Number QC300202 (EIA-535AB00)
Outline Drawing (See Table I) (First Angle Projection)  (Other shapes are permitted within the dimensions given)	Product Description Fixed Tantalum Capacitors with Non-Solid Electrolyte and Porous Anode Electrical Circuit Typical Construction Silver Case, Axial Lead, Polarized, Nickel Positive, Copper Negative Lead, Case Insolated, Elastomer Seal Application/Assessment Level Assessment Level(s): E Performance Grade: Long Life

Information on the availability of components
qualified to this specification is given in
the Qualified Products List.



Documents
Document Sharing Hub

PART ONE - GENERAL DATA

1. GENERAL DATA

1.1 RECOMMENDED METHODS OF MOUNTING

- a. By the leads in the absence of vibration or shock.
- b. By body clamp and leads if vibration or shock can exist.

1.2 DIMENSIONS

TABLE I

CASE SIZE REFERENCE	DIMENSIONS (mm)			
	ϕ (Max.)	L1 (Max.)	L2 +,-6.35	d +,-0.025
D	2.92	7.62	38.1	0.500
A	2.92	10.20	38.1	0.500
B	3.68	15.20	38.1	0.500
C	5.72	19.80	38.1	0.500

1.3 RATINGS AND CHARACTERISTICS

Capacitance Range	(see Table II)
Tolerance On Rated Capacitance	+,-5%; +,-10%, +,-20%
Rated Voltage (Ur)	(see Table II)
Climatic Category	55/85/21
Rated Temperature	85 C
Variation of Capacitance With Temperature	(see Table II)
Tangent Of Loss Angle	(see Table II)
Leakage Current	(see Table II)
Impedance	(see Table II)
Reverse Voltage	0 (No reversal of voltage permitted)