

EIA-535ACAB

DETAIL SPECIFICATION

Fixed Tantalum Capacitors With Non-Solid Electrolyte And Foil Electrode

EIA-535ACAB

MAY 1987

ELECTRONIC INDUSTRIES ASSOCIATION
ENGINEERING DEPARTMENT



NOTICE

EIA Engineering Standards and Publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for his particular need. Existence of such Standards and Publications shall not in any respect preclude any member or non-member of EIA from manufacturing or selling products not conforming to such Standards and Publications, nor shall the existence of such Standards and Publications preclude their voluntary use by those other than EIA members, whether the standard is to be used either domestically or internationally.

Recommended Standards and Publications are adopted by EIA without regard to whether or not their adoption may involve patents on articles, materials, or processes. By such action, EIA does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the Recommended Standard or Publication.

Published by

ELECTRONIC INDUSTRIES ASSOCIATION
Engineering Department
2001 Eye Street, N.W.
Washington, D.C. 20006

Copyright 1987
ELECTRONIC INDUSTRIES ASSOCIATION

PRICE: \$9.00

QC 300 203 / US0002

February 1984

INTERNATIONAL ELECTROTECHNICAL COMMISSION

*Quality Assessment System
for Electronic Components*

IECQ

Detail Specification for use in electronic equipment:

Fixed Tantalum Capacitors with Non-Solid Electrolyte
and Foil Electrode

Originator:

ECCB

**THE ELECTRONIC COMPONENTS
CERTIFICATION BOARD, INC.**

The U.S. National Authorized Institution
for the IEC

QUALITY ASSESSMENT SYSTEM
FOR ELECTRONIC COMPONENTS

2001 Eye Street, N.W.
Washington, D.C. 20006
USA



Documents

Document Sharing Hub






EIA-535ACAB

**FIXED TANTALUM CAPACITORS WITH NON-SOLID
ELECTROLYTE AND FOIL ELECTRODE**

This Standard represents US adoption of International Electrotechnical Commission Quality Assessment Systems (IECQ) Detail Specification QC300203/US0002, February 1984. It is issued as an EIA document to provide a Specification in the National Electronic Components Quality Assessment System (NECQ).

IEC documents referenced in this Detail Specification (e.g. QC 300000) may be obtained from the American National Standards Institute, 1430 Broadway, New York, New York 10018. EIA numbers are assigned to these IEC documents for reference purposes and to facilitate later publication of equivalent EIA documents.

National Standards Organization ELECTRONIC INDUSTRIES ASSOCIATION	Detail Specification Number QC300203/US0002 (EIA-535ACAB)
Generic Specification Number Electronic components of assessed quality in accordance with QC300000 (IEC384-1) (EIA-5350000)	Blank Detail Specification Number QC300203 (EIA-535AC00)
Outline Drawing (SEE TABLE I) (THIRD ANGLE PROJECTION) 	Product Description FIXED TANTALUM CAPACITORS WITH NON-SOLID ELECTROLYTE AND FOIL ELECTRODE
	Electrical Circuit POLAR  BI-POLAR 
	Typical Construction HERMETICALLY SEALED, AXIAL LEAD, POLAR AND BI-POLAR, ETCHED AND HI-ETCHED FOIL
	Application/Assessment Level PREMIUM QUALITY, HIGH RELIABILITY DESIGN FOR THE MOST DEMANDING APPLICATIONS. ASSESSMENT LEVEL: E PERFORMANCE GRADE: LONG LIFE

Information on the availability of components
qualified to this specification is given in
the Qualified Products List.



Documents

Document Sharing Hub

EIA-535ACAB
 QC300203/US0002
 Page 2

1. GENERAL DATA

1.1 RECOMMENDED METHODS OF MOUNTING

- a. By leads in absence of vibration or shock.
- b. By body clamp and leads if vibration or shock can exist.

1.2 DIMENSIONS

TABLE 1

Dimensions- mm (inches)				
CASE CODE	Basic Case		Insulated Case	
	L $\frac{1}{\text{---}}$	$\varnothing$	$\varnothing$ Max	C Max
	± 1.60 (.062)	± 0.40 (.016)		
A	17.50 (.688)	4.80 (1.88)	5.60 (.219)	30.20 (1.188)
B	23.00 (.969)	7.15 (.281)	7.90 (.312)	37.30 (1.469)
C	36.55 (1.438)	9.55 (.375)	10.30 (.406)	49.25 (1.938)
D	54.00 (2.125)	9.55 (.375)	10.30 (.406)	66.70 (2.625)
E	69.85 (2.750)	9.55 (.375)	10.30 (.406)	82.55 (3.250)

1/ Length of basic case; Shrink-Fitted insulation shall lap over the ends of the capacitor body.

Notes:

1. The weld shall not be enclosed in the end seal.

1.3 RATINGS AND CHARACTERISTICS

Capacitance range	See Table II
Tolerance on rated capacitance	See Table II
Rated voltage	See Table II
Upper category voltage	See Table II
Climatic category	55/125/56
Rated temperature	-55 to +125°C
Variation of Capacitance with temperature	See Table II
Tangent of loss angle	See Table II
Leakage current	See Table II
Impedance	See Table II
Reverse voltage (polar capacitors only)	3 VDC
Vibration severity	20g
Bump severity	Not applicable
Shock severity	100g