



ANSI/EIA-520DAAA-1990
APPROVED: May 18, 1990

EIA-520DAAA

EIA SPECIFICATION

Detail Specification on 1 Pole Toggle Switches

EIA-520DAAA

JUNE 1990

ELECTRONIC INDUSTRIES ASSOCIATION
ENGINEERING DEPARTMENT



Approved For Use In
The NECQ System



Documents

Document Sharing Hub

NOTICE

EIA Engineering Standards and Publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for his particular need. Existence of such Standards and Publications shall not in any respect preclude any member or nonmember of EIA from manufacturing or selling products not conforming to such Standards and Publications, nor shall the existence of such Standards and Publications preclude their voluntary use by those other than EIA members, whether the standard is to be used either domestically or internationally.

Recommended Standards and Publications are adopted by EIA without regard to whether or not their adoption may involve patents on articles, materials, or processes. By such action, EIA does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the Recommended Standard or Publication.

This EIA Specification is considered to have International Standardization implication, but the International Electrotechnical Commission activity has not progressed to the point where a valid comparison between the EIA Specification and the IEC document can be made.

This Specification does not purport to address all safety problems associated with its use or all applicable regulatory requirements. It is the responsibility of the user of this Specification to establish appropriate safety and health practices and to determine the applicability of regulatory limitations before its use.

(From EIA Standards Proposal No. 2193 formulated under the cognizance of the EIA P-13.2 Subcommittee on Toggle, Rocker, Paddle & Slide Switches.)

APPROVED FOR USE IN THE NECQ SYSTEM AS NQ/EIA-520DAAA.



Published by

ELECTRONIC INDUSTRIES ASSOCIATION
Engineering Department
2001 Pennsylvania Ave, N.W.
Washington, D.C. 20006

PRICE: \$12.00

COPYRIGHT 1990

All rights reserved
Printed in U.S.A.

NATIONAL STANDARDS ORGANIZATION Electronic Industries Association 2001 Eye Street N. W. Washington, D.C. 20006	Detail Specification Number EIA-520DAAA
Generic Specification Number Electronic components of assessed quality in accordance with EIA-5200000	Blank Detail Specification Number EIA-520DA00
Outline Drawing - MAXIMUM ENCLOSURE DIMENSIONS  39.6 (1.56) MAX 42.2 (1.66) MAX 32.3 MAX (1.27) 16.1 (.63) MAX	Product Description - toggle switch - standard size - one pole - watertight seal - 20 A max. current rating - 277 V max. voltage rating - 2 toggle lever styles - 3 terminal styles Electrical Circuit See Table 1  (typical) Typical Construction - metal toggle lever - metal mounting bushing - plastic housing
NOTES: 1) See Fig. 1 thru 3 for detail dimensions. 2) Dimensions are denoted as follows: 0.0 = mm (0.000) = inch	Application Electrical equipment in hostile environments

Information on the availability of components
qualified to this specification is given in
the Qualified Products List



Documents

Document Sharing Hub

INTRODUCTION

The complete requirements for the switches described herein shall consist of this detail specification and the current issues of EIA-5200000 and EIA-520D000.

SECTION ONE - GENERAL DATA

1.0 General Data

1.1 Scope

The standard size, one pole watertight toggle switches of certified quality covered by this detail specification

- a) mount in a 12.4 mm (.49 inch) diameter mounting hole.
- b) have a maximum rated voltage of 277 volts.
- c) have a maximum rated current of 20 amperes.

1.2 Type Designation

Switches covered by this detail specification shall be described by the following in the order shown:

- a) The number for this detail specification.
- b) The switching circuit per Table 1.
- c) The toggle lever locking combination, if any, per Table 1. Insert "X" if no locking combination is desired.
- d) The terminal style per Figure 3.

Example of Type Designation: EIA520DAAA01X1




TABLE 1 - SWITCHING CIRCUIT

switching circuit number	available locking combination (see fig.2)	circuit made with toggle lever in			electrical rating code (table II)
		keyway side	center	opposite keyway side	
01	(all)	1-2	OFF	2-3	1
02	D,F,G	OFF	(none)	2-3	1
03	D,F,G	1-2	(none)	2-3	1
04	F	mom. OFF	(none)	2-3	2
05	E,F,K,L,M,N	mom. 1-2	OFF	2-3	2
06	F	mom. 1-2	(none)	OFF	2
07	E,L,N	mom. 1-2	OFF	mom. 2-3	2
08	F	mom. 1-2	(none)	2-3	2
21	E,F,K,M	[1]	OFF	2-3	1
31	E,F,K,M	[1]	1-2	2-3	1
51	E	[1]	1-2	mom. 2-3	2
61	E	mom. 1-2	OFF	[1]	2

NOTE: [1] No toggle lever position. This switching circuitry has two toggle lever positions with one position being the normal center position.

1.3 Marking

The marking of the switch and package shall be in accordance with the requirements of subclause 2.5 of the Generic Specification. The switches shall be marked with the following information:

- terminal identification per Figure 1.
- type designation per 1.2
- manufacturer's name
- date code per RS-476

1.4 Ordering Information

Orders for switches covered by this Specification shall contain the following information as a minimum:


- the applicable part number per subclause 1.2.
- "per EIA520DAAA dated (insert issue date)"

1.5 Certified Records of Released Lot - not required.

1.6 Safety Considerations

The user shall consider the suitability of the switch with regard to any safety requirements applicable to the equipment.

1.7 Common Features



1.8 Dimensional Parameter

1.8.1 Mounting Dimensions

The mounting dimensions shall be in accordance with Figure 1 and are common to all switches covered by this detail specification. The configuration is optional within the specified dimensions. The original dimensions are in inches.

1.8.2 Toggle lever Dimensions

The toggle lever dimensions shall be in accordance with Figure 2.

1.8.3 Terminal Dimensions

The terminal dimensions shall be in accordance with Figure 3. Terminals which are not functionally required shall be omitted.

1.8.4 Mounting Hardware

The dimensions of the mounting hardware shall be in accordance with Figure 4 for the hex nut, Figure 5 for the internal tooth lockwasher, and Figure 6 for the keying washer.

1.8.5 Terminal Hardware

The dimensions of the terminal hardware shall be in accordance with Figure 7 for the screw with the captive internal tooth lockwasher or, at the option of the manufacturer, with Figure 8 for the pan head screw and with Figure 9 for the split ring lockwasher.