



ANSI/EIA 60384-15-2020
Approved: September 4, 2020

EIA STANDARD

EIA 60384-15

Fixed capacitors for use in electronic equipment - Part 15: Sectional specification: Fixed tantalum capacitors with non-solid or solid electrolyte

EIA 60384-15

(IEC 60384-15:2017 Edition 2.0, IDT)

These materials are subject to copyright claims of IEC and ECIA. No part of this publication may be reproduced in any form, including an electronic retrieval system, without the prior written permission of ECIA. All requests pertaining to the EIA 60384-21 Standard should be submitted to ECIA.

September 2020



Electronic Components Industry Association

NOTICE

EIA Engineering Standards and Publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for his particular need. Existence of such Standards and Publications shall not in any respect preclude any member or nonmember of ECIA from manufacturing or selling products not conforming to such Standards and Publications, nor shall the existence of such Standards and Publications preclude their voluntary use by those other than ECIA members, whether the standard is to be used either domestically or internationally.

Standards and Publications are adopted by ECIA in accordance with the American National Standards Institute (ANSI) patent policy. By such action, ECIA does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the Standard or Publication.

This EIA Standard is identical (IDT) with the International Standard IEC Publication 60384-15:2017 Edition 2: Fixed Capacitors for Use in Electronic Equipment – Part 15: Sectional specification: Fixed tantalum capacitors with non-solid or solid electrolyte.

This document is the EIA Standard EIA 60384-15-2020: Fixed Capacitors for Use in Electronic Equipment - Part 15: Sectional specification: Fixed tantalum capacitors with non-solid or solid electrolyte.

The text, figures and tables of IEC 60384-15:2017 Edition 2 are used in this Standard with the consent of the IEC and the American National Standards Institute (ANSI). The IEC copyrighted material has been reproduced with permission from ANSI. The IEC Foreword and Introduction are not part of the requirements of this standard but are included for information purposes only.

This Standard does not purport to address all safety problems associated with its use or all applicable regulatory requirements. It is the responsibility of the user of this Standard to establish appropriate safety and health practices and to determine the applicability of regulatory limitations before its use.

(From Standards Proposal No. SP-5443.01, formulated under the cognizance of the EIA Steering Committee for Passive Electronic Components Standards (S-1)).

Published by

©ELECTRONIC COMPONENTS INDUSTRY ASSOCIATION 2020
Standards & Technology Department
13873 Park Center Road, Suite 315
Herndon, VA 20171

**PLEASE !
DON'T VIOLATE
THE
LAW!**

This document is copyrighted by the ECIA and may not be reproduced without permission.

Organizations may obtain permission to reproduce a limited number of copies through entering into a license agreement. For information, contact:

IHS Markit
15 Inverness Way East
Englewood, CO 80112-5704 or call
USA and Canada (1-877-413-5186), International (303-397-7956)

CONTENTS

FOREWORD	iv
1 General	1
1.1 Scope	1
1.2 Object	1
1.3 Normative references	1
1.4 Information to be given in a detail specification.....	2
1.4.1 General.....	2
1.4.2 Outline drawing and dimensions	2
1.4.3 Mounting	2
1.4.4 Ratings and characteristics	2
1.4.5 Marking	3
1.5 Terms and definitions	3
1.6 Marking	3
1.6.1 General.....	3
1.6.2 Information for marking	4
1.6.3 Marking on capacitors	4
1.6.4 Marking on packaging	4
2 Preferred ratings and characteristics	4
2.1 Preferred characteristics.....	4
2.2 Preferred values of ratings	4
2.2.1 Nominal capacitance (C_N)	4
2.2.2 Tolerance on nominal capacitance	5
2.2.3 Rated voltage (U_R)	5
2.2.4 Category voltage (U_C)	5
2.2.5 Reverse voltage	5
2.2.6 Surge voltage (U_{RS} or U_{CS}).....	5
2.2.7 Ripple (if required)	5
2.2.8 Rated temperature	6
3 Quality assessment procedures.....	6
3.1 Primary stage of manufacture	6
3.2 Structurally similar components	6
3.3 Certified test records of released lots	6
3.4 Qualification approval procedures.....	6
3.4.1 General.....	6
3.4.2 Qualification approval on the basis of the fixed sample size procedure.....	6
3.4.3 Tests.....	7
3.5 Quality conformance inspection	14
3.5.1 Formation of inspection lots	14
3.5.2 Test schedule.....	15
3.5.3 Delayed delivery.....	15
3.5.4 Assessment levels.....	15
4 Test and measurement procedures	16
4.1 Visual inspection and check of dimensions	16
4.2 Electrical tests	16
4.2.1 Leakage current	16
4.2.2 Capacitance	17
4.2.3 Tangent of loss angle ($\tan \delta$).....	17

4.2.4	Impedance (if required)	17
4.2.5	Insulation resistance of the external insulation (if required)	18
4.2.6	Voltage proof of the external insulation (if required)	18
4.3	Robustness of terminations	19
4.3.1	General.....	19
4.3.2	Initial inspection	19
4.3.3	Test Ua1, Ub and Uc applicable	19
4.3.4	Special bending test.....	19
4.4	Resistance to soldering heat	20
4.4.1	General.....	20
4.4.2	Conditions.....	20
4.4.3	Final inspections and requirements	21
4.5	Solderability	21
4.5.1	General.....	21
4.5.2	Test conditions.....	21
4.5.3	Final inspections and requirements	21
4.6	Rapid change of temperature.....	21
4.6.1	General.....	21
4.6.2	Initial inspection	21
4.6.3	Test conditions.....	21
4.6.4	Recovery.....	21
4.6.5	Final inspections and requirements	21
4.7	Vibration.....	21
4.7.1	General.....	21
4.7.2	Test condition.....	22
4.7.3	Final inspections and requirements	22
4.8	Bump.....	22
4.8.1	General.....	22
4.8.2	Mounting	22
4.8.3	Test conditions.....	22
4.8.4	Final inspections and requirements	22
4.9	Shock	23
4.9.1	General.....	23
4.9.2	Mounting	23
4.9.3	Test conditions.....	23
4.9.4	Final inspections and requirements	23
4.10	Climatic sequence	23
4.10.1	General.....	23
4.10.2	Initial inspection	23
4.10.3	Dry heat	23
4.10.4	Damp heat, cyclic, Test Db, first cycle.....	24
4.10.5	Cold	24
4.10.6	Low air pressure (if required)	24
4.10.7	Damp heat, cyclic, Test Db, remaining cycles.....	24
4.10.8	Recovery.....	24
4.10.9	Sealing (if required).....	24
4.10.10	Final inspections and requirements	24
4.11	Damp heat, steady state	24
4.11.1	General.....	24
4.11.2	Initial inspection	25

4.11.3	Final inspections and requirements	25
4.12	Endurance	25
4.12.1	General	25
4.12.2	Initial inspection	25
4.12.3	Test conditions	25
4.12.4	Recovery	25
4.12.5	Final inspections and requirements	25
4.13	Surge voltage	26
4.13.1	General	26
4.13.2	Initial inspection	26
4.13.3	Test conditions	26
4.13.4	Final inspections and requirements	26
4.14	Reverse voltage (if required)	26
4.14.1	General	26
4.14.2	Initial inspection	26
4.14.3	Test conditions	26
4.14.4	Final inspections and requirements	27
4.15	Characteristics at high and low temperature	27
4.15.1	General	27
4.15.2	Final inspections and requirements	27
4.16	Charge and discharge (if required)	27
4.16.1	General	27
4.16.2	Initial inspection	27
4.16.3	Test conditions	27
4.16.4	Recovery	28
4.16.5	Final inspections and requirements	28
4.17	Component solvent resistance	28
4.18	Solvent resistance of the marking	28
4.19	High surge current (if required)	28
4.19.1	General	28
4.19.2	Initial inspection	28
4.19.3	Final inspections and requirements	28
	Bibliography	29
	Figure 1 – Apparatus of special bending test	20
	Table 1 – Rated, category and surge voltages	5
	Table 2 – Sampling plan for qualification approval tests	8
	Table 3 – Test schedule for qualification approval	9
	Table 4 – Lot-by-Lot inspection	15
	Table 5 – Periodic Inspection	16
	Table 6 – Vibration test frequencies	22
	Table 7 – Shock peak acceleration/pulse duration	23
	Table 8 – Test temperature	26

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FIXED CAPACITORS FOR USE IN ELECTRONIC EQUIPMENT –

Part 15: Sectional specification: Fixed tantalum capacitors with non-solid or solid electrolyte

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60384-15 has been prepared by IEC technical committee 40: Capacitors and resistors for electronic equipment.

This second edition cancels and replaces the first edition published in 1982, Amendment 1:1987 and Amendment 2:1992, and constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) Revision of the structure in accordance with ISO/IEC Directives, Part 2:2016 (seventh edition) to the extent practicable, and harmonization between other similar kinds of documents.

b) In addition, Clause 4 and all the tables have been reviewed in order to prevent duplications and contradictions.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
40/2523/FDIS	40/2535/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

The list of all parts of the IEC 60384 series, under the general title *Fixed capacitors for use in electronic equipment*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

Part 15: Sectional specification: Fixed tantalum capacitors with non-solid or solid electrolyte

1 General

1.1 Scope

This part of IEC 60384 applies to through-hole/leaded polar and bipolar tantalum electrolyte capacitors with solid and non-solid electrolyte for use in electronic equipment.

It includes capacitors for long-life applications and capacitors for general-purpose applications.

Capacitors for special purpose application may need additional requirements.

This document covers two basic sub-families:

- Sub-family 1: Fixed non-solid electrolyte tantalum capacitors with porous anode.
- Sub-family 2: Fixed solid electrolyte tantalum capacitors with porous anode.

1.2 Object

The object of this document is to prescribe preferred ratings and characteristics and to select from IEC 60384-1:2016 the appropriate quality assessment procedures, tests and measuring methods and to give general performance requirements for this type of capacitor. Test severities and requirements prescribed in detail specifications referring to this sectional specification shall be of equal or higher performance level, because lower performance levels are not permitted.

1.3 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60063, *Preferred number series for resistors and capacitors*

IEC 60068-1:2013, *Environmental testing – Part 1: General and guidance*

IEC 60068-2-6, *Environmental testing – Part 2-6: Tests – Test Fc: Vibration (sinusoidal)*

IEC 60068-2-14, *Environmental testing – Part 2-14: Tests – Test N: Change of temperature*

IEC 60384-1:2016, *Fixed capacitors for use in electronic equipment – Part 1: Generic specification*

IEC 60417, *Graphical symbols for use on equipment*

IEC 61193-2:2007, *Quality assessment system – Part 2: Selection and use of sampling plans for inspection of electronic components and packages*

ISO 3, *Preferred numbers – Series of preferred numbers*

1.4 Information to be given in a detail specification

1.4.1 General

Detail specifications shall be derived from the blank detail specification.

Detail specifications shall not specify requirements inferior to those of the generic, sectional or blank detail specification. When more severe requirements are included, they shall be listed in 1.9 of the detail specification and indicated in the test schedules, for example, by an asterisk.

The information given in 1.4.2 may, for convenience, be presented in tabular form.

The following information shall be given in each detail specification and the values quoted shall preferably be selected from those given in the appropriate clause of this sectional specification.

1.4.2 Outline drawing and dimensions

There shall be an illustration of the capacitors as an aid to easy recognition and for comparison of the capacitors with others.

Dimensions and their associated tolerances, which affect interchangeability and mounting, shall be given in the detail specification. All dimensions shall preferably be stated in millimetres. However, when the original dimensions are given in inches, the converted metric dimensions in millimetres shall be added.

The numerical values of the body shall be given as follows:

- for general: the length, width and height;
- for cylindrical body: the diameter and length.

The numerical values of the terminals shall be given as follows:

- for general: the spacing;
- for leaded terminals: the diameter and spacing.

When the configuration is other than described above, the detail specification shall state such dimensional information as will adequately describe the capacitor.

1.4.3 Mounting

The detail specification shall specify the method of mounting to be applied for normal use and for the application of the vibration and the bump or shock tests. The design of the capacitor may be such that special mounting fixtures are required in its use. In this case, the detail specification shall describe the mounting fixtures and they shall be used in the application of the vibration and bump or shock tests.

1.4.4 Ratings and characteristics

1.4.4.1 General

The ratings and characteristics shall be given in accordance with the relevant clauses of this specification, together with the information in 1.4.4.2, 1.4.4.3 and 1.4.4.4.

1.4.4.2 Nominal capacitance range

See 2.2.1.

When products approved to the detail specification have different capacitance ranges, the following statement should be added:

"The nominal capacitance range available in each voltage range is given in the register of approvals, available for example on the IECQ on-line certificate system website www.iecq.org".

1.4.4.3 Particular characteristics

Additional characteristics may be listed, when they are considered necessary to specify adequately the component for design and application purposes.

1.4.4.4 Soldering

The detail specification shall specify the test methods, severities and requirements applicable for the solderability test and the resistance to soldering heat tests.

1.4.5 Marking

The detail specification shall specify the content of the marking on the capacitor and on the packaging. When there are deviations from 1.6, these shall be given in the detail specification.

1.5 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

1.5.1

capacitance

<electrolytic capacitor> equivalent circuit having capacitance and resistance in series measured with alternating current, approximately sinusoidal waveform at a specified frequency

1.5.2

capacitor

<long-life grade> capacitors intended for applications where a high degree of stability of characteristics over a long life is essential

1.5.3

capacitor

<general-purpose grade> capacitors intended for applications where the high performance level of long-life grade capacitors is not required

1.6 Marking

1.6.1 General

See IEC 60384-1:2016, 2.4, with the details of 1.6.2, 1.6.3 and 1.6.4.

1.6.2 Information for marking

The information given in the marking is normally selected from the following list; the relative importance of each item is indicated by its position in the list:

- a) polarity of the terminations (unless identified by the construction);
- b) nominal capacitance;
- c) rated voltage (d.c. voltage may be indicated by the symbol: --- (IEC 60417-5031:2002) or ---);
- d) tolerance on nominal capacitance;
- e) year and month (or year and week) of manufacture;
- f) manufacturer's name and/or trade mark;
- g) manufacturer's type designation;
- h) reference to the detail specification.

1.6.3 Marking on capacitors

The capacitor shall be clearly marked with a), b) and c) of 1.6.2 and with as many as possible of the remaining items as is considered necessary. Any duplication of information in the marking on the capacitor should be avoided.

1.6.4 Marking on packaging

The packaging containing the capacitors should be clearly marked with all of the information listed in 1.6.2 as necessary.

2 Preferred ratings and characteristics

2.1 Preferred characteristics

Preferred climatic categories only shall be given in the preferred characteristics.

The capacitors covered by this specification are classified into climatic categories according to the general rules given in IEC 60068-1:2013, Annex A.

The lower and upper category temperature shall be taken from the following:

- lower category temperature: $-55\text{ }^{\circ}\text{C}$;
- upper category temperature: $+85\text{ }^{\circ}\text{C}$ and $+125\text{ }^{\circ}\text{C}$.
- duration of the damp heat, steady state test: 21 and 56 days.

The severities for the cold and dry heat tests are the lower and upper category temperatures respectively.

2.2 Preferred values of ratings

2.2.1 Nominal capacitance (C_N)

Preferred values of nominal capacitance are shown in microfarad (μF).

Preferred values of nominal capacitance shall be taken from the E12 series of IEC 60063 and their decimal multiples. These values are:

1,0 – 1,2 – 1,5 – 1,8 – 2,2 – 2,7 – 3,3 – 3,9 – 4,7 – 5,6 – 6,8 – 8,2;