

EIA INTERIM STANDARD

IS-39

Ceramic Dielectric Axial Capacitors (Glass Encapsulated)

IS-39

MARCH 1987

ELECTRONIC INDUSTRIES ASSOCIATION
ENGINEERING DEPARTMENT



NOTICE

EIA Engineering Standards and Publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for his particular need. Existence of such Standards and Publications shall not in any respect preclude any member or non-member of EIA from manufacturing or selling products not conforming to such Standards and Publications, nor shall the existence of such Standards and Publications preclude their voluntary use by those other than EIA members, whether the standard is to be used either domestically or internationally.

Recommended Standards and Publications are adopted by EIA without regard to whether or not their adoption may involve patents on articles, materials, or processes. By such action, EIA does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the Recommended Standard or Publication.

EIA INTERIM STANDARDS

EIA Interim Standards contain information deemed to be of technical value to the industry, and are published at the request of the originating Committee without necessarily following the rigorous public review and resolution of comments which is a procedural part of the development of an EIA Recommended Standard.

EIA Interim Standards should be reviewed on an annual basis by the formulating Committee and a decision made on whether to proceed to develop an EIA Recommended Standard on this subject. EIA Interim Standards must be cancelled by the Committee and removed from the EIA Standards Catalog before the end of their fifth year of existence.

This Interim Standard was formulated under the cognizance of the EIA P-2.1 Working Group on Ceramic Capacitors.

Published by
ELECTRONIC INDUSTRIES ASSOCIATION
Engineering Department
2001 Eye Street, N.W.
Washington, D.C. 20006

PRICE: \$5.00

Printed in U.S.A.



Documents

Document Sharing Hub

E.I.A. Standard Specification Sheet
for
Glass Encapsulated Axial Capacitors-Ceramic Dielectric




FIGURE 1

<u>Style</u>	<u>L. Max.</u>	<u>D Max.</u>	<u>+ .004 (0.10)</u> <u>M - .001 (0.03)</u>
AG1710	.170 (4.32)	.100 (2.54)	.020 (0.51)
AG2010	.200 (5.08)	.100 (2.54)	.020 (0.51)
AG2610	.260 (6.60)	.100 (2.54)	.020 (0.51)
AG3015	.290 (7.37)	.150 (3.81)	.020 (0.51)
AG4015	.400 (10.16)	.150 (3.81)	.020 (0.51)

- Notes: 1. AG = Glass Encapsulated, Axial Leaded.
2. All dimensions - inches (mm).