

EIA SPECIFICATION

NQ-EIA/IS-43AJ

Cable For LAN Twisted Pair Data Communications – Detail Specification For Type 9, Plenum Cable

NQ-EIA/IS-43AJ

SEPTEMBER 1988

ELECTRONIC INDUSTRIES ASSOCIATION
ENGINEERING DEPARTMENT



NOTICE

EIA Engineering Standards and Publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for his particular need. Existence of such Standards and Publications shall not in any respect preclude any member or non-member of EIA from manufacturing or selling products not conforming to such Standards and Publications, nor shall the existence of such Standards and Publications preclude their voluntary use by those other than EIA members, whether the standard is to be used either domestically or internationally.

Recommended Standards and Publications are adopted by EIA without regard to whether or not their adoption may involve patents on articles, materials, or processes. By such action, EIA does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the Recommended Standard or Publication.

Copyright 1988


Published by

ELECTRONIC INDUSTRIES ASSOCIATION
Engineering Department
2001 Eye Street, N.W.
Washington, D.C. 20006

PRICE: \$10.00

Published in U.S.A.

NQ-EIA/IS-43AJ

System Standard Organization Electronic Industries Association	Detail Specification Number NQ-EIA/IS-43AJ
Omnibus Specification Number: EIA/IS-43 Electronic Components of assessed quality in accordance with:	Blank Detail Specification: None
Outline Drawing: Cross Section 	Product Description Exchange Cable for use With Data Processing Equipment Type 9 Plenum Cable Two Insulated Data Grade Media (DGM) Copper Conductor Pairs in a Single Fluorocarbon Jacket
	Electrical Circuit
	Typical Construction
	Application/Assessment Level Assessment Level: C Performance Grade: IEEE 802.5

Information on the availability of components
qualified to this specification is given in
the Qualified Products List.



Documents
Document Sharing Hub

NQ-EIA/IS-43AJ

CONTENTS

1.0	Scope and Objective	1
1.1	Scope	1
1.2	Objective	1
2.0	General Data	1
2.1	General	1
2.2	Ordering Information	1
3.0	Specific Cable Requirements	2
3.1	Configuration	2
3.1.1	Conductors	2
3.1.2	Shields	2
3.1.3	Fillers	2
3.1.4	Rip Cord	2
3.1.5	Jacket	2
3.2	Electrical Specifications	3
3.2.1	Crosstalk	3
3.2.2	Impedance	3
3.2.3	Attenuation	4
3.2.4	DC Resistance of Conductors	4
3.3	Cable Mechanical Specifications	4
3.3.1	Mechanical Tests	4
3.3.2	Safety Requirements	5
3.3.3	DGM Core Flammability	5
3.4	Inspection Requirements	5



1.0 SCOPE AND OBJECTIVE

1.1 SCOPE

This Detail Specification defines Type 9 Plenum cable used with the Token Ring LAN Cabling System. Type 9 P consists of 2 twisted pairs of Data Grade Media (DGM) shielded with aluminum tape and braided shields, all cabled into a single fluorocarbon jacketed assembly. The Cabling System is intended to be compatible with IEEE Standard 802.5. It is designed to be used as a total building wiring system. The Cabling System may be used as the communications medium for a Token Ring Network as well as for other data equipment.

1.2 OBJECTIVE

The objective of the Detail Specification is to provide a document describing Type 9 P cable as a basis for certification under the NECQ system and for acquisition of conforming cable.

2.0 GENERAL DATA

2.1 GENERAL

Cable provided under this Detail Specification shall conform to all general and specific requirements applicable to Type 9 P cable in Omnibus Specification EIA/IS-43, Exchange Cable for Use with Data Processing Equipment, and those requirements specified herein.

2.2 ORDERING INFORMATION

Orders for cable covered by this Detail Specification shall include the following information:

1. Identification of cable type
2. Length required
3. Special requirements of reel size or type
4. Other unique requirements not covered in this specification

