

EIA/IS-749

EIA INTERIM STANDARD

Rectified Mains Application Expected Wear-Out Lifetime Test

EIA/IS-749

JANUARY 1998

**ELECTRONIC INDUSTRIES ASSOCIATION
ENGINEERING DEPARTMENT**



NOTICE

EIA Engineering Standards and Publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for his particular need. Existence of such Standards and Publications shall not in any respect preclude any member or nonmember of EIA from manufacturing or selling products not conforming to such Standards and Publications, nor shall the existence of such Standards and Publications preclude their voluntary use by those other than EIA members, whether the standard is to be used either domestically or internationally.

Standards and Publications are adopted by EIA in accordance with the American National Standards Institute (ANSI) patent policy. By such action, EIA does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the Standard or Publication.

EIA INTERIM STANDARDS

EIA Interim Standards contain information deemed to be of technical value to the industry, and are published at the request of the originating Committee without necessarily following the rigorous public review and resolution of comments which is a procedural part of the development of an EIA Standard.

EIA Interim Standards should be reviewed on an annual basis by the formulating Committee and a decision made on whether to proceed to develop an EIA Standard on this subject. EIA Interim Standards must be cancelled by the Committee and removed from the EIA Standards Catalog before the end of their third year of existence.

Publication of this EIA Interim Standard for trial use and comment has been approved by the Electronic Industries Association. Distribution of this EIA Interim Standard for comment shall not continue beyond 36 months from the date of publication. It is expected that following this 36 month period, this EIA Interim Standard, revised as necessary, will be submitted to the American National Standards Institute for approval as an American National Standard. Suggestions for revision should be directed to: Bernie Aronson, Engineering Department, Electronic Industries Association, 2500 Wilson Boulevard, Arlington, VA 22201.

(From Project Number 3873, formulated under the cognizance of the EIA P-2.4 Aluminum Electrolytic Capacitors Subcommittee.)

Published by

OELECTRONIC INDUSTRIES ASSOCIATION 1998

Engineering Department
2500 Wilson Boulevard
Arlington, VA 22201

**PRICE: Please refer to the current
Catalog of EIA, JEDEC, and TIA STANDARDS and ENGINEERING PUBLICATIONS
or call Global Engineering Documents, USA and Canada (1-800-854-7179)
International (303-397-7956)**

All rights reserved
Printed in U.S.A.

CONTENTS

	Page
Preface	
Clause	
1 Scope	1
2 Test circuit	1
3 Test fixtures	2
4 Preconditioning	3
5 Initial measurement	3
6 Test environment	3
7 Recovery per test interval	3
8 Measurement per test interval	3
9 Test completion	3
Table	
1 Definition of wear-out failure	1
2 Test conditions	3
Figure	
1 Suggested test circuit	1
2 Screw terminal style capacitor test fixture	2
3 Copper bus structure for screw terminal style capacitors	2