

Heat capacity and enthalpy of liquids: Halogenated ethanes and ethylenes

ESDU Copyright material. For current status contact ESDU.

Endorsed by
The Institution of Chemical Engineers

ESDU DATA ITEMS

Data Items provide validated information in engineering design and analysis for use by, or under the supervision of, professionally qualified engineers. The data are founded on an evaluation of all the relevant information, both published and unpublished, and are invariably supported by original work of ESDU staff engineers or consultants. The whole process is subject to independent review for which crucial support is provided by industrial companies, government research laboratories, universities and others from around the world through the participation of some of their leading experts on ESDU Technical Committees. This process ensures that the results of much valuable work (theoretical, experimental and operational), which may not be widely available or in a readily usable form, can be communicated concisely and accurately to the engineering community.

We are constantly striving to develop new work and review data already issued. Any comments arising out of your use of our data, or any suggestions for new topics or information that might lead to improvements, will help us to provide a better service.

THE PREPARATION OF THIS DATA ITEM

The work on this particular Data Item was monitored and guided by the Physical Data and Reaction Kinetics Committee, which first met in 1966 and now has the following membership:

Chairman

Mr C.F. Beaton — B.P. Chemicals International Ltd, UK

Members

Dr D. Ambrose	— National Physical Laboratory, Teddington, UK
Dr A.G. Carter	— Davy Powergas Ltd, UK
Dr G. Hobson	— Imperial Chemical Industries Ltd, Wilton, UK
Mr D.T. Jamieson	— National Engineering Laboratory, East Kilbride, UK
Mr A.R. Maizels	— Stone & Webster Engineering Ltd, Milton Keynes, UK
Mr G.M. Rowell	— Humphreys & Glasgow Ltd, UK
Dr M. Schoenberg [†]	— Hoechst AG, Frankfurt, Germany
Dr L.A.K. Staveley	— Oxford University, Oxford, UK.

[†] Corresponding Member.

The technical work involved in the assessment of the available information and the construction and subsequent development of the Data Item was undertaken by

Mrs S.D. Sriskandarajah — Engineer.

The person with overall responsibility for the work in this subject area is Mr N. Thompson, Head of Fluid Mechanics and Physical Properties Group.

HEAT CAPACITY AND ENTHALPY OF LIQUIDS: HALOGENATED ETHANES AND ETHYLENES

1. INTRODUCTION

This Data Item presents values of saturated liquid heat capacity and enthalpy for the halogenated ethanes and ethylenes listed in Table I.

The data on which these values are based are the most reliable available and for most compounds the range covered is from the melting temperature to the normal boiling point or to the limit of the experimental data whichever is the higher. In common with other ESDU Data Items, quantities are expressed in SI units and conversion factors to other units are provided in Section 3.

Section 4 describes the procedure used to obtain the values of heat capacity presented and indicates the effect of pressure. Values of enthalpy have been derived from values of heat capacity as explained in Section 5. Section 6 gives an explanation of the Tables and indicates the uncertainties in the values presented in them.

Section 7 contains all the sources of data used in the preparation of this Data Item. For convenience when using these Tables, a fold-out flap attached to the last page provides an index to the Data Item, showing against the name of each compound the page and Table number where the data relating to it appear.

2. NOTATION AND UNITS

The SI unit of heat capacity is the joule per kilogram kelvin (J/kg K). A convenient multiple unit for the range of heat capacities in this Data Item is the kilojoule per kilogram kelvin (kJ/kg K) and is adopted here.

a_1, a_2, a_3	constants for each liquid in Equations (4.1) and (5.1)	kJ/kg K
c	heat capacity	kJ/kg K
h	enthalpy	kJ/kg
T	thermodynamic temperature	K

Subscripts

c	denotes value at critical point
m	denotes value at melting point
r	denotes reduced quantity, e.g. $T_r = T/T_c$
s	denotes value at saturation pressure.

3. CONVERSION FACTORS

$$1 \text{ kJ/kg K} = 0.239 \ 006 \text{ cal/g K} \\ = 0.238 \ 846 \text{ Btu/lb } ^\circ\text{F}$$

$$1 \text{ kJ/kg} = 0.239 \ 006 \text{ cal/g} \\ = 0.429 \ 923 \text{ Btu/lb.}$$

Issued March 1977
With Amendment A – May 2003

4. HEAT CAPACITY

4.1 Heat Capacity at Saturation Pressure

For many liquids it has been suggested (Reference 7) that a good representation of heat capacity data over a wide range of temperature is given by the equation

$$c_s = a_1(1 - T_r)^{-2/3} + a_2(1 - T_r)^{-1/3} + a_3. \quad (4.1)$$

For the liquids considered in this Data Item, the derived values of a_1 , a_2 and a_3 given in Table I are a correlated set of values giving the best fit to the data for the liquid halogenated ethanes and ethylenes not only as individual compounds but also as members of their chemical series based on molecular structure.

Since the available experimental data do not cover the full liquid range, the data used to evaluate the constants in Equation (4.1) have, where possible, been extended to the melting temperature and to the boiling point using as a guide the available data plotted on a reduced temperature scale.

The experimental data for the heat capacity of some compounds exhibit a minimum at temperatures near the normal melting temperature; this behaviour is well established for chloroethane. This phenomenon could not be reproduced with the chosen 3 constant equation. To obtain an adequate fit to the experimental data, the fitted equation for chloroethane was truncated at a temperature above the melting temperature and a constant value of c_s taken between that temperature and the melting temperature.

The complete range of data for each compound was fitted by Equation (4.1) and correlation of the values of the constants with molecular structure was used to estimate the heat capacities of those liquids for which either very few or no data were available.

Using the values of the constants in Table I together with the values of T_c also given in Table I, values of c_s in kJ/kg K have been calculated for each compound from Equation (4.1) and are presented in Tables II to VI. Users' attention is drawn to the limits of applicability of Equation (4.1) given in Table I. Any extrapolation beyond these limits should be carried out with caution.

4.2 Effect of Pressure

The experimental data reported in each Derivation are either at 1 atm pressure or at saturation pressure. Except at temperatures very near the critical point, the differences between the values of liquid heat capacity at 1 atm pressure and at saturation pressures are not significant.

5. ENTHALPY AT SATURATION PRESSURE

Values of liquid enthalpy for each compound may be calculated from the equation,

$$h_s = -T_c \left[3a_1(1 - T_r)^{1/3} + \frac{3}{2}a_2(1 - T_r)^{2/3} + a_3(1 - T_r) \right]_{T_r^*}^{T_r}, \quad (5.1)$$

obtained by integrating Equation (4.1). T_r^* denotes the reduced temperature at which the enthalpy is set to zero. The enthalpy base temperature for all the compounds except hexafluoroethane, has been taken as 25 °C = 298.15 K at which the liquid was arbitrarily assigned an enthalpy of zero. For hexafluoroethane where T_c is less than 298.15 K, the normal melting temperature has been taken as the base temperature. For pentachlorofluoroethane where the melting temperature is above 25 °C, Equation (5.1) has been

extrapolated from the melting temperature to 25 °C in deriving the enthalpy data. The values of enthalpies in kJ/kg have been calculated for each compound from Equation (5.1) and are presented in Tables VII to XI.

6. EXPLANATION OF TABLES

6.1 Notes on Compounds Considered

The compounds are numbered from 1 to 48 in the list of compounds on page 17 and these numbers are used to identify the compounds in the Tables where space does not permit the use of the name. The compounds are identified by a systematic name but for most compounds alternative names and refrigerant numbers, in accordance with Reference 1, are given by which the compounds may be identified in other literature.

The values of T_m and T_c for the compounds have been taken from Data Items 76004 and 76009. Compounds for which no, or few, experimental data exist and for which values of the constants were estimated as described in Section 4.1 are indicated by an asterisk against their compound number in Table I.

Tables II to VI present values of heat capacity and Tables VII to XI present values of enthalpy at 10 K intervals of temperature from the melting temperature to either the normal boiling point or to the limit of the experimental data.

6.2 Accuracy of Data

The experimental data which are assessed to be the most reliable have a repeatability of about ± 1 per cent, although differences in the methods used by different workers, and also in the purity of samples, can increase the uncertainties to about ± 2 per cent. Reliable data are not available for all the compounds considered nor over the whole temperature range covered.

Although it is considered that the correlation procedures adopted keep the errors in the values presented to a minimum the user should allow for an uncertainty of ± 5 per cent in the values of heat capacity given to 3 decimal places and in the values of enthalpy given to 1 decimal place in the Tables. This uncertainty increases to ± 10 per cent for the values of heat capacity given to 2 decimal places and for the values of enthalpy given to the nearest integer in the Tables.

7. REFERENCES AND DERIVATION

References

The references given are recommended sources of information supplementary to that in this Data Item.

1. ASHRAE *Standard designation of refrigerants.* ASHRAE Standard 34-57, American Society of Heating, Refrigerating and Air-Conditioning Engineers, New York, 1957. Approved as number of designation of refrigerants. ASA B79 1-1960, American Standards Association, New York, 1960.
2. TIMMERMANS, J. *Physico-chemical constants of pure organic compounds.* Vol. 2, Elsevier, New York, 1965.
3. BSI *Recommended names for chemicals in industry.* British Standards Institution, BS2474: 1965.
4. REID, R.C. *The properties of liquids and gases, their correlation and estimation.* 2nd Edition, McGraw-Hill, New York, 1966.
5. HMSO *Classification of chemicals in the Brussels nomenclature and in the United Kingdom customs and excise tariff.* HMSO, London, UK, 1973.
6. ASHRAE *Thermophysical properties of refrigerants.* American Society of Heating, Refrigerating and Air-Conditioning Engineers, New York, 1973.

7. WATSON, J.T.R. Private communication. National Engineering Laboratory, East Kilbride, UK, 1975.

Derivation

The Derivation lists selected sources that have assisted in the preparation of this Data Item.

8. VON REIS, M.A. The specific heat of liquid organic compounds and their relationship to the molecular weight. (In German). *Ann. Phys. Chem.*, Ser. 3, Vol. 13, pp. 447–465, 1881.
9. JENKIN, C.F.
SHORTHOSE, D.N. The thermal properties of ethyl chloride. Special Report No. 14, Department of Scientific and Industrial Research, Food Investigation Board, UK, 1924.
10. LE BLANC, M.
MÖBIUS, E.
TIMMERMANS, J. *Ber. Verhandl. Sächs. Akad. Wissenschaft. Leipzig, Math. Phys. Klasse*, Vol. 85, p. 75, 1933. As quoted in: *Physicochemical constants of pure organic compounds*. Vol. 1, Elsevier, 1950.
11. MEHL, W. The specific heats of several liquid refrigerants. (In German). *Z. Ges. Kält. Ind.*, Vol. 41, pp. 152–153, 1934.
12. PERLICK, A. Calorimetric measurement on sulphur dioxide, methylene chloride, difluoromonochloroethane and tetrafluorodichloroethane. (In German). *Z. Ges. Kält. Ind.*, Vol. 44, No. 11, pp. 201–206, 1937.
13. RIEDEL, L. Determination of the thermal properties of trifluorotrichloroethane. (In German). *Z. Ges. Kält. Ind.*, Vol. 45, pp. 221–225, 1938.
14. BENNING, A.F.
McHARNES, R.C.
MARKWOOD, W.H.
SMITH, W.J. Thermodynamic properties of fluorochloromethanes and -ethanes. Heat capacity of the liquid and vapor of three fluorochloromethanes and trifluorotrichloroethane. *Ind. Eng. Chem.*, Vol. 32, No. 7, pp. 976–980, 1940.
15. RIEDEL, L. The determination of the specific heat of ethyl chloride and methylene chloride in the liquid state. (In German). *Z. Ges. Kält. Ind.*, Vol. 47, p. 87, 1940.
16. PITZER, K.S. The heat capacities, heats of transition and fusion, and entropies of ethylene dichloride and ethylene dibromide. *J. Am. Chem. Soc.*, Vol. 62, No. 2, pp. 331–335, 1940.
17. RIEDEL, L. Determination of the thermal and calorific properties of difluoromonochloroethane. (In German). *Z. Ges. Kält. Ind.*, Vol. 48, No. 1, pp. 105–107, 1941.
18. RUSSELL, H. J.
GOLDING, D.R.V.
YOST, D.M. The heat capacity, heats of transition, fusion and vaporization, vapor pressure and entropy of 1,1,1-trifluoroethane. *J. Am. Chem. Soc.*, Vol. 66, No. 1, pp. 16–20, 1944.
19. RUBIN, T.R.
LEVEDAHL, B.H.
YOST, D.M. The heat capacity, heat of transition, vaporization, vapor pressure and entropy of 1,1,1-trichloroethane. *J. Am. Chem. Soc.*, Vol. 66, No. 2, pp. 279–282, 1944.
20. PACE, E.L.
ASTON, J.G. The thermodynamics of hexafluoroethane from calorimetric and spectroscopic data. *J. Am. Chem. Soc.*, Vol. 70, No. 2, pp. 566–570, 1948.
21. GORDON, J.
GIAUQUE, W.F. The entropy of ethyl chloride. Heat capacity from 13 to 287 K. Vapor pressure, heats of fusion and vaporization. *J. Am. Chem. Soc.*, Vol. 70, No. 4, pp. 1506–1510, 1948.
22. PALMER, G. Thermal conductivity of liquids. *Ind. Eng. Chem.*, Vol. 40, No. 1, pp. 89–92, 1948.
23. D'HONT, M.
JUNGERS, J.C. The molar heat of 1,1-dibromoethane and 1,1,2-tribromoethane in the liquid phase. (In French). *Bull. Soc. Chim. Belges*, Vol. 58, pp. 196–204, 1949.
24. CROWE, R.W.
SMYTH, C.P. Heat capacities, dielectric constants and molecular rotational freedom in solid trichloroethanes and disubstituted propanes. *J. Am. Chem. Soc.*, Vol. 72, No. 9, pp. 4009–4015, 1950.
25. OLIVER, G.D.
GRISARD, J.W.
CUNNINGHAM, C.W. Thermodynamic properties and *P-V-T* relations of chlorotrifluoroethylene. *J. Am. Chem. Soc.*, Vol. 73, No. 12, pp. 5719–5722, 1951.
26. FURUKAWA, G.T.
McCOSKEY, R.E.
REILLY, M.L. Heat capacity, heats of fusion and vaporization, and vapor pressure of tetrafluoroethylene. *J. Res. Nat. Bur. Stand.*, Vol. 51, No. 2, pp. 69–72, 1953.

27. BUBUSHYAN, M.B. Thermodynamic properties of liquid freon-113 in a wide range of temperature and pressure. (In Russian). *Teploenergetika*, Vol. 3, pp. 49–51, 1954.
28. SHEINDLIN, A.
BUBUSHYAN, M.B. Experimental determination of density and heat capacity c_p of liquid freon-113. (In Russian). *Kholod. Tekhn.*, Vol. 31, No. 4, pp. 53–55, 1954.
29. RUITER, L.H.
TIMMERMANS, J. Ph.D. Thesis, University of Amsterdam, Holland, 1955. As quoted in: *Physicochemical constants of pure organic compounds*. Vol. 2, Elsevier, 1965.
30. STAVELEY, L.A.K.
TUPMAN, W.I.
HART, K.R. Some thermodynamic properties of the systems benzene + ethylene dichloride, benzene + carbon tetrachloride, acetone + chloroform, acetone + carbon disulphide. *Trans. Faraday Soc.*, Vol. 51, pp. 323–343, 1955.
31. ASTON, J.G.
WILLS, P.E.
ZOLKI, T.P. The heat capacities from 10.9 K. Heats of transition, fusion and vaporization, vapor pressures and entropy of pentafluorochloroethane, the barrier hindering internal rotation. *J. Am. Chem. Soc.*, Vol. 77, No. 15, pp. 3939–3941, 1955.
32. PLANK, R. F-115, a neglected refrigerant. (In German). *Kältetechnik*, Vol. 8, pp. 127–128, 1956.
33. LI, J.C.M.
PITZER, K.S. The thermodynamic properties of 1,1-dichloroethane: Heat capacities from 14 to 294 K, heats of fusion and vaporization, vapor pressure and entropy of the ideal gas. The barrier to internal rotation. *J. Am. Chem. Soc.*, Vol. 78, No. 6, pp. 1077–1080, 1956.
34. CHERNEEVA, L.I. An experimental determination of specific heat for liquid freon-142. (In Russian). *Teploenergetika*, Vol. 5, No. 12, pp. 71–78, 1958.
35. VAN WIE, N.H.
EBEL, R.A. Some thermodynamic properties of freon-114. United States Atomic Energy Commission Report No. K-1430, Vol. 1, 1959.
36. HILDENBRAND, D.L.
McDONALD, R.A.
KRAMER, W.R.
STULL, D.R. Thermodynamic and spectroscopic study of vinylidene chloride. I. Thermodynamic properties of the solid, liquid and ideal gas. *J. Chem. Phys.*, Vol. 30, No. 4, pp. 930–934, 1959.
37. MARTIN, J.J. Thermodynamic properties of dichlorotetrafluoroethane. *J. Chem. Eng. Data*, Vol. 5, No. 3, pp. 334–336, 1960.
38. VASCOV, Y.T. An apparatus for the determination of the specific heat of liquids. (In Russian). *Izv. Vuzov. Instr. Bldg.*, Vol. 7, No. 4, pp. 155–157, 1964.
39. RASTORGUEV, Yu.L.
GANIEV, Yu.A. Investigation of the heat capacity of selected solvents. (In Russian). *Izv. Vyssh. Ucheb. Zaved., Neft. Gaz.*, Vol. 10, No. 1, pp. 79–82, 1967.
40. LEBEDEV, B.V.
RABINOVICH, I.B.
BUDARINA, V.A. Heat capacity of vinyl chloride, poly (vinyl chloride) and poly (vinylidene chloride) in the region 60–300 K. (In Russian). *Vysokomol. Soedin. Ser. A*, Vol. 9, No. 3, pp. 488–494, 1967.
41. ANDON, R.J.L.
COUNSELL, J.F.
LEE, D.A.
MARTIN, J.F. Thermodynamic properties of aliphatic halogen compounds. Part 2. – Heat capacity of 1,1,1-trichloroethane. *J. Chem. Soc., Faraday Trans. I*, Vol. 69, No. 9, pp. 1721–1726, 1973.
42. GRUZDEV, V.A.
SHELUDYAKOV, E.P.
KIRIYANENKO, A.A.
KOLOTOV, Ya.L.
LAVROV, V.A.
SHILYAKOV, A.A.
SHESTOVA, A.I.
SHUMSKAYA, A.I. Thermophysical properties of freons. *Fluid Mech. Sov. Res.*, Vol. 3, No. 4, pp. 172–176, 1974.