



ESDU 91010

Issued December 1991

With Amendment A

April 1993

Re-issued February 2012

Response of structures to galloping excitation Background and approximate estimation

ESDU Copyright material. For current status contact ESDU.

Copyright Engineering Sciences Data Unit
Provided by IHS Markit under license with ESDU
No reproduction or networking permitted without license from IHS

ESDU DATA ITEMS

Data Items provide validated information in engineering design and analysis for use by, or under the supervision of, professionally qualified engineers. The data are founded on an evaluation of all the relevant information, both published and unpublished, and are invariably supported by original work of ESDU staff engineers or consultants. The whole process is subject to independent review for which crucial support is provided by industrial companies, government research laboratories, universities and others from around the world through the participation of some of their leading experts on ESDU Technical Committees. This process ensures that the results of much valuable work (theoretical, experimental and operational), which may not be widely available or in a readily usable form, can be communicated concisely and accurately to the engineering community.

We are constantly striving to develop new work and review data already issued. Any comments arising out of your use of our data, or any suggestions for new topics or information that might lead to improvements, will help us to provide a better service.

THE PREPARATION OF THIS DATA ITEM

The work on this particular Data Item was monitored and guided by the Wind Engineering Panel. This Panel, which took over the work on wind engineering previously monitored by the Fluid Mechanics Steering Group, first met in 1979 and now has the following membership:

Chairman	
Mr T.V. Lawson	— Bristol University
Members	
Mr A. Allsop	— Ove Arup and Partners
Mr C.W. Brown	— Independent
Prof. J.E. Cermak*	— Colorado State University, USA
Dr N.J. Cook	— Building Research Establishment
Prof. A.G. Davenport*	— University of Western Ontario, Canada
Dr D.M. Deaves	— Atkins Research and Development
Dr R.G.J. Flay*	— University of Auckland, New Zealand
Dr A.R. Flint	— Flint and Neill
Mr R.I. Harris	— Cranfield Institute of Technology
Dr J.D. Holmes*	— CSIRO, Australia
Prof. K.C. Mehta*	— Texas Tech. Univ., USA
Mr R.H. Melling	— Independent
Dr W. Moores	— Meteorological Office, UK
Dr G.A. Mowatt	— Earl and Wright Ltd
Mr J.R.C. Pedersen	— Independent
Mr R.E. Whitbread	— BMT Fluid Mechanics Ltd
Mr G. Wiskin	— British Broadcasting Corporation.

* Corresponding Member

The technical work involved in the assessment of the available information and the construction and subsequent development of the Data Item was undertaken by

Mr B.C. Freeman — Senior Engineer.

The person with overall responsibility for the work in this subject area is Mr N. Thompson, Head of the Wind Engineering Group.

RESPONSE OF STRUCTURES TO GALLOPING EXCITATION BACKGROUND AND APPROXIMATE ESTIMATION

CONTENTS

	Page
1. NOTATION AND UNITS	1
1.1 Axis Systems and Definitions	5
1.2 Force Coefficients	5
2. INTRODUCTION	6
3. BACKGROUND	7
3.1 Response to Galloping	7
3.1.1 The galloping mechanism	7
3.1.2 Limit cycles and divergence	7
3.1.3 Soft and hard oscillators	7
3.1.4 Along-wind and across-wind galloping	8
3.1.5 Torsional galloping	9
3.1.6 Stall galloping	9
3.1.7 Wake galloping	9
3.2 Response to Other Aeroelastic Instabilities	9
4. CALCULATION METHODS	10
4.1 Assessment of Galloping Potential	10
4.2 Estimation of Response Amplitudes	12
5. METHODS OF REDUCING OR ELIMINATING GALLOPING	13
5.1 Aerodynamic Methods	13
5.2 Structural Methods	13
6. WORKED EXAMPLE	14
7. REFERENCES AND DERIVATION	15
7.1 References	15
7.2 Derivation	16
FIGURES 1 to 4	17 to 19
APPENDIX A BASIS OF METHODS	20
A1. Basic Assumptions of the Method	20
A2. Wind Direction and Wind Speed	20
A3. Wind Loading	21

A4.	Susceptibility to Galloping	21
A4.1	‘Soft’ and ‘Hard’ Oscillators	22
A4.2	Den Hartog criterion	22
A5.	Onset Wind Speed, Minimum Damping	22
A6.	Response Amplitude	24
A6.1	Alternative solution	25
APPENDIX B THE HAND CALCULATION METHOD		27
B1.	Basis of the Hand Calculation Method	27

RESPONSE OF STRUCTURES TO GALLOPING EXCITATION Background and Approximate Estimation

1. NOTATION AND UNITS

		<i>Units</i>	
		<i>SI</i>	<i>British</i>
b	width of front face of structure	m	ft
C_D, C_L	wind-axis force coefficients	—	—
C_F	general force coefficient; (force per unit length)/($\frac{1}{2}\rho V^2 b$)	—	—
$C_{FP},$ C_{FQ}, C_{FR}	force coefficients in 0P, 0Q and 0R directions	—	—
$C_{F_{pk}}$	local peak value of force coefficient (see Section 4)	—	—
F	general aerodynamic force	N	lbf
F_{Qj}	mode-generalised aerodynamic force	N	lbf
H	overall height of vertical structure (see Sketch 1.1)	m	ft
h_c	reference height (see Sketch 1.1)	m	ft
h_0	height above ground of lowest point on structure (see Sketch 1.1)	m	ft
L	structure length, H for vertical structure and W for horizontal structure	m	ft
l	distance along structure (see Sketch 1.1)	m	ft
M_j	overall mode-generalised mass for mode j	kg	*slug
n_j	natural frequency of mode j	Hz	Hz
0P, 0Q, 0R	system of right-handed rectangular principal structural axes	—	—
$Q, \dot{Q}$	general translational deflection and velocity	m and m/s	ft and ft/s

For Footnotes, refer to end of Notation Section

Issued December 1991
With Amendment A, April 1993
Re-issued February 2012 – 27 pages

Q_{oj}	general mode-generalised amplitude of motion in mode j	m	ft
$P_j, \dot{P}_j, \ddot{P}_j$	mode-generalised deflection, velocity and acceleration respectively for mode j , i.e. values at location where $\mu_j = 1$, for translational motion in $0P$ and $0Q$ directions	m, m/s and m/s ²	ft, ft/s and ft/s ²
$Q_j, \dot{Q}_j, \ddot{Q}_j$			
$p_j, \dot{p}_j, \ddot{p}_j$	deflection, velocity and acceleration respectively at location l on structure for translational motion in $0P$ and $0Q$ directions	m, m/s and m/s ²	ft, ft/s and ft/s ²
$q_j, \dot{q}_j, \ddot{q}_j$			
r	distance along $0R$ direction	m	ft
V	hourly-mean wind speed	m/s	ft/s
V_R	relative wind speed, resultant of hourly-mean wind speed and structure velocity	m/s	ft/s
V_z	hourly-mean wind speed at height z above wind-speed profile zero-plane	m/s	ft/s
W	overall length of horizontal structure (see Sketch 1.1)	m	ft
$0x, 0y, 0z$	system of right-handed rectangular wind axes with x -axis along mean wind direction and z -axis vertically upwards	—	—
z	height above wind-speed profile zero-plane	m	ft
z_0	terrain roughness parameter	m	ft
ζ_a	aerodynamic damping ratio	—	—
ζ_s	structural damping ratio, expressed as fraction of critical damping	—	—
θ	angular location in oscillation cycle; $2\pi n_j t$	rad	rad
μ_j	mode shape function describing deflected shape of structure in mode j	—	—
ρ	air density	kg/m ³	slug/ft ³ *
ϕ	flow incidence	rad	rad
ϕ_P	angle between wind direction for which $C_L = 0$ and $0P$ axis (see Sketch A2.1)	rad	rad
$\Delta\phi_{pk}$	location of peak force coefficient relative to mean incidence (see Section 4)	degree [†]	degree [†]
$\Delta\phi_z$	location of $C_F = 0$ point relative to mean incidence (see Section 4)	degree [†]	degree [†]

For Footnotes, refer to end of Notation Section.


ϕ_0	angle between mean wind direction at initial equilibrium and OP axis (see Sketch A2.1)	rad	rad
ψ	angle between OR -axis of structure and vertical in plane normal to mean wind direction (see Sketch 1.1)	rad	rad

Suffixes


hc	denotes value at height h_c above ground
j	denotes value relating to mode j

* 1 slug = 32.174 lb (pound mass).


† The unit is strictly the radian, but degrees are used for convenience in the calculation method.




(a) Cantilever structures



(b) Single-span structures



(c) Two-span, bridge-type structures



(d) Single-support structures

Sketch 1.1 Geometrical Parameters


1.1 Axis Systems and Definitions

The wind properties are described in terms of a wind axis system, $0x$, $0y$, $0z$ of right-handed Cartesian coordinates. The $0x$ axis is aligned along the mean wind direction and the $0z$ axis is vertically upward.

The structural geometry is often described in terms of a body axis system, $0X$, $0Y$, $0Z$, of right-handed Cartesian co-ordinates. The $0X$ axis will usually be aligned with an axis of symmetry if one exists or along a dominant feature. The $0Z$ axis will often be aligned along the 'long' axis of a structure if one dimension is much larger than the others.

The structural response is more conveniently described in terms of response in normal modes of vibration along the principal axes $0P$, $0Q$, $0R$. These again form a right-handed Cartesian co-ordinate system. This system may coincide with the body-axis system but does not necessarily do so.

Sketch 1.2 shows the systems applied to an equal angle cross-section with the simplifying assumption that $0z$, $0Z$ and $0R$ are coincident.



Sketch 1.2 Axis systems

1.2 Force Coefficients

Force coefficients in the wind axis system are the drag coefficient, C_D , along the $0x$ direction and the lift or across-wind coefficient C_L in the $0y$ or $0z$ direction depending on whether the structure is predominantly vertical or horizontal.

In the present Item the wind incidence is taken as the angle between the $0x$ axis projected onto the $0PQ$ plane and the $0P$ axis, positive in the sense of clockwise rotation of the wind about the $0R$ axis. Zero incidence is defined as a condition for which $C_L = 0$. There may be more than one condition for which this occurs, each effectively defining a different structural system and care should be taken to use a consistent value throughout. In the particular case in Sketch 1.2, zero incidence could be taken along $0P$ (as shown) or along $-0P$, for example.

Care should be taken that data used for force coefficients conforms to the sign convention shown. In particular, the convention of C_L opposite to that shown is often used elsewhere.

2. INTRODUCTION

Galloping is an aeroelastic response mechanism in which the fluid-dynamic loading results from the velocity of motion of the structure.

Galloping can affect lightly-damped, flexible structures or elements such as lighting standards, cables and stays of both circular and non-circular cross section. It is unlikely to be a problem for conventional buildings but can affect less rigid or lightly-damped rectangular-sectioned towers and structural elements.

Section 3 of this Item provides background to the phenomenon of galloping and the basis for its analysis. Brief mention is included of other aeroelastic phenomena such as classical flutter.

Section 4 provides a simplified method of analysis of galloping response of structures with force coefficient variations representative of sharp-edged sections. Consideration is given firstly to assessment of the potential for galloping and secondly the estimation of approximate response amplitudes. The method is also implemented for more general force coefficient variation in a computer program in Reference 6.

Since galloping response is usually undesirable, Section 5 outlines methods of reducing or eliminating it.

Section 6 provides a worked example of the application of the method in Section 4.

The basis of the analysis for the method is given in Appendix A and that specific to the simplified methods of Section 4, in Appendix B.

The analysis in this Item (in common with that widely used elsewhere) assumes that the flow is quasi steady, *i.e.* the wind loading can be determined from the instantaneous effective incidence and relative wind speed using mean force coefficient characteristics. Typically this is valid if $n_j b/V$ is less than about 0.1. For higher frequency parameter the effects of vortex shedding, which produces peak responses for $n_j b/V$ of around 0.15 to 0.25, will lead to variation in the mean loading also. At still higher values, around 0.5 to 1, the flow distribution may lag behind the appropriate condition for the instantaneous incidence*. If sufficient information were available the general method could be modified to include this time lag.

* This can lead to across-wind galloping of circular sections since the wind load then has a lateral component